

www.tuv.com

Appendix 1

Test Results

Disturbance Voltage on AC Mains


TUV Rheinland Hong Kong Ltd.

Continuous Disturbance

Test Information

EUT Name:	Avantwave BT Module
Serial Number:	BTR60X(00110728013-001)
Test Description:	FCC Part 15.107 Class B
Operating Conditions:	Transmit Mode
Operator Name:	Cyrus Chan
Comment:	120V 60Hz
Description:	CE N

Conducted Emission (FCC Part 15.107) - Class B



Result Table Single

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)
0.185000	45.1	22.3
0.372000	39.5	22.7
1.962000	27.5	9.5
2.351000	25.8	8.9


TUV Rheinland Hong Kong Ltd.

Continuous Disturbance

Test Information

EUT Name:	Avantwave BT Module
Serial Number:	BTR60X(00110728013-001)
Test Description:	FCC Part 15.107 Class B
Operating Conditions:	Transmit Mode
Operator Name:	Cyrus Chan
Comment:	120V 60Hz
Description:	CE L1

Conducted Emission (FCC Part 15.107) - Class B



Result Table_Single


Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)
0.187000	44.2	24.9
0.268000	39.7	25.0
0.359000	40.2	28.2
0.421000	38.1	26.0

03/08/2011

16:43:32

www.tuv.com


Carrier Frequency Separation




Date: 3.AUG.2011 13:37:07

www.tuv.com

Number of hopping channels




Date: 9.JUN.2011 11:56:13




Date: 9.JUN.2011 11:57:38

www.tuv.com

Dwell Time



Date: 9 JUN. 2011 12:04:13




Date: 9 JUN. 2011 12:06:35

www.tuv.com

20dB Bandwidth

Modulation: 8 DPSK


Tx frequency: 2402MHz



Date: 9.JUN.2011 12:17:10

Modulation: 8 DPSK


Tx frequency: 2441MHz



Date: 9.JUN.2011 12:15:21


www.tuv.com

Modulation: 8 DPSK
Tx frequency: 2480MHz



Date: 9.JUN.2011 12:13:34


Modulation: GFSK
Tx frequency: 2402MHz



Date: 9.JUN.2011 12:09:09


www.tuv.com

Modulation: GFSK
Tx frequency: 2441MHz



Date: 9.JUN.2011 12:10:48

Modulation: GFSK
Tx frequency: 2480MHz




Date: 9.JUN.2011 12:12:05

www.tuv.com

Peak Output Power

Modulation: GFSK


Tx frequency: 2402MHz



Date: 9.JUN.2011 12:46:49

Modulation: GFSK


Tx frequency: 2441MHz



Date: 9.JUN.2011 12:48:10


www.tuv.com

Modulation: GFSK
Tx frequency: 2480MHz



Date: 9.JUN.2011 12:48:44


Modulation: Pi/4 DQPSK
Tx frequency: 2402MHz



Date: 9.JUN.2011 12:52:36


www.tuv.com

Modulation: Pi/4 DQPSK
Tx frequency: 2441MHz



Date: 9.JUN.2011 12:52:01


Modulation: Pi/4 DQPSK
Tx frequency: 2480MHz




Date: 9.JUN.2011 12:51:20

www.tuv.com

Modulation: 8 DPSK
Tx frequency: 2402MHz




Modulation: 8 DPSK
Tx frequency: 2441MHz



www.tuv.com

Modulation: 8 DPSK
Tx frequency: 2480MHz




Date: 9.JUN.2011 12:55:45

www.tuv.com


Band Edge Compliance

Tx frequency: 2402MHz (conducted measurement; hopping on)



Date: 9.JUN.2011 12:34:12


Tx frequency: 2480MHz (conducted measurement; hopping on)



Date: 9.JUN.2011 12:32:50


www.tuv.com

Tx frequency: 2402MHz (conducted measurement; hopping off)



Date: 9.JUN.2011 12:35:43


Tx frequency: 2480MHz (conducted measurement; hopping off)




Date: 9.JUN.2011 12:38:26

www.tuv.com

Tx frequency: 2402MHz (radiated measurement)



www.tuv.com




Site: DG-CB03	Polarization: Horizontal	Temperature: 23
Limit: FCC_RF_1G-40G_(Peak)	Power: AC 120V/60Hz	Humidity: 51 %
EUT: Bluetooth module	Distance: 3m	
M/N: BTR60X		
Mode: TX		
Note: 3M 2402		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2377.360	15.32	31.93	47.25	74.00	-26.75	peak	

www.tuv.com

Tx frequency: 2480MHz (radiated measurement)



www.tuv.com

Radiated Emission Measurement


File :Bluetooth module (basic

Data :#19

Date: 2011/06/09

Time: 21:23:53

80.0 dBuV/m



Site DG-CB03

Polarization: **Horizontal**

Temperature: 23

Limit: FCC_RF_1G-40G_(Peak)

Power: AC 120V/60Hz

Humidity: 51 %

EUT: Bluetooth module

Distance: 3m

M/N: BTR60X

Mode: TX


Note: 3M TX 2480

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.896	18.59	31.80	50.39	74.00	-23.61	peak	

www.tuv.com


Spurious Emissions - Conducted

Tx frequency: 2402MHz



Date: 9.JUN.2011 12:44:06


Tx frequency: 2441MHz



Date: 9.JUN.2011 12:42:44

www.tuv.com

Tx frequency: 2480MHz



Date: 9.JUN.2011 12:41:26