



<b>Prüfbericht - Nr.: 14030236 001</b>			<b>Seite 1 von 15</b>		
<i>Test Report No.:</i>			<i>Page 1 of 15</i>		
<b>Auftraggeber:</b> <i>Client:</i>		<b>AvantWave Limited</b> 3 Rd. Floor, Photonics centre No. 2 Science Park Avenue East Hong Kong Science Park Shatin Hong Kong			
<b>Gegenstand der Prüfung:</b> <i>Test Item:</i>		<b>Stereo Bluetooth Receiver</b>			
<b>Bezeichnung:</b> <i>Identification:</i>		<b>BHA400</b>		<b>Serien-Nr.:</b> <i>Serial No.:</i>	
				<b>Engineering sample</b>	
<b>Wareneingangs-Nr.:</b> <i>Receipt No.:</i>		<b>00120619161-001</b>		<b>Eingangsdatum:</b> <i>Date of Receipt:</i>	
				<b>19.06.2012</b>	
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of test item at delivery:</i>			Test sample(s) is/are not damaged and suitable for testing.		
<b>Prüfört:</b> <i>Testing Location:</i>		<b>Hong Kong Productivity Council</b> HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong  <b>TÜV Rheinland Hong Kong Ltd.</b> 8/F., First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong			
<b>Prüfgrundlage:</b> <i>Test Specification:</i>		<b>FCC Part 15 Subpart C</b> <b>ANSI C63.4-2003</b> <b>CISPR 22:1997</b>			
<b>Prüfergebnis:</b> <i>Test Results:</i>		<b>Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.</b>  The above mentioned product was tested and <b>passed</b> .			
<b>Prüflaboratorium:</b> <i>Testing Laboratory:</i>		<b>TÜV Rheinland Hong Kong Ltd.</b> 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong			
<b>geprüft/ tested by:</b>			<b>kontrolliert/ reviewed by:</b>		
31.07.2012 Joey Leung Test Engineer		31.07.2012 Sharon Li Section Manager			
<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name/Stellung</b> <i>Name/Position</i>	<b>Unterschrift</b> <i>Signature</i>
					
<b>Sonstiges:</b> <i>Other Aspects</i>		<b>FCCID: XQN-BHA400</b>			
<b>Abkürzungen:</b>		<b>Abbreviations:</b>			
P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet		P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested			
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>					

## Table of Content

### Page

<b>Cover Page .....</b>	<b>1</b>
<b>Table of Content .....</b>	<b>2</b>
<b>Product information .....</b>	<b>3</b>
Manufacturers declarations.....	3
Product function and intended use .....	4
Submitted documents.....	4
Remark.....	4
Special accessories and auxiliary equipment .....	4
<b>List of Test and Measurement Instruments.....</b>	<b>5</b>
<b>Results FCC Part 15 – Subpart C .....</b>	<b>6</b>
Subclause 15.203 – Antenna Information.....	Pass .....6
Subclause 15.204 – Antenna Information.....	Pass .....6
Subclause 15.207 – Disturbance Voltage on AC Mains .....	Pass .....6
Subclause 15.247 (a)(1) – Carrier Frequency Separation .....	Pass .....7
Subclause 15.247 (a)(1)(iii) – Number of hopping channels.....	Pass .....7
Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time).....	Pass .....8
Subclause 15.247 (a) – 20 dB Bandwidth .....	Pass .....8
Subclause 15.247 (a) – Hopping Sequence.....	Pass .....9
Subclause 15.247 (a) – Equal Hopping Frequency Use .....	Pass .....10
Subclause 15.247 (a) – Receiver Input Bandwidth.....	Pass .....11
Subclause 15.247 (a) – Receiver Hopping Capability .....	Pass .....11
Subclause 15.247 (b)(1) – Peak Output Power.....	Pass .....11
Subclause 15.247 (d) – Band edge compliance of conducted emissions .....	Pass .....12
Subclause 15.205 – Band edge compliance of radiated emissions .....	Pass .....12
Subclause 15.247 (d) – Spurious Conducted Emissions.....	Pass .....13
Subclause 15.247 (c) – Spurious Radiated Emissions .....	Pass .....14
<b>Appendix 1 – Test protocols .....</b>	<b>26 pages</b>
<b>Appendix 2 – Test setup .....</b>	<b>2 pages</b>
<b>Appendix 3 – Photo documentation .....</b>	<b>6 pages</b>
<b>Appendix 4 – Product documentation .....</b>	<b>14 pages</b>

## Product information

### Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK; Pi/4 DQPSK; 8 DPSK
Number of channels	79
Channel separation	1 MHz
Type of antenna	Chip antenna
Antenna gain (dBi)	0
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	$V_{\text{nor}}$ : 5.0V
Independent Operation Modes	Page scan Inquiry scan Connection state - ACL Link Connection state - SCO Link

## Product function and intended use

The test item is a Bluetooth audio receiver based on the Bluetooth technology.

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s.

An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using phase shift keying (PSK) techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a Pi/4-DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation. The USB connector is for charging only, no data exchange supported.

## Submitted documents

Circuit Diagram  
Block Diagram  
Bill of material  
User Manual  
Label Artwork

## Remark

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases.

## Special accessories and auxiliary equipment

### Test Setup

Since an audio gateway is required to setup a Bluetooth SCO link, Apple iPod Touch, which provided by client, was used in the immunity test to act as an audio gateway.

### Additional accessory used for testing

The product has been tested together with the following additional accessory:

AC/DC Power adaptor

Model number: KSD10-050-1000

Input: 100-240VAC, 50/60Hz, 300mA

Output: 5VDC 1000mA

## List of Test and Measurement Instruments

### Hong Kong Productivity Council (Registration number: 90656)

Equipment used	Manufacturer	Model No.	S/N	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	25-May-13
Test Receiver	R & S	ESU40	100190	26-May-13
Bi-conical Antenna	R & S	HK116	100242	05-May-13
Log Periodic Antenna	R & S	HL223	841516/020	06-May-13
Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	15-Nov-13
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-13
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28-Oct-13
Horn Antenna	EMCO	3115	9002-3351	11-May-13
Active Loop Antenna	EMCO	6502	9107-2651	19-Apr-13
FSP 30 Spectrum Analyser	R & S	FSP 30	100007	17-Sep-12

## Results FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
<b>Requirement:</b>	No antenna other than that furnished by the responsible party shall be used with the device	
<b>Results:</b>	Permanent attached antenna	
<b>Verdict:</b>	Pass	

Subclause 15.204 – Antenna Information		Pass
<b>Requirement:</b>	Provide information for every antenna proposed for the use with the EUT	
<b>Results:</b>	a) Antenna type: Chip antenna b) Manufacturer and model no: N.A. c) Gain with reference to an isotropic radiator: 0 dBi	
<b>Verdict:</b>	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains						Pass
Test Port: AC mains input port of the adaptor Applied Voltage: 120VAC Adaptor Model: KSD10-050-1000 Mode of operation: Music playing mode						
Live measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dBµV	Average dBµV	Limit QP (dBµV)	Limit AV (dBµV)	Verdict
0,15 – 0,5	0.413	35.0	18.1	66 - 56	56 - 46	Pass
> 0,5 - 5	0.612	31.8	14.2	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass
Neutral measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dBµV	Average dBµV	Limit QP (dBµV)	Limit AV (dBµV)	Verdict
0,15 – 0,5	0.408	32.7	21.6	66 - 56	56 - 46	Pass
> 0,5 - 5	0.612	32.0	19.0	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass
Results: The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz does not exceed the limits. For test Results plots refer to Appendix 1, page 2-3.						

Subclause 15.247 (a)(1) – Carrier Frequency Separation		Pass
Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 5.0V from AC/DC adaptor as stated in page 4 Temperature : 23°C Humidity : 50%		
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.  The centre frequencies of the hopping channels are separated by more than the 2/3*20dB bandwidth. For test Results plots refer to Appendix 1, page 4.	
Verdict:	Pass	


Subclause 15.247 (a)(1)(iii) – Number of hopping channels		Pass
Requirement:	Frequency hopping systems operating in the 2400MHz-2483.5MHz bands shall use at least 15 hopping frequencies.	
Test Specification :	FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation :	Tx mode (hopping on), 8DPSK	
Port of testing :	Temporary antenna port	
Detector :	Peak	
RBW/VBW :	1 MHz / 3 MHz	
Supply voltage :	5.0V from AC/DC adaptor as stated in page 4	
Temperature :	23°C	
Humidity :	50%	
Results:	The total number of hopping frequencies is more than 15. For test Results plots refer to Appendix 1, page 5.	
Verdict:	Pass	

Subclause 15.247 (a)(1)(iii) – Time of Occupancy (Dwell Time)		Pass
Requirement:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.	
Test Specification :	FCC Part 15 Subpart A – Subclause 15.31	
Mode of operation :	Tx mode (hopping on), DH5 packet	
Port of testing :	Temporary antenna port	
Detector :	Peak	
RBW/VBW :	1 MHz / 3 MHz	
Supply voltage :	5.0V from AC/DC adaptor as stated in page 4	
Temperature :	23°C	
Humidity :	50%	
Results:	Time period calculation = 0.4 x 79 = 31.6s Dwell time = 64 x 2.92 x 10 <sup>-3</sup> = 186.88 x 10 <sup>-3</sup> s 	

Subclause 15.247 (a) – 20 dB Bandwidth		Pass	
Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.		
Test Specification :	FCC Part 15 Subpart A – Subclause 15.31		
Mode of operation :	Tx mode (2402MHz, 2441MHz, 2480MHz)		
Port of testing :	Temporary antenna port		
Detector :	Peak		
RBW/VBW :	30 kHz / 100 kHz		
Supply voltage :	5.0V from AC/DC adaptor as stated in page 4		
Temperature :	23°C		
Humidity :	50%		
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.  For test protocols refer to Appendix 1, page 7-9.		
GFSK Modulation			
Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.462	1.020	1.482
2441	0.462	1.020	1.482
2480	0.462	1.020	1.482



8DPSK Modulation			
Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.648	0.672	1.320
2441	0.654	0.672	1.326
2480	0.660	0.666	1.326

Subclause 15.247 (a) – Hopping Sequence	Pass
Requirement: The hopping sequence is generated and provided with an example.	
<p>Hopping sequence</p> <p>The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto the hop frequencies.</p> 	

**Example data:**

Hop sequence {k} for CONNECTION STATE:

CLK start: 0x0000010

ULAP: 0x00000000

#ticks: 00 02 | 04 06 | 08 0a | 0c 0e | 10 12 | 14 16 | 18 1a | 1c 1e |

0x0000010:	08 66	10 70	12 19	14 23	16 01	18 05	20 33	22 37
0x0000030:	24 03	26 07	28 35	30 39	32 72	34 76	36 25	38 29
0x0000050:	40 74	42 78	44 27	46 31	48 09	50 13	52 41	54 45
0x0000070:	56 11	58 15	60 43	62 47	32 17	36 19	34 49	38 51
0x0000090:	40 21	44 23	42 53	46 55	48 33	52 35	50 65	54 67
0x00000b0:	56 37	60 39	58 69	62 71	64 25	68 27	66 57	70 59
0x00000d0:	72 29	76 31	74 61	78 63	01 41	05 43	03 73	07 75
0x00000f0:	09 45	13 47	11 77	15 00	64 49	66 53	68 02	70 06
0x0000110:	01 51	03 55	05 04	07 08	72 57	74 61	76 10	78 14
0x0000130:	09 59	11 63	13 12	15 16	17 65	19 69	21 18	23 22
0x0000150:	33 67	35 71	37 20	39 24	25 73	27 77	29 26	31 30
0x0000170:	41 75	43 00	45 28	47 32	17 02	21 04	19 34	23 36
0x0000190:	33 06	37 08	35 38	39 40	25 10	29 12	27 42	31 44
0x00001b0:	41 14	45 16	43 46	47 48	49 18	53 20	51 50	55 52
0x00001d0:	65 22	69 24	67 54	71 56	57 26	61 28	59 58	63 60
0x00001f0:	73 30	77 32	75 62	00 64	49 34	51 42	57 66	59 74
0x0000210:	53 36	55 44	61 68	63 76	65 50	67 58	73 03	75 11
0x0000230:	69 52	71 60	77 05	00 13	02 38	04 46	10 70	12 78
0x0000250:	06 40	08 48	14 72	16 01	18 54	20 62	26 07	28 15
0x0000270:	22 56	24 64	30 09	32 17	02 66	06 74	10 19	14 27
0x0000290:	04 70	08 78	12 23	16 31	18 03	22 11	26 35	30 43
0x00002b0:	20 07	24 15	28 39	32 47	34 68	38 76	42 21	46 29
0x00002d0:	36 72	40 01	44 25	48 33	50 05	54 13	58 37	62 45
0x00002f0:	52 09	56 17	60 41	64 49	34 19	36 35	50 51	52 67
0x0000310:	38 21	40 37	54 53	56 69	42 27	44 43	58 59	60 75
0x0000330:	46 29	48 45	62 61	64 77	66 23	68 39	03 55	05 71
0x0000350:	70 25	72 41	07 57	09 73	74 31	76 47	11 63	13 00
0x0000370:	78 33	01 49	15 65	17 02	66 51	70 67	03 04	07 20
0x0000390:	68 55	72 71	05 08	09 24	74 59	78 75	11 12	15 28
0x00003b0:	76 63	01 00	13 16	17 32	19 53	23 69	35 06	39 22
0x00003d0:	21 57	25 73	37 10	41 26	27 61	31 77	43 14	47 30
0x00003f0:	29 65	33 02	45 18	49 34	19 04	21 08	23 20	25 24

**Subclause 15.247 (a) – Equal Hopping Frequency Use**
**Pass**

Requirement: Each of the transmitter's hopping channels is used equally on average.

Equal hopping frequency use

The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.

<b>Subclause 15.247 (a) – Receiver Input Bandwidth</b>	<b>Pass</b>
Requirement: The associated receiver(s) complies with the requirement that its input bandwidth matches the bandwidth of the transmitted signal.	
Receiver input bandwidth The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth was verified during Bluetooth RF conformance testing.	

<b>Subclause 15.247 (a) – Receiver Hopping Capability</b>	<b>Pass</b>
Requirement: The associated receiver has the ability to shift frequencies in synchronisation with the transmitted signals.	
Receiver hopping Capability The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.	

Subclause 15.247 (b)(1) – Peak Output Power					Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz) Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 3 MHz / 10 MHz Supply voltage : 5.0V from AC/DC adaptor as stated in page 4 Temperature : 23°C Humidity : 50%					
Requirement: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400 – 2483.5 MHz band: 0.125 Watts.					
Results: For test protocols please refer to Appendix 1, page 10-14.					
GFSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-16.31	0.00	-16.310	1 / 30.0	Pass
2441	-15.61	0.00	-15.610	1 / 30.0	Pass
2480	-15.64	0.00	-15.640	1 / 30.0	Pass
Pi/4 DQPSK Modulation					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-11.61	0.00	-11.610	1 / 30.0	Pass

2441	-10.81	0.00	-10.810	1 / 30.0	Pass
2480	-10.88	0.00	-10.880	1 / 30.0	Pass
<b>8DPSK Modulation</b>					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-11.46	0.00	-11.460	1 / 30.0	Pass
2441	-10.54	0.00	-10.540	1 / 30.0	Pass
2480	-10.66	0.00	-10.660	1 / 30.0	Pass

<b>Subclause 15.247 (d) – Band edge compliance of conducted emissions</b>		<b>Pass</b>
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2480MHz), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 5.0V from AC/DC adaptor as stated in page 4 Temperature : 23°C Humidity : 50%		
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.  There is no peak found outside any 100 kHz bandwidth of the operating frequency band. For test protocols refer to Appendix 1, page 15-16.	

<b>Subclause 15.205 – Band edge compliance of radiated emissions</b>		<b>Pass</b>
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2480MHz), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 5.0V from AC/DC adaptor as stated in page 4 Temperature : 23°C Humidity : 50%		
Requirement:	Radiated emissions which fall in the restricted bands, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).	
Results:	There is no peak found in the restricted bands. For test protocols refer to Appendix 1, page 17-24.	

<b>Subclause 15.247 (d) – Spurious Conducted Emissions</b>					<b>Pass</b>
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), 8DPSK Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 5.0V from AC/DC adaptor as stated in page 4 Temperature : 23 °C Humidity : 50 %					
<b>Requirement:</b> In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
<b>Results:</b> Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.  There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(d). For test protocols refer to Appendix 1, page 25-26.					
<b>Operating frequency (MHz)</b>	<b>Spurious frequency (MHz)</b>	<b>Spurious Level (dBm)</b>	<b>Reference value (dBm)</b>	<b>Delta (dB)</b>	<b>Verdict</b>
2402	4800	-56.24	-20.20	-36.04	Pass
2441	4850	-59.47	-16.62	-42.85	Pass
2480	4950	-59.72	-15.64	-44.08	Pass

Subclause 15.247 (c) – Spurious Radiated Emissions		Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), 8DPSK Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 5.0V from AC/DC adaptor as stated in page 4 Temperature : 23°C Humidity : 50%		
Requirement:	In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section15.205(a), must also comply with the radiated emission limits specified in section 15.205(c).	
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.  All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.	
Tx frequency 2402MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
479.998	35.10	46.0 / QP
1601.865	51.78	74.0 / PK
1601.994	49.30	54.0 / AV
4804.279	53.90	74.0 / PK
4804.022	37.70	54.0 / AV
Tx frequency 2402MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
1601.974	51.11	74.0 / PK
1601.990	49.26	54.0 / AV
4803.856	47.98	74.0 / PK
4804.000	33.61	54.0 / AV
Tx frequency 2441MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
479.994	35.00	46.0 / QP
1627.941	51.29	74.0 / PK
1627.973	49.67	54.0 / AV
4881.663	53.97	74.0 / PK
4881.968	37.66	54.0 / AV
Tx frequency 2441MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
1627.965	51.82	74.0 / PK

1627.981	50.06	54.0 / AV
4882.224	47.67	74.0 / PK
4881.968	33.58	54.0 / AV
Tx frequency 2480MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
479.993	34.80	46.0 / QP
1653.974	49.88	74.0 / PK
1653.974	47.65	54.0 / AV
4959.696	54.14	74.0 / PK
4959.920	38.26	54.0 / AV
Tx frequency 2480MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
479.999	33.80	46.0 / QP
1654.099	51.53	74.0 / PK
1653.987	49.90	54.0 / AV
4960.304	47.79	74.0 / PK
4960.048	33.69	54.0 / AV