Minila Air 共通裏面FCCラベル

149.7x49.7mm / R1mm



	JP • 68key	US·67key/KR·68key US·67key功能	UK+68key
1	Winキー、Appキーを無効化 II	nvalidate the Win key and the App key	Win鍵、App鍵無效化
2	CapsLockとCtrlの入替	Change CapsLock key and Ctrl key	CapsLock與Ctrl切換
3	左Fnキーをスペースに変更 CI	hange the left Fn key into the Spacebar	左Fn鍵變更為空白鍵
4	右Fnキーをスペースに変更 Ch	ange the right Fn key into the Spaceba	右Fn鍵變更為空白鍵
(5)	EscとE/Jの入替 Change Esc and [E/J]	Escと[~]の入替 Change Esc and [~]/Esc與[~]切換	Escと[`¦¬]の入替 Change Esc and [`¦¬]
6	右ShiftとDelの入替 Change the right Shift and Del	[←(Backspace)]と[¦\]の入替 Change [←] and [¦\]/[←]與[¦\]切換	

工機出荷時は全てOFFになっています。DIPスイッチを操作する時は、必ず主製品の電源スイッチをオフにしてください。オンの状態で操作すると故障の原因になりますのでご注意ください。DIPスイッチを操作する場合は水の側い棒状のしたができるででは高ください。DIPスイッチを操作する場合は水の側い棒状のした様とできる機能が一部異なります。

The factory default is OFF. Before operating the DIP switch, please turn off the Power switch of this product first. Please be aware that if operating the DIP switch, when the Power switch is on, machine failure may occur. When operating the DIP switch, and please use a stick with a sharp end. 出版設定本のFr、維持でDIP開設は、対象を手機を再送して構造制度を再送す。講法を実施制度の支援を再送して表現を開始を表現を表現を表現を表現を表現を表現して表現を表現を表現した。

「P技術・込み消息な効率・議使用的網条と細的棒状物操作DIP開開®・
This device complies with Part 15 of the FCC Rules and with RSS-210

This device complies with Part 15 of the FCC Rules and with RSS-210 of Industry Canada. Operation is subject to the following two conditions: (I) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation. Microsoft Windowssi. 米国マクロソフト社の米国及び、その他の国に対力登録商機です。Windows is registered trademark of Microsoft Corporation in the United States and other countries. Bluetooth is a registered trademark of Bluetooth Side. FLICOIS of Proy 少株式会社の登録商標です。FILCO is a registered trademark of DIATEC CORPORATION. Windows 商標為Microsoft 版權所有. FILCOIR 時期 Place No. 18 This Research Corporation 版權所有.

Made in Taiwan



FCC ID : XS8-MINILAAIR IC : 11166A-MINILAAIR CMIIT ID: XXXXXXXXXX



RXXXXXXXXXX



KCC-REM-FKB-FIL CFF02XXXXXXXX





