

FCC RF Test Report

Applicant : Mobinnova Hong Kong Limited
EQUIPMENT : Netbook with (1)WWAN card (2) WLAN+BT
combo module
Brand Name : Mobinnova
MODEL NAME : Beam
FCC ID : XTT-BEAMATT
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz /
871.4 ~ 891.6 MHz
WCDMA Band II : 1852.4 ~ 1907.6 MHz /
1932.4 ~ 1987.6 MHz
MAX. ERP/EIRP POWER : GSM850 (GPRS 8) : 0.86 W
GSM850 (EDGE 8) : 0.25 W
GSM1900 (GPRS 8) : 1.18 W
GSM1900 (EDGE 8) : 0.60 W
WCDMA Band V (WCDMA) : 0.10 W
WCDMA Band II (WCDMA) : 0.26 W
EMISSION DESIGNATOR : GMSK : 244KGXW
8PSK : 246KG7W
QPSK : 4M18F9W

The product was received on Jun. 18, 2009 and completely tested on Jul. 09, 2009. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

| | |
|---|-----------|
| REVISION HISTORY | 3 |
| SUMMARY OF TEST RESULT | 4 |
| 1 GENERAL DESCRIPTION | 5 |
| 1.1 Applicant..... | 5 |
| 1.2 Manufacturer | 5 |
| 1.3 Feature of Equipment Under Test..... | 6 |
| 1.4 Testing Site..... | 8 |
| 1.5 Applied Standards | 8 |
| 1.6 Ancillary Equipment List | 8 |
| 2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST | 9 |
| 2.1 Test Mode..... | 9 |
| 2.2 Connection Diagram of Test System | 10 |
| 3 TEST RESULT | 11 |
| 3.1 Conducted Output Power Measurement..... | 11 |
| 3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement | 13 |
| 3.3 Occupied Bandwidth Measurement | 19 |
| 3.4 Band Edge Measurement..... | 26 |
| 3.5 Conducted Emission Measurement | 33 |
| 3.6 Field Strength of Spurious Radiation Measurement | 49 |
| 3.7 Frequency Stability Measurement..... | 67 |
| 4 LIST OF MEASURING EQUIPMENT | 71 |
| 5 UNCERTAINTY OF EVALUATION | 72 |
| 6 CERTIFICATION OF TAF ACCREDITATION | 73 |
| APPENDIX A. PHOTOGRAPHS OF EUT | |
| APPENDIX B. SETUP PHOTOGRAPHS | |



REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|------------|---------|-------------------------|---------------|
| FG961822 | Rev. 01 | Initial issue of report | Oct. 29, 2009 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | IC Rule | Description | Limit | Result |
|----------------|-------------------------------------|------------------------------------|---|--|--------|
| 3.1 | §2.1046 | N/A | Conducted Output Power | N/A | PASS |
| 3.2 | §22.913(a)(2) | RSS-132(4.4) SRSP-503(5.1.3) | Effective Radiated Power | < 7 Watts for FCC (<6.3 Watts for IC) | PASS |
| 3.2 | §24.232(c) | RSS-133 (6.4) SRSP-510(5.1.2) | Equivalent Isotropic Radiated Power | < 2 Watts | PASS |
| 3.3 | §2.1049 §22.917(a) §24.238(a) | N/A | Occupied Bandwidth | N/A | PASS |
| 3.4 | §2.1051 §22.917(a) §24.238(a) | RSS-132 (4.5.1) RSS-133 (6.5.1) | Band Edge Measurement | < 43+10log ₁₀ (P[Watts]) | PASS |
| 3.5 | §2.1051 §22.917(a) §24.238(a) | RSS-132 (4.5.1) RSS-133 (6.5.1) | Conducted Emission | < 43+10log ₁₀ (P[Watts]) | PASS |
| 3.6 | §2.1053 §22.917(a) §24.238(a) | RSS-132 (4.5.1) RSS-133 (6.5.1) | Field Strength of Spurious Radiation | < 43+10log ₁₀ (P[Watts]) | PASS |
| 3.7 | §2.1055 §22.355 §24.235 | RSS-132(4.3) RSS-133(6.3) | Frequency Stability for Temperature & Voltage | < 2.5 ppm | PASS |



1 General Description

1.1 Applicant

Mobinnova Hong Kong Limited

unit 1501, 15/F On Hong Commercial Building, 145 Hennessy Road, Hong Kong

1.2 Manufacturer

FOXCONN

No. 4, MingSheng St., TuCheng City, Taipei County, Taiwan R.O.C.

1.3 Feature of Equipment Under Test

| Product Feature & Specification | |
|--|---|
| Equipment | Netbook with (1)WWAN card (2) WLAN+BT combo module |
| Brand Name | Mobinnova |
| Model Name | Beam |
| FCC ID | XTT-BEAMATT |
| Tx Frequency | GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz |
| Rx Frequency | GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz |
| Maximum Output Power to Antenna | GSM850 : 31.83 dBm GSM1900 : 28.65 dBm WCDMA Band V : 22.65 dBm WCDMA Band II : 23.00 dBm |
| Maximum ERP/EIRP | GSM850 (GPRS 8) : 0.86 W (29.33 dBm) GSM850 (EDGE 8) : 0.25 W (23.91 dBm) GSM1900 (GPRS 8) : 1.18 W (30.73 dBm) GSM1900 (EDGE 8) : 0.60 W (27.79 dBm) WCDMA Band V (WCDMA) : 0.10 W (19.89 dBm) WCDMA Band II (WCDMA) : 0.26 W (24.21 dBm) |
| Antenna Type | Fixed Internal Antenna |
| HW Version | C |
| SW Version | BSP 9.4.3 |
| Type of Modulation | GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM HSUPA : BPSK |
| Type of Emission | GMSK : 244KGXW 8PSK : 246KG7W QPSK : 4M18F9W |
| EUT Stage | Identical Prototype |

Remark:

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter (PCB).

List of Accessory:

| Specification of Accessory | | |
|--------------------------------|---------------------------|--|
| AC Adapter | Brand Name | Delta |
| | Model Name | ADP-36HH AA |
| | Power Rating | I/P:100-240Vac, 50-60Hz, 1A; O/P: 15Vdc, 2.4A |
| | AC Power Cord Type | 1.8 meter shielded cable with ferrite core |
| Battery | Brand Name | Sanyo |
| | Model Name | 3UR18650-1-T0512 |
| | Power Rating | 10.8Vdc, 2250mAh |
| | Type | Li-ion |
| WWAN Module | Brand Name | Sierra Wireless |
| | Model Name | MC 8790 |
| WLAN + Bluetooth Module | Brand Name | AMPAK |
| | Model Name | GC 8601 |
| LCD Panel | Brand Name | CMO |
| | Model Name | N089L6-L03 |

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For accessories equipped with this EUT, please refer to the appendix of the external photo.

1.4 Testing Site

| | | | |
|--------------------|---|-----------|-------------------------|
| Test Site | SPORTON INTERNATIONAL INC. | | |
| Test Site Location | No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978 | | |
| Test Site No. | Sporton Site No. | | FCC/IC Registration No. |
| | TH02-HY | 03CH07-HY | TW1022/4086B-1 |

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI C63.4-2003
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1. | System Simulator | R&S | CMU200 | N/A | N/A | Unshielded, 1.8 m |

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30MHz to 19000 MHz for GSM1900 and WCDMA Band II.

| Test Modes | | |
|----------------------|---|--|
| Band | Radiated TCs | Conducted TCs |
| GSM 850 | <ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link ■ GPRS 8 Link + 802.11b Tx CH11 | <ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link |
| GSM 1900 | <ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link ■ GPRS 8 Link + 802.11b Tx CH11 | <ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link |
| WCDMA Band V | <ul style="list-style-type: none"> ■ WCDMA Link | <ul style="list-style-type: none"> ■ WCDMA Link |
| WCDMA Band II | <ul style="list-style-type: none"> ■ WCDMA Link | <ul style="list-style-type: none"> ■ WCDMA Link |

Note: The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for QPSK link; only these modes were used for all tests.

The conducted power tables are as follows:


| Conducted Power | | | | | | |
|-----------------|--------------|-------|-------|---------|--------|--------------|
| Band | GSM850 | | | GSM1900 | | |
| Channel | 128 | 189 | 251 | 512 | 661 | 810 |
| Frequency | 824.2 | 836.4 | 848.8 | 1850.2 | 1880.0 | 1909.8 |
| GPRS 8 | 31.83 | 31.80 | 31.59 | 28.24 | 28.33 | 28.65 |
| GPRS 10 | 28.87 | 28.86 | 28.65 | 25.38 | 25.45 | 25.78 |
| GPRS 12 | 25.96 | 25.88 | 25.72 | 22.40 | 22.49 | 22.80 |
| EGPRS 8 | 27.02 | 26.97 | 26.80 | 25.35 | 25.45 | 25.79 |
| EGPRS 10 | 27.00 | 26.95 | 26.70 | 25.35 | 25.44 | 25.75 |
| EGPRS 12 | 25.91 | 25.87 | 25.71 | 22.35 | 22.45 | 22.79 |

(*Unit: dBm)

| Conducted Power | | | | | | |
|-----------------|--------------|--------------|-------|---------------|--------------|--------|
| Band | WCDMA Band V | | | WCDMA Band II | | |
| Channel | 4132 | 4182 | 4233 | 9262 | 9400 | 9538 |
| Frequency | 826.4 | 836.4 | 846.6 | 1852.4 | 1880.0 | 1907.6 |
| RMC 12.2K | 22.22 | 22.65 | 22.32 | 22.47 | 23.00 | 22.89 |
| HSDPA Subtest-1 | 22.10 | 22.49 | 22.08 | 22.32 | 22.88 | 22.87 |
| HSDPA Subtest-2 | 21.99 | 22.48 | 22.14 | 22.27 | 22.93 | 22.88 |
| HSDPA Subtest-3 | 21.71 | 22.06 | 21.81 | 21.95 | 22.41 | 22.30 |
| HSDPA Subtest-4 | 21.43 | 22.00 | 21.73 | 21.89 | 22.37 | 22.28 |
| HSUPA Subtest-1 | 20.82 | 21.43 | 20.99 | 21.17 | 21.62 | 22.02 |
| HSUPA Subtest-2 | 19.13 | 19.62 | 19.29 | 19.59 | 20.01 | 19.87 |
| HSUPA Subtest-3 | 20.20 | 20.70 | 20.36 | 20.69 | 21.15 | 21.13 |
| HSUPA Subtest-4 | 19.70 | 20.18 | 19.86 | 20.14 | 20.53 | 20.50 |
| HSUPA Subtest-5 | 21.20 | 21.74 | 21.39 | 21.61 | 22.04 | 22.03 |

(*Unit: dBm)

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

| Cellular Band | | | |
|--------------------------|-------------|-----------------|-----------------------|
| Modes | Channel | Frequency (MHz) | Conducted Power (dBm) |
| GSM850 (GPRS 8) | 128 (Low) | 824.2 | 31.83 |
| | 189 (Mid) | 836.4 | 31.80 |
| | 251 (High) | 848.8 | 31.59 |
| GSM850 (EDGE 8) | 128 (Low) | 824.2 | 27.02 |
| | 189 (Mid) | 836.4 | 26.97 |
| | 251 (High) | 848.8 | 26.80 |
| WCDMA Band V (12.2k bps) | 4132 (Low) | 826.4 | 22.22 |
| | 4182 (Mid) | 836.4 | 22.65 |
| | 4233 (High) | 846.6 | 22.32 |

| PCS Band | | | |
|---------------------------|-------------|-----------------|-----------------------|
| Modes | Channel | Frequency (MHz) | Conducted Power (dBm) |
| GSM1900 (GPRS 8) | 512 (Low) | 1850.2 | 28.24 |
| | 661 (Mid) | 1880.0 | 28.33 |
| | 810 (High) | 1909.8 | 28.65 |
| GSM1900 (EDGE 8) | 512 (Low) | 1850.2 | 25.35 |
| | 661 (Mid) | 1880.0 | 25.45 |
| | 810 (High) | 1909.8 | 25.79 |
| WCDMA Band II (12.2k bps) | 9262 (Low) | 1852.4 | 22.47 |
| | 9400 (Mid) | 1880.0 | 23.00 |
| | 9538 (High) | 1907.6 | 22.89 |

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup



**3.2.5 Test Result of ERP**

| GSM850 (GPRS 8) Radiated Power ERP | | | | | | |
|---|---------------------|---------------------|---------------------|---------------------|----------------------|--------------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -18.65 | -48.12 | 0.00 | -1.08 | 28.39 | 0.69 |
| 836.40 | -18.02 | -48.28 | 0.00 | -0.93 | 29.33 | 0.86 |
| 848.80 | -18.69 | -48.35 | 0.00 | -0.76 | 28.90 | 0.78 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -21.04 | -47.97 | 0.00 | -1.08 | 25.85 | 0.38 |
| 836.40 | -20.28 | -48.01 | 0.00 | -0.93 | 26.80 | 0.48 |
| 848.80 | -19.30 | -48.05 | 0.00 | -0.76 | 27.99 | 0.63 |

| GSM850 (EDGE 8) Radiated Power ERP | | | | | | |
|---|---------------------|---------------------|---------------------|---------------------|----------------------|--------------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -24.04 | -48.12 | 0.00 | -1.08 | 23.00 | 0.20 |
| 836.40 | -23.44 | -48.28 | 0.00 | -0.93 | 23.91 | 0.25 |
| 848.80 | -24.04 | -48.35 | 0.00 | -0.76 | 23.55 | 0.23 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -26.02 | -47.97 | 0.00 | -1.08 | 20.87 | 0.12 |
| 836.40 | -25.18 | -48.01 | 0.00 | -0.93 | 21.90 | 0.15 |
| 848.80 | -24.31 | -48.05 | 0.00 | -0.76 | 22.98 | 0.20 |



| WCDMA Band V (WCDMA) Radiated Power ERP | | | | | | |
|---|-------------|-------------|-------------|-------------|--------------|------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40 | -27.15 | -48.12 | 0.00 | -1.08 | 19.89 | 0.10 |
| 836.40 | -27.81 | -48.28 | 0.00 | -0.93 | 19.54 | 0.09 |
| 846.60 | -29.13 | -48.35 | 0.00 | -0.76 | 18.46 | 0.07 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40 | -29.23 | -47.97 | 0.00 | -1.08 | 17.66 | 0.06 |
| 836.40 | -28.66 | -48.01 | 0.00 | -0.93 | 18.42 | 0.07 |
| 846.60 | -29.62 | -48.05 | 0.00 | -0.76 | 17.67 | 0.06 |

**3.2.6 Test Result of EIRP**

| GSM1900 (GPRS 8) Radiated Power EIRP | | | | | | |
|---|---------------------|---------------------|---------------------|---------------------|-----------------------|---------------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -23.91 | -51.88 | 0.00 | 1.96 | 29.93 | 0.98 |
| 1880.00 | -24.26 | -52.99 | 0.00 | 2.00 | 30.73 | 1.18 |
| 1909.80 | -26.47 | -54.28 | 0.00 | 1.98 | 29.79 | 0.95 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -23.90 | -52.13 | 0.00 | 1.96 | 30.19 | 1.04 |
| 1880.00 | -25.70 | -53.17 | 0.00 | 2.00 | 29.47 | 0.89 |
| 1909.80 | -28.69 | -54.13 | 0.00 | 1.98 | 27.42 | 0.55 |

| GSM1900 (EDGE 8) Radiated Power EIRP | | | | | | |
|---|---------------------|---------------------|---------------------|---------------------|-----------------------|---------------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -26.89 | -51.88 | 0.00 | 1.96 | 26.95 | 0.50 |
| 1880.00 | -27.20 | -52.99 | 0.00 | 2.00 | 27.79 | 0.60 |
| 1909.80 | -29.42 | -54.28 | 0.00 | 1.98 | 26.84 | 0.48 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -26.60 | -52.13 | 0.00 | 1.96 | 27.49 | 0.56 |
| 1880.00 | -28.66 | -53.17 | 0.00 | 2.00 | 26.51 | 0.45 |
| 1909.80 | -32.23 | -54.13 | 0.00 | 1.98 | 23.88 | 0.24 |



| WCDMA Band II (WCDMA) Radiated Power EIRP | | | | | | |
|---|-------------|-------------|-------------|-------------|---------------|-------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40 | -30.00 | -51.88 | 0.00 | 1.96 | 23.84 | 0.24 |
| 1880.00 | -31.57 | -52.99 | 0.00 | 2.00 | 23.42 | 0.22 |
| 1907.60 | -32.50 | -54.28 | 0.00 | 1.98 | 23.76 | 0.24 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40 | -29.88 | -52.13 | 0.00 | 1.96 | 24.21 | 0.26 |
| 1880.00 | -33.25 | -53.17 | 0.00 | 2.00 | 21.92 | 0.16 |
| 1907.60 | -34.74 | -54.13 | 0.00 | 1.98 | 21.37 | 0.14 |

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.
3. The RBW was replaced by 10 kHz, due to the spectrum analyzer IF-Filter including an excess of the limit. A worst case correction factor of $10 \log (1\% \text{ BW/measurement RBW})$ was implemented.

3.3.4 Test Setup






3.3.5 Test Result (Plots) of Occupied Bandwidth


| | | | |
|-------------|-------------|---------------|------|
| Band : | GSM 850 | Power Stage : | High |
| Test Mode : | GPRS 8 Link | | |

99% Occupied Bandwidth Plot on Channel 189



Date: 29..JUN.2009 21:54:56

26dB Bandwidth Plot on Channel 189




Date: 29..JUN.2009 21:52:05




| | | | |
|-------------|-------------|---------------|------|
| Band : | GSM 850 | Power Stage : | High |
| Test Mode : | EDGE 8 Link | | |

99% Occupied Bandwidth Plot on Channel 189



Date: 29..JUN.2009 22:27:39


26dB Bandwidth Plot on Channel 189




Date: 29..JUN.2009 22:24:54



| | | | |
|--------------------|-------------|----------------------|------|
| Band : | GSM 1900 | Power Stage : | High |
| Test Mode : | GPRS 8 Link | | |

99% Occupied Bandwidth Plot on Channel 661

Date: 9..JUL.2009 08:51:48


26dB Bandwidth Plot on Channel 661

Date: 29..JUL.2009 22:46:36




| | | | |
|-------------|-------------|---------------|------|
| Band : | GSM 1900 | Power Stage : | High |
| Test Mode : | EDGE 8 Link | | |

99% Occupied Bandwidth Plot on Channel 661



Date: 29..JUN.2009 23:26:06

26dB Bandwidth Plot on Channel 661




Date: 29..JUN.2009 23:23:50




| | | | |
|-------------|--------------|---------------|------|
| Band : | WCDMA Band V | Power Stage : | High |
| Test Mode : | WCDMA Link | | |

99% Occupied Bandwidth Plot on Channel 4182



Date: 30..JUN.2009 00:30:38

26dB Bandwidth Plot on Channel 4182




Date: 30..JUN.2009 00:28:04




| | | | |
|-------------|---------------|---------------|------|
| Band : | WCDMA Band II | Power Stage : | High |
| Test Mode : | WCDMA Link | | |

99% Occupied Bandwidth Plot on Channel 9400



Date: 30..JUN.2009 00:02:54

26dB Bandwidth Plot on Channel 9400



Date: 30..JUN.2009 00:01:28

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3.4.4 Test Setup






3.4.5 Test Result (Plots) of Conducted Band Edge


| | | | |
|-------------|-------------|---------------|------|
| Band : | GSM850 | Power Stage : | High |
| Test Mode : | GPRS 8 Link | | |

Lower Band Edge Plot on Channel 128



Date: 29..TIN.2009 21:57:03

Higher Band Edge Plot on Channel 251




Date: 29..TIN.2009 22:01:43




| | | | |
|-------------|-------------|---------------|------|
| Band : | GSM850 | Power Stage : | High |
| Test Mode : | EDGE 8 Link | | |

Lower Band Edge Plot on Channel 128



Date: 29..TIN.2009 22:29:37

Higher Band Edge Plot on Channel 251




Date: 29..TIN.2009 22:33:38




| | | | |
|-------------|-------------|---------------|------|
| Band : | GSM1900 | Power Stage : | High |
| Test Mode : | GPRS 8 Link | | |

Lower Band Edge Plot on Channel 512



Date: 29..JUN..2009 22:51:02

Higher Band Edge Plot on Channel 810




Date: 29..JUN..2009 23:01:40




| | | | |
|-------------|-------------|---------------|------|
| Band : | GSM1900 | Power Stage : | High |
| Test Mode : | EDGE 8 Link | | |

Lower Band Edge Plot on Channel 512



Date: 29..JUN..2009 23:27:59


Higher Band Edge Plot on Channel 810



Date: 29..JUN..2009 23:31:12


| | | | |
|--------------------|--------------|----------------------|------|
| Band : | WCDMA Band V | Power Stage : | High |
| Test Mode : | WCDMA Link | | |

Lower Band Edge Plot on Channel 4132



Date: 30 JUN 2009 00:35:18

Higher Band Edge Plot on Channel 4233




Date: 30 JUN 2009 00:36:32




| | | | |
|-------------|---------------|---------------|------|
| Band : | WCDMA Band II | Power Stage : | High |
| Test Mode : | WCDMA Link | | |

Lower Band Edge Plot on Channel 9262



Date: 30..JUN..2009 00:06:03

Higher Band Edge Plot on Channel 9538



Date: 30..JUN..2009 00:07:12

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

3.5.4 Test Setup






3.5.5 Test Result (Plots) of Conducted Emission


| | | | |
|-------------|-------------|-----------|-------|
| Band : | GSM850 | Channel : | CH189 |
| Test Mode : | GPRS 8 Link | | |

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 29..TIN.2009 22:05:14


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 29..TIN.2009 22:06:28




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 29.JUN.2009 22:07:07

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 29.JUN.2009 22:08:06




| | | | |
|-------------|-------------|-----------|-------|
| Band : | GSM850 | Channel : | CH189 |
| Test Mode : | EDGE 8 Link | | |

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 29..JUN.2009 22:19:48


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 29..JUN.2009 22:21:11




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 29.JUN.2009 22:21:39

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 29.JUN.2009 22:22:17




| | | | |
|-------------|-------------|-----------|-------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | GPRS 8 Link | | |

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 29..JUN.2009 23:05:04


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 29..JUN.2009 23:06:06




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 29.JUN.2009 23:06:45


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 29.JUN.2009 23:07:21



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 29..JUN.2009 23:07:50




| | | | |
|-------------|-------------|-----------|-------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | EDGE 8 Link | | |

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 29..JUN.2009 23:15:10


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 29..JUN.2009 23:14:35




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 29.JUN.2009 23:11:45


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 29.JUN.2009 23:11:12




Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 29..JUN.2009 23:10:09



| | | | |
|--------------------|--------------|------------------|--------|
| Band : | WCDMA Band V | Channel : | CH4182 |
| Test Mode : | WCDMA Link | | |

Conducted Emission Plot between 30MHz ~ 1GHz


Date: 30..JUN..2009 00:23:15

Conducted Emission Plot between 1GHz ~ 3GHz

Date: 30..JUN..2009 00:24:27




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 30.JUN.2009 00:24:56

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 30.JUN.2009 00:25:21




| | | | |
|-------------|---------------|-----------|--------|
| Band : | WCDMA Band II | Channel : | CH9400 |
| Test Mode : | WCDMA Link | | |

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 30..JUN..2009 00:14:52


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 30..JUN..2009 00:17:19




Conducted Emission Plot between 3GHz ~ 7GHz




Date: 30.JUN.2009 00:18:18

Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 30.JUN.2009 00:18:49

Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 30 JUN 2009 00:19:22

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. Emission level (dBm) = output power + substitution Gain.


3.6.4 Test Setup





3.6.5 Test Result of Field Strength of Spurious Radiated


| | | | |
|-----------------|--|---------------------|------------|
| Band : | GSM850 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 1669 | -55.37 | -13 | -42.37 | -60.59 | -55.22 | 3.39 | 5.39 | H | Pass |
| 2509 | -41.59 | -13 | -28.59 | -49.79 | -41.85 | 3.71 | 6.12 | H | Pass |
| 3346 | -49.69 | -13 | -36.69 | -59.15 | -52.41 | 3.13 | 8.00 | H | Pass |
| 7530 | -41.96 | -13 | -28.96 | -64.64 | -45.81 | 6.22 | 12.22 | H | Pass |




| | | | |
|-----------------|--|---------------------|----------|
| Band : | GSM850 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1669 | -55.58 | -13 | -42.58 | -62.78 | -55.43 | 3.39 | 5.39 | V | Pass |
| 2509 | -36.45 | -13 | -23.45 | -48.2 | -36.71 | 3.71 | 6.12 | V | Pass |
| 3346 | -49.12 | -13 | -36.12 | -60.95 | -51.84 | 3.13 | 8.00 | V | Pass |
| 4175 | -46.27 | -13 | -33.27 | -59.54 | -50.11 | 3.01 | 9.00 | V | Pass |
| 7530 | -40.97 | -13 | -27.97 | -64.46 | -44.82 | 6.22 | 12.22 | V | Pass |




| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM850 | Temperature : | 24~26°C |
| Test Mode : | EDGE 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 1669 | -58.32 | -13 | -45.32 | -63.08 | -58.17 | 3.39 | 5.39 | H | Pass |
| 2509 | -50.75 | -13 | -37.75 | -59.87 | -51.01 | 3.71 | 6.12 | H | Pass |
| 3346 | -51.13 | -13 | -38.13 | -61.79 | -53.85 | 3.13 | 8.00 | H | Pass |




| | | | |
|-----------------|--|---------------------|----------|
| Band : | GSM850 | Temperature : | 24~26°C |
| Test Mode : | EDGE 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 1669 | -57.07 | -13 | -44.07 | -63.43 | -56.92 | 3.39 | 5.39 | V | Pass |
| 2509 | -48.10 | -13 | -35.10 | -58.1 | -48.36 | 3.71 | 6.12 | V | Pass |
| 3346 | -51.51 | -13 | -38.51 | -63.07 | -54.23 | 3.13 | 8.00 | V | Pass |
| 7530 | -40.66 | -13 | -27.66 | -64.02 | -44.51 | 6.22 | 12.22 | V | Pass |




| | | | |
|-----------------|--|---------------------|------------|
| Band : | GSM850 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link + 802.11b Tx CH11 | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1669 | -48.91 | -13 | -35.91 | -56.04 | -48.76 | 3.39 | 5.39 | H | Pass |
| 2509 | -41.90 | -13 | -28.90 | -50.28 | -42.16 | 3.71 | 6.12 | H | Pass |
| 4175 | -49.36 | -13 | -36.36 | -61.55 | -53.2 | 3.01 | 9.00 | H | Pass |
| 7530 | -41.04 | -13 | -28.04 | -65.21 | -44.89 | 6.22 | 12.22 | H | Pass |




| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM850 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link + 802.11b Tx CH11 | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1669 | -51.27 | -13 | -38.27 | -58.28 | -51.12 | 3.39 | 5.39 | V | Pass |
| 2509 | -37.56 | -13 | -24.56 | -49.22 | -37.82 | 3.71 | 6.12 | V | Pass |
| 4175 | -47.72 | -13 | -34.72 | -60.54 | -51.56 | 3.01 | 9.00 | V | Pass |
| 4915 | -47.00 | -13 | -34.00 | -61.71 | -50.84 | 3.72 | 9.71 | V | Pass |
| 7530 | -42.11 | -13 | -29.11 | -65.27 | -45.96 | 6.22 | 12.22 | V | Pass |




| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM1900 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 3760 | -51.09 | -13 | -38.09 | -62.97 | -53.61 | 4.88 | 7.40 | H | Pass |
| 5636 | -40.29 | -13 | -27.29 | -59.62 | -43.55 | 5.55 | 8.81 | H | Pass |




| | | | |
|-----------------|--|---------------------|----------|
| Band : | GSM1900 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -48.00 | -13 | -35.00 | -62.76 | -51.03 | 4.88 | 7.91 | V | Pass |
| 5636 | -36.10 | -13 | -23.10 | -57.09 | -40.32 | 5.55 | 9.77 | V | Pass |
| 9396 | -38.79 | -13 | -25.79 | -65.52 | -43.4 | 6.91 | 11.52 | V | Pass |
| 11280 | -33.34 | -13 | -20.34 | -63.65 | -37.47 | 7.23 | 11.36 | V | Pass |




| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM1900 | Temperature : | 24~26°C |
| Test Mode : | EDGE 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 5636 | -43.75 | -13 | -30.75 | -60.68 | -47.01 | 5.55 | 8.81 | H | Pass |




| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM1900 | Temperature : | 24~26°C |
| Test Mode : | EDGE 8 Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 3760 | -49.16 | -13 | -36.16 | -63.51 | -52.19 | 4.88 | 7.91 | V | Pass |
| 5636 | -40.94 | -13 | -27.94 | -60.96 | -45.16 | 5.55 | 9.77 | V | Pass |
| 11280 | -35.03 | -13 | -22.03 | -65.11 | -39.16 | 7.23 | 11.36 | V | Pass |




| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM1900 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link + 802.11b Tx CH11 | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -50.30 | -13 | -37.30 | -62.4 | -52.82 | 4.88 | 7.40 | H | Pass |
| 5636 | -41.45 | -13 | -28.45 | -60.43 | -44.71 | 5.55 | 8.81 | H | Pass |




| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM1900 | Temperature : | 24~26°C |
| Test Mode : | GPRS 8 Link + 802.11b Tx CH11 | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 3760 | -46.42 | -13 | -33.42 | -61.5 | -49.45 | 4.88 | 7.91 | V | Pass |
| 4928 | -48.05 | -13 | -35.05 | -63.46 | -51.82 | 5.3 | 9.07 | V | Pass |
| 5636 | -41.58 | -13 | -28.58 | -61.07 | -45.8 | 5.55 | 9.77 | V | Pass |




| | | | |
|------------------------|--|----------------------------|------------|
| Band : | WCDMA Band V | Temperature : | 24~26°C |
| Test Mode : | WCDMA Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1669 | -52.94 | -13 | -39.94 | -58.65 | -52.79 | 3.39 | 5.39 | H | Pass |




| | | | |
|------------------------|--|----------------------------|----------|
| Band : | WCDMA Band V | Temperature : | 24~26°C |
| Test Mode : | WCDMA Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |






| | | | |
|------------------------|--|----------------------------|------------|
| Band : | WCDMA Band II | Temperature : | 24~26°C |
| Test Mode : | WCDMA Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -38.56 | -13 | -25.56 | -54.32 | -41.08 | 4.88 | 7.40 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | WCDMA Band II | Temperature : | 24~26°C |
| Test Mode : | WCDMA Link | Relative Humidity : | 41~43% |
| Test Engineer : | Kai Wang | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -42.33 | -13 | -29.33 | -58.83 | -45.36 | 4.88 | 7.91 | V | Pass |
| 5636 | -40.40 | -13 | -27.40 | -60.19 | -44.62 | 5.55 | 9.77 | V | Pass |

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



3.7.6 Test Result of Temperature Variation

| | | | |
|----------------------|---------|------------------|-----|
| Band : | GSM 850 | Channel : | 189 |
| Limit (ppm) : | 2.5 | | |

| Temperature (°C) | GPRS 8 | | EDGE 8 | | Result |
|------------------|-----------------|-----------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -53 | -0.06 | 44 | 0.05 | PASS |
| -20 | -20 | -0.02 | 50 | 0.06 | |
| -10 | -46 | -0.05 | 47 | 0.06 | |
| 0 | 29 | 0.03 | 38 | 0.04 | |
| 10 | 25 | 0.03 | 37 | 0.04 | |
| 20 | 21 | 0.02 | 40 | 0.05 | |
| 30 | -36 | -0.04 | 32 | 0.04 | |
| 40 | -58 | -0.07 | -39 | -0.05 | |
| 50 | -43 | -0.05 | 48 | 0.06 | |

| | | | |
|----------------------|----------|------------------|-----|
| Band : | GSM 1900 | Channel : | 661 |
| Limit (ppm) : | 2.5 | | |

| Temperature (°C) | GPRS 8 | | EDGE 8 | | Result |
|------------------|-----------------|-----------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -69 | -0.04 | -78 | -0.04 | PASS |
| -20 | -53 | -0.03 | 52 | 0.03 | |
| -10 | -93 | -0.05 | -73 | -0.04 | |
| 0 | -74 | -0.04 | 42 | 0.02 | |
| 10 | -35 | -0.02 | -86 | -0.05 | |
| 20 | -70 | -0.04 | -35 | -0.02 | |
| 30 | -49 | -0.03 | -82 | -0.04 | |
| 40 | -70 | -0.04 | -66 | -0.03 | |
| 50 | -66 | -0.03 | -59 | -0.03 | |



| | | | |
|----------------------|--------------|------------------|------|
| Band : | WCDMA Band V | Channel : | 4182 |
| Limit (ppm) : | 2.5 | | |

| Temperature (°C) | WCDMA | | Result |
|---------------------|--------------------|--------------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -50 | -0.06 | PASS |
| -20 | -45 | -0.05 | |
| -10 | -38 | -0.04 | |
| 0 | 15 | 0.02 | |
| 10 | -18 | -0.02 | |
| 20 | -22 | -0.03 | |
| 30 | -19 | -0.02 | |
| 40 | 25 | 0.03 | |
| 50 | 42 | 0.05 | |

| | | | |
|----------------------|---------------|------------------|------|
| Band : | WCDMA Band II | Channel : | 9400 |
| Limit (ppm) : | 2.5 | | |

| Temperature (°C) | WCDMA | | Result |
|---------------------|--------------------|--------------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -39 | -0.02 | PASS |
| -20 | 15 | 0.01 | |
| -10 | -54 | -0.03 | |
| 0 | -48 | -0.03 | |
| 10 | 38 | 0.02 | |
| 20 | 42 | 0.02 | |
| 30 | 36 | 0.02 | |
| 40 | 47 | 0.02 | |
| 50 | 58 | 0.03 | |

**3.7.7 Test Result of Voltage Variation**

| Band & Channel | Mode | Voltage (Volt) | Freq. Dev. (Hz) | Deviation (ppm) | Limit (ppm) | Result |
|-------------------------|--------|----------------|-----------------|-----------------|-------------|--------|
| GSM 850 CH189 | GPRS 8 | 11.4 | 21 | 0.02 | 2.5 | PASS |
| | | BEP | -17 | -0.02 | | |
| | | 15.0 | 23 | 0.03 | | |
| | EDGE 8 | 11.4 | 19 | 0.02 | | |
| | | BEP | 15 | 0.02 | | |
| | | 15.0 | -23 | -0.03 | | |
| GSM 1900 CH661 | GPRS 8 | 11.4 | -42 | -0.02 | | |
| | | BEP | -52 | -0.03 | | |
| | | 15.0 | -46 | -0.02 | | |
| | EDGE 8 | 11.4 | -73 | -0.04 | | |
| | | BEP | -75 | -0.04 | | |
| | | 15.0 | -77 | -0.04 | | |
| WCDMA Band V CH4182 | WCDMA | 11.4 | 18 | 0.02 | | |
| | | BEP | 29 | 0.03 | | |
| | | 15.0 | 34 | 0.04 | | |
| WCDMA Band II CH9400 | WCDMA | 11.4 | -28 | -0.01 | | |
| | | BEP | -34 | -0.02 | | |
| | | 15.0 | -25 | -0.01 | | |

Note:

1. Normal Voltage = 11.4V.
2. Battery End Point (BEP) = 8.0 V.



4 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Due Date | Remark |
|---------------------------|--------------|-----------|------------|--------------------------|------------------|---------------|-----------------------|
| System Simulator | R&S | CMU200 | 116456 | N/A | Jun. 05, 2008 | Jun. 04, 2010 | Conducted (TH02-HY) |
| Spectrum Analyzer | R&S | FSP40 | 100055 | 9kHz~40GHz | Jun. 23, 2009 | Jun. 22, 2010 | Conducted (TH02-HY) |
| Thermal Chamber | TEN BILLION | TTH-D35P | TBN-930701 | N/A | Aug. 01, 2008 | Jul. 31, 2009 | Conducted (TH02-HY) |
| Bilog Antenna | SCHAFFNER | CBL6111C | 2726 | 30MHz~1GHz | Nov. 20, 2008 | Nov. 19, 2009 | Radiation (03CH07-HY) |
| Spectrum Analyzer | R&S | FSP | 101067 | 9kHz~30GHz | Dec. 02, 2008 | Dec. 01, 2009 | Radiation (03CH07-HY) |
| Double Ridge Horn Antenna | ESCO | 3117 | 00075962 | 1G~18GHz | Aug. 18, 2008 | Aug. 17, 2009 | Radiation (03CH07-HY) |
| Pre Amplifier | Agilent | 8449B | 3008A02362 | 1G~26.5GHz | Dec. 17, 2008 | Dec. 16, 2009 | Radiation (03CH07-HY) |
| Pre Amplifier | COM-POWER | PA-103A | 161241 | 10~1000MHz. 32dB.GAIN | Mar. 27, 2009 | Mar. 26, 2010 | Radiation (03CH07-HY) |
| Double Ridge Horn Antenna | ESCO | 3117 | 00066584 | 1G~18GHz | Aug. 06, 2008 | Aug. 05, 2009 | Radiation (03CH07-HY) |
| Loop Antenna | R&S | HFH2-Z2 | 860004/001 | 9 kHz~30 MHz | May 22, 2008 | May 21, 2010 | Radiation (03CH07-HY) |
| System Simulator | R&S | CMU200 | 117997 | N/A | May 14, 2009 | May 13, 2011 | Radiation (03CH07-HY) |

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| Contribution | Uncertainty of x_i | | $u(x_i)$ |
|--|----------------------|--------------------------|----------|
| | dB | Probability Distribution | |
| Receiver reading | 0.41 | Normal(k=2) | 0.21 |
| Antenna factor calibration | 0.83 | Normal(k=2) | 0.42 |
| Cable loss calibration | 0.25 | Normal(k=2) | 0.13 |
| Pre Amplifier Gain calibration | 0.27 | Normal(k=2) | 0.14 |
| RCV/SPA specification | 2.50 | Rectangular | 0.72 |
| Antenna Factor Interpolation for Frequency | 1.00 | Rectangular | 0.29 |
| Site imperfection | 1.43 | Rectangular | 0.83 |
| Mismatch | +0.39/-0.41 | U-shaped | 0.28 |
| Combined standard uncertainty Uc(y) | 1.27 | | |
| Measuring uncertainty for a level of confidence of 95% U=2Uc(y) | 2.54 | | |

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

| Contribution | Uncertainty of x_i | | $u(x_i)$ | C_i | $C_i * u(x_i)$ |
|---|----------------------|--------------------------|----------|-------|----------------|
| | dB | Probability Distribution | | | |
| Receiver reading | ±0.10 | Normal(k=1) | 0.10 | 1 | 0.10 |
| Antenna factor calibration | ±1.70 | Normal(k=2) | 0.85 | 1 | 0.85 |
| Cable loss calibration | ±0.50 | Normal(k=2) | 0.25 | 1 | 0.25 |
| Receiver Correction | ±2.00 | Rectangular | 1.15 | 1 | 1.15 |
| Antenna Factor Directional | ±1.50 | Rectangular | 0.87 | 1 | 0.87 |
| Site imperfection | ±2.80 | Triangular | 1.14 | 1 | 1.14 |
| Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2)$ | +0.34/-0.35 | U-shaped | 0.244 | 1 | 0.244 |
| Combined standard uncertainty Uc(y) | 2.36 | | | | |
| Measuring uncertainty for a level of confidence of 95% U=2Uc(y) | 4.72 | | | | |

6 Certification of TAF Accreditation



Certificate No. : L1190-090417

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

| | |
|--------------------------------|--|
| Accreditation Criteria | : ISO/IEC 17025:2005 |
| Accreditation Number | : 1190 |
| Originally Accredited | : December 15, 2003 |
| Effective Period | : January 10, 2007 to January 09, 2010 |
| Accredited Scope | : Testing Field, see described in the Appendix |
| Specific Accreditation Program | : Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities |



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : April 17, 2009

P1, total 20 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix



Appendix A. Photographs of EUT

Please refer to Sporton report number EP961822 as below.