

# **FCC Test Report**

FCC ID : XU8TEW817DTR

: AC750 Wireless Travel Router **Equipment** 

Model No. TEW-817DTR

**Brand Name** : TRENDnet

**Applicant** : TRENDnet, Inc.

**Address** : 20675 Manhattan Place, Torrance, CA 90501,

USA

: 47 CFR FCC Part 15.247 Standard

**Received Date** : Sep. 04, 2014

**Tested Date** : Sep. 04 ~ Sep. 10, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

**Testing Laboratory** 

Page: 1 of 62

Report No.: FR4N1401AC



## **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	7
1.4	The Equipment List	
1.5	Test Standards	
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	
3	TRANSMITTER TEST RESULTS	11
3.1	Conducted Emissions	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	
3.4	Power Spectral Density	19
3.5	Unwanted Emissions into Restricted Frequency Bands	21
3.6	Emissions in Non-Restricted Frequency Bands	49
4	TEST LABORATORY INFORMATION	62



## **Release Record**

Report No.	Version	Description	Issued Date
FR4N1401AC	Rev. 01	Initial issue	Mar. 06, 2015
FR4N1401AC	Rev. 02	Removed model of antenna. (Page 5)	Mar. 27, 2015

Report No.: FR4N1401AC Page: 3 of 62



## **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.532MHz 42.87 (Margin -3.13dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2483.50MHz 52.99 (Margin -1.01dB) – AV 2390.00MHz 52.99 (Margin -1.01dB) – AV	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 28.44	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR4N1401AC Page: 4 of 62



## 1 General Description

## 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information								
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS			
2400-2483.5	b	2412-2462	1-11 [11]	1 NOTE 4	1-11 Mbps			
2400-2483.5	g	2412-2462	1-11 [11]	1 NOTE 4	6-54 Mbps			
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15			
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	MCS 0-15			

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.

Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.

Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

Note 4: 802.11b/g is transmitting signal through chain 0 only.

#### 1.1.2 Antenna Details

Ant.	Type	Connector	(	Operating Freque	encies (MHz) / Ar	ntenna Gain (dBi	)
No.	1 300	Comicotor	2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
1	PIFA	N/A	2	3	3	3	3

## 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	100-240Vac
-------------------	------------

#### 1.1.4 Accessories

N/A

Report No.: FR4N1401AC Page: 5 of 62



## 1.1.5 Channel List

Frequency	band (MHz)	2400~	2483.5	
802.11 b /	g / n HT20	802.11n HT40		
Channel	Channel Frequency(MHz)		Frequency(MHz)	
1	2412	3	2422	
2	2417	4	2427	
3	2422	5	2432	
4	2427	6	2437	
5	2432	7	2442	
6	2437	8	2447	
7	2442	9	2452	
8	2447			
9	2452			
10	2457			
11	2462			

## 1.1.6 Test Tool and Duty Cycle

Test Tool	MT7620, V1.0.6.0				
	Mode	Duty cycle (%)	Duty factor (dB)		
	11b	100.00%	0.00		
Duty Cycle and Duty Factor	11g	99.93%	0.00		
	HT20	99.63%	0.02		
	HT40	98.26%	0.08		

Report No.: FR4N1401AC Page: 6 of 62




## 1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	14
11b	2437	12
11b	2462	12
11g	2412	10
11g	2437	20
11g	2462	11
HT20	2412	0F//13
HT20	2437	20/25
HT20	2462	10/15
HT40	2422	08/0D
HT40	2437	12/18
HT40	2452	09/0F

## 1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	Signal cable / Length (m)	
1	Notebook	DELL	Latitude E6440	3NXMD12	RJ45, 10m non-shielded w/o core	

## 1.3 Test Setup Chart



Report No.: FR4N1401AC Page: 7 of 62



## 1.4 The Equipment List

Test Item	Conducted Emission							
Test Site	Conduction room 1 / (0	Conduction room 1 / (CO01-WS)						
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration U							
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014			
LISN	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014			
LISN (Support Unit)	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014			
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 23, 2014	Apr. 22, 2015			
50 ohm terminal (Support Unit)	NA	50	04	Apr. 18, 2014	Apr. 17, 2015			
Measurement Software	AUDIX	e3	6.120210k	NA	NA			
Note: Calibration Inte	rval of instruments listed	d above is one year.						

Test Item	Radiated Emission	Radiated Emission						
Test Site	966 chamber1 / (03Cl	966 chamber1 / (03CH01-WS)						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101498	Jan. 25, 2014	Jan. 24, 2015			
Receiver	R&S	ESR3	101658	Jan. 10, 2014	Jan. 09, 2015			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 03, 2014	Jan. 02, 2015			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 13, 2014	Feb. 12, 2015			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014			
Amplifier	Burgeon	BPA-530	100219	Nov. 22, 2013	Nov. 21, 2014			
Preamplifier	Agilent	83017A	MY39501308	Dec. 16, 2013	Dec. 15, 2014			
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 16, 2013	Dec. 15, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 16, 2013	Dec. 15, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 16, 2013	Dec. 15, 2014			
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 16, 2013	Dec. 15, 2014			
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 16, 2013	Dec. 15, 2014			
Measurement Software	AUDIX	e3	6.120210g	NA	NA			
Note: Calibration Inte	rval of instruments liste	d above is one year.						

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014			
Note: Calibration Interval of instruments listed above is two year.								

Report No.: FR4N1401AC Page: 8 of 62



Test Item	RF Conducted								
Test Site	(TH01-WS)	(TH01-WS)							
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until				
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015				
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014				
Power Sensor	Anritsu	MA2411B	1027366	Oct. 24, 2013	Oct. 23, 2014				
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA				
Note: Calibration Interval of instruments listed above is one year.									

#### 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty							
Parameters	Uncertainty						
Bandwidth	±34.134 Hz						
Conducted power	±0.808 dB						
Frequency error	±34.134 Hz						
Temperature	±0.6 °C						
Conducted emission	±2.670 dB						
AC conducted emission	±2.92 dB						
Radiated emission ≤ 1GHz	±3.26 dB						
Radiated emission > 1GHz	±4.94 dB						

Report No.: FR4N1401AC Page: 9 of 62



## 2 Test Configuration

## 2.1 Testing Condition

Test Item Test Site		Ambient Condition	Tested By	
AC Conduction	CO01-WS	20°C / 65%	Peter Lin	
Radiated Emissions	03CH01-WS	22°C / 61-64%	Aska Huang	
RF Conducted	TH01-WS	23°C / 64%	Brad Wu	

FCC site registration No.: 657002IC site registration No.: 10807A-1

## 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	HT20	2437	MCS 0	
Radiated Emissions ≤1GHz	HT20	2437	MCS 0	
Radiated Emissions >1GHz	11b	2412 / 2437 / 2462	1 Mbps	
Maximum Output Power	11g	2412 / 2437 / 2462	6 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	MCS 0	
Power spectral density	HT40	2422 / 2437 / 2452	MCS 0	

#### NOTE:

Report No.: FR4N1401AC Page: 10 of 62

<sup>1.</sup> The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Z-plane** results were found as the worst case and were shown in this report.



## 3 Transmitter Test Results

#### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit							
Frequency Emission (MHz) Quasi-Peak Average							
0.15-0.5	66 - 56 *	56 - 46 *					
0.5-5	56	46					
5-30 60 50							
Note 1: * Decreases with the logarithm of the frequency.							

#### 3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

#### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR4N1401AC Page: 11 of 62




#### 3.1.4 Test Result of Conducted Emissions



Report No.: FR4N1401AC Page: 12 of 62





Report No.: FR4N1401AC Page: 13 of 62



## 3.2 6dB and Occupied Bandwidth


#### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

#### 3.2.2 Test Procedures

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

#### 3.2.3 Test Setup




Report No.: FR4N1401AC Page: 14 of 62



## 3.2.4 Test Result of 6dB and Occupied Bandwidth


Modulation	NI	Eron (MU=)	6dB Bandwidth (MHz)				Limit (Idua)
Mode	N <sub>TX</sub>	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Limit (kHz)
11b	1	2412	10.09				500
11b	1	2437	10.09				500
11b	1	2462	10.03				500
11g	1	2412	16.35				500
11g	1	2437	16.35				500
11g	1	2462	16.35				500
HT20	2	2412	17.57	17.10			500
HT20	2	2437	17.04	17.04			500
HT20	2	2462	17.33	17.57			500
HT40	2	2422	36.29	36.29			500
HT40	2	2437	36.29	36.29			500
HT40	2	2452	36.29	36.29			500



Report No.: FR4N1401AC Page: 15 of 62



Modulation	N.	Freq.		99% Occupied E	Bandwidth (MHz)	
Mode	N <sub>TX</sub>	(MHz)	Chain 0	Chain 1	Chain 2	Chain 3
11b	1	2412	12.45			
11b	1	2437	12.37			
11b	1	2462	12.37			
11g	1	2412	16.97			
11g	1	2437	20.84			
11g	1	2462	16.98			
HT20	2	2412	17.76	17.74		
HT20	2	2437	18.58	18.27		
HT20	2	2462	17.77	17.75		
HT40	2	2422	36.68	36.68	36.68	
HT40	2	2437	36.80	36.76		
HT40	2	2452	36.76	36.76		



Report No.: FR4N1401AC Page: 16 of 62



### 3.3 RF Output Power

#### 3.3.1 Limit of RF Output Power

Con	duct	ed power shall not exceed 1Watt.
$\boxtimes$	Ant	enna gain <= 6dBi, no any corresponding reduction is in output power limit.
	Ant	enna gain > 6dBi
		Non Fixed, point to point operations.  The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
		Fixed, point to point operations Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
		Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

#### 3.3.2 Test Procedures

Maximum Peak Conducted Output Power

#### □ Spectrum analyzer

- 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
- 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
- 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.

#### Nower meter

- A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power (For reference only)

#### Nower meter

 A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

#### 3.3.3 Test Setup



Report No.: FR4N1401AC Page: 17 of 62



## 3.3.4 Test Result of Maximum Output Power

Modulation Mode	N <sub>TX</sub>	Freq.	Peak	k conducted output power (dBm)		Total Power	Total Power	Limit	
Wiode		(IVITIZ)	Chain 0	Chain 1	Chain 2	Chain 3	(mW)	(dBm)	(dBm)
11b	1	2412	23.49				223.357	23.49	30.00
11b	1	2437	22.98				198.609	22.98	30.00
11b	1	2462	22.76				188.799	22.76	30.00
11g	1	2412	25.10				323.594	25.10	30.00
11g	1	2437	26.31				427.563	26.31	30.00
11g	1	2462	24.92				310.456	24.92	30.00
HT20	2	2412	24.12	24.17			519.442	27.16	30.00
HT20	2	2437	25.49	25.37			698.347	28.44	30.00
HT20	2	2462	23.89	24.09			501.355	27.00	30.00
HT40	2	2422	21.36	21.30			271.669	24.34	30.00
HT40	2	2437	23.88	24.15			504.359	27.03	30.00
HT40	2	2452	21.66	21.88			300.725	24.78	30.00

Modulation Mode	N <sub>TX</sub>	Freq.	Conduc	Conducted (average) output power (dBm)		Total Power	Total Power	Limit	
Wiode		(MHz)	Chain 0	Chain 1	Chain 2	Chain 3	(mW)	(dBm)	(dBm)
11b	1	2412	20.28				106.660	20.28	30.00
11b	1	2437	19.52				89.536	19.52	30.00
11b	1	2462	19.41				87.297	19.41	30.00
11g	1	2412	18.12				64.863	18.12	30.00
11g	1	2437	22.47				176.604	22.47	30.00
11g	1	2462	18.22				66.374	18.22	30.00
HT20	2	2412	16.68	16.85			94.976	19.78	30.00
HT20	2	2437	20.76	20.65			235.269	23.72	30.00
HT20	2	2462	16.55	16.72			92.175	19.65	30.00
HT40	2	2422	13.82	13.71			47.595	16.78	30.00
HT40	2	2437	17.18	17.42			107.447	20.31	30.00
HT40	2	2452	14.27	14.29			53.584	17.29	30.00

Note: Conducted average output power is for reference only.

Report No.: FR4N1401AC Page: 18 of 62



### 3.4 Power Spectral Density

#### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

#### 3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - Set the RBW = 30kHz, VBW = 100kHz.
  - Detector = Peak, Sweep time = auto couple.
  - 3. Trace mode = max hold, allow trace to fully stabilize.
  - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - 1. Set the RBW = 100kHz, VBW = 300 kHz.
  - 2. Detector = RMS, Sweep time = auto couple.
  - 3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
  - 4. Perform the measurement over a single sweep.
  - 5. Use the peak marker function to determine the maximum amplitude level.

#### 3.4.3 Test Setup




Report No.: FR4N1401AC Page: 19 of 62



## 3.4.4 Test Result of Power Spectral Density

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Total Power Spectral Density (dBm/30kHz)	Limit (dBm/3kHz)
11b	1	2412	-8.68	8.00
11b	1	2437	-9.47	8.00
11b	1	2462	-9.67	8.00
11g	1	2412	-8.14	8.00
11g	1	2437	-1.82	8.00
11g	1	2462	-8.64	8.00
HT20	2	2412	-6.40	8.00
HT20	2	2437	-2.44	8.00
HT20	2	2462	-6.34	8.00
HT40	2	2422	-12.54	8.00
HT40	2	2437	-9.39	8.00
HT40	2	2452	-10.36	8.00

Note: Test result for HT20 / HT40 is bin-by-bin summing measured value of each TX port.



Report No.: FR4N1401AC Page: 20 of 62



## 3.5 Unwanted Emissions into Restricted Frequency Bands

#### 3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit									
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)						
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300						
0.490~1.705	24000/F(kHz)	33.8 - 23	30						
1.705~30.0	30	29	30						
30~88	100	40	3						
88~216	150	43.5	3						
216~960	200	46	3						
Above 960	500	54	3						

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:** 

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.5.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR4N1401AC Page: 21 of 62



## 3.5.3 Test Setup




Report No.: FR4N1401AC

Page: 22 of 62



#### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR4N1401AC Page: 23 of 62



Modulation	HT20				Test Freq. (MHz) 243				2437				
Polarization				Vertical									
	90	Leve	el (dBu\	//m)									
	80												
	70												
	60										FCC	CLAS	S.B
	50												
							6						
	40						Ĭ						
	30	1	2	3 4		5							_
	20												
	10												
	0												
		30	100.	20	0. 30	0. 4		00. 60 ency (MHz)	0. 700.	. 800.	90	00.	1000
			г						F	D l-		МТ	т
			Fr	eq. t	level	Limit	Margin	reading	Factor	Remark		NT ligh	Turn Table
				1Hz	dBuV/m	dBuV/	m dB	dBuV	dB			m m	deg
					aza,,								8
	1		- 5	0.24	27.99	40.00	-12.01	44.53	-16.54	Peak			
	2		11	0.68	30.42	43.50	-13.08	50.53	-20.11	Peak			
	3		14	1.79			-14.02	46.66	-17.18	Peak			
	4			3.67			-12.66		-19.62	Peak			
	5						-16.18		-15.62	Peak			
	6		41	1.26	38.99	46.00	-7.01	52.37	-13.38	Peak			

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR4N1401AC Page: 24 of 62



### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR4N1401AC Page: 25 of 62





49.88

4.99

Peak

Note 1: Emission Level  $(dBuV/m) = SA Reading (dBuV/m) + Factor^* (dB)$ 

\*Factor includes antenna factor, cable loss and amplifier gain

4824.00 54.87 74.00 -19.13

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 26 of 62

Report Version: Rev. 02

6



Modulation	11b		Test Freq. (N	2437					
Polarization	Horizontal								
90 Level (dBu	V/m)								
80					FCC CLASS-B				
70									
60 24									
33	6 8			FCC	C CLASS-B (AVG)				
50	<del>  5   1</del>								
40									
30									
20									
10									
"									
1000 4	000. 6000. 80	00. 10000. 12000.	. 14000. 16000 ncy (MHz)	0. 18000. 20000.	. 22000. 2500				
г.	F-dd			-t Domenia	: ANT Tur				
FI	level	Limit Margin	reading	ctor Remark	High Tab				
1		dBuV/m dB		dB	cm deg				
		54.00 -10.25		3.68 Averag	ge				
	90.00 57.52 83.50 44.54	74.00 -16.48		3.68 Peak					
		74.00 -9.46		3.30 Averag 3.30 Peak	ge				
	74.00 47.91			5.10 Averag	e				
	74.00 51.41			5.10 Peak					
		54.00 -4.14		9.33 Averag	ge				
8 73:	11.00 55.77	74.00 -18.23	46.44	9.33 Peak					

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 27 of 62

Report Version: Rev. 02



Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical		




		Emission level		Ū	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	43.83	54.00	-10.17	47.51	-3.68	Average		
2	2390.00	57.09	74.00	-16.91	60.77	-3.68	Peak		
3	2483.50	43.19	54.00	-10.81	46.49	-3.30	Average		
4	2483.50	56.43	74.00	-17.57	59.73	-3.30	Peak		
5	4874.00	52.85	54.00	-1.15	47.75	5.10	Average		
6	4874.00	54.78	74.00	-19.22	49.68	5.10	Peak		
7	7311.00	51.54	54.00	-2.46	42.21	9.33	Average		
8	7311.00	55.71	74.00	-18.29	46.38	9.33	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 28 of 62





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 29 of 62



Modulation		11b	11b			Test Freq. (MHz)			2462		
Polarization	Vert	Vertical				1					
90	Level	(dBuV/m)									
80											
00									FCC CLAS	S-B	
70											
60		2									
-		4	6 5					FCC C	LASS-B (A	(VG)	
50		1	+								
40											
30											
20											
10											
0		4000	2000			44000 4	2000 400			05000	
	1000	4000.	6000. 80	000. 100		. 14000. 1 ency (MHz)	6000. 1800	00. 20000. 2	22000.	25000	
		Freq. I	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	
		-	level			reading			High	Table	
		MHz	dBuV/m	dBuV/ı	n dB	dBuV	dB		cm	deg	
1		2483.50	43.95	54.00	-10.05	47.25	-3.30	Average			
2		2483.50				62.57	-3.30	Peak			
3		4924.00				47.31	5.20	Average			
					40 47	40 33					

5.20

9.39

9.39

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

4924.00 54.53 74.00 -19.47 49.33 7386.00 50.67 54.00 -3.33 41.28 7386.00 55.94 74.00 -18.06 46.55

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 30 of 62


Report Version: Rev. 02

4

5



### 3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR4N1401AC Page: 31 of 62






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 32 of 62





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 33 of 62



Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		
. Lev	vel (dBuV/m)		




	Freq. 6	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	45.84	54.00	-8.16	49.52	-3.68	Average		
2	2390.00	60.16	74.00	-13.84	63.84	-3.68	Peak		
3	2483.50	45.92	54.00	-8.08	49.22	-3.30	Average		
4	2483.50	61.27	74.00	-12.73	64.57	-3.30	Peak		
5	4874.00	35.43	54.00	-18.57	30.33	5.10	Average		
6	4874.00	47.34	74.00	-26.66	42.24	5.10	Peak		
7	7311.00	52.89	54.00	-1.11	43.56	9.33	Average		
8	7311.00	67.60	74.00	-6.40	58.27	9.33	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 34 of 62






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 35 of 62






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 36 of 62



## 3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR4N1401AC Page: 37 of 62



Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		
90 Level (dBu\	//m)		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1608.00	43.46	54.00	-10.54	50.21	-6.75	Average		
2	1608.00	49.97	74.00	-24.03	56.72	-6.75	Peak		
3	2390.00	52.74	54.00	-1.26	56.42	-3.68	Average		
4	2390.00	72.84	74.00	-1.16	76.52	-3.68	Peak		
5	4824.00	36.41	54.00	-17.59	31.42	4.99	Average		
6	4824.00	50.23	74.00	-23.77	45.24	4.99	Peak		

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 38 of 62



Modulation			HT2	0		-	Test Freq	. (MHz)	2	2437	
Polarization	)		Hori	zontal		<b>.</b>			1		
	90	Level	(dBuV/m)								_
	80										
	ou									FCC CLAS	S-B
	70			8							
	60		4								
			6	+ +					FCC (	CLASS-B (A	VG)
	50										
	40	)——	3								
	20										
	30	,									
	20										_
	10										
	(	1000	4000.	6000. 8	000. 100			5000. 180	00. 20000.	22000.	25000
							ncy (MHz)				
			Freq. I			Margin		Factor	Remark	ANT	Turn
			MHz	level	dBuV/r	n dB	reading dBuV	dB		High cm	Table deg
			11112	ubuv/III	ubuv/i	ıı ub	abav	ub		CIII	ueg
	1		2390.00	46.69	54.00	-7.31	50.37	-3.68	Average		
	2		2390.00			-16.14	61.54	-3.68	Peak		
	3		2483.50				50.22	-3.30	Average		
	4		2483.50				62.44	-3.30	Peak		
	5 6		4874.00 4874.00				36.59 49.72	5.10 5.10	Average Peak		
			7311.00				42.85	9.33			
	7		/311.44	57.18	54.00	-1.87	47.85	9.33	Average		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 39 of 62

Report Version: Rev. 02



Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	44.53	54.00	-9.47	48.21	-3.68	Average		
2	2390.00	57.90	74.00	-16.10	61.58	-3.68	Peak		
3	2483.50	44.23	54.00	-9.77	47.53	-3.30	Average		
4	2483.50	57.02	74.00	-16.98	60.32	-3.30	Peak		
5	4874.00	41.98	54.00	-12.02	36.88	5.10	Average		
6	4874.00	53.53	74.00	-20.47	48.43	5.10	Peak		
7	7311.00	51.67	54.00	-2.33	42.34	9.33	Average		
8	7311.00	66.76	74.00	-7.24	57.43	9.33	Peak		

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 40 of 62



2

3

4

5

6

Modulation		HT	20			Test Fre	q. (MHz)		2462				
Polarization		Hor	izontal		•								
	90 Leve	l (dBuV/m)											
	80												
		2							FCC CLAS	SS-B			
	70												
	60												
		1 4	6					FCC	CLASS-B (A	WG)			
	50												
	40	-	5							_			
	30												
	30												
	20												
	10												
	01000	4000.	6000. 80	00. 100			16000. 180	00. 20000.	22000.	25000			
					Frequ	ency (MHz)							
		Freq.		Limit	Margir	n SA		Remark	ANT	Turn			
			level			reading			High				
		MHz	dBuV/m	dBuV/n	ı dB	dBuV	dB		cm	deg			
	1	2483.50	52.23	54.00	-1.77	55.53	-3.30	Average					
	_	2403.30	52.25	34.00	1.,,	55.55	3.50	Ave. uge					

76.23

31.53

46.52

30.73

45.44

-3.30

5.20

5.20

9.39

9.39

Peak Average

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

2483.50 72.93 74.00 -1.07

4924.00 36.73 54.00 -17.27


4924.00 51.72 74.00 -22.28 7386.00 40.12 54.00 -13.88 7386.00 54.83 74.00 -19.17

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 41 of 62



Modulation		HT20	Test Freq. (MHz) 2462					62		
Polarization		Vertical								
90	Level (dBu	//m)								
90	Level (dBu	//m)								




		Emission level		Ū	SA reading		Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		CM	deg
1	2483.50	50.23	54.00	-3.//	53.53	-3.30	Average		
2	2483.50	71.34	74.00	-2.66	74.64	-3.30	Peak		
3	4924.00	38.82	54.00	-15.18	33.62	5.20	Average		
4	4924.00	51.73	74.00	-22.27	46.53	5.20	Peak		
5	7386.00	39.82	54.00	-14.18	30.43	9.39	Average		
6	7386.00	54.01	74.00	-19.99	44.62	9.39	Peak		

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 42 of 62



#### Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40 3.5.8



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR4N1401AC Page: 43 of 62



Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		
90 Level (dBu	V/m)		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
4	2200 00		<u></u>	4 07			A		
1	2390.00	52.13	54.00	-1.87	55.81	-3.68	Average		
2	2390.00	67.56	74.00	-6.44	71.24	-3.68	Peak		
3	4844.00	32.52	54.00	-21.48	27.49	5.03	Average		
4	4844.00	45.57	74.00	-28.43	40.54	5.03	Peak		
5	7266.00	36.92	54.00	-17.08	27.62	9.30	Average		
6	7266.00	49.57	74.00	-24.43	40.27	9.30	Peak		

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 44 of 62



Modulation			HT4	.0		-	Test Fre	q. (MHz)	:	2437				
Polarization			Hori	zontal										
	90Le	vel (dE	BuV/m)											
	80									FCC CLAS	S-B			
	70	24												
	-													
	60	1							FCC	CLASS-B (A	WG)			
	50	В	- 6	8										
	40													
	40		5											
	30										-			
	20													
	20													
	10													
	0													
	<b>1</b> 0	000	4000.	6000.	8000. 100		. 14000. 1 ncy (MHz)	16000. 180	00. 20000.	22000.	25000			
			_			_					_			
			Freq.	tmissio level		Margin	SA		Remark	ANT	Turn Table			
			MHz		dBuV/ı	n dB	reading dBuV	dB		High cm	deg			
			PHIZ	ubuv/III	ubuv/i	ii ub	ubuv	ub		CIII	ueg			
	1	2	390.00	52.86	54.00	-1.14	56.54	-3.68	Average					
	2			68.93		-5.07	72.61	-3.68	Peak					
	3	2	483.50	50.62	54.00	-3.38	53.92	-3.30	Average					
	4	2	483.50	68.15	74.00	-5.85	71.45	-3.30	Peak					
	5	4	874.00	34.72	54.00	-19.28	29.62	5.10	Average					
	<u> </u>	4	07/ 00	/7 EO	7/ 00	26 42	12 10	E 10	Dook					

42.48

5.10

9.33

9.33

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

4874.00 47.58 74.00 -26.42

7311.00 38.26 54.00 -15.74 28.93

7311.00 50.95 74.00 -23.05 41.62

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Report No.: FR4N1401AC Page: 45 of 62

Report Version: Rev. 02

7



Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	49.19	54.00	-4.81	52.87	-3.68	Average		
2	2390.00	64.74	74.00	-9.26	68.42	-3.68	Peak		
3	2483.50	47.20	54.00	-6.80	50.50	-3.30	Average		
4	2483.50	65.92	74.00	-8.08	69.22	-3.30	Peak		
5	4874.00	34.58	54.00	-19.42	29.48	5.10	Average		
6	4874.00	45.96	74.00	-28.04	40.86	5.10	Peak		
7	7311.00	36.99	54.00	-17.01	27.66	9.33	Average		
8	7311.00	49.76	74.00	-24.24	40.43	9.33	Peak		

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 46 of 62



Modulation		HT40				Test Freq. (MHz)				452				
Polarization		Horizontal												
90 <mark>L</mark>	evel (dE	BuV/m)												
80														
80												ı	CC CLAS	S-B
70	2									+				
60														
				6								FCC CL	ASS-B (A	WG)
50		4		Ĭ										
40														
		3												
30														
20														
10														
10														
0 <mark>1</mark>	000	4000.	6000.	8000.	100	00. 1200 Frequ	0. 14		6000.	1800	0. 20	000. 22	2000.	25000
		Freq. I	- Fmissi	on Li	mit			, БА	Fact	or	Rema	ark	ANT	Turi
			leve			i iui 61		nding		01	TTC.	ui k	High	Tab
		MHz	dBuV/ı	m dB	uV/m	dB		BuV	dB				cm	deg
1	2	483.50	52.9	- <u>-</u>	90	-1.02	56	5.28	-3.	30	Δνει	rage		
2		483.50				-3.97		3.33	-3.		Peal	_		
3	4	904.00				-21.23		7.61	5.			rage		
4	4	904.00	45.5	1 74	.00	-28.49	46	.35	5.	16	Peal	k _		
5		356.00						3.23	9.			rage		
6	7	356.00	49.9	1 74	.00	-24.09	46	.55	9.	36	Peal	k		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 47 of 62

Report Version: Rev. 02



Modulation	HT40		Test Freq.	24	2452						
Polarization	Vertical										
90 Level (dBu	V/m)										
30											



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	50.99	54.00	-3.01	54.29	-3.30	Average		
2		66.15			69.45	-3.30	Peak		
3	4904.00	33.41	54.00	-20.59	28.25	5.16	Average		
4	4904.00	45.54	74.00	-28.46	40.38	5.16	Peak		
5	7356.00	37.99	54.00	-16.01	28.63	9.36	Average		
6	7356.00	50.81	74.00	-23.19	41.45	9.36	Peak		

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR4N1401AC Page: 48 of 62



## 3.6 Emissions in Non-Restricted Frequency Bands

## 3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.6.3 Test Procedures


#### Reference level measurement

- Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Use the peak marker function to determine the maximum PSD level

#### **Emission level measurement**

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Scan Frequency range is up to 25GHz
- 4. Use the peak marker function to determine the maximum amplitude level

### 3.6.4 Test Setup



### 3.6.5 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding 10  $log(N_{ANT})$  since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

Report No.: FR4N1401AC Page: 49 of 62




## 3.6.6 Unwanted Emissions into Non-Restricted Frequency Bands

#### 802.11b




Report No.: FR4N1401AC Report Version: Rev. 02






Report No.: FR4N1401AC Page: 51 of 62






Report No.: FR4N1401AC Page: 52 of 62






Report No.: FR4N1401AC Page: 53 of 62





Report No.: FR4N1401AC Page: 54 of 62






Report No.: FR4N1401AC Page: 55 of 62




## 802.11n HT20




Report No.: FR4N1401AC Page: 56 of 62





Report No.: FR4N1401AC Page: 57 of 62






Report No.: FR4N1401AC Page: 58 of 62




## 802.11n HT40




Report No.: FR4N1401AC Page: 59 of 62





Report No.: FR4N1401AC Page: 60 of 62





Report No.: FR4N1401AC Page: 61 of 62



# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C. Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

<u>==END</u>==

Report No.: FR4N1401AC Page: 62 of 62