

FCC TEST REPORT

REPORT NO.: RF951206L13

MODEL NO.: Q802XKG

RECEIVED: Dec. 27, 2006

TESTED: Jan. 09 ~ Jan. 23, 2007

ISSUED: Jan. 25, 2007

APPLICANT: Qcom Technology Inc.

ADDRESS: 7F, NO. 178, MING CHUAN E. RD. SEC 3,
TAIPEI TAIWAN R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 66 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



Table of Contents

1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3.	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	7
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:	8
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	9
3.4	DESCRIPTION OF SUPPORT UNITS	10
4.	TEST TYPES AND RESULTS	11
4.1	CONDUCTED EMISSION MEASUREMENT	11
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	11
4.1.2	TEST INSTRUMENTS	11
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD	12
4.1.5	TEST SETUP	13
4.1.6	EUT OPERATING CONDITIONS	13
4.1.7	TEST RESULTS	14
4.2	RADIATED EMISSION MEASUREMENT	20
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	20
4.2.2	TEST INSTRUMENTS	21
4.2.3	TEST PROCEDURES	22
4.2.4	DEVIATION FROM TEST STANDARD	22
4.2.5	TEST SETUP	23
4.2.6	EUT OPERATING CONDITIONS	23
4.2.7	TEST RESULTS	24
4.3	6dB BANDWIDTH MEASUREMENT	38
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	38
4.3.2	TEST INSTRUMENTS	38
4.3.3	TEST PROCEDURE	39
4.3.4	DEVIATION FROM TEST STANDARD	39
4.3.5	TEST SETUP	39
4.3.6	EUT OPERATING CONDITIONS	39
4.3.7	TEST RESULTS	40
4.4	MAXIMUM PEAK OUTPUT POWER	44
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	44
4.4.2	INSTRUMENTS	44
4.4.1	TEST PROCEDURES	45
4.4.2	DEVIATION FROM TEST STANDARD	45
4.4.3	TEST SETUP	45

4.4.4	EUT OPERATING CONDITIONS	45
4.4.3	TEST RESULTS	46
4.5	POWER SPECTRAL DENSITY MEASUREMENT	47
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	47
4.5.2	TEST INSTRUMENTS	47
4.5.3	TEST PROCEDURE	48
4.5.4	DEVIATION FROM TEST STANDARD	48
4.5.5	TEST SETUP	48
4.5.6	EUT OPERATING CONDITION	48
4.5.7	TEST RESULTS	49
4.6	BAND EDGES MEASUREMENT	53
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	53
4.6.2	TEST INSTRUMENTS	53
4.6.3	TEST PROCEDURE	53
4.6.4	DEVIATION FROM TEST STANDARD	53
4.6.5	EUT OPERATING CONDITION	53
4.6.6	TEST RESULTS	54
4.7	ANTENNA REQUIREMENT	64
4.7.1	STANDARD APPLICABLE	64
4.7.2	ANTENNA CONNECTED CONSTRUCTION	64
5.	INFORMATION ON THE TESTING LABORATORIES	65
APPENDIX-A	A-1

1. CERTIFICATION

PRODUCT: 802.11b/g Wireless PCI Express Mini Card
MODEL: Q802XKG
BRAND: Qcom Technology Inc.
APPLICANT: Qcom Technology Inc.
TESTED: Jan. 09 ~ Jan. 23, 2007
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.4-2003

The above equipment (model: Q802XKG) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Peggy Chen , **DATE:** Jan. 25, 2007
Peggy Chen

TECHNICAL ACCEPTANCE : Long Chen , **DATE:** Jan. 25, 2007
Responsible for RF Long Chen

APPROVED BY : Gary Chang , **DATE:** Jan. 25, 2007
Gary Chang / Supervisor

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -17.41dB at 0.216MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.04dB at 4924.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.55 dB
Radiated emissions	30MHz ~ 200MHz	3.59 dB
	200MHz ~ 1000MHz	3.61 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	802.11b/g Wireless PCI Express Mini Card
MODEL NO.	Q802XKG
FCC ID	RUJ-Q802XKG
POWER SUPPLY	3.3Vdc from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	40.644mW
ANTENNA TYPE	Refer to Note 1 as below
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

- The following antennas were provided to the EUT.

ITEM	Brand	Model	Antenna Type	Maximum Gain (dBi)		Connector	Manufacturer
				W/O Cable loss	With cable loss		
1	Quanta	KW3	PIFA	Main (Black): 2.54	1.01	UFL	Wha Yu
				Aux (Gray): 3.48	1.20		
2	Hitachi	HFT10-LG02	Film	5.24	4.51	UFL	Hitachi
3	Hitachi	HFT10-LG01	Film	3.10	2.37	UFL	Hitachi
4	Quanta	TW3	PIFA	Main (Black): 2.406	0.23	UFL	Wha Yu
				Aux (Gray): 4.016	1.04		
5	Quanta	TW7	PIFA	Main (Black): 1.91	2.51	UFL	HON HAI
				Aux (Gray): 2.12	-1.38		
6	Quanta	SW1	PIFA	Main (Black): 4.047	2.31	UFL	HON HAI
				Aux (Gray): 2.149	-0.15		
7	Quanta	TW3	PIFA	Main (Black): 3.385	1.62	UFL	HON HAI
				Aux (Gray): 2.714	0.23		
8	Quanta	TW7	PIFA	Main (Black): 1.204	-0.87	UFL	Wha Yu
				Aux (Gray): 1.546	-0.95		

*Antenna 2 & 5 have the highest gain of the two different antenna type therefore chosen for the final test and presented.

2. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
3. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
4. The above EUT information was declared by the manufacturer and for more detailed features description, please refers to the manufacturer's specifications or User's Manual.


3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.


CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Test Mode A



Test Mode B



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	√	√	√	√	For Antenna item 2
B	-	√	√	-	For Antenna item 5

Where PLC: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

“-”: Means no effect.

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	11	OFDM	BPSK	6
B	802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
B	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
B	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Bandedge Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 11	DSSS	DBPSK	1
B	802.11b	1 to 11	1, 11	DSSS	DBPSK	1
A	802.11g	1 to 11	1, 11	OFDM	BPSK	6
B	802.11g	1 to 11	1, 11	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	16484462992	E2K24CLNS
2	CONTROLLOR BOARD	NA	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.2m USB cable
2	NA

NOTE: 1. All power cords of the above support units are non shielded (1.8m).

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Sep. 25, 2007
RF signal cable Woken	5D-FB	Cable-HYCO3-01	Jan. 06, 2008
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 08, 2008
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jan. 16, 2008
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Connected the EUT to the notebook via USB cable and placed on the testing table.
- b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the system in full functions.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 65%RH, 991hPa
TESTED BY	Match Tsui	INPUT POWER (SYSTEM)	120Vac, 60 Hz

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.10	42.54	-	42.64	-	64.43	54.43	-21.79	-
2	0.216	0.10	45.45	-	45.55	-	62.96	52.96	-17.41	-
3	0.548	0.10	26.28	-	26.38	-	56.00	46.00	-29.62	-
4	1.809	0.20	28.61	-	28.81	-	56.00	46.00	-27.19	-
5	6.047	0.30	21.14	-	21.44	-	60.00	50.00	-38.56	-
6	13.512	0.44	27.13	-	27.57	-	60.00	50.00	-32.43	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 65%RH, 991hPa
TESTED BY	Match Tsui	INPUT POWER (SYSTEM)	120Vac, 60 Hz

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.10	39.56	-	39.66	-	64.61	54.61	-24.95	-
2	0.318	0.10	32.26	-	32.36	-	59.76	49.76	-27.40	-
3	0.826	0.18	20.49	-	20.67	-	56.00	46.00	-35.33	-
4	1.922	0.22	29.54	-	29.76	-	56.00	46.00	-26.24	-
5	5.832	0.33	21.38	-	21.71	-	60.00	50.00	-38.29	-
6	13.668	0.47	27.65	-	28.12	-	60.00	50.00	-31.88	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 65%RH, 991hPa
TESTED BY	Match Tsui	INPUT POWER (SYSTEM)	120Vac, 60 Hz

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	44.43	-	44.53	-	64.79	54.79	-20.26	-
2	0.216	0.10	45.34	-	45.44	-	62.96	52.96	-17.52	-
3	0.748	0.11	24.10	-	24.21	-	56.00	46.00	-31.79	-
4	1.863	0.20	29.57	-	29.77	-	56.00	46.00	-26.23	-
5	3.867	0.28	25.21	-	25.49	-	56.00	46.00	-30.51	-
6	13.250	0.43	26.40	-	26.83	-	60.00	50.00	-33.17	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 65%RH, 991hPa
TESTED BY	Match Tsui	INPUT POWER (SYSTEM)	120Vac, 60 Hz

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.10	43.31	-	43.41	-	64.43	54.43	-21.02	-
2	0.216	0.10	45.37	-	45.47	-	62.96	52.96	-17.49	-
3	0.442	0.11	26.47	-	26.58	-	57.03	47.03	-30.46	-
4	1.594	0.22	28.18	-	28.40	-	56.00	46.00	-27.60	-
5	6.199	0.33	21.36	-	21.69	-	60.00	50.00	-38.31	-
6	12.941	0.46	26.79	-	27.25	-	60.00	50.00	-32.75	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 65%RH, 991hPa
TESTED BY	Match Tsui	INPUT POWER (SYSTEM)	120Vac, 60 Hz

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.10	42.61	-	42.71	-	65.58	55.58	-22.87	-
2	0.185	0.10	42.73	-	42.83	-	64.25	54.25	-21.42	-
3	0.521	0.10	25.34	-	25.44	-	56.00	46.00	-30.56	-
4	1.723	0.19	28.13	-	28.32	-	56.00	46.00	-27.68	-
5	7.066	0.31	22.74	-	23.05	-	60.00	50.00	-36.95	-
6	12.887	0.42	25.60	-	26.02	-	60.00	50.00	-33.98	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 65%RH, 991hPa
TESTED BY	Match Tsui	INPUT POWER (SYSTEM)	120Vac, 60 Hz

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.10	43.54	-	43.64	-	65.18	55.18	-21.54	-
2	0.248	0.10	36.12	-	36.22	-	61.84	51.84	-25.62	-
3	0.537	0.13	23.20	-	23.33	-	56.00	46.00	-32.67	-
4	1.734	0.22	29.33	-	29.55	-	56.00	46.00	-26.45	-
5	5.512	0.32	21.65	-	21.97	-	60.00	50.00	-38.03	-
6	13.172	0.46	27.90	-	28.36	-	60.00	50.00	-31.64	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	May. 08, 2007
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Aug. 07, 2007
BILOG Antenna SCHWARZBECK	VULB9168	9168-153	Jan. 04, 2008
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-563	Jul. 26, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170242	Jan. 16, 2008
Preamplifier Agilent	8449B	3008A01911	Sep. 13, 2007
Preamplifier Agilent	8447D	2944A10638	Dec. 20, 2007
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	218188/218189	Nov. 14, 2007
RF signal cable Worken	8D-FB	Cable-HYCH9-01	Mar. 08, 2007
Software	ADT_Radiated_V7.6	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA
Turn Table EMCO	2087-2.03	NA	NA
Antenna Tower & Turn Table Controller EMCO	2090	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 9.

3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4. The IC Site Registration No. is IC4924A-9.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

RADIATED WORST-CASE DATA: BELOW 1GHz

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Quasi-Peak
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	A
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	94.15	33.49 QP	43.50	-10.01	1.50 H	89	24.41	9.07
2	101.92	37.60 QP	43.50	-5.90	1.50 H	89	28.22	9.38
3	150.52	42.34 QP	43.50	-1.16	1.50 H	89	28.68	13.66
4	162.18	35.04 QP	43.50	-8.46	1.50 H	89	21.73	13.30
5	199.12	32.26 QP	43.50	-11.24	1.50 H	89	21.86	10.39
6	379.90	31.51 QP	46.00	-14.49	1.50 H	89	16.26	15.25
7	412.95	32.30 QP	46.00	-13.70	1.50 H	89	16.20	16.10
8	667.60	31.03 QP	46.00	-14.97	1.50 H	89	9.32	21.70
9	951.40	31.06 QP	46.00	-14.94	1.50 H	89	5.32	25.73

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	61.10	31.51 QP	40.00	-8.49	1.50 V	157	18.46	13.05
2	125.25	37.20 QP	43.50	-6.30	1.50 V	157	25.44	11.76
3	156.35	42.34 QP	43.50	-1.16	1.50 V	157	28.80	13.54
4	467.37	26.66 QP	46.00	-19.34	1.50 V	157	8.91	17.75
5	642.32	29.67 QP	46.00	-16.33	1.50 V	157	8.19	21.48
6	947.52	34.52 QP	46.00	-11.48	1.50 V	157	8.81	25.71

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Quasi-Peak
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	B
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	82.48	28.51 QP	40.00	-11.49	3.00 H	121	20.33	8.18
2	117.47	37.36 QP	43.50	-6.14	1.50 H	93	26.09	11.26
3	152.46	42.24 QP	43.50	-1.26	1.50 H	93	28.62	13.62
4	162.18	35.98 QP	43.50	-7.52	1.50 H	93	22.68	13.30
5	383.79	32.29 QP	46.00	-13.71	1.50 H	93	16.96	15.34
6	414.89	33.01 QP	46.00	-12.99	1.50 H	93	16.85	16.16
7	951.40	32.58 QP	46.00	-13.42	1.50 H	93	6.84	25.73

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	61.10	31.91 QP	40.00	-8.09	1.50 V	195	18.86	13.05
2	123.31	36.38 QP	43.50	-7.12	1.50 V	195	24.69	11.69
3	156.35	41.92 QP	43.50	-1.58	1.50 V	195	28.38	13.54
4	467.37	26.04 QP	46.00	-19.96	1.50 V	195	8.29	17.75
5	642.32	28.00 QP	46.00	-18.00	1.50 V	195	6.52	21.48
6	947.52	34.53 QP	46.00	-11.47	1.50 V	195	8.82	25.71

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	A
TESTED BY	Lori Chiu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.28 PK	74.00	-18.72	1.06 H	200	24.07	31.21
2	2390.00	44.83 AV	54.00	-9.17	1.06 H	200	13.62	31.21
3	*2412.00	98.57 PK			1.06 H	200	67.37	31.20
4	*2412.00	94.18 AV			1.06 H	200	62.98	31.20
5	3216.00	57.69 PK	78.57	-20.88	1.13 H	26	25.34	32.35
6	3216.00	56.58 AV	74.18	-17.60	1.13 H	26	24.23	32.35
7	4824.00	51.27 PK	74.00	-22.73	1.00 H	201	14.84	36.42
8	4824.00	47.83 AV	54.00	-6.17	1.00 H	201	11.40	36.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.38 PK	74.00	-19.62	1.04 V	115	23.17	31.21
2	2390.00	44.34 AV	54.00	-9.66	1.04 V	115	13.13	31.21
3	*2412.00	90.47 PK			1.04 V	115	59.27	31.20
4	*2412.00	86.16 AV			1.04 V	115	54.96	31.20
5	3216.00	55.94 PK	70.47	-14.53	1.02 V	267	23.59	32.35
6	3216.00	54.39 AV	66.16	-11.77	1.02 V	267	22.04	32.35
7	4824.00	51.74 PK	74.00	-22.26	1.11 V	48	15.32	36.42
8	4824.00	48.22 AV	54.00	-5.78	1.11 V	48	11.80	36.42

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	A
TESTED BY	Lori Chiu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	100.09 PK			1.30 H	209	68.88	31.21
2	*2437.00	95.61 AV			1.30 H	209	64.40	31.21
3	3248.00	55.23 PK	80.09	-24.86	1.17 H	188	22.97	32.26
4	3248.00	54.01 AV	75.61	-21.60	1.17 H	188	21.75	32.26
5	4874.00	52.51 PK	74.00	-21.49	1.09 H	217	15.98	36.53
6	4874.00	48.06 AV	54.00	-5.94	1.09 H	217	11.53	36.53

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	92.95 PK			1.15 V	274	61.74	31.21
2	*2437.00	88.79 AV			1.15 V	274	57.58	31.21
3	3248.00	52.21 PK	72.95	-20.74	1.16 V	119	19.95	32.26
4	3248.00	50.10 AV	68.79	-18.69	1.16 V	119	17.84	32.26
5	4874.00	52.18 PK	74.00	-21.82	1.11 V	50	15.65	36.53
6	4874.00	49.19 AV	54.00	-4.81	1.11 V	50	12.66	36.53

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	A
TESTED BY	Lori Chiu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	102.57 PK			1.02 H	19	71.35	31.22
2	*2462.00	98.24 AV			1.02 H	19	67.02	31.22
3	2487.00	60.74 PK	74.00	-13.26	1.02 H	19	29.51	31.23
4	2487.00	50.10 AV	54.00	-3.90	1.02 H	19	18.87	31.23
5	3216.00	55.48 PK	82.57	-27.09	1.10 H	189	23.13	32.35
6	3216.00	54.89 AV	78.24	-23.35	1.10 H	189	22.54	32.35
7	4924.00	52.11 PK	74.00	-21.89	1.00 H	328	15.47	36.63
8	4924.00	48.97 AV	54.00	-5.03	1.00 H	328	12.33	36.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	94.93 PK			1.00 V	105	63.71	31.22
2	*2462.00	90.76 AV			1.00 V	105	59.54	31.22
3	2487.00	56.70 PK	74.00	-17.30	1.00 V	105	25.47	31.23
4	2487.00	45.42 AV	54.00	-8.58	1.00 V	105	14.19	31.23
5	3282.00	52.25 PK	74.93	-22.68	1.43 V	288	20.10	32.15
6	3282.00	50.86 AV	70.76	-19.90	1.43 V	288	18.71	32.15
7	4924.00	54.41 PK	74.00	-19.59	1.08 V	56	17.77	36.63
8	4924.00	52.22 AV	54.00	-1.78	1.08 V	56	15.58	36.63

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	B
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	58.69 PK	74.00	-15.31	1.45 H	212	27.32	31.37
2	2386.00	48.27 AV	54.00	-5.73	1.45 H	212	16.90	31.37
3	*2412.00	105.30 PK			1.41 H	216	73.84	31.46
4	*2412.00	101.04 AV			1.41 H	216	69.58	31.46
5	3216.00	50.29 PK	85.30	-35.01	1.19 H	178	17.18	33.11
6	3216.00	46.90 AV	81.04	-34.14	1.19 H	178	13.79	33.11
7	4824.00	55.15 PK	74.00	-18.85	1.00 H	72	18.02	37.13
8	4824.00	52.48 AV	54.00	-1.52	1.00 H	72	15.35	37.13

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	57.13 PK	74.00	-16.87	1.50 V	205	25.76	31.37
2	2386.00	46.62 AV	54.00	-7.38	1.50 V	205	15.25	31.37
3	*2412.00	101.38 PK			1.50 V	205	69.92	31.46
4	*2412.00	96.95 AV			1.50 V	205	65.49	31.46
5	3216.00	44.33 PK	81.38	-37.05	1.38 V	253	11.22	33.11
6	3216.00	38.28 AV	76.95	-38.67	1.38 V	253	5.17	33.11
7	4824.00	54.46 PK	74.00	-19.54	1.35 V	76	17.33	37.13
8	4824.00	51.69 AV	54.00	-2.31	1.35 V	76	14.56	37.13

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	B
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	105.10 PK			1.29 H	229	73.56	31.54
2	*2437.00	100.83 AV			1.30 H	227	69.29	31.54
3	3249.00	49.11 PK	85.10	-35.99	1.15 H	156	15.92	33.19
4	3249.00	45.47 AV	80.83	-35.36	1.15 H	156	12.28	33.19
5	4874.00	55.05 PK	74.00	-18.95	1.50 H	75	17.76	37.29
6	4874.00	52.95 AV	54.00	-1.05	1.50 H	75	15.66	37.29

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	101.56 PK			1.20 V	210	70.02	31.54
2	*2437.00	96.95 AV			1.20 V	210	65.41	31.54
3	3249.00	46.10 PK	81.56	-35.46	1.45 V	214	12.91	33.19
4	3249.00	38.97 AV	76.95	-37.98	1.45 V	214	5.78	33.19
5	4874.00	54.09 PK	74.00	-19.91	1.35 V	76	16.80	37.29
6	4874.00	51.48 AV	54.00	-2.52	1.35 V	76	14.19	37.29

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	B
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	104.18 PK			1.29 H	230	72.56	31.62
2	*2462.00	99.92 AV			1.29 H	230	68.30	31.62
3	2487.00	59.13 PK	74.00	-14.87	1.25 H	232	27.42	31.71
4	2487.00	48.52 AV	54.00	-5.48	1.25 H	232	16.81	31.71
5	3282.00	50.04 PK	84.18	-34.14	1.00 H	161	16.77	33.27
6	3282.00	46.80 AV	79.92	-33.12	1.00 H	161	13.53	33.27
7	4924.00	56.00 PK	74.00	-18.00	1.15 H	73	18.56	37.44
8	4924.00	52.96 AV	54.00	-1.04	1.15 H	73	15.52	37.44

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	99.70 PK			1.48 V	305	68.08	31.62
2	*2462.00	95.65 AV			1.48 V	305	64.03	31.62
3	2487.00	57.24 PK	74.00	-16.76	1.48 V	305	25.53	31.71
4	2487.00	47.12 AV	54.00	-6.88	1.48 V	305	15.41	31.71
5	3282.00	47.20 PK	79.70	-32.50	1.34 V	295	13.93	33.27
6	3282.00	41.94 AV	75.65	-33.71	1.34 V	295	8.67	33.27
7	4924.00	54.96 PK	74.00	-19.04	1.22 V	79	17.52	37.44
8	4924.00	51.42 AV	54.00	-2.58	1.22 V	79	13.98	37.44

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	A
TESTED BY	Lori Chiu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.78 PK	74.00	-19.22	1.05 H	201	23.57	31.21
2	2390.00	44.44 AV	54.00	-9.56	1.05 H	201	13.23	31.21
3	*2412.00	96.26 PK			1.05 H	201	65.06	31.20
4	*2412.00	86.21 AV			1.05 H	201	55.01	31.20
5	3216.00	58.11 PK	76.26	-18.15	1.37 H	105	25.76	32.35
6	3216.00	57.17 AV	66.21	-9.04	1.37 H	105	24.82	32.35
7	4824.00	48.62 PK	74.00	-25.38	1.13 H	143	12.20	36.42
8	4824.00	36.33 AV	54.00	-17.67	1.13 H	143	-0.09	36.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.78 PK	74.00	-19.22	1.00 V	266	23.57	31.21
2	2390.00	44.19 AV	54.00	-9.81	1.00 V	266	12.98	31.21
3	*2412.00	88.83 PK			1.00 V	266	57.63	31.20
4	*2412.00	78.72 AV			1.00 V	266	47.52	31.20
5	3216.00	55.16 PK	68.83	-13.67	1.14 V	24	22.81	32.35
6	3216.00	53.99 AV	58.72	-4.73	1.14 V	24	21.64	32.35
7	4824.00	47.13 PK	74.00	-26.87	1.20 V	36	10.71	36.42
8	4824.00	34.15 AV	54.00	-19.85	1.20 V	36	-2.27	36.42

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	A
TESTED BY	Lori Chiu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	98.88 PK			1.22 H	177	67.67	31.21
2	*2437.00	88.86 AV			1.22 H	177	57.65	31.21
3	3248.00	55.54 PK	78.88	-23.34	1.06 H	175	23.28	32.26
4	3248.00	54.16 AV	68.86	-14.70	1.06 H	175	21.90	32.26
5	4874.00	47.44 PK	74.00	-26.56	1.00 H	177	10.91	36.53
6	4874.00	36.28 AV	54.00	-17.72	1.00 H	177	-0.25	36.53

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	90.94 PK			1.14 V	231	59.73	31.21
2	*2437.00	80.60 AV			1.14 V	231	49.39	31.21
3	3248.00	52.68 PK	70.94	-18.26	1.30 V	177	20.42	32.26
4	3248.00	50.64 AV	60.60	-9.96	1.30 V	177	18.38	32.26
5	4874.00	45.56 PK	74.00	-28.44	1.00 V	164	9.03	36.53
6	4874.00	34.97 AV	54.00	-19.03	1.00 V	164	-1.56	36.53

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	A
TESTED BY	Lori Chiu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	100.86 PK			1.03 H	19	69.64	31.22
2	*2462.00	90.42 AV			1.03 H	19	59.20	31.22
3	2483.50	60.80 PK	74.00	-13.20	1.02 H	18	29.57	31.23
4	2483.50	47.11 AV	54.00	-6.89	1.02 H	18	15.88	31.23
5	3282.00	55.58 PK	80.86	-25.28	1.00 H	199	23.43	32.15
6	3282.00	54.45 AV	70.42	-15.97	1.00 H	199	22.30	32.15
7	4924.00	49.24 PK	74.00	-24.76	1.00 H	256	12.61	36.63
8	4924.00	36.20 AV	54.00	-17.80	1.00 H	256	-0.43	36.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	91.82 PK			1.00 V	74	60.60	31.22
2	*2462.00	81.47 AV			1.00 V	74	50.25	31.22
3	2483.50	55.54 PK	74.00	-18.46	1.00 V	74	24.31	31.23
4	2483.50	45.02 AV	54.00	-8.98	1.00 V	74	13.79	31.23
5	3282.00	52.84 PK	71.82	-18.98	1.00 V	288	20.69	32.15
6	3282.00	50.71 AV	61.47	-10.76	1.00 V	288	18.56	32.15
7	4924.00	47.67 PK	74.00	-26.33	1.12 V	265	11.04	36.63
8	4924.00	34.41 AV	54.00	-19.59	1.12 V	265	-2.23	36.63

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	B
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.23 PK	74.00	-10.77	1.36 H	228	31.84	31.39
2	2390.00	49.12 AV	54.00	-4.88	1.36 H	228	17.73	31.39
3	*2412.00	104.28 PK			1.34 H	231	72.82	31.46
4	*2412.00	92.82 AV			1.34 H	231	61.36	31.46
5	3216.00	49.35 PK	84.28	-34.93	1.56 H	356	16.24	33.11
6	3216.00	45.39 AV	72.82	-27.43	1.56 H	356	12.28	33.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.99 PK	74.00	-16.01	1.22 V	208	26.60	31.39
2	2390.00	47.95 AV	54.00	-6.05	1.22 V	208	16.56	31.39
3	*2412.00	101.39 PK			1.22 V	208	69.93	31.46
4	*2412.00	90.88 AV			1.22 V	208	59.42	31.46
5	3216.00	46.49 PK	81.39	-34.90	1.31 V	95	13.38	33.11
6	3216.00	38.80 AV	70.88	-32.08	1.31 V	95	5.69	33.11

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	B
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	103.96 PK			1.33 H	214	72.42	31.54
2	*2437.00	92.72 AV			1.33 H	214	61.18	31.54
3	3249.00	49.65 PK	74.00	-24.35	1.16 H	157	16.46	33.19
4	3249.00	45.62 AV	54.00	-8.38	1.16 H	157	12.43	33.19

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	100.22 PK			1.37 V	286	68.68	31.54
2	*2437.00	90.10 AV			1.37 V	286	58.56	31.54
3	3249.00	46.21 PK	74.00	-27.79	1.04 V	267	13.02	33.19
4	3249.00	39.75 AV	54.00	-14.25	1.04 V	267	6.56	33.19

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	24deg. C, 64%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TEST MODE	B
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	103.44 PK			1.06 H	226	71.82	31.62
2	*2462.00	92.56 AV			1.06 H	226	60.94	31.62
3	2483.50	56.82 PK	74.00	-17.18	1.06 H	226	25.12	31.70
4	2483.50	47.70 AV	54.00	-6.30	1.06 H	226	16.00	31.70
5	3282.00	49.00 PK	83.44	-34.44	1.30 H	224	15.73	33.27
6	3282.00	45.61 AV	72.56	-26.95	1.30 H	224	12.34	33.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	101.20 PK			1.48 V	305	69.58	31.62
2	*2462.00	90.88 AV			1.48 V	305	59.26	31.62
3	2483.50	58.57 PK	74.00	-15.43	1.48 V	305	26.87	31.70
4	2483.50	47.64 AV	54.00	-6.36	1.48 V	305	15.94	31.70
5	3282.00	47.13 PK	81.20	-34.07	1.21 V	324	13.86	33.27
6	3282.00	40.26 AV	70.88	-30.62	1.21 V	324	6.99	33.27

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.3.7 TEST RESULTS

802.11b DSSS MODULATION


MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 66%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.28	0.5	PASS
6	2437	12.16	0.5	PASS
11	2462	12.16	0.5	PASS


CH1



CH6



CH11




802.11g OFDM MODULATION


MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 66%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.48	0.5	PASS
6	2437	16.44	0.5	PASS
11	2462	16.48	0.5	PASS


CH1



CH6



CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007
ANRITSU SYNTHESIZED SIGNAL GENERATOR	68247B	984703	May 08, 2007
TEKTRONIX OSCILLOSCOPE	TDS1012	C037299	Nov. 27, 2007
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.1 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.2 DEVIATION FROM TEST STANDARD

No deviation

4.4.3 TEST SETUP



4.4.4 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.3 TEST RESULTS

802.11b DSSS MODULATION

MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 66%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	39.994	16.02	30	PASS
6	2437	40.644	16.09	30	PASS
11	2462	31.989	15.05	30	PASS

802.11g OFDM MODULATION

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 66%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	25.293	14.03	30	PASS
6	2437	25.410	14.05	30	PASS
11	2462	25.177	14.01	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6


4.5.7 TEST RESULTS

802.11b DSSS MODULATION

MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 66%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-13.44	8	PASS
6	2437	-13.55	8	PASS
11	2462	-14.38	8	PASS

CH1




802.11g OFDM MODULATION


MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg. C, 66%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-15.59	8	PASS
6	2437	-15.78	8	PASS
11	2462	-15.63	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 12 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS MODULATION

Test Mode A

NOTE 1: The band edge emission plot on following second page shows 51.36dBc delta between carrier maximum power and local maximum emission in restrict band (2.387320000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 98.57dBuV/m (Peak), so the maximum field strength in restrict band is $98.57 - 51.36 = 47.21$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on following second page shows 56.80dBc delta between carrier maximum power and local maximum emission in restrict band (2.385120000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 94.18dBuV/m (Average), so the maximum field strength in restrict band is $94.18 - 56.80 = 37.38$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on following third page shows 51.23dBc delta between carrier maximum power and local maximum emission in restrict band (2.488060000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 102.57dBuV/m (Peak), so the maximum field strength in restrict band is $102.57 - 51.23 = 51.34$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on following forth page shows 55.13dBc delta between carrier maximum power and local maximum emission in restrict band (2.487460000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 98.24dBuV/m (Average), so the maximum field strength in restrict band is $98.24 - 55.13 = 43.11$ dBuV/m which is under 54dBuV/m limit.



Test Mode B



NOTE 1: The band edge emission plot on following first page shows 51.36dBc delta between carrier maximum power and local maximum emission in restrict band (2.387320000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 105.30dBuV/m (Peak), so the maximum field strength in restrict band is $105.30 - 51.36 = 53.94$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on following first page shows 56.80dBc delta between carrier maximum power and local maximum emission in restrict band (2.385120000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 101.04dBuV/m (Average), so the maximum field strength in restrict band is $101.04 - 56.80 = 44.24$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on following second page shows 51.23dBc delta between carrier maximum power and local maximum emission in restrict band (2.488060000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 104.18dBuV/m (Peak), so the maximum field strength in restrict band is $104.18 - 51.23 = 52.95$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on following third page shows 55.13dBc delta between carrier maximum power and local maximum emission in restrict band (2.487460000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 99.92dBuV/m (Average), so the maximum field strength in restrict band is $99.92 - 55.13 = 44.79$ dBuV/m which is under 54dBuV/m limit.







802.11g OFDM MODULATION

Test Mode A

NOTE 1: The band edge emission plot on following second page shows 46.16dBc delta between carrier maximum power and local maximum emission in restrict band (2.339600000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 96.26dBuV/m (Peak), so the maximum field strength in restrict band is $96.26 - 46.16 = 50.10$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on following second page shows 53.45dBc delta between carrier maximum power and local maximum emission in restrict band (2.390000000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 86.21dBuV/m (Average), so the maximum field strength in restrict band is $86.21 - 53.45 = 32.76$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on following third page shows 46.12dBc delta between carrier maximum power and local maximum emission in restrict band (2.485100000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 100.86dBuV/m (Peak), so the maximum field strength in restrict band is $100.86 - 46.12 = 54.74$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on following forth page shows show 51.40dBc delta between carrier maximum power and local maximum emission in restrict band (2.483500000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 90.42dBuV/m (Average), so the maximum field strength in restrict band is $90.42 - 51.40 = 39.02$ dBuV/m which is under 54dBuV/m limit.



Test Mode B



NOTE 1: The band edge emission plot on following first page shows 46.16dBc delta between carrier maximum power and local maximum emission in restrict band (2.38920GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 104.28dBuV/m (Peak), so the maximum field strength in restrict band is $104.28 - 46.16 = 58.12$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on following first page shows 53.45dBc delta between carrier maximum power and local maximum emission in restrict band (2.390000000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 92.82dBuV/m (Average), so the maximum field strength in restrict band is $92.82 - 53.45 = 39.37$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on following second page shows 46.12dBc delta between carrier maximum power and local maximum emission in restrict band (2.485100000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 103.44dBuV/m (Peak), so the maximum field strength in restrict band is $103.44 - 46.12 = 57.32$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on following third page shows show 51.40dBc delta between carrier maximum power and local maximum emission in restrict band (2.483500000GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 92.56dBuV/m (Average), so the maximum field strength in restrict band is $92.56 - 51.40 = 41.16$ dBuV/m which is under 54dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antennas used in this product are PIFA antenna and Film antenna with U.FL antenna connector. The maximum Gain of the antenna is 4.51dBi.

5. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, NCC
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.