

## 丝 印 图

第1页,共1页 机型: 版 本: 1 生效日期: T8240后壳 编码: SS-14-23-403-1 1.8mm 45mm 1.05 6.18mm INSIGNIA 2.73 82mm 82mm 123.6mm INSIGNIA **1.16** Made in China Model:NS-15AT08 | Input Rating:5V=2.0Amax FCC ID: XUZNS-15AT08 | IC:10558A-NS15AT08
This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1)this device may not cause harmful 16.6mm cluding interference that may cause undesired operatio 0.57 6. 03mm 23.46mm 19.27mm Made in China Model:NS-15AT08 | Input Rating:5V=2.0Amax FCC ID: XUZNS-15AT08 | IC:10558A-NS15AT08
This device complies with part 15 of the FCC Rules.Operation is subject Sn贴纸粘贴位置 10.65mm 字符表面丝印 PT COOL GRAY 6C 40.00 mm 40.00 mm  $\mathbf{\Omega}$ • MIC NS-15AT08 V:1.0H 14E06A000001 T8240RK-88T V:1.0H 1:2 ■ MICRO SD Reset SN贴纸 图档比例 1:1 备注: 1. 印刷文字及图形不可断线或模糊不清 一般公差值为±0.1mm 2. 印刷颜色不可有色偏,脏点,漏白 镜片类公差值为±0.05mm 3. 表面不可有磨损 4. 丝印表面须具耐磨, 耗磨性 5. 图纸尺寸标示中带\*号的为重点管制尺寸 审核/日期: 核准/日期: 编制/日期: 6. 感应镜片印刷油墨中不能含有金属、导电成份

QP-007-FM16-1