	Report No: R3413_RFEXP Issue No: 2	FCC ID: XX6-SRG3900XN	
	Test No: T5507	Test Report	Page: 1 of 5



dB Technology
|----- (Cambridge Ltd.) -----|

EMC
Testing

EMC
Consultancy

EMC
Training

23, Headington Drive,
Cambridge.
CB1 9HE
Tel : 01954 251974 (test site)
or : 01223 241140 (accounts)
Fax : 01954 251907
web : www.dbtechnology.co.uk
email: mail@dbtechnology.co.uk

REPORT ON RF EXPOSURE CALCULATIONS

**Performed at:
TWENTY PENCE TEST SITE**

**Twenty Pence Road,
Cottenham,
Cambridge
U.K.
CB24 8PS**

on

Sepura PLC

SRG3900 XN

dated


3rd November 2014

Document History

Issue	Date	Affected page(s)	Description of modifications	Revised by	Approved by
1	3/11/14		Initial release		
2	11/12/14	All	Added calculations for lower gain antenna	DS	DB

Based on report template:
v090319

*This report shall not be reproduced except in full, without the written approval of:
dB Technology (Cambridge) Ltd.*

	Report No: R3413_RFEXP	FCC ID: XX6-SRG3900XN	
	Issue No: 2		
	Test No: T5507	Test Report	Page: 2 of 5

Equipment Under Test (EUT): SRG3900 XN

Test Commissioned by: Sepura PLC
Radio House
St Andrews Road
Cambridge
Cambridgeshire
CB4 1GR

Representative: Steve Wood

Test Started: 27th August 2014

Test Completed: 30th October 2014

Test Engineer: Dave Smith


Date of Report: 3rd November 2014

Written by: Dave Smith

Signature: 

Date: 3rd November 2014

dB Technology can only report on the specific unit(s) tested at its site. The responsibility for extrapolating this data to a product line lies solely with the manufacturer.


	Report No: R3413_RFEXP Issue No: 2	FCC ID: XX6-SRG3900XN	
	Test No: T5507	Test Report	Page: 3 of 5

1 EUT Details

1.1 General

The EUT was a TETRA Voice + Data Mobile Station.

The nominal output power is 40dBm (10W).

	Report No: R3413_RFEXP Issue No: 2	FCC ID: XX6-SRG3900XN	
	Test No: T5507	Test Report	Page: 4 of 5

RF Exposure Evaluation: OET Bulletin 65 97-01 CFR 47 1.1310

Manufacturer: Sepura

Product: SRG3900XN

Numeric Gain

Antenna 1: 300-00390 5dBi 3.16 Tetra only

Frequency (MHz)	809	869
Output Power (mW):	10000	10000
Numerical Antenna Gain:	3.16	3.16
Duty cycle (%):	25	25
Distance (cm):	35	35
Power Density (mW/cm2):	0.513	0.513
FCC Limits: (mW/cm2)		
General:(f/1500)	0.54 PASS	0.58 PASS

Output power is nominal output as specified by the manufacturer and verified in the test report.

Antenna gain is taken from the supplied data sheets.


Duty Cycle is based on Tetra System in which each channel is divided into 4 slots - with equal time allocation.

$$\text{Total Power, } P(\text{Watts}) = \text{Output Power} \times \text{Antenna Gain} \times \frac{\text{Duty Cycle}}{100}$$

$$\text{Power at a Distance, } d(\text{metres}) = \frac{P}{4 \pi d^2}$$

Conclusion:

At a distance of 35cm the maximum power density is 0.513 mW/cm2 which is below the general environment limit of 0.54 mW/cm2

	Report No: R3413_RFEXP Issue No: 2	FCC ID: XX6-SRG3900XN	
	Test No: T5507	Test Report	Page: 5 of 5

RF Exposure Evaluation: OET Bulletin 65 97-01 CFR 47 1.1310

Manufacturer: Sepura

Product: SRG3900XN

Numeric Gain

Antenna 2: 300-00993 OdBd 1.64 For use with DMU configuration

Frequency (MHz)	809	869
Output Power (mW):	10000	10000
Numerical Antenna Gain:	1.64	1.64
Duty cycle (%):	25	25
Distance (cm):	35	35
Power Density (mW/cm2):	0.266	0.266
FCC Limits: (mW/cm2)		
General:(f/1500)	0.54 PASS	0.58 PASS

Output power is nominal output as specified by the manufacturer and verified in the test report.

Antenna gain is taken from the supplied data sheets.

Duty Cycle is based on Tetra System in which each channel is divided into 4 slots - with equal time allocation.

$$\text{Total Power, } P(\text{ Watts }) = \text{Output Power} \times \text{Antenna Gain} \times \frac{\text{Duty Cycle}}{100}$$

$$\text{Power at a Distance, } d(\text{ metres }) = \frac{P}{4 \pi d^2}$$

Conclusion:

At a distance of 35cm the maximum power density is 0.266 mW/cm2 which is below the general environment limit of 0.54 mW/cm2