



## FCC PART 22 and 90 TEST REPORT

For

**Sepura plc**

Radio House, St. Andrews Road, Cambridge CB4 1GR UK

**FCC ID: XX6SEM8010**

<b>Report Type:</b> Class II permissive change	<b>Product Type:</b> DMR Mobile Radio
<b>Test Engineer:</b> <u>Dean Liu</u>	
<b>Report Number:</b> <u>RDG150921002-00A1</u>	
<b>Report Date:</b> <u>2015-11-16</u>	
<b>Reviewed By:</b> <u>Sula Huang RF Leader</u>	
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
DESCRIPTION OF TEST CONFIGURATION .....	5
EQUIPMENT MODIFICATIONS .....	5
SUPPORT EQUIPMENT LIST AND DETAILS .....	5
<b>SUMMARY OF TEST RESULTS .....</b>	<b>6</b>
<b>FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....</b>	<b>7</b>
APPLICABLE STANDARD .....	7
<b>FCC §2.1046 &amp; § 22.727 &amp; §90.205- RF OUTPUT POWER .....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
TEST PROCEDURE .....	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST DATA .....	9
<b>FCC §2.1049&amp; §22.357 &amp; § 22.731 &amp; §90.209 &amp; §90.210 – OCCUPIED BANDWIDTH &amp; EMISSION MASK</b>	<b>11</b>
APPLICABLE STANDARD .....	11
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST PROCEDURE .....	12
TEST DATA .....	12

---

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Sepura plc*'s product, model: *SEM8010* (FCC ID: *XX6SEM8010*) (the "EUT") in this report is a *DMR Mobile Radio*, which was measured approximately: 17.2 cm (L) x 19.5 cm (H) x 5.8 cm (T), rated input voltage: 13.6 VDC or 15 VDC powered from AC/DC adapter.

*\* All measurement and test data in this report was gathered from production sample serial number: 7PR531531GD0275 (Assigned by applicant). The EUT was received on 2015-09-24.*

### Objective

This test report is prepared on behalf of *Sepura plc* in accordance with Part 2, Part22, and Part 90 of the Federal Communications Commission rules.

This is the CIIPC application of the device. The difference between the original device and new device is as follows:

1. Change the low power level from 5W to 1W.
2. Updated the emission designator.
3. Updated the MPE evaluation

Please refer to the Permissive Change Declaration Letter.

According to the changes, it will impact the test results of RF power output and Occupied bandwidth&Emission mask, so in this report, we update the test data of RF power output &Occupied bandwidth&Emission mask for low power level and updated MPE evaluation.

### Related Submittal(s)/Grant(s)

Original submission with FCC ID: *XX6SEM8010* which is granted on 2014-12-22.

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 22 – Public Mobile Service  
Part 90 – Private Land Mobile Radio Service

Applicable Standards: TIA-603-D.

## **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in a test mode.

### EUT Specification:

Test Software Version	DMR Manager_V1.89		
Test Frequency(MHz)	For FCC part 90		
	136.0125	155.0125	173.9875
	For FCC part 22		
	161.01		
Set	High Power Level: 25W, Low Power Level: 1W		

Operating Frequency Band	136-174 MHz
Modulation Mode	FM/4FSK
Channel Spacing	12.5 kHz
Modulation Type	Analog(FM); Digital(4FSK)
Rated Output Power	25W(High); 1W(Low)

### Equipment Modifications

No modifications were made to the unit tested.

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Results
§2.1091	Maximum Permissible Exposure	Compliance
§2.1046; § 22.727;§90.205	RF Output Power	Compliance
§2.1047;§90.207	Modulation Characteristic	Compliance*
§2.1049;§22.357;§ 22.731;§90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliance
§2.1051; §22.861;§90.210	Spurious Emission at Antenna Terminal	Compliance*
§2.1053; §22.861;§90.210	Spurious Radiated Emissions	Compliance*
§2.1055; § 22.355;§90.213	Frequency Stability	Compliance*
§90.214	Transient Frequency Behavior	Compliance*

Compliance\*: Please refer to the report number RDG140724006-00 granted on 2014-12-17, with FCC ID: XX6SEM8010.

## **FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

### **Applicable Standard**

According to 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for Maximum Permissible Exposure (MPE)

<b>Limits for Occupational/Controlled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (E) (V/m)</b>	<b>Magnetic Field Strength (H) (A/m)</b>	<b>Power Density (S) (mW/cm<sup>2</sup>)</b>	<b>Averaging Time  E ,  H  or S (minutes)</b>
0.3- 3.0	614	1.63	(100)*	6
3.0 - 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6

f = frequency in MHz;

\* = Plane-wave equivalent power density;

### **MPE Calculation**

**Predication of MPE limit at a given distance**

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

Frequency	Conducted Output Power	Duty Cycle	Typical Antenna Gain		Distance	Power Density	Limit
MHz	mW		dBi	numeric	cm	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>
155	28050	50%	0	1.0	35	0.91	1.0

Note1: The manufacturer does not specify an antenna to be used with this device , but a typical installation has a gain up to 0dBi.

Note2: The target power is 25W (43.98 dBm)  $\pm 0.5\text{dB}$  = 28050mW (44.48dBm)

**Radio Exposure Statement:**

Using the parameters given in the above calculation, a minimum antenna to person distance of 35 cm is required to meet the limits for occupational/controlled exposure.

Result: Compliance.



**FCC §2.1046 & § 22.727 & §90.205- RF OUTPUT POWER****Applicable Standard**

FCC §2.1046, § 22.727 and §90.205.

**Test Procedure**

Conducted RF Output Power:

TIA-603-D section 2.2.1

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer setting:

RBW	VBW
100 kHz	300 kHz

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
Mini-Circuits	Attenuator	UNAT-10 <sup>+</sup>	15542	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06
Pasternack	RF Coaxial Cable	RF-01(30cm)	/	2015-05-06	2016-05-06
Pasternack	RF Coaxial Cable	RF-02(30cm)	/	2015-05-06	2016-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

Temperature:	27.5 °C
Relative Humidity:	58 %
ATM Pressure:	100.3 kPa

*The testing was performed by Dean Liu on 2015-09-26.*

*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to following tables.*

FCC Part 90:

Modulation mode	Channel Spacing	f <sub>c</sub>	Conducted Output Power
		MHz	W
FM	12.5 kHz	136.0125	0.998
		155.0125	0.927
		173.9875	0.920
4FSK		136.0125	0.991
		155.0125	0.916
		173.9875	0.914

FCC Part 22:

Modulation mode	Channel Spacing	$f_c$	Conducted Output Power
		MHz	W
FM	12.5 kHz	161.01	0.935
4FSK		161.01	0.927

## FCC §2.1049 & §22.357 & § 22.731 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

### Applicable Standard

FCC §2.1049, §22.357, § 22.731, §90.209 and §90.210

Applicable Emission Masks

Frequency band (MHz)	Mask for equipment with audio low pass filter	Mask for equipment without audio low pass filter
Below 25	A or B	A or C
25-50	B	C
72-76	B	C
150-174	B, D, or E	C, D or E
150 paging only	B	C
220-222	F	F
421-512	B, D, or E	C, D, or E
450 paging only	B	G
806-809/851-854	B	H
809-824/854-869	B	G
896-901/935-940	I	J
902-928	K	K
929-930	B	G
4940-4990 MHz	L or M	L or M
5850-5925		
All other bands	B	C

**Emission Mask D**—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth  $f_0$  to 5.625 kHz removed from  $f_0$ : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least  $7.27(f_d - 2.88 \text{ kHz})$  dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 12.5 kHz: At least  $50 + 10 \log(P)$  dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

## §22.357 Emission types.

Any authorized station in the Public Mobile Services may transmit emissions of any type(s) that comply with the applicable emission rule, i.e. §22.359, §22.861 or §22.917

## §22.731 Emission limitations.

Upon application for multichannel operation, the FCC may authorize emission bandwidths wider than those specified in §22.357, provided that spectrum utilization is equal to or better than that achieved by single channel operation.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
HP	RF Communications Test Set	8920A	00 235	2015-05-09	2016-05-09
Mini-Circuits	Attenuator	UNAT-10 <sup>+</sup>	15542	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06
Pasternack	RF Coaxial Cable	RF-01(30cm)	/	2015-05-06	2016-05-06
Pasternack	RF Coaxial Cable	RF-02(30cm)	/	2015-05-06	2016-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	27.1~27.3 °C
<b>Relative Humidity:</b>	58~60 %
<b>ATM Pressure:</b>	100.3~100.5 kPa

*The testing was performed by Dean Liu on 2015-09-26 and 2015-10-24.*

*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to the following tables and plots.*

*FCC Part 90:*

Modulation Mode	Channel Spacing	$f_c$	99% Occupied Bandwidth	26 dB Bandwidth
	kHz	MHz	kHz	kHz
FM	12.5	155.0125	9.90	10.35
4FSK			7.31	9.42

*FCC Part 22:*

Modulation Mode	Channel Spacing	$f_c$	99% Occupied Bandwidth	26 dB Bandwidth
	kHz	MHz	kHz	kHz
FM	12.5	161.01	9.90	10.35
4FSK			7.57	9.57

Emission Designator

Per CFR 47 §2.201& §2.202&,  $B_n = 2M + 2D$

#### **For FM Mode (Channel Spacing: 12.5 kHz)**

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = \rightarrow 11K0$

F3E portion of the designator represents an FM voice transmission

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

#### **For Digital Mode (Channel Spacing: 12.5 kHz)**

Emission Designator 7K60FXD and 7K60FXW


The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.57 kHz. The emission mask was obtained from 47CFR 90.210(d).

FXD and FXW portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60FXD and 7K60FXW.


Part 90:

## Occupied Bandwidth – FM, 155.0125 MHz




Date: 26.SEP.2015 16:37:56


## Emission Mask - Type D



Date: 26.SEP.2015 16:22:46


**Occupied Bandwidth –4FSK, 155.0125 MHz**

Date: 24.OCT.2015 17:15:29


**Emission Mask - Type D**

Date: 24.OCT.2015 17:17:27

Part 22:

**Occupied Bandwidth – FM, 161.01 MHz**

Date: 26.SEP.2015 16:31:15

**Occupied Bandwidth –Type D**

Date: 26.SEP.2015 16:46:22

**\*\*\*\*\* END OF REPORT \*\*\*\*\***