

FCC §1.1310 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to 1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

| Limits for Occupational/Controlled Exposure | | | | |
|---|-----------------------------------|-----------------------------------|---|--|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E , H or S (minutes) |
| 0.3- 3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0 - 30 | 1842/f | 4.89/f | (900/f ²)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | / | / | f/300 | 6 |
| 1500-100,000 | / | / | 5 | 6 |

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Calculation

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

| Frequency | Max. Target Conducted Output Power | Typical Antenna Gain | | Distance | Power Density | Limit |
|-----------|------------------------------------|----------------------|---------|----------|--------------------|--------------------|
| MHz | mW | dBi | numeric | cm | mW/cm ² | mW/cm ² |
| 450.0125 | 40300 | 0 | 1.0 | 49 | 1.34 | 1.50 |

Radio Exposure Statement:

Using the parameters given in the above calculation, a minimum antenna to person distance of 49 cm is required to meet the limits for occupational/controlled exposure.

Result: Compliant.