

Modular Approval Request FCC (per DA 00-1407)

FCC ID:XXD-WSD3070-01

Items to be covered		Answer from applicant	
	The modular transmitter must have its own RF shielding.	YES	
2.	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	YES	
1.	The modular transmitter must have its own power supply regulation.	YES	W.E.
	The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c). The antenna must either be permanently attached or employ a "unique" enterprise (ct all permatical between the modular transmitter and the complex (ct all permatical between the modular transmitter).	YES	N D 3
	a "unique" antenna coupler (at all connections between the module and the antenna, including the cable)	A	
	and the state of t		F1.76
	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed.	YES	
		W.REBU	
	A series of the device into which it is eventually instance.	共创资的 排一加资	
j.	The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the	YES	200
	outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	
	may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the	mat (Class) (Ambalish S	
i A	latter case, a copy of these instructions must be included in the application for equipment authorization.	1. 4.1641.00i. 1 2. 40.60 0 0 0	To the
	The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A	YES	-3 (0)
copy of these instructions mu authorization. For example, requirements that must be met b Section 15.231. For instance, d under Section 15.231(e), in whi	copy of these instructions must be included in the application for equipment		
	Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.		
•	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine	YES	
	environmental evaluation for RF Exposure to demonstrate compliance. In		
	addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section		
	15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users,		

Note: If compliance with one or more of the numbered requirements, listed above, cannot be demonstrated, it may be possible to obtain a "Limited Modular Approval" (LMA).

Name and surname of applicant (or authorized representative): _ Christopher Vinckier

Date: 2009-12-9

Signature: