APPENDIX I
RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.407(f), U-NII devices are subject to the radio frequency radiation exposure requirements specified in §§ 1.1307(b), 2.1091 and 2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a "general population/uncontrolled" environment. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

EUT Specification

EUT	802.11a/n AP (Master)
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☒ WLAN: 5.18GHz ~ 5.23GHz ☐ WLAN: 5.725GHz ~ 5.850GHz ☐ Others: <u>Bluetooth: 2.402 GHz ~ 2.482 GHz</u>
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others: _____
Exposure classification	General Population/Uncontrolled exposure *(S=1mW/cm²)*
Antenna diversity	☐ Single antenna ☒ Multiple antennas 　☐ Tx diversity 　☐ Rx diversity 　☒ Tx/Rx diversity
Max. output power	IEEE 802.11a mode: 2.50 dBm (0.0018mW) draft 802.11n Standard-20 MHz Channel mode: 4.89 dBm (0.0031mW) draft 802.11n Wide-40 MHz Channel mode: 4.94 dBm (0.0031mW)
Antenna gain (Max)	Gain: IEEE 802.11a: 14.84 dBi (Numeric gain: 30.48) Gain: MIMO: 14.84 dBi + 10 log (2) = 17.85 dBi (Numeric gain: 60.95)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Remark:
1. *The maximum output power is <u>4.94dBm (0.0031mW)</u> at <u>5190MHz</u> (with <u>60.95 numeric antenna gain</u>.)*
2. *For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.*

TEST RESULTS

No non-compliance noted.

Calculation

Given $\quad E = \dfrac{\sqrt{30 \times P \times G}}{d}$ $\quad$ & $\quad S = \dfrac{E^2}{3770}$

$\qquad$ Where $\quad$ E = Field strength in Volts / meter

$\qquad\qquad$ P = Power in Watts
$\qquad\qquad$ G = Numeric antenna gain
$\qquad\qquad$ d = Distance in meters

$\qquad\qquad$ S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$\qquad$ P (mW) = P (W) / 1000 and
$\qquad$ d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \qquad \textbf{\textit{Equation 1}}$$

$\qquad$ Where $\quad$ d = Distance in cm
$\qquad\qquad$ P = Power in mW
$\qquad\qquad$ G = Numeric antenna gain
$\qquad\qquad$ S = Power density in mW / cm2

Maximum Permissible Exposure

EUT output power = 0.0031mW

Numeric Antenna gain = 60.95

Substituting the MPE safe distance using d = 20 cm into Equation 1:

Yields

$\qquad S = 0.000199 \times P \times G$

Where $\quad$ P = Power in mW

$\qquad\qquad$ G = Numeric antenna gain

$\qquad\qquad$ S = Power density in mW / cm^2

→ Power density = 0.000376 mW / cm^2

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.)