

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

DIGITAL WIRELESS CAMERA

MODEL No.: CM386C

BRAND NAME: LYD

FCC ID: XZF-CM386C

REPORT NO.: ED10010061-1

ISSUE DATE: February 25, 2010

Prepared for

**SHENZHEN LYD TECHNOLOGY CO.,LTD
Building A, Cunnan Industrial Estate, Shuidou Laowei, Longhua Town, Bao'an
District, Shenzhen, China**

Prepared by

DONGGUAN EMTEK CO., LTD

**No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

VERIFICATION OF COMPLIANCE

Applicant:	SHENZHEN LYD TECHNOLOGY CO.,LTD Building A, Cunnan Industrial Estate, Shuidou Laowei, Longhua Town, Bao'an District, Shenzhen, China
Product Description:	DIGITAL WIRELESS CAMERA
Brand Name:	LYD
Model Number:	CM386C
Serial Number:	N/A
File Number:	ED10010061-1
Date of Test:	January 19, 2010 to February 24, 2010

We hereby certify that:

The above equipment was tested by DONGGUAN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Approved By



Nicol Lee / Q.A. Manager
DONGGUAN EMTEK CO., LTD.

Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION.....	5
1.2 RELATED SUBMITTAL(S) / GRANT (S)	6
1.3 TEST METHODOLOGY	6
1.4 SPECIAL ACCESSORIES	6
1.5 EQUIPMENT MODIFICATIONS	6
1.6 TEST FACILITY	7
2. SYSTEM TEST CONFIGURATION	8
2.1 EUT CONFIGURATION	8
2.2 EUT EXERCISE	8
2.3 TEST PROCEDURE	8
2.4 LIMITATION	8
2.5 CONFIGURATION OF TESTED SYSTEM	12
3. DESCRIPTION OF TEST MODES.....	13
4. CONDUCTED EMISSIONS TEST	14
4.1 MEASUREMENT PROCEDURE:.....	14
4.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
4.3 MEASUREMENT EQUIPMENT USED:	14
4.4 MEASUREMENT RESULT:.....	15
4.5 CONDUCTED MEASUREMENT PHOTOS:	17
5. RADIATED EMISSION TEST	18
5.1 MEASUREMENT PROCEDURE	18
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
5.3 MEASUREMENT EQUIPMENT USED:	20
5.4 MEASUREMENT RESULT	20
5.5 RADIATED MEASUREMENT PHOTOS:	24
5. CHANNEL SEPARATION TEST	25
6.1 MEASUREMENT PROCEDURE	25
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	25
6.3 MEASUREMENT EQUIPMENT USED:	25
6.4 MEASUREMENT RESULTS:.....	25
6. 20DB BANDWIDTH TEST	28
7.1 MEASUREMENT PROCEDURE	28
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	28
7.3 MEASUREMENT EQUIPMENT USED:	28
7.4 MEASUREMENT RESULTS:.....	28

7. QUANTITY OF HOPPING CHANNEL TEST	31
8.1 MEASUREMENT PROCEDURE.....	31
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	31
8.3 MEASUREMENT EQUIPMENT USED:	31
8.4 MEASUREMENT RESULTS:	31
8. TIME OF OCCUPANCY (DWELL TIME) TEST	33
9.1 MEASUREMENT PROCEDURE.....	33
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	33
9.3 MEASUREMENT EQUIPMENT USED:	33
9.4 MEASUREMENT RESULTS:	33
10. MAXIMUM PEAK OUTPUT POWER TEST	36
10.1 MEASUREMENT PROCEDURE.....	36
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	36
10.3 MEASUREMENT EQUIPMENT USED:	36
10.4 MEASUREMENT RESULTS:	36
11. BAND EDGE TEST	37
11.1 MEASUREMENT PROCEDURE.....	37
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	37
11.3 MEASUREMENT EQUIPMENT USED:	37
11.4 MEASUREMENT RESULTS:	37
12. ANTENNA APPLICATION	39
12.1 ANTENNA REQUIREMENT	39
12.2. RESULT.....	39

1. GENERAL INFORMATION

1.1 Product Description

The SHENZHEN LYD TECHNOLOGY CO.,LTD Model: CM386C (referred to as the EUT in this report) The EUT is an short range, lower power, DIGITAL WIRELESS CAMERA designed as an " Input Device. It is designed by way of utilizing the GFSK modulation achieves the system operating.

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: 2410.875-2468.25MHz
- B). Modulation: GFSK
- C). Number of Channel: 18
- D). Channel space: 3.375MHz
- E). Rated RF Output Power: 15mW
- F). BIT Rate of Transmission: 100kbps
- G). Antenna Type: Soldered on PCB
- H). Antena GAIN: 0dBi(Peak)
- I). Power Supply: AC100-240V,50/60Hz

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2410.875	6	2431.125	12	2451.375
1	2414.25	7	2434.5	13	2454.75
2	2417.625	8	2437.875	14	2458.125
3	2421	9	2441.25	15	2461.5
4	2424.375	10	2444.625	16	2464.875
5	2427.75	11	2448	17	2468.25

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: XZF-CM386C filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (receiver) is compliance with Subpart B is authorized under a DoC procedure.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab.

: Accredited by CNAS, 2005.11.02
The certificate is valid until 2010.11
The Laboratory has been assessed and proved to be in compliance with CNAS/CL01:2006(identical to ISO/IEC17025:2005)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen, 2008.5

The certificate is valid until 2009.12

The Laboratory has been assessed according to the requirements ISO/IEC 17025

Accredited by FCC, Nov. 05, 2008

The Certificate Registration Number is 247565.

Accredited by Industry Canada, May 24, 2008

The Certificate Registration Number is 46405-4480

Name of Firm

: DONGGUAN EMTEK CO., LTD

Site Location

: No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions(Not apply in the report)

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the **frequency range between 0.15 MHz and 30MHz** using **CISPR Quasi-Peak and average detector mode**.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

2.4 Limitation

(1) Channel Separation test

FCC Part 15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 Bandwidth of the hopping channel, whichever is greater.

Frequency Range (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz

(2)	20dB Bandwidth					
	Frequency	Limit(kHz)				
	Range(MHz)	Quantity of Hopping Channel	50	25	15	75
		902-928	<250	>250	NA	NA
		2400-2483.5	NA	NA	>1000	<1000

(3) Quantity of Hopping Channel

FCC Part 15, Subpart C Section 15.247

Frequency Range (MHz)	Limit(Quantity of Hopping Channel)			
	20dB bandwidth <250kHz	20dB bandwidth >250kHz	20dB bandwidth <1MHz	20dB bandwidth >1MHz
902-928	50	25	NA	NA
2400-2483.5	NA	NA	75	15
5725-5850	NA	NA	75	NA

(4) Time of Occupancy(Dwell Time)

FCC Part 15, Subpart C Section 15.247

Frequency Range (MHz)	LIMIT(rms)		
	20dB bandwidth <250kHz(50Channel)	20dB bandwidth >250kHz(25Channel)	20dB bandwidth <1MHz(75Channel)
902-928	400(20S)	400(10S)	NA
2400-2483.5	NA	NA	400(30S)
5725-5850	NA	NA	400(30S)

Note: The “()”is all channel’s average time of occupancy.

(5) Maximum Peak Output Power

FCC Part 15, Subpart C Section 15.247

Frequency Range (MHz)	Quantity of Hopping Channel	LIMIT(W)			
		50	25	15	75
902-928		1(30dBm)	0.125(21dBm)	NA	NA
2400-2483.5		NA	NA	0.125(21dBm)	1(30dBm)
5725-5850		NA	NA	NA	1(30dBm)

(6) Band edge

FCC Part15, Subpart C Section 15.247, In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Operating Frequency Range(MHz)	Spurious emission frequency	Limit Peak power ration to emission(dBc)	Emission level(dBuV/m)
902-928	<902	>20	NA
	>928	>20	NA
	960-1240	NA	54
2400-2483.5	<2400	>20	NA
	>2483.5-2500	NA	54
5725-5850	<5350-5460	NA	54
	<5725	>20	NA
	>5850	>20	NA

(7) Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

(8) Radiated Emission

FCC Part 15, Subpart C Section 15.209 limit of radiated emission for frequency below 1000GHz. The emissions from an intentional radiator shall not exceed the field strength level specified in the following table:

Frequency (MHz)	Field strength $\mu\text{V/m}$	Distance(m)	Field strength at 3m $\text{dB}\mu\text{V/m}$
30-88	100	3	40
88-216	150	3	43.5
216-960	200	3	46
Above 960	500	3	54

Remark: 1. Emission level in $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

FCC Part 15, Section 15.35(b) limit of radiated emission for frequency above 1000MHz

Frequency(MHz)	Class A($\text{dB}\mu\text{V/m}$)(at 3m)		Class B($\text{dB}\mu\text{V/m}$)(at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency(MHz)	Filed Strength of Fundamental(at 3m)		Filed Strength of Harmonics(at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
902-928	114	94	74.0	54.0
2400-2483.5	114	94	74.0	54.0
5725-5875	114	94	74.0	54.0
24000-24250	128	108	88.0	68.0

2.5 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	DIGITAL WIRELESS CAMERA	LYD	CM386C	XZF- CM386C	N/A	<i>EUT</i>

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.

3. Description of test modes

The EUT (DIGITAL WIRELESS CAMERA) has been tested under normal operating condition.

This EUT is a FHSS system, we use blue test to control the EUT with LPT1, Let EUT hopping on and transmit at every channel with highest power, Only output power use conducted method, others are using radiated method. After sirfdemo330R1 send the command to EUT, it can be removed, and the EUT keep hopping. 18 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for best.


Channel	Frequency(MHz)
0	2410.875
8	2437.875
17	2468.25

4. Conducted Emissions Test

4.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.


4.2 Test SET-UP (Block Diagram of Configuration)




4.3 Measurement Equipment Used:

Conducted Emission Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2009	05/29/2010
L.I.S.N	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2009	05/29/2010
L.I.S.N	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2009	05/29/2010
50ΩCoaxial Switch	Anritsu	MP59B	M20531	05/29/2009	05/29/2010

4.4 Measurement Result:



Conducted Emission Measurement



Site site #1

Phase: N

Temperature: 25

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 50 %

EUT: DIGITAL WIRELESS CAMERA

M/N: CM386C

Mode: Transmitting

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.3700	49.62	0.00	49.62	58.50	-8.88	QP	
2		0.3700	38.39	0.00	38.39	48.50	-10.11	AVG	
3		1.0400	46.89	0.00	46.89	56.00	-9.11	QP	
4		1.0400	35.98	0.00	35.98	46.00	-10.02	AVG	
5		1.4100	47.42	0.00	47.42	56.00	-8.58	QP	
6		1.4100	37.44	0.00	37.44	46.00	-8.56	AVG	
7		1.7150	47.20	0.00	47.20	56.00	-8.80	QP	
8		1.7150	37.24	0.00	37.24	46.00	-8.76	AVG	
9		1.7750	48.00	0.00	48.00	56.00	-8.00	QP	
10		1.7750	36.68	0.00	36.68	46.00	-9.32	AVG	
11		24.0000	47.57	0.00	47.57	60.00	-12.43	QP	
12	*	24.0000	44.14	0.00	44.14	50.00	-5.86	AVG	

4.5 Conducted Measurement Photos:




5. Radiated Emission Test

5.1 Measurement Procedure


- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



5.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSP7	839511/010	05/29/2009	05/29/2010
Spectrum Analyzer	HP	E4407B	839840481	05/29/2009	05/29/2010
EMI Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2009	05/29/2010
Pre-Amplifier	HP	8447D	2944A07999	05/29/2009	05/29/2010
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2009	05/29/2010
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2009	05/29/2010
Horn Antenna	Electro-Metrics	EM-6961	103314	05/29/2009	05/29/2010
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/29/2009	05/29/2010

5.4 Measurement Result

Operation Mode: TX Mode Test Date : January 29, 2010
Frequency Range: 30~1000MHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Margin (dB)	Note
242.990	V	42.19	46.00	-3.81	PK
319.505	V	43.24	46.00	-2.76	PK
417.800	V	39.37	46.00	-6.63	PK
466.955	V	43.21	46.00	-2.79	PK
540.700	V	40.18	46.00	-5.82	PK
960.225	V	38.74	46.00	-7.26	PK
243.000	H	39.69	46.00	-6.31	PK
319.490	H	43.32	46.00	-2.68	PK
417.800	H	41.37	46.00	-4.63	PK
442.400	H	40.88	46.00	-5.12	PK
466.970	H	42.21	46.00	-3.79	PK
951.600	H	43.66	46.00	-2.34	PK

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.209.

Note: (1) All Readings are Peak Value.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: CH0: 2410.875MHz Test Date : January 29, 2010
Frequency Range: 1-25GHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4821.76	V	52.42	40.26	74	54	-21.58	-13.74
7231.69	V	50.24	41.74	74	54	-23.76	-12.26
9643.54	V	51.38	42.20	74	54	-22.62	-11.80
12054.34	V	55.26	41.78	74	54	-18.74	-12.22
4821.76	H	54.24	42.39	74	54	-19.76	-11.61
7231.69	H	56.85	43.76	74	54	-17.15	-10.24
9643.54	H	52.20	41.03	74	54	-21.80	-12.97
12054.34	H	54.68	43.46	74	54	-19.32	-10.54

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: CH8: 2437.875MHz Test Date : January 29, 2010
Frequency Range: 1-25GHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4875.76	V	52.48	45.25	74	54	-21.52	-8.75
7313.63	V	55.24	42.13	74	54	-18.76	-11.87
9751.56	V	56.87	43.25	74	54	-17.13	-10.75
12189.33	V	53.65	40.26	74	54	-20.35	-13.74
4875.76	H	55.69	43.68	74	54	-18.31	-10.32
7313.63	H	53.67	41.14	74	54	-20.33	-13.86
9751.56	H	55.75	40.28	74	54	-18.25	-13.72
12189.33	H	50.33	37.26	74	54	-23.67	-16.74

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.


Operation Mode: CH17: 2468.25MHz Test Date : January 29, 2010
Frequency Range: 1-25GHz Temperature : 28 °C
Test Result: PASS Humidity : 65 %
Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4936.55	V	62.15	47.28	74	54	-11.85	-6.72
7404.76	V	53.45	42.15	74	54	-20.55	-11.85
9873.12	V	45.72	34.26	74	54	-28.28	-19.74
12341.43	V	53.44	46.20	74	54	-20.56	-7.80
4936.55	H	56.57	42.36	74	54	-17.43	-11.64
7404.76	H	53.42	40.10	74	54	-20.58	-13.90
9873.12	H	55.48	42.28	74	54	-18.52	-11.72
12341.43	H	58.75	46.76	74	54	-15.25	-7.24

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.

5.5 Radiated Measurement Photos:




5. Channel Separation test

6.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:



Same as 4.3 Radiated Emission Measurement.


6.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	January 29, 2010
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %

Channel number	Channel frequency (MHz)	Separation Read Value (MHz)	20dB Down BW(MHz)	Separation Limit 2/3 20dB Down BW(MHz)
0	2410.875	3.45	>3.15	>2.10
8	2437.875	3.40	>3.38	>2.26
17	2468.25	3.35	>3.13	>2.08






6. 20dB Bandwidth test

7.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used:



Same as 4.3 Radiated Emission Measurement.


7.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	January 29, 2010
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %

Channel number	Channel frequency (MHz)	20dB Down BW(MHz)
0	2410.875	3.15
8	2437.875	3.38
17	2468.25	3.13






7. Quantity of Hopping Channel Test

8.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:


Same as 4.3 Radiated Emission Measurement.

8.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	January 29, 2010
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel(Limit)
2410.875-2468.25MHz	18	15




8. Time of Occupancy (Dwell Time) test

9.1 Measurement Procedure

- Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

Same as 4.3 Radiated Emission Measurement.

9.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	January 29, 2010
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %

Mode	Number of transmission in a 82 (18 Hopping*0.4)	Length of transmissions time(msec)	Result (msec)	Limit (msec)
DH1	13*7.2/5	0.410	7.675	400
DH3	13*7.2/5	0.460	8.611	400
DH5	13*7.2/5	0.460	8.611	400


This system hopping 13 hops in any 5s, and for each hop it transmit 2 pulses, the pulse dwell are 410μs, 460μs, 460μs, so the dwell times are:

$$13/5*7.2*0.41=7.675\text{ms}$$


$$13/5*7.2*0.46=8.611\text{ms}$$

$$13/5*7.2*0.46=8.611\text{ms}$$

DH1



DH3



DELTA MARKER 2
 460 μ s
 Ref 10 dBm
 Att 40 dB

RBW 100 kHz
 Delta 2 [T1]
 -4.97 dB
 460.000000 μ s

Marker 1 [T1]
 -27.86 dBm
 1.460000 μ s

1 PK
 UTED

Center 2.46825 GHz
 500 μ s

SPECTRUM
 RECEIVER
 MIXED


ALL MARKER
 OFF

10. MAXIMUM PEAK OUTPUT POWER TEST

10.1 Measurement Procedure

- Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	Boonton	4232A	29001	05/29/2009	05/29/2010
Power sensor	Boonton	51011-EMC	31184	05/29/2009	05/29/2010

10.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	January 29, 2010
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %


Channel number	Channel Frequency (MHz)	Reading Power (dBm)	Cable Loss (dB)	Result (dBm)	Result (mW)	Limit (mW)	Pass/Fail
0	2410.875	11.05	0.62	11.67	14.69	125	PASS
8	2437.875	10.89	0.57	11.46	13.99	125	PASS
17	2468.25	10.73	0.68	11.41	13.84	125	PASS

11. Band EDGE test

11.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

11.2 Test SET-UP (Block Diagram of Configuration)



11.3 Measurement Equipment Used:

Same as 4.3 Radiated Emission Measurement.

11.4 Measurement Results:

Refer to attached data chart.



Spectrum Detector:	PK	Test Date :	January 29, 2010
Test By:	Andy	Temperature :	28 °C
Test Result:	PASS	Humidity :	65 %

1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
<2400	-26.54	-69.98	43.44	>20dBc
>2483.5	-21.31	-68.54	47.23	>20dBc

2. Radiated emission test

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)	
		QP	AV	QP	AV
<2400	V	60.24	48.72	74.00	54.00
>2483.5	V	56.87	43.64	74.00	54.00



12. Antenna Application

12.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.240.

FCC part 15C section 15.247 requirements:

Systems operating in the 2.4GHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

12.2. Result

The EUT's antenna is soldered on PCB, The antenna's gain is 0dBi and meets the requirement.