

# FCC §15.247 (i), §2.1091 – RF Exposure

# **FCC ID: Y2P-WR1200**

#### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

**Limits for Occupational / Controlled Exposure** 

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

#### **Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

<sup>\* =</sup> Power density limit is applicable at frequencies greater than 100 MHz

<sup>\* =</sup> Plane-wave equivalent power density



## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna, R=0.2m

#### **TEST RESULTS**

	ANT	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenn a (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Total Power Density (S) (mW/ cm2)	Limit (mW / cm2	Result	
2462 (2.4G	Α	20±1	21	125.89	3.162 (5dBi)	0.07924	0.158482	4 5	1	Dana
Hz WIFI)	В	20±1	21	125.89	3.162 (5dBi)	0.07924		ı	Pass	
5745	Α	20±1	21	125.89	3.162 (5dBi)	0.07924	0.158482	1	Door	
(U-NII-3)	В	20±1	21	125.89	3.162 (5dBi)	0.07924		1	Pass	

## For the Max simultaneous transmission MPE:

	Power Density (S) (mW/ cm2)	Total Power Density (S) (mW/ cm2)	Limit (mW/ cm2)	Result	
2.4GHz WIFI	0.158482	0.316964	1	Pass	
5.8GHz WIFI	0.158482	0.510904	_	1 055	