

Test Report

FCC Part15 Subpart C

Product Name : Zipp Mini
Model No. : LTH200
FCC ID : Y2SLTH200
IC : 9452A-LTH200

Applicant : LIBRATONE A/S

Address : Marielundvej 43A, DK-2730 Herlev, Denmark

Date of Receipt : Jun. 25, 2015
Test Date : Jun. 25, 2015~ Aug. 14, 2015
Issued Date : Aug. 21, 2015
Report No. : 1560642R-RF-US-P06V01
Report Version : V 1.1

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : Aug. 21, 2015

Report No. : 1560642R-RF-US-P06V01



Product Name : Zipp Mini
Applicant : LIBRATONE A/S
Address : Marielundvej 43A, DK-2730 Herlev, Denmark
Manufacturer : Goertek Inc
Address : No 268 Dongfang Rd., New&high-tech Industry Development
Zone Weifang Shandong Province 261031, PRC.
Model No. : LTH200
FCC ID : Y2SLTH200
IC : 9452A-LTH200
EUT Voltage : AC 100~240V, 50/60Hz, 1.0A
Brand Name : LIBRATONE
Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2015
ANSI C63.4: 2014; ANSI C63.10: 2013
Industry Canada RSS-Gen Issue 4/RSS-247 Issue 1
Test Result : Complied
Performed Location : Suzhou EMC Laboratory
No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech
Development Zone., Suzhou, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392; IC Lab Code: 4075B


Documented By :


Elaine Wang Senior Engineer

Reviewed By :


Harry Zhao RF Engineering Manager

Approved By :


Dream Cao Director

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	:	BSMI, NCC
USA	:	FCC
Japan	:	VCCI
China	:	CNAS

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site :<http://www.quietek.com/tw/ctg/cts/accreditations.htm>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site :
<http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com

LinKou Testing Laboratory :

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com

Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : service@quietek.com

TABLE OF CONTENTS

Description	Page
1. General Information.....	8
1.1. EUT Description	8
1.1. Mode of Operation	11
1.2. Tested System Details.....	12
1.3. Configuration of Tested System	13
1.4. EUT Exercise Software	14
2. Technical Test.....	15
2.1. Summary of Test Result	15
2.2. Test Environment	17
3. Conducted Emission	18
3.1. Test Equipment	18
3.2. Test Setup	18
3.3. Limit.....	19
3.4. Test Procedure	19
3.5. Uncertainty	19
3.6. Test Result	20
4. Radiated Emission	22
4.1. Test Equipment	22
4.2. Test Setup	23
4.3. Limit.....	24
4.4. Test Procedure	24
4.5. Uncertainty	25
4.6. Test Result	26
5. 20dB Bandwidth	31
5.1. Test Equipment	31
5.2. Test Setup	31
5.3. Limit.....	31
5.4. Test Procedure	32
5.5. Uncertainty	32
5.6. Test Result	33
6. Carrier Frequency Separation	39
6.1. Test Equipment	39
6.2. Test Setup	39
6.3. Limit.....	39
6.4. Test Procedure	40
6.5. Uncertainty	40
6.6. Test Result	41

7.	Number of Hopping Frequencies	47
7.1.	Test Equipment	47
7.2.	Test Setup	47
7.3.	Limit.....	47
7.4.	Test Procedure	48
7.5.	Uncertainty	48
7.6.	Test Result	49
8.	Time of Occupancy (Dwell Time).....	55
8.1.	Test Equipment	55
8.2.	Test Setup	55
8.3.	Limit.....	55
8.4.	Test Procedure	56
8.5.	Uncertainty	56
8.6.	Test Result	57
9.	Peak Output Power	63
9.1.	Test Equipment	63
9.2.	Test Setup	63
9.3.	Limit.....	63
9.4.	Test Procedure	64
9.5.	Uncertainty	64
9.6.	Test Result	65
10.	Band-edge Compliance of RF Conducted Emissions	71
10.1.	Test Equipment	71
10.2.	Test Setup	71
10.3.	Limit.....	71
10.4.	Test Procedure	72
10.5.	Uncertainty	72
10.6.	Test Result	73
11.	Spurious RF Conducted Emissions.....	77
11.1.	Test Equipment	77
11.2.	Test Setup	77
11.3.	Limit.....	77
11.4.	Test Procedure	78
11.5.	Uncertainty	78
11.6.	Test Result	79
12.	Radiated Emission Band Edge.....	88
12.1.	Test Equipment	88
12.2.	Test Setup	89

12.3. Limit.....	89
12.4. Test Procedure	89
12.5. Uncertainty	90
12.6. Test Result	91

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
1560642R-RF-US-P06V01	V1.0	Initial Issued Report	Aug. 17, 2015
1560642R-RF-US-P06V01	V1.1	Changed EUT voltage	Aug. 21, 2015

1. General Information

1.1. EUT Description

Product Name	Zipp Mini
Brand Name	LIBRATONE
Model No.	LTH200
Working Voltage	AC 100~240V, 50/60Hz, 1.0A
Bluetooth Specification	3.0 + Version 4.0
Frequency Range	2402- 2480 MHz
Channel Number	V3.0+HS: 79 V4.0: 40
Channel Separation	V3.0+HS: 1MHz V4.0: 2MHz
Type of Modulation	V3.0: GFSK, Pi/4 DQPSK, 8DPSK V4.0: GFSK
Data Rate	V3.0: 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK) V4.0: 1Mbps
Antenna Type	Reference to Antenna List
Peak Antenna Gain	Reference to Antenna List

Bluetooth Working Frequency of Each Channel: (For V3.0)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

Bluetooth Working Frequency of Each Channel: (For V4.0)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	07	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz

Bluetooth Antenna List

Antenna	Manufacturer	Model No.	Peak Gain
PIFA Antenna	Goertek	N/A	1.2dBi for 2.4GHz

1.1. Mode of Operation

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmitter-1Mbps(GFSK_DH5)
Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z axis, and shown the worst case on this report.

1.2. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook	Asus	N80V	8BN0AS226971468	N/A

1.3. Configuration of Tested System



1.4. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of all equipment.
3	Input the RF commands, and set the test mode and channel, then press OK to start continue Transmit.

2. Technical Test

2.1. Summary of Test Result

☒ No deviations from the test standards

☐ Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(b)(1)	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2015 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2015 15.247(d)	Yes	No

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	RSS-Gen Issue 4 November 2014 Section 8.8	Yes	No
Radiated Emission	RSS-247 Issue 1 May 2015 Section 5.5	Yes	No
RF Antenna Conducted Spurious	RSS-247 Issue 1 May 2015 Section 5.5	Yes	No
Radiated Emission Band Edge	RSS-Gen Issue 4 November 2014 Section 8.10	Yes	No
Occupied Bandwidth	RSS-Gen Issue 4 November 2014 Section 6.6 RSS-247 Issue 1 May 2015 Section 5.2	Yes	No
Power Output	RSS-247 Issue 1 May 2015 Section 5.4	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100726	2016.03.10
Two-Line V-Network	R&S	ENV216	100043	2016.03.10
Two-Line V-Network	R&S	ENV216	100044	2015.09.16
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2016.03.01
50ohm Termination	SHX	TF2	07081401	2015.09.16
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2016.01.07

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

According to FCC ANSI C63.4: 2014 & ANSI C63.10: 2013.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Engineer: Scott	
Site: TR5	Time: 2015/07/05 - 10:25
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Line
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.158	45.878	36.147	-19.690	65.568	9.731	QP
2		0.158	35.026	25.295	-20.542	55.568	9.731	AV
3		0.226	41.807	32.097	-20.788	62.595	9.710	QP
4		0.226	32.474	22.764	-20.121	52.595	9.710	AV
5		0.278	39.742	30.042	-21.133	60.875	9.700	QP
6		0.278	31.413	21.713	-19.462	50.875	9.700	AV
7		0.350	38.360	28.660	-20.602	58.962	9.700	QP
8		0.350	31.843	22.143	-17.119	48.962	9.700	AV
9		0.414	34.291	24.588	-23.277	57.568	9.703	QP
10		0.414	27.224	17.521	-20.344	47.568	9.703	AV
11		0.470	34.744	25.044	-21.770	56.514	9.700	QP
12		0.470	27.797	18.097	-18.717	46.514	9.700	AV

Engineer: Scott	
Site: TR5	Time: 2015/07/05 - 10:31
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Neutral
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.158	45.637	35.906	-19.931	65.568	9.731	QP
2		0.158	35.275	25.544	-20.293	55.568	9.731	AV
3		0.222	42.216	32.496	-20.528	62.744	9.720	QP
4		0.222	35.195	25.475	-17.549	52.744	9.720	AV
5		0.286	41.441	31.731	-19.199	60.640	9.710	QP
6		0.286	34.955	25.245	-15.685	50.640	9.710	AV
7		0.350	38.602	28.896	-20.360	58.962	9.706	QP
8		0.350	32.237	22.531	-16.725	48.962	9.706	AV
9		0.466	36.704	27.004	-19.881	56.585	9.700	QP
10		0.466	30.764	21.064	-15.821	46.585	9.700	AV
11		0.534	32.360	22.660	-23.640	56.000	9.700	QP
12		0.534	25.341	15.641	-20.659	46.000	9.700	AV

Note: All the test modes are pretested and mode 1 was found to be the worst mode, so the data of this test mode was recorded.

4. Radiated Emission

4.1. Test Equipment

Radiated Emission / AC-2


Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2016.03.10
Loop Antenna	R&S	HFH2-Z2	833799/003	2015.11.25
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2015.10.10
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2016.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2016.01.07

Radiated Emission / AC-5


Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Preamplifier	Miteq	NSP1800-25	1364185	2016.05.03
Preamplifier	Quietek	AP-040G	CHM-0906001	2016.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2015.10.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2015.06.08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.04.10
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2016.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2016.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2016.03.01
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2016.01.07

4.2. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

According to ANSI C63.4: 2014; ANSI C63.10: 2013.

The EUT is placed on a turn table which is 1.5 meter for above 1G and 0.8 meter for below 1G above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level.

This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2014 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the “cone of radiation” of EUT. The 3dB beamwidth is 60~10 degrees for H-plane and 90~10 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor – Preamplifier Gain

Mode 1: Transmitter-1Mbps(GFSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4799.5	37.4	7.7	45.1	54(Note3)	-8.9	PK
	V	4799.5	39.3	7.7	47.0	54(Note3)	-7.0	PK
	H	7206.0	29.9	12.6	42.6	54(Note3)	-11.4	PK
	V	7206.0	28.2	12.6	40.8	54(Note3)	-13.2	PK
	H	9608.0	26.5	15.1	41.6	54(Note3)	-12.4	PK
	V	9608.0	26.6	15.1	41.7	54(Note3)	-12.3	PK
39	H	4884.5	37.0	7.8	44.8	54(Note3)	-9.2	PK
	V	4884.5	37.7	7.8	45.5	54(Note3)	-8.5	PK
	H	7323.0	28.8	12.9	41.7	54(Note3)	-12.3	PK
	V	7323.0	28.9	12.9	41.8	54(Note3)	-12.2	PK
	H	9764.0	26.7	15.4	42.1	54(Note3)	-11.9	PK
	V	9764.0	27.2	15.4	42.6	54(Note3)	-11.4	PK
78	H	4961.0	33.9	7.9	41.8	54(Note3)	-12.2	PK
	V	4961.0	35.6	7.9	43.5	54(Note3)	-10.5	PK
	H	7440.0	29.7	13.3	43.0	54(Note3)	-11.0	PK
	V	7440.0	28.9	13.3	42.2	54(Note3)	-11.8	PK
	H	9920.0	26.0	14.9	40.9	54(Note3)	-13.1	PK
	V	9920.0	26.6	14.9	41.5	54(Note3)	-12.5	PK

Note: 1. Measure Level = Reading Level + Factor.

- The test frequency range, 9kHz~30MHz, 18GHz~25GHz, both of the worst case are at least 6dB below the limits, therefore no data appear in the report.
- This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 2: Transmitter-2Mbps(Pi/4 DQPSK _DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4799.5	38.3	7.7	46.0	54(Note3)	-8.0	PK
	V	4808.0	36.3	7.7	44.0	54(Note3)	-10.0	PK
	H	7206.0	29.1	12.6	41.7	54(Note3)	-12.3	PK
	V	7206.0	28.0	12.6	40.6	54(Note3)	-13.4	PK
	H	9608.0	26.4	15.1	41.5	54(Note3)	-12.5	PK
	V	9608.0	26.3	15.1	41.4	54(Note3)	-12.6	PK
39	H	4884.5	33.9	7.8	41.7	54(Note3)	-12.3	PK
	V	4884.5	36.1	7.8	43.9	54(Note3)	-10.1	PK
	H	7323.0	28.7	12.9	41.6	54(Note3)	-12.4	PK
	V	7323.0	28.6	12.9	41.5	54(Note3)	-12.5	PK
	H	9764.0	27.1	15.4	42.5	54(Note3)	-11.5	PK
	V	9764.0	27.8	15.4	43.2	54(Note3)	-10.8	PK
78	H	4961.0	33.0	7.9	40.9	54(Note3)	-13.1	PK
	V	4961.0	34.5	7.9	42.4	54(Note3)	-11.6	PK
	H	7440.0	29.3	13.3	42.6	54(Note3)	-11.4	PK
	V	7440.0	28.8	13.3	42.1	54(Note3)	-11.9	PK
	H	9920.0	26.6	14.9	41.5	54(Note3)	-12.5	PK
	V	9920.0	26.3	14.9	41.2	54(Note3)	-12.8	PK

Note: 1. Measure Level = Reading Level + Factor.

2. The test frequency range, 9kHz~30MHz, 18GHz~25GHz, both of the worst case are at least 6dB below the limits, therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 3: Transmitter-3Mbps(8DPSK_DH5)


CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	4808.0	36.2	7.7	43.9	54(Note3)	-10.1	PK
	V	4799.5	38.5	7.7	46.2	54(Note3)	-7.8	PK
	H	7206.0	28.2	12.6	40.8	54(Note3)	-13.2	PK
	V	7206.0	28.1	12.6	40.7	54(Note3)	-13.3	PK
	H	9608.0	25.9	15.1	41.0	54(Note3)	-13.0	PK
	V	9608.0	26.4	15.1	41.5	54(Note3)	-12.5	PK
39	H	4884.5	34.4	7.8	42.2	54(Note3)	-11.8	PK
	V	4884.5	36.1	7.8	43.9	54(Note3)	-10.1	PK
	H	7323.0	27.9	12.9	40.8	54(Note3)	-13.2	PK
	V	7323.0	28.0	12.9	40.9	54(Note3)	-13.1	PK
	H	9764.0	26.3	15.4	41.7	54(Note3)	-12.3	PK
	V	9764.0	27.5	15.4	42.9	54(Note3)	-11.1	PK
78	H	4960.0	32.5	8.0	40.5	54(Note3)	-13.5	PK
	V	4961.0	34.1	7.9	42.0	54(Note3)	-12.0	PK
	H	7440.0	28.9	13.3	42.2	54(Note3)	-11.8	PK
	V	7440.0	28.7	13.3	42.0	54(Note3)	-12.0	PK
	H	9920.0	26.6	14.9	41.5	54(Note3)	-12.5	PK
	V	9920.0	26.5	14.9	41.4	54(Note3)	-12.6	PK

Note: 1. Measure Level = Reading Level + Factor.

2. The test frequency range, 9kHz~30MHz, 18GHz~25GHz, both of the worst case are at least 6dB below the limits, therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.


The worst case of Radiated Emission below 1GHz:

Engineer: Scott	
Site: AC2	Time: 2015/07/13 - 09:57
Limit: FCC_Part15.209_RE(3m)_ClassB	Margin: 0
Probe: AC2_10M(30-1000M)20150408	Polarity: Horizontal
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		34.525	29.360	35.711	-10.640	40.000	-6.351	QP
2		395.222	39.765	44.709	-6.235	46.000	-4.944	QP
3		479.220	37.528	40.440	-8.472	46.000	-2.912	QP
4	*	571.215	34.003	35.183	-11.997	46.000	-1.180	QP
5		883.210	37.624	36.594	-8.376	46.000	1.030	QP
6		960.101	38.812	36.701	-15.188	54.000	2.111	QP

Engineer: Scott	
Site: AC2	Time: 2015/07/13 - 09:57
Limit: FCC_Part15.209_RE(3m)_ClassB	Margin: 0
Probe: AC2_10M(30-1000M)20150408	Polarity: Vertical
EUT: Zipp Mini	Power: AC 120 V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	48.101	29.235	42.639	-10.765	40.000	-13.404	QP
2		395.615	36.221	41.155	-9.779	46.000	-4.934	QP
3		439.250	36.359	40.106	-9.641	46.000	-3.747	QP
4		479.991	43.621	46.521	-2.379	46.000	-2.900	QP
5		571.010	37.184	38.364	-8.816	46.000	-1.180	QP
6		960.215	38.816	36.704	-15.184	54.000	2.112	QP

5. 20dB Bandwidth


5.1 Test Equipment

20dB Bandwidth / TR8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2016.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2 Test Setup



5.3 Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

5.4 Test Procedure

According to ANSI C63.10: 2013& ANSI C63.4: 2014

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW \geq 1% of the 20dB bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-Zipp Mini function to measure 20 dB down one side of the emission. Reset the marker-Zipp Mini function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-Zipp Mini reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

5.5 Uncertainty

The measurement uncertainty is defined as ± 1 kHz

5.6 Test Result

Product	:	Zipp Mini
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	923.8	866.64
39	2441	925.4	864.15
78	2480	927.5	865.25

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



Product	:	Zipp Mini
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1237	1169.8
39	2441	1230	1170.8
78	2480	1313	1179.0

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



Product	:	Zipp Mini
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1281	1183.6
39	2441	1262	1168.1
78	2480	1278	1194.1

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



6. Carrier Frequency Separation


6.1. Test Equipment

Carrier Frequency Separation / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2016.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping

channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

6.4. Test Procedure

According to ANSI C63.10: 2013& ANSI C63.4: 2014

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) \geq 1% of the span

Video (or Average) Bandwidth VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-Zipp Mini function to determine the separation between the peaks of the adjacent channels.

6.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

6.6. Test Result


Product	:	Zipp Mini
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




Product	:	Zipp Mini
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass

Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Zipp Mini
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7. Number of Hopping Frequencies


7.1. Test Equipment

Number of Hopping Frequencies / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2016.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

7.4. Test Procedure

According to ANSI C63.10: 2013& ANSI C63.4: 2014

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.

7.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result


Product	:	Zipp Mini
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass

2400 - 2441 MHz




2441 - 2482 MHz



Product	:	Zipp Mini
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass

2400 - 2441 MHz



2441- 2482MHz



Product	:	Zipp Mini
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass

2400 - 2441 MHz



2441 - 2482 MHz



8. Time of Occupancy (Dwell Time)


8.1. Test Equipment

Time of Occupancy (Dwell Time) / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2016.01.07
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2016.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75

hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.4. Test Procedure

According to ANSI C63.10: 2013& ANSI C63.4: 2014

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-Zipp Mini function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

8.5. Uncertainty

The measurement uncertainty is defined as ± 0.1 us

8.6. Test Result


Product	:	Zipp Mini
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-1Mbps (GFSK_DH1)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	123.26	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6\text{sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $0.3816\text{ms} \times 323 = 123.26\text{msec}$

Channel 39 (2441MHz)-(DH1)






Product	:	Zipp Mini
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-1Mbps (GFSK_DH3)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	263.25	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6 \text{ sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $1.625 \text{ ms} \times 162 = 263.25 \text{ msec}$

Channel 39 (2441MHz) - (DH3)






Product	:	Zipp Mini
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-1Mbps (GFSK_DH5)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	333.16	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6 \text{ sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $2.897 \text{ ms} \times 115 = 333.16 \text{ msec}$

Channel 39 (2441MHz) - (DH5)





9. Peak Output Power


9.1. Test Equipment

Peak Output Power / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2016.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with

directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

According to ANSI C63.10: 2013& ANSI C63.4: 2014

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured.

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

9.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB

9.6. Test Result

Product	:	Zipp Mini
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	7.416	30.00	Pass
39	2441	7.826	30.00	Pass
78	2480	8.233	30.00	Pass

DH5 2402MHz



DH5 2441MHz



DH5 2480MHz



Product	:	Zipp Mini
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	6.143	30.00	Pass
39	2441	6.523	30.00	Pass
78	2480	6.739	30.00	Pass

2DH5 2402MHz



2DH5 2441MHz




2DH5 2480MHz



Product	:	Zipp Mini
Test Item	:	Power Output
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	6.465	30.00	Pass
39	2441	6.853	30.00	Pass
78	2480	7.061	30.00	Pass

3DH5 2402MHz



3DH5 2441MHz



3DH5 2480MHz



10. Band-edge Compliance of RF Conducted Emissions


10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2016.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz

bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

10.4. Test Procedure

According to ANSI C63.10: 2013& ANSI C63.4: 2014

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-Zipp Mini function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-Zipp Mini value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

10.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB

10.6. Test Result

Product	:	Zipp Mini
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel 00 (2402MHz)



Channel 78 (2480MHz)



Product	:	Zipp Mini
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel 00 (2402MHz)



Channel 78 (2480MHz)



Product	:	Zipp Mini
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel 00 (2402MHz)



Channel 78 (2480MHz)



Product	:	Zipp Mini
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Site	:	TR-8
Test Mode	:	Mode: Hopping Mode



11. Spurious RF Conducted Emissions


11.1. Test Equipment

Spurious RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2016.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

11.2. Test Setup



11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in

Section 15.209(a) of FCC part 15 is not required.

11.4. Test Procedure

According to ANSI C63.10: 2013.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.

The level displayed must comply with the limit specified in this section.

11.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB

11.6. Test Result

Product	:	Zipp Mini
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps (GFSK_DH5)

Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Zipp Mini
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps (Pi/4 DQPSK_DH5)

Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



Product	:	Zipp Mini
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps (8DPSK_DH5)

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




12. Radiated Emission Band Edge

12.1. Test Equipment

☒ Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2016.03.10
Preamplifier	Miteq	NSP1800-25	1364185	2016.05.03
Preamplifier	QuieTek	AP-040G	CHM-0906001	2016.05.03
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2015.10.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	733	2016.02.26
DRG Horn	ETS-Lindgren	3117	00167055	2015.07.16
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2016.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2016.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2015.08.07
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2016.01.07

12.2. Test Setup



12.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

12.4. Test Procedure

According to ANSI C63.10: 2013& ANSI C63.4: 2014

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with

sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.

If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative “marker-Zipp Mini” method may be employed.

12.5. Uncertainty

The measurement uncertainty above 1G is defined as $\pm 3.9 \text{ dB}$
below 1G is defined as $\pm 3.8 \text{ dB}$

12.6. Test Result


All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 100ms;


Average = Peak Measure Level+ Duty Factor

Duty Factor= $20 \cdot \text{LOG}(\text{Pulse Number} \cdot \text{On Time}/100) = -30.63\text{dB}$ in worst condition in normal use.

Pulse Number




Site: AC5	Time: 2015/06/26 - 11:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 1: Transmit at CH2402 by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2373.270	50.739	13.803	-23.261	74.000	36.937	PK
2		2390.000	48.304	11.313	-25.696	74.000	36.991	PK
3	*	2401.913	100.702	63.696	N/A	N/A	37.007	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1		2373.270	50.739	20.109	-33.891	54.000	-30.63	AV
2		2390.000	48.304	17.674	-36.326	54.000	-30.63	AV
3	*	2401.913	100.702	70.072	N/A	N/A	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:12
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 1: Transmit at CH2402 by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2371.940	56.208	19.281	-17.792	74.000	36.927	PK
2		2390.000	54.350	17.359	-19.650	74.000	36.991	PK
3	*	2402.055	101.240	64.233	N/A	N/A	37.006	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1		2371.940	56.208	25.578	-28.422	54.000	-30.63	AV
2		2390.000	54.350	23.720	-30.280	54.000	-30.63	AV
3	*	2402.055	101.240	70.610	N/A	N/A	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 1: Transmit at CH2480 by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.914	101.746	64.409	N/A	N/A	37.336	PK
2		2483.500	53.824	16.453	-20.176	74.000	37.371	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1	*	2479.914	101.746	71.116	N/A	N/A	-30.63	AV
2		2483.500	53.824	23.194	-30.806	54.000	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:17
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 1: Transmit at CH2480 by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.947	101.711	64.374	N/A	N/A	37.337	PK
2		2483.500	56.076	18.705	-17.924	74.000	37.371	PK
3		2494.313	57.122	19.646	-16.878	74.000	37.476	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1	*	2479.947	101.711	71.081	N/A	N/A	-30.63	AV
2		2483.500	56.076	25.446	-28.554	54.000	-30.63	AV
3		2494.313	57.122	26.492	-27.508	54.000	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:21
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 2: Transmit at CH2402 by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2359.827	50.103	13.265	-23.897	74.000	36.838	PK
2		2390.000	48.485	11.494	-25.515	74.000	36.991	PK
3	*	2402.008	99.074	62.067	N/A	N/A	37.006	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1		2359.827	50.103	19.473	-34.527	54.000	-30.63	AV
2		2390.000	48.485	17.855	-36.145	54.000	-30.63	AV
3	*	2402.008	99.074	68.444	N/A	N/A	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 2: Transmit at CH2402 by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2349.235	56.200	19.417	-17.800	74.000	36.783	PK
2		2390.000	53.946	16.955	-20.054	74.000	36.991	PK
3	*	2402.103	99.040	62.033	N/A	N/A	37.007	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1		2349.235	56.200	25.570	-28.430	54.000	-30.63	AV
2		2390.000	53.946	23.316	-30.684	54.000	-30.63	AV
3	*	2402.103	99.040	68.410	N/A	N/A	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 2: Transmit at CH2480 by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.914	100.344	63.007	N/A	N/A	37.336	PK
2		2483.500	54.963	17.592	-19.037	74.000	37.371	PK
3		2492.872	56.272	18.810	-17.728	74.000	37.463	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1	*	2479.914	100.344	69.714	N/A	N/A	-30.63	AV
2		2483.500	54.963	24.333	-29.667	54.000	-30.63	AV
3		2492.872	56.272	25.642	-28.358	54.000	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 2: Transmit at CH2480 by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.914	100.344	63.007	N/A	N/A	37.336	PK
2		2483.500	55.341	17.970	-18.659	74.000	37.371	PK
3		2491.376	56.852	19.404	-17.148	74.000	37.447	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1	*	2479.914	100.344	69.714	N/A	N/A	-30.63	AV
2		2483.500	55.341	24.711	-29.289	54.000	-30.63	AV
3		2491.376	56.852	26.222	-27.778	54.000	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:31
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 3: Transmit at CH2402 by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2384.718	56.335	19.355	-17.665	74.000	36.980	PK
2		2390.000	53.873	16.882	-20.127	74.000	36.991	PK
3	*	2401.913	99.245	62.239	N/A	N/A	37.007	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1		2384.718	56.335	25.705	-28.295	54.000	-30.63	AV
2		2390.000	53.873	23.243	-30.757	54.000	-30.63	AV
3	*	2401.913	99.245	68.615	N/A	N/A	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 3: Transmit at CH2402 by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2374.837	56.610	19.662	-17.390	74.000	36.948	PK
2		2390.000	54.370	17.379	-19.630	74.000	36.991	PK
3	*	2401.913	99.245	62.239	N/A	N/A	37.007	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1		2374.837	56.610	25.980	-28.020	54.000	-30.63	AV
2		2390.000	54.370	23.740	-30.260	54.000	-30.63	AV
3	*	2401.913	99.245	68.615	N/A	N/A	-30.63	AV


Site: AC5	Time: 2015/06/26 - 11:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 3: Transmit at CH2480 by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.947	100.337	63.000	N/A	N/A	37.337	PK
2		2483.500	54.230	16.859	-19.770	74.000	37.371	PK
3		2484.952	56.364	18.979	-17.636	74.000	37.386	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1	*	2479.947	100.337	69.707	N/A	N/A	-30.63	AV
2		2483.500	54.230	23.600	-30.400	54.000	-30.63	AV
3		2484.952	56.364	25.734	-28.266	54.000	-30.63	AV

Site: AC5	Time: 2015/06/26 - 11:38
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Zipp Mini	Power: AC 120V/60Hz
Note: Mode 3: Transmit at CH2480 by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	100.439	63.102	N/A	N/A	37.338	PK
2		2483.500	55.654	18.283	-18.346	74.000	37.371	PK
3		2488.725	56.516	19.094	-17.484	74.000	37.422	PK

No	Mark	Frequency (MHz)	Peak Level (dBuV/m)	AV Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Duty Factor (dB)	Type
1	*	2479.980	100.439	69.809	N/A	N/A	-30.63	AV
2		2483.500	55.654	25.024	-28.976	54.000	-30.63	AV
3		2488.725	56.516	25.886	-28.114	54.000	-30.63	AV

— The End —