



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Applicant : Outform Ltd.

Address : R405, East, Buliding 203,Tai Ran Industrial Zone, Chengongmiao,
Futian, Shenzhen, China

Product Name : Retail Tablet

Model Name : UID0352: RETAIL TABLET L, UID0356: RETAIL TABLET XL,
UID0357: RETAIL TABLET XXL, UID0075: ADVERTISING DISPLAY L,
UID0078: ADVERTISING DISPLAY XL, UID0081: ADVERTISING
DISPLAY XXL, UID0052/56/57/75/78/81-XX(XX is A-Z ,the color and
adaptor type, such as:BU/BE/BK/WU/WE/WK, B is black, W is white,
U is USA, E is Europe, K is UK)

Brand Name : I-DISPLAY

FCC ID : Y34-UID0357

Report No. : MTE/EAH/E11121698

Date of Issue : Jan. 19, 2012

Issued by : Most Technology Service Co., Ltd.

Address : No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan,
Shenzhen, Guangdong, China

Tel : 86-755-8617 0306

Fax : 86-755-8617 0310

The report consists 65 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	3
2. GENERAL INFORMATION.....	4
2.1 Product Information.....	4
2.2 Objective.....	5
2.3 Test Standards and Results	5
2.4 Environmental Conditions.....	5
3. TEST FACILITY	6
4. TEST EQUIPMENT LIST	7
5. 47 CFR Part 15 C 15.247 Requirements.....	8
5.1 6dB Bandwidth	8
5.1.1 Definition	8
5.1.2 Test Description	8
5.1.3 Test Result.....	8
5.2 Peak Output Power	15
5.2.1 Definition	15
5.2.2 Test Description	15
5.2.3 Test Result.....	15
5.3 Conducted Spurious Emission	17
5.3.1 Definition	17
5.3.2 Test Description	17
5.3.3 Test Result.....	17
5.4 Band Edge	23
5.4.1 Definition	23
5.4.2 Test Description	23
5.4.3 Test Result.....	23
5.5 Power Spectral Density (PSD).....	31
5.5.1 Definition	31
5.5.2 Test Description	31
5.5.3 Test Result.....	31
5.6 Conducted Emission	37
5.6.1 Definition	37
5.6.2 Test Description	37
5.6.3 Test Result.....	37
5.7 Radiated Emission	44
5.7.1 Definition	44
5.7.2 Test Description	45
5.7.3 Test Result.....	46
APPENDIX 1	63
PHOTOGRAPHS OF TEST SETUP	63

1. VERIFICATION OF CONFORMITY

Equipment Under Test: Retail Tablet

Brand Name: I-DISPLAY

Model Number: UID0352: RETAIL TABLET L, UID0356: RETAIL TABLET XL,
UID0357: RETAIL TABLET XXL

Series Model Number: UID0075: ADVERTISING DISPLAY L, UID0078: ADVERTISING DISPLAY XL,
UID0081: ADVERTISING DISPLAY XXL, UID0352/356/357/075/078/081-XX
(XX is A-Z, the color and adaptor type, such as: BU/BE/BK/WU/WE/WK, B is black, W is white, U is USA, E is Europe, K is UK)

FCC ID: Y34-UID0357

Applicant: Outform Ltd.
R405, East, Buliding 203, Tai Ran Industrial Zone, Chengongmiao, Futian,
Shenzhen, China

Manufacturer: Outform Ltd.
R405, East, Buliding 203, Tai Ran Industrial Zone, Chengongmiao, Futian,
Shenzhen, China

Technical Standards: 47 CFR Part 15 Subpart C

File Number: MTE/EAH/E11121698

Date of test: Dec. 28, 2011-Jan. 12, 2012

Deviation: None

Condition of Test Sample: Normal

Test Result: PASS

The above equipment was tested by *MOST* for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepared by (+ signature):


Dona Liu


Jan. 12, 2012

Review by (+ signature):


Elva Wong

Jan. 16, 2012

Approved by (+ signature):


Yvette Zhou(Manager)

Jan. 19, 2012



2. GENERAL INFORMATION

2.1 Product Information

Description:	Retail Tablet
Model Name:	UID0352: RETAIL TABLET L, UID0356: RETAIL TABLET XL, UID0357: RETAIL TABLET XXL
Series Number:	UID0075: ADVERTISING DISPLAY L, UID0078: ADVERTISING DISPLAY XL, UID0081: ADVERTISING DISPLAY XXL, UID0352/356/357/075/078/081-XX(XX is A-Z, the color and adaptor type, such as: BU/BE/BK/WU/WE/WK, B is black, W is white, U is USA, E is Europe, K is UK)
Model Difference description:	<ol style="list-style-type: none"> 1. The series models are different in model name and size with the same functions. 2. The size of “L” is 15.6 inch. 3. The size of “XL” is 18.5 inch. 4. The size of “XXL” is 21.5 inch.
Frequency Range:	2412MHz – 2462MHz
Number of Channels:	IEEE 802.11b/g/nmode: 11 Channels
Modulation Technique:	IEEE 802.11b mode: DSSS (1, 2, 5.5 and 11 Mbps) IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mbps) 802.11n Standard-20 MHz Channel mode: OFDM (6.5, 13, 19.5, 26, 39, 52, 58.5, 65.0Mbps)
Antenna Type:	Internal Fixed
Antenna Gain:	2.0dBi
Power Supply:	DC 12V by AC adapter (100-240V, 50/60Hz)
Temperature Range:	-20°C ~ +50°C

NOTE:

1. For a more detailed features description about the EUT, please refer to User's Manual.

2.2 Objective

Perform FCC Part 15 Subpart B tests for FCC Marking.

2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.247(a)(2)	6dB Bandwidth	PASS	2011/12/28-2012/01/10
2	15.247(b)(3)	Peak Output Power	PASS	2011/12/28-2012/01/10
3	15.247(d)	conducted spurious emission	PASS	2011/12/28-2012/01/10
4	15.247(d)	Band Edge	PASS	2011/12/28-2012/01/10
5	15.247(e)	Power Spectral Density	PASS	2011/12/28-2012/01/10
6	15.207	Conducted Emission	PASS	2012-01-09
7	15.247(d) 15.205 15.209	Radiated Emission	PASS	2012-01-10

Note:

1. The test result judgment is decided by the limit of measurement standard
2. The information of measurement uncertainty is available upon the customer's request.

2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

3. TEST FACILITY

Test Site:	Most Technology Service Co., Ltd.
Location:	No.5, Nangshan 2nd Rd., North Hi-Tech Industrial park, Nanshan, Shenzhen, Guangdong, China
Description:	<p>There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4 and CISPR 16 requirements.</p> <p>The FCC Registration Number is 490827.</p>
Site Filing:	<p>The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.</p>
Instrument Tolerance:	All measuring equipment is in accord with ANSI C63.4 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.
Ground Plane:	<p>Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna. It has no holes or gaps having longitudinal dimensions larger than one-tenth of a wavelength at the highest frequency of measurement up to 1GHz.</p>

4. TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at MOST for testing. The equipment conforms to the CISPR 16-1/ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	Manufacturer	Model No.	S/N	Calibration due date
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
2	Spectrum Analyzer	Agilent	E7405A	US44210471	2012/03/14
3	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2012/03/14
4	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
5	Terminator	Hubersuhner	50Ω	No.1	2012/03/14
6	RF Cable	SchwarzBeck	N/A	No.1	2012/03/14
7	Test Receiver	Rohde & Schwarz	ESPI	101202	2012/03/14
8	Bilog Antenna	Sunol	JB3	A121206	2012/03/14
9	Horn Antenna	TRC	N/A	N/A	2012/03/14
10	Cable	Resenberger	N/A	NO.1	2012/03/14
11	Cable	SchwarzBeck	N/A	NO.2	2012/03/14
12	Cable	SchwarzBeck	N/A	NO.3	2012/03/14
13	DC Power Filter	DuoJi	DL2×30B	N/A	2012/03/14
14	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2012/03/14
15	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2012/03/14
16	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14
17	Absorbing Clamp	Luthi	MDS21	3635	2012/03/14
18	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14
19	AC Power Source	Kikusui	AC40MA	LM003232	2012/03/14
20	Test Analyzer	Kikusui	KHA1000	LM003720	2012/03/14
21	Line Impedence Network	Kikusui	LIN40MA-PCR-L	LM002352	2012/03/14
22	ESD Tester	Kikusui	KES4021	LM003537	2012/03/14
23	EMC PRO System	EM Test	UCS-500-M4	V0648102026	2012/03/14
24	Signal Generator	IFR	2032	203002/100	2012/03/14
25	Amplifier	A&R	150W1000	301584	2012/03/14
26	CDN	FCC	FCC-801-M2-25	47	2012/03/14
27	CDN	FCC	FCC-801-M3-25	107	2012/03/14
28	EM Injection Clamp	FCC	F-203I-23mm	403	2012/03/14
29	RF Cable	MIYAZAKI	N/A	No.1/No.2	2012/03/14
30	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2012/03/14
31	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2012/03/14
32	8 Loop Antenna	ARA	PLA-1030/B	1029	2012/02/19

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 15 C 15.247 Requirements

5.1 6dB Bandwidth

5.1.1 Definition

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.1.2 Test Description

The EUT is powered by the Battery, is coupled to the Spectrum Analyzer (SA) through the Attenuator/DC Block. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power. The RF load attached to the EUT antenna terminal is 50Ohm.




Figure 1: RF Test Setup

5.1.3 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.


5.1.3.1 802.11b Test Mode

The minimum occupied bandwidth for the fundamental frequency 2442MHz is 7.8 MHz. This occupied bandwidth complies with the FCC requirement.


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	8.3	≥ 500	PASS
7	2442	7.8	≥ 500	PASS
11	2462	8.4	≥ 500	PASS


B. Test Plot:



(CH Low)



(CH Mid)



(CH High)


5.1.3.2 802.11g Test Mode

The minimum occupied bandwidth for the fundamental frequency 2412MHz is 15.3MHz. This occupied bandwidth complies with the FCC requirement.


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	15.3	≥ 500	PASS
7	2442	15.4	≥ 500	PASS
11	2462	15.5	≥ 500	PASS


B. Test Plot:



(CH Low)



(CH Mid)




(CH High)

5.1.3.3 802.11n Test Mode


The minimum occupied bandwidth for the fundamental frequency 2412MHz is 15.3MHz. This occupied bandwidth complies with the FCC requirement.

A. Test Verdict:


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	15.3	≥ 500	PASS
7	2442	16.1	≥ 500	PASS
11	2462	16.3	≥ 500	PASS

B. Test Plot:

(CH Low)



(CH Mid)



(CH High)

5.2 Peak Output Power

5.2.1 Definition

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

5.2.2 Test Description



The EUT which is powered by AC adapter, is coupled to the Power Meter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

5.2.3 Test Result

The EUT operates at maximum output power mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

5.2.3.1 802.11b Test Mode

The maximum output power for the fundamental frequency 2462MHz is 6.138dBm. This power complies with the FCC requirement.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	4.972	0.003	30	1	PASS
7	2442	6.014	0.004			PASS
11	2462	6.138	0.004			PASS

5.2.3.2 802.11g Test Mode

The maximum output power for the fundamental frequency 2462 MHz is 5.986dBm. This power complies with the FCC requirement.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	3.551	0.002	30	1	PASS
7	2442	5.475	0.003			PASS
11	2462	5.986	0.003			PASS

5.2.3.3 802.11n Test Mode

The maximum output power for the fundamental frequency 2462 MHz is 5.973dBm. This power complies with the FCC requirement.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	4.455	0.003	30	1	PASS
7	2442	5.341	0.003			PASS
11	2462	5.973	0.004			PASS

5.3 Conducted Spurious Emission

5.3.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

5.3.2 Test Description


See section 5.1.2 of this report.

5.3.3 Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

5.3.3.1 802.11b Test Mode


Test Plot:



(CH Low, 9kHz to 25GHz)



(CH Mid, 9kHz to 25GHz)




(CH High, 9kMHz to 25GHz)

Note:


1. The power of the Module transmitting frequency should be ignored.

5.3.3.2 802.11g Test Mode


Test Plot:



(CH Low, 9kHz to 25GHz)



(CH Mid, 9kHz to 25GHz)




(CH High, 9kHz to 25GHz)

Note:


1. The power of the Module transmitting frequency should be ignored.

5.3.3.3 802.11n Test Mode


Test Plot:



(CH Low, 9kHz to 25GHz)



(CH Mid, 9kHz to 25GHz)




(CH High, 9kHz to 25GHz)

5.4 Band Edge

5.4.1 Definition

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

5.4.2 Test Description




5.4.3 Test Result

The EUT operates at continuous transmit test mode. The lowest and highest channels are tested to verify the band edge emissions.


5.4.3.1 802.11b Test Mode

Test Mode		Channel Marked Frequency	Limit (dBuV/m)	Test Result Highest Emission (dBuV/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
WIFI	Low Channel	2390MHz	74(Peak) 54(Average)	67.27	45.20	51.62	31.87
		2400MHz		67.38	46.28	52.44	32.69
	High Channel	2483.5MHz		66.01	45.13	65.94	43.43
		2500MHz		58.92	39.84	60.37	38.29


Test Plot:




(CH Low, Vertical, Peak)



(CH Low, Horizontal, Peak)



(CH High, Vertical, Peak)




(CH High, Horizontal, Peak)


5.4.3.2 802.11g Test Mode

Test Mode		Channel Marked Frequency	Limit (dBuV/m)	Test Result Highest Emission (dBuV/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
WIFI	Low Channel	2390MHz	74(Peak) 54(Average)	60.73	36.57	61.18	37.17
		2400MHz		72.21	50.25	71.55	50.53
	High Channel	2483.5MHz		72.79	49.08	71.16	48.38
		2500MHz		60.27	39.73	59.77	38.14


Test Plot:




(CH Low, Horizontal, Peak)



(CH Low, Vertical, Peak)



(CH High, Horizontal, Peak)




(CH High, Vertical, Peak)

5.4.3.3 802.11n Test Mode

Test Mode		Channel Marked Frequency	Limit (dBuv/m)	Test Result Highest Emission (dBuv/m)			
				Vertical		Horizontal	
				Peak	Average	Peak	Average
WIFI	Low Channel	2390MHz	74(Peak) 54(Average)	59.47	36.39	61.10	37.08
		2400MHz		69.87	50.75	69.55	50.33
	High Channel	2483.5MHz		68.64	49.12	69.80	48.92
		2500MHz		59.39	39.66	59.72	38.68


Test Plot:




(CH Low, Horizontal, Peak)



(CH Low, Vertical, Peak)



(CH High, Horizontal, Peak)



(CH High, Vertical, Peak)

5.5 Power Spectral Density (PSD)

5.5.1 Definition

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.5.2 Test Description

See section 5.1.2 of this report.

5.5.3 Test Result


The lowest, middle and highest channels are tested to verify the power spectral density.



5.5.3.1 802.11b Test Mode

A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-10.68	≤ 8	PASS
7	2442	-9.377	≤ 8	PASS
11	2462	-6.417	≤ 8	PASS

B. Test Plot:






5.5.3.2 802.11g Test Mode


A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-12.65	≤ 8	PASS
7	2442	-11.21	≤ 8	PASS
11	2462	-9.295	≤ 8	PASS


B. Test Plot:



(CH Low)



(CH Mid)




(CH High)

5.5.3.3 802.11n Test Mode


A. Test Verdict:

Channel	Frequency (MHz)	PSD (dBm)	Limits(dBm)	Result
1	2412	-14.55	≤ 8	PASS
7	2442	-10.14	≤ 8	PASS
11	2462	-17.17	≤ 8	PASS


B. Test Plot:



(CH Low)



(CH Mid)



(CH High)

5.6 Conducted Emission

5.6.1 Definition

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).


Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

5.6.2 Test Description

The EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power.



5.6.3 Test Result

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The Wifi model was carried out for 802.11b/g/n modulation types, 802.11b High channel modulation type was the worst case condition for model UID0352: RETAIL TABLET L, UID0356: RETAIL TABLET XL and UID0357: RETAIL TABLET XXL, The test data was shown on the summary data page.



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Conducted Emission Measurement

File: UID0352: RETAIL TABLET L

Data: #12

Date: 2012-01-09

Time: 17:37:50



Site site #1

Phase: **L1**

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0352: RETAIL TABLET L

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2060	39.97	11.96	51.93	63.37	-11.44	QP	
2		0.3660	34.84	10.89	45.73	58.59	-12.86	QP	
3		0.9740	26.57	10.00	36.57	56.00	-19.43	QP	
4		2.3220	23.50	9.32	32.82	56.00	-23.18	QP	
5		5.9780	18.19	11.41	29.60	60.00	-30.40	QP	
6		14.3180	16.61	9.00	25.61	60.00	-34.39	QP	

*:Maximum data x:Over limit l:over margin

Engineer Signature: Rex



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Conducted Emission Measurement

File: UID0352: RETAIL TABLET L

Data: #13

Date: 2012-01-09

Time: 17:38:58



Site: site #1

Phase: N

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0352: RETAIL TABLET L

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2140	41.16	11.91	53.07	63.05	-9.98	QP	
2		0.3260	33.62	11.16	44.78	59.55	-14.77	QP	
3		0.8060	27.32	10.00	37.32	56.00	-18.68	QP	
4		1.4460	28.26	9.55	37.81	56.00	-18.19	QP	
5		3.5780	19.45	10.58	30.03	56.00	-25.97	QP	
6		7.9140	17.97	10.25	28.22	60.00	-31.78	QP	

*:Maximum data x:Over limit l:over margin

Engineer Signature: Rex



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Conducted Emission Measurement

File: UID0356: RETAIL TABLET XL

Data: #12

Date: 2012-01-11

Time: 12:37:50



Site: site #1

Phase: L1

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0356: RETAIL TABLET XL

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2060	40.47	11.96	52.43	63.37	-10.94	QP	
2		0.6420	29.12	10.00	39.12	56.00	-16.88	QP	
3		1.4100	25.62	9.59	35.21	56.00	-20.79	QP	
4		4.0460	22.39	11.05	33.44	56.00	-22.56	QP	
5		6.9300	21.97	10.84	32.81	60.00	-27.19	QP	
6		14.3180	17.61	9.00	26.61	60.00	-33.39	QP	

*:Maximum data x:Over limit l:over margin

Engineer Signature: Rex



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Conducted Emission Measurement

File: UID0356: RETAIL TABLET XL

Data: #13

Date: 2012-01-11

Time: 12:38:58



Site: site #1

Phase: **N**

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0356: RETAIL TABLET XL

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2140	40.16	11.91	52.07	63.05	-10.98	QP	
2		0.7260	29.34	10.00	39.34	56.00	-16.66	QP	
3		1.4460	28.76	9.55	38.31	56.00	-17.69	QP	
4		3.0900	22.28	10.09	32.37	56.00	-23.63	QP	
5		4.8940	20.34	11.89	32.23	56.00	-23.77	QP	
6		14.3260	19.50	9.00	28.50	60.00	-31.50	QP	

*:Maximum data x:Over limit l:over margin

Engineer Signature: Rex



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Conducted Emission Measurement

File: UID0357: RETAIL TABLET XXL

Data: #5

Date: 2012-01-11

Time: 6:03:45



Site: site #1

Phase: N

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0357: RETAIL TABLET XXL

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2060	39.04	11.96	51.00	63.37	-12.37	QP	
2		0.3780	31.60	10.81	42.41	58.32	-15.91	QP	
3		0.9300	28.66	10.00	38.66	56.00	-17.34	QP	
4		1.4540	26.50	9.55	36.05	56.00	-19.95	QP	
5		3.2140	20.26	10.21	30.47	56.00	-25.53	QP	
6		4.8660	18.31	11.87	30.18	56.00	-25.82	QP	

*:Maximum data x:Over limit l:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement


File: UID0357: RETAIL TABLET XXL

Data: #6

Date: 2012-01-11

Time: 6:05:13

80.0 dBuV



Site: site #1

Phase: L1

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

M/N: UID0357: RETAIL TABLET XXL

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2100	38.56	11.93	50.49	63.21	-12.72	QP	
2		0.3183	33.29	11.21	44.50	59.75	-15.25	QP	
3		0.8900	27.45	10.00	37.45	56.00	-18.55	QP	
4		1.7220	24.15	9.28	33.43	56.00	-22.57	QP	
5		4.6100	18.48	11.61	30.09	56.00	-25.91	QP	
6		7.8780	12.41	10.27	22.68	60.00	-37.32	QP	

*:Maximum data x:Over limit l:over margin

Engineer Signature: Allen

5.7 Radiated Emission

5.7.1 Definition

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).


According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.


5.7.2 Test Description

A. Test Setup:



Blow 1GHz:



Above 1GHz:**B. Test procedures**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
 Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO
 Above 1GHz : (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

5.7.3 Test Result

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			

From 30MHz to 1GHz:

The Wifi model was carried out for 802.11b/g/n modulation types, 802.11b High channel modulation type was the worst case condition for model UID0352: RETAIL TABLET L, UID0356: RETAIL TABLET XL and UID0357: RETAIL TABLET XXL, The test data was shown on the summary data page.

Below 1 GHz



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File: UID0357: RETAIL TABLET XXL

Data: #11

Date: 2012-1-11

Time: 9:02:46



Site: site #1

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Retail Tablet

Distance:

M/N: UID0357: RETAIL TABLET XXL

Mode: WIFI Mode

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	I	256.0100	24.05	17.44	41.49	46.00	-4.51	QP	0	
2	*	266.6800	23.63	18.47	42.10	46.00	-3.90	QP	0	
3	I	320.0298	24.80	17.00	41.80	46.00	-4.20	QP	0	
4		399.5700	20.88	18.69	39.57	46.00	-6.43	QP	0	
5	I	480.0800	19.33	21.70	41.03	46.00	-4.97	QP	0	
6		640.1300	15.18	24.00	39.18	46.00	-6.82	QP	0	

*:Maximum data x:Over limit I:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File: UID0357: RETAIL TABLET XXL

Data: #12

Date: 2012-1-11

Time: 9:04:39



Site site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 61 %

EUT: Retail Tablet

Distance:

M/N: UID0357: RETAIL TABLET XXL

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	I	77.5300	23.44	11.52	34.96	40.00	-5.04	QP	0	
2		255.0400	21.74	17.40	39.14	46.00	-6.86	QP	0	
3	*	266.6800	22.65	18.47	41.12	46.00	-4.88	QP	0	
4		320.0298	22.37	17.00	39.37	46.00	-6.63	QP	0	
5		480.0800	13.88	21.70	35.58	46.00	-10.42	QP	0	
6		640.1300	12.98	24.00	36.98	46.00	-9.02	QP	0	

*:Maximum data x:Over limit I:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File: UID0352: RETAIL TABLET L

Data: #9

Date: 2012-1-10

Time: 16:17:39



Site site #1

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

Distance:

M/N: UID0352: RETAIL TABLET L

Mode: WIFI Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		164.8300	16.94	17.21	34.15	43.50	-9.35	QP	0	
2		263.7700	21.83	18.09	39.92	46.00	-6.08	QP	0	
3	!	376.2900	23.12	18.21	41.33	46.00	-4.67	QP	0	
4	*	498.5100	20.54	21.43	41.97	46.00	-4.03	QP	0	
5	!	780.7798	15.41	26.18	41.59	46.00	-4.41	QP	0	
6	!	829.2798	14.02	26.97	40.99	46.00	-5.01	QP	0	

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File: UID0352: RETAIL TABLET L

Data: #10

Date: 2012-1-10

Time: 16:13:44



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

Distance:

M/N: UID0352: RETAIL TABLET L

Mode: WIFI Mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	I	74.6200	22.89	11.65	34.54	40.00	-5.46	QP	0	
2		299.6600	20.66	19.30	39.96	46.00	-6.04	QP	0	
3	*	372.4100	24.07	18.22	42.29	46.00	-3.71	QP	0	
4	I	499.4800	20.32	21.41	41.73	46.00	-4.27	QP	0	
5	I	668.2600	17.27	24.43	41.70	46.00	-4.30	QP	0	
6	I	836.0700	14.42	27.10	41.52	46.00	-4.48	QP	0	

*:Maximum data x:Over limit I:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File: UID0356: RETAIL TABLET XL

Data: #11

Date: 2012-1-10

Time: 14:10:59



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

Distance:

M/N: UID0356: RETAIL TABLET XL

Mode: WIFI Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		77.5300	20.10	11.52	31.62	40.00	-8.38	QP	0	
2		224.0000	19.88	16.38	36.26	46.00	-9.74	QP	0	
3	*	299.6600	22.91	19.30	42.21	46.00	-3.79	QP	0	
4		374.3500	21.61	18.24	39.85	46.00	-6.15	QP	0	
5		449.0400	19.15	20.12	39.27	46.00	-6.73	QP	0	
6	!	674.0800	16.26	24.54	40.80	46.00	-5.20	QP	0	

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen



Address: No. 5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310


Radiated Emission Measurement

File: UID0356: RETAIL TABLET XL

Data: #12

Date: 2012-1-10

Time: 14:13:01



Site site #1

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part 15 B 3M Radiation

Power: DC 12V Adapter AC 120V/60Hz

Humidity: 60 %

EUT: Retail Tablet

Distance:

M/N: UID0356: RETAIL TABLET XL

Mode: WIFI Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		74.6200	21.59	11.65	33.24	40.00	-6.76	QP	0	
2	*	177.4398	22.33	16.83	39.16	43.50	-4.34	QP	0	
3		356.8900	20.87	18.24	39.11	46.00	-6.89	QP	0	
4		449.0400	19.18	20.12	39.30	46.00	-6.70	QP	0	
5	!	772.0500	14.83	25.96	40.79	46.00	-5.21	QP	0	
6		899.1200	12.51	27.39	39.90	46.00	-6.10	QP	0	

*:Maximum data x:Over limit !:over margin

Engineer Signature: Allen

Above 1 GHz

Operation Mode: TX/ IEEE 802.11b/CH Low **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4824.0	H	32.10	14.52	23.54	55.64	38.06	74.00	54.00	-15.94
N/A	H								
4824.0	V	33.45	15.03	23.36	56.81	38.39	74.00	54.00	-15.61
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11b/CH Mid **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Peak	AV	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dB)
4884.0	H	30.54	10.29	23.54	54.08	33.83	74.00	54.00	-20.17
N/A	H								
4884.0	V	31.69	11.20	23.36	55.05	34.56	74.00	54.00	-19.44
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11b/CH High **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Peak	AV	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dB)
4924.0	H	27.98	9.53	23.54	51.52	33.87	74.00	54.00	-20.13
N/A	H								
4924.0	V	26.78	9.42	23.36	50.14	32.78	74.00	54.00	-21.22
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11g/CH Low **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Peak	AV	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dB)
4824.0	H	34.18	13.54	23.54	57.72	37.08	74.00	54.00	-16.92
N/A	H								
4824.0	V	32.51	12.96	23.36	55.87	36.32	74.00	54.00	-17.68
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11g/CH Mid **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4884.0	H	31.06	11.87	23.54	54.60	35.41	74.00	54.00	-18.59
N/A	H								
4884.0	V	30.25	10.39	23.36	53.61	33.75	74.00	54.00	-20.25
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11g/CH High **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Peak	AV	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dB)
4924.0	H	28.94	10.87	23.54	52.48	34.41	74.00	54.00	-19.59
N/A	H								
4924.0	V	29.12	9.85	23.36	52.48	33.21	74.00	54.00	-20.79
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11n/CH Low **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
4824.0	H	32.48	14.47	23.54	55.02	38.01	74.00	54.00	-15.91
N/A	H								
4824.0	V	31.75	13.26	23.36	55.11	36.62	74.00	54.00	-17.38
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11n/CH Mid **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Peak	AV	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dB)
4884.0	H	30.82	11.69	23.54	54.36	35.23	74.00	54.00	-18.77
N/A	H								
4884.0	V	31.29	10.41	23.36	54.65	33.77	74.00	54.00	-20.23
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

Operation Mode: TX/ IEEE 802.11n/CH High **Test Date:** Jan. 12, 2012
Model Name: UID0357: RETAIL TABLET XXL **Tested by:** Habby Guo
Temperature: 20°C **Polarity:** Ver. / Hor.
Humidity: 70 % RH

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actual Fs		Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF	Peak	AV	Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)			(dBuV/m)	(dBuV/m)	(dB)
4924.0	H	29.78	9.43	23.54	53.32	32.97	74.00	54.00	-21.03
N/A	H								
4924.0	V	28.12	10.03	23.36	51.48	33.39	74.00	54.00	-20.61
N/A	V								

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).


APPENDIX 1


PHOTOGRAPHS OF TEST SETUP

CE TEST SETUP



RE TEST SETUP





CONDUCTED SPURIOUS EMISSION TEST SETUP



-----END OF REPORT-----