

FCC REPORT

Applicant: Posturite LTD

Address of Applicant: The Mill, Berwick, East Sussex, BN26 6SZ, UK

Equipment Under Test (EUT)

Product Name: Wireless Mouse

Model No.: 9820099, 9820102, 9820103

Trade Mark:



FCC ID: Y35-9820099D

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249:2010

Date of sample receipt: June 26, 2012


Date of Test: July 11, 2012

Date of report issued: July 11, 2012

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

The image shows a handwritten signature in black ink over a circular blue stamp. The stamp contains the text "GLOBAL UNITED TECHNOLOGY SERVICES CO.", "GTS", and "GLOBAL TESTING".

Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	July 11, 2012	Original

Prepared By:

Oscar. Li

Date:

July 11, 2012

Project Engineer

Check By:

Hans. Hu

Date:

July 11, 2012

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION.....	2
3 CONTENTS.....	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 TEST FACILITY	6
5.6 TEST LOCATION.....	6
5.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5.8 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 ANTENNA REQUIREMENT:	8
6.2 CONDUCTED EMISSIONS	9
6.3 RADIATED EMISSION METHOD	12
6.3.1 <i>Field Strength of The Fundamental Signal</i>	14
6.3.2 <i>Spurious emissions</i>	15
6.3.3 <i>Bandedge emissions</i>	19
6.4 20dB OCCUPY BANDWIDTH.....	20
7 TEST SETUP PHOTO.....	22
8 EUT CONSTRUCTIONAL DETAILS.....	24

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Posturite LTD
Address of Applicant:	The Mill, Berwick, East Sussex, BN26 6SZ, UK
Manufacturer:	SHENZHEN BONDIDEA TECHNOLOGY CO., LIMITED
Address of Manufacturer:	No 10th, honghualing industrial park, longxi , longgang, Shenzhen , China
Factory:	SHENZHEN BONDIDEA TECHNOLOGY CO., LIMITED
Address of factory :	No 10th, honghualing industrial park, longxi , longgang, Shenzhen , China

5.2 General Description of E.U.T.

Product Name:	Wireless Mouse
Model No.:	9820099, 9820102, 9820103
Operation Frequency:	2408MHz -2474MHz
Channel number:	34
Channel separation:	2MHz
Modulation type:	GFSK
Antenna Type:	Integral
Antenna Gain:	0dBi
Power supply:	DC 5V by USB Port
Remark:	Only the model No. 9820099 was tested. 9820099, 9820102, 9820103 are identical in the same PCB layout, interior structure and electrical circuits. The only differences are the model name and appearance color for commercial purpose.

5.3 Test mode

Transmitting mode	Keep the EUT in transmitting mode.
-------------------	------------------------------------

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	77.16	79.70	78.64

Final Test Mode:

According to ANSI C63.4 standards, the test results are both the "worst case" and "worst setup":

Y axis (see the test setup photo)

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
IBM	Notebook	T42	GTS209	DoC
IBM	AC Adapter	92P1024	N/A	DoC

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• FCC —Registration No.: 600491

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission.

The acceptance letter from the FCC is maintained in our files. Registration 600491, July 20, 2010.

• Industry Canada (IC)

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. Has been

Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-1.

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

5.7 Other Information Requested by the Customer

None.

5.8 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 30 2011	Mar. 29 2013
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 03 2012	Jul. 02 2013
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 25 2012	Feb. 24 2013
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 29 2012	June 28 2013
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2011	Mar. 29 2013
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	Mar. 31 2012	Mar. 30 2013
9	Coaxial Cable	GTS	N/A	GTS211	Mar. 31 2012	Mar. 30 2013
10	Coaxial cable	GTS	N/A	GTS210	Mar. 31 2012	Mar. 30 2013
11	Coaxial Cable	GTS	N/A	GTS212	Mar. 31 2012	Mar. 30 2013
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 03 2012	Jul. 02 2013
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 03 2012	Jul. 02 2013
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 29 2012	June 28 2013
15	Band filter	Amindeon	82346	GTS219	Mar. 31 2012	Mar. 30 2013

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS252	Sep. 08 2011	Sep. 07 2013
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	Jul. 03 2012	Jul. 02 2013
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	Jul. 03 2012	Jul. 02 2013
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	Jul. 03 2012	Jul. 02 2013
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	Jul. 03 2012	Jul. 02 2013
6	Coaxial Cable	GTS	N/A	GTS227	Jul. 03 2012	Jul. 02 2013
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Thermo meter	KTJ	TA328	GTS233	Jul. 05 2012	Jul. 04 2013

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 09 2012	July 08 2013

6 Test results and Measurement Data

6.1 Antenna requirement:


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
E.U.T Antenna: <p><i>The RF antenna is a PCB antenna, the best case gain of the antenna is 0dBi</i></p>	
	

6.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.4:2003																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> <p>* Decreases with the logarithm of the frequency.</p>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
Test setup:	<div><p style="text-align: center;">Reference Plane</p><p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p></div>																
Test procedure:	<ol style="list-style-type: none">1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.																
Test Instruments:	Refer to section 5.8 for details																
Test mode:	Refer to section 5.3 for details																
Test results:	Pass																

Measurement data:


Line:



Trace: 22
 Condition : FCC PART15 QP LISN(2011) LINE
 Job No. : 688RF
 Test Mode : TX
 Test Engineer: Blue

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.211	31.20	0.65	0.10	31.95	53.18	-21.23	Average
2	0.211	34.86	0.65	0.10	35.61	63.18	-27.57	QP
3	0.558	28.40	0.54	0.10	29.04	46.00	-16.96	Average
4	0.558	31.80	0.54	0.10	32.44	56.00	-23.56	QP
5	1.610	32.06	0.42	0.10	32.58	46.00	-13.42	Average
6	1.610	34.62	0.42	0.10	35.14	56.00	-20.86	QP
7	3.346	24.49	0.34	0.10	24.93	46.00	-21.07	Average
8	3.346	27.69	0.34	0.10	28.13	56.00	-27.87	QP
9	12.318	32.88	0.20	0.20	33.28	50.00	-16.72	Average
10	12.318	28.47	0.20	0.20	28.87	60.00	-31.13	QP
11	20.486	39.76	0.14	0.21	40.11	50.00	-9.89	Average
12	20.486	40.86	0.14	0.21	41.21	60.00	-18.79	QP


Neutral:




Condition : FCC PART15 QP LISN(2011) NEUTRAL
 Job No. : 688RF
 Test Mode : TX
 Test Engineer: Blue

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.209	29.87	0.65	0.10	30.62	53.23	-22.61	Average
2	0.209	35.95	0.65	0.10	36.70	63.23	-26.53	QP
3	0.767	24.96	0.51	0.10	25.57	46.00	-20.43	Average
4	0.767	29.89	0.51	0.10	30.50	56.00	-25.50	QP
5	1.191	27.88	0.46	0.10	28.44	46.00	-17.56	Average
6	1.191	33.78	0.46	0.10	34.34	56.00	-21.66	QP
7	1.610	26.95	0.42	0.10	27.47	46.00	-18.53	Average
8	1.610	33.62	0.42	0.10	34.14	56.00	-21.86	QP
9	11.807	31.83	0.20	0.20	32.23	50.00	-17.77	Average
10	11.807	36.40	0.20	0.20	36.80	60.00	-23.20	QP
11	20.924	34.46	0.14	0.21	34.81	50.00	-15.19	Average
12	20.924	40.45	0.14	0.21	40.80	60.00	-19.20	QP

6.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.00		Quasi-peak Value
	88MHz-216MHz		43.50		Quasi-peak Value
	216MHz-960MHz		46.00		Quasi-peak Value
	960MHz-1GHz		54.00		Quasi-peak Value
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	Below 1GHz				
	<div></div>				
	Above 1GHz				

	 <p>The diagram illustrates the test setup. An EUT (Equipment Under Test) is placed on a Turn Table at a height of 0.8m. The Turn Table is 3m away from an Antenna Tower. The Antenna Tower has a Horn Antenna at a height of 4m. A Spectrum Analyzer is connected to the Antenna Tower via an Amplifier. The Spectrum Analyzer is also connected to the Antenna Tower. The distance between the EUT and the Antenna Tower is 3m. The height of the Antenna Tower is 4m. The height of the Turn Table is 0.8m. The height of the Horn Antenna is 1m.</p>
<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
<p>Test Instruments:</p>	<p>Refer to section 5.8 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Pass</p>

Measurement data:

6.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2408.00	41.86	27.57	5.40	0.00	74.83	114.00	-39.17	Horizontal
2408.00	45.83	27.57	5.40	0.00	78.80	114.00	-35.20	Vertical
2440.00	41.69	27.48	5.43	0.00	74.60	114.00	-39.40	Horizontal
2440.00	45.76	27.48	5.43	0.00	78.67	114.00	-35.33	Vertical
2474.00	42.49	27.50	5.46	0.00	75.45	114.00	-38.55	Horizontal
2474.00	46.74	27.50	5.46	0.00	79.70	114.00	-34.30	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2408.00	31.26	27.57	5.40	0.00	64.23	94.00	-29.77	Horizontal
2408.00	35.99	27.57	5.40	0.00	68.96	94.00	-25.04	Vertical
2440.00	30.85	27.48	5.43	0.00	63.76	94.00	-30.24	Horizontal
2440.00	35.86	27.48	5.43	0.00	68.77	94.00	-25.23	Vertical
2474.00	31.78	27.50	5.46	0.00	64.74	94.00	-29.26	Horizontal
2474.00	36.76	27.50	5.46	0.00	69.72	94.00	-24.28	Vertical

According to the follow transmitter output power (P_t) formula:

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E=electric field strength in V/m

d= measurement distance in meters (m).

According to the above test data, $E_{max}=79.70\text{dBuV/m}=0.00966\text{V/m}$, $d=3\text{m}$, $g_t=1$

$$P_t = (E \times d)^2 / (30 \times g_t) = (0.00966 \times 3)^2 / (30 \times 1) = 0.00002799\text{W}$$

6.3.2 Spurious emissions

■ Below 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
39.02	38.04	16.58	0.65	32.06	23.21	40.00	-16.79	Vertical
52.95	37.99	16.20	0.80	31.95	23.04	40.00	-16.96	Vertical
102.36	37.26	15.98	1.21	31.77	22.68	43.50	-20.82	Vertical
302.48	38.40	16.11	2.37	32.17	24.71	46.00	-21.29	Vertical
349.25	39.24	16.30	2.62	32.03	26.13	46.00	-19.87	Vertical
758.04	38.33	22.53	4.31	31.27	33.90	46.00	-12.10	Vertical
40.14	38.16	16.58	0.66	32.06	23.34	40.00	-16.66	Horizontal
55.61	38.55	16.06	0.82	31.95	23.48	40.00	-16.52	Horizontal
102.00	37.09	16.01	1.21	31.77	22.54	43.50	-20.96	Horizontal
239.15	39.10	15.06	2.06	32.16	24.06	46.00	-21.94	Horizontal
362.99	38.44	16.45	2.68	31.99	25.58	46.00	-20.42	Horizontal
766.06	38.77	22.63	4.33	31.28	34.45	46.00	-11.55	Horizontal

■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4816.00	23.97	31.79	8.61	24.17	40.20	74.00	-33.80	Vertical
7224.00	26.34	36.19	11.66	26.46	47.73	74.00	-26.27	Vertical
9632.00	20.35	38.01	14.16	25.44	47.08	74.00	-26.92	Vertical
12040.00	*					74.00		Vertical
14448.00	*					74.00		Vertical
4816.00	23.09	31.78	8.60	24.17	39.30	74.00	-34.70	Horizontal
7224.00	26.24	36.19	11.66	26.46	47.63	74.00	-26.37	Horizontal
9632.00	18.31	38.01	14.16	25.44	45.04	74.00	-28.96	Horizontal
12040.00	*					74.00		Horizontal
14448.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4816.00	15.24	31.79	8.61	24.17	31.47	54.00	-22.53	Vertical
7224.00	17.94	36.19	11.66	26.46	39.33	54.00	-14.67	Vertical
9632.00	12.22	38.01	14.16	25.44	38.95	54.00	-15.05	Vertical
12040.00	*					54.00		Vertical
14448.00	*					54.00		Vertical
4816.00	14.36	31.78	8.60	24.17	30.57	54.00	-23.43	Horizontal
7224.00	17.84	36.19	11.66	26.46	39.23	54.00	-14.77	Horizontal
9632.00	10.18	38.01	14.16	25.44	36.91	54.00	-17.09	Horizontal
12040.00	*					54.00		Horizontal
14448.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is too weak instrument of signal is unable to test.

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	25.00	31.85	8.66	24.10	41.41	74.00	-32.59	Vertical
7320.00	27.13	36.37	11.72	26.71	48.51	74.00	-25.49	Vertical
9760.00	18.11	38.35	14.25	25.36	45.35	74.00	-28.65	Vertical
12200.00	*					74.00		Vertical
14640.00	*					74.00		Vertical
4880.00	24.15	31.85	8.66	24.10	40.56	74.00	-33.44	Horizontal
7320.00	25.96	36.37	11.72	26.78	47.27	74.00	-26.73	Horizontal
9760.00	17.63	38.35	14.25	25.36	44.87	74.00	-29.13	Horizontal
12200.00	*					74.00		Horizontal
14640.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	16.40	31.85	8.66	24.10	32.81	54.00	-21.19	Vertical
7320.00	18.60	36.37	11.72	26.71	39.98	54.00	-14.02	Vertical
9760.00	10.10	38.35	14.25	25.36	37.34	54.00	-16.66	Vertical
12200.00	*					54.00		Vertical
14640.00	*					54.00		Vertical
4880.00	15.55	31.85	8.66	24.10	31.96	54.00	-22.04	Horizontal
7320.00	17.43	36.37	11.72	26.78	38.74	54.00	-15.26	Horizontal
9760.00	9.62	38.35	14.25	25.36	36.86	54.00	-17.14	Horizontal
12200.00	*					54.00		Horizontal
14640.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4948.00	25.97	31.91	8.71	24.05	42.54	74.00	-31.46	Vertical
7422.00	27.53	36.56	11.77	27.03	48.83	74.00	-25.17	Vertical
9896.00	17.96	38.81	14.35	25.27	45.85	74.00	-28.15	Vertical
12370.00	*					74.00		Vertical
14844.00	*					74.00		Vertical
4948.00	24.62	31.91	8.71	24.05	41.19	74.00	-32.81	Horizontal
7422.00	26.61	36.56	11.79	27.03	47.93	74.00	-26.07	Horizontal
9896.00	19.16	38.72	14.35	25.29	46.94	74.00	-27.06	Horizontal
12370.00	*					74.00		Horizontal
14844.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4948.00	16.96	31.91	8.71	24.05	33.53	54.00	-20.47	Vertical
7422.00	18.85	36.56	11.77	27.03	40.15	54.00	-13.85	Vertical
9896.00	9.67	38.81	14.35	25.27	37.56	54.00	-16.44	Vertical
12370.00	*					54.00		Vertical
14844.00	*					54.00		Vertical
4948.00	15.61	31.91	8.71	24.05	32.18	54.00	-21.82	Horizontal
7422.00	17.93	36.56	11.79	27.03	39.25	54.00	-14.75	Horizontal
9896.00	10.87	38.72	14.35	25.29	38.65	54.00	-15.35	Horizontal
12370.00	*					54.00		Horizontal
14844.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

6.3.3 Bandedge emissions

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	40.41	27.91	5.30	30.37	43.25	74.00	-30.75	Horizontal
2390.00	42.42	27.59	5.38	30.18	45.21	74.00	-28.79	Horizontal
2310.00	44.11	27.91	5.30	30.37	46.95	74.00	-27.05	Vertical
2390.00	45.53	27.59	5.38	30.18	48.32	74.00	-25.68	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	28.29	27.91	5.30	30.37	31.13	54.00	-22.87	Horizontal
2390.00	30.64	27.59	5.38	30.18	33.43	54.00	-20.57	Horizontal
2310.00	32.75	27.91	5.30	30.37	35.59	54.00	-18.41	Vertical
2390.00	34.62	27.59	5.38	30.18	37.41	54.00	-16.59	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	42.18	27.53	5.47	29.93	45.25	74.00	-28.75	Horizontal
2500.00	40.67	27.55	5.49	29.93	43.78	74.00	-30.22	Horizontal
2483.50	45.32	27.53	5.47	29.93	48.39	74.00	-25.61	Vertical
2500.00	44.51	27.55	5.49	29.93	47.62	74.00	-26.38	Vertical


Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	29.80	27.53	5.47	29.93	32.87	54.00	-21.13	Horizontal
2500.00	28.95	27.55	5.49	29.93	32.06	54.00	-21.94	Horizontal
2483.50	33.38	27.53	5.47	29.93	36.45	54.00	-17.55	Vertical
2500.00	32.46	27.55	5.49	29.93	35.57	54.00	-18.43	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

6.4 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.4:2003
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.8 for details
Test mode:	Transmitting mode
Test results:	Pass

Measurement Data


Dongle:

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.626	Pass
Middle	1.607	Pass
Highest	1.578	Pass


Test plot as follows:



Lowest channel




Middle channel



Highest channel

7 Test Setup Photo

Radiated Emission








Conducted Emission



8 EUT Constructional Details







-----End-----