RF Exposure Evaluation declaration

Product Name	modlet gateway
Model No.	TE1210
FCC ID	Y38TE1210

Applicant	ThinkEco Inc.
Address	148 Madison Avenue, 8th Floor, New York, NY, United States,10016

Date of Receipt	Apr. 06, 2012
Date of Declaration	Apr. 11, 2012
Report No.	124197R-RFUSP42V01

1.   RF Exposure Evaluation

1.1.   Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*Pi*R^2)$

Where

Pd = power density in mW/cm^2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm^2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2.   Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18℃ and 78％ RH.

1.3. Test Result of RF Exposure Evaluation

Product : modlet gateway
Test Item : RF Exposure Evaluation
Test Site : No.3 OATS

Antenna Gain:

The maximum Gain measured in fully anechoic chamber is 2.0 dBi in logarithm scale.

Zigbee

Output Power Into Antenna & RF Exposure Evaluation Distance (2.0 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)
1	2405.00	1.3274	0.000419
9	2445.00	1.3243	0.000418
16	2480.00	0.6138	0.000194

Power density in column 4 is much lower than the limit (1 mW/cm^2).