MPE Calculation : RFID

RF function or Mode	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm^2)	Requriment (mW/cm^2)
RFID	917.10	~	926.90	25.00	2.79	27.79	601.174	0.120	0.611
		~							
		~							
		~							
		~							
		~							
		~							

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$ \textbf{S} = \text{EIRP} / (4\ R^2\ \pi) $$
$$ = 601.174\ / (4 \times 20^2 \times \pi) $$
$$ = 0.12\ \text{mW/cm}^2 $$

- Note

S= Maximum power density(mW/cm^2)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenn

▪ **Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm^2)	Averageing time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f^2	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC