

version 7.0.



FCC PART 15.247 TEST REPORT

For

Galaxy Microsystems Ltd.

Room 1101-1103, 11/F, Enterprise Square Two, 3 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong

FCC ID: Y3GGALAPAD7G2

| Report Type: Original Report | | Product Type: Galapad 7 |
|------------------------------|---|-------------------------|
| Test Engineer: | Leon Chen | leon then |
| Report Number: | R2DG1305 | 508007-00A |
| Report Date: | 2013-07-3 Ivan Cao | 1 |
| Reviewed By: | | . Ivan Can |
| Test Laboratory: | Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn | |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above

TABLE OF CONTENTS

| GENERAL INFORMATION | 4 |
|--|----------|
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 4 |
| Objective | |
| RELATED SUBMITTAL(S)/GRANT(S) | |
| TEST METHODOLOGY | |
| TEST FACILITY | |
| SYSTEM TEST CONFIGURATION | |
| DESCRIPTION OF TEST CONFIGURATION | |
| EUT EXERCISE SOFTWARE | |
| EQUIPMENT MODIFICATIONS | |
| EXTERNAL CABLE | |
| BLOCK DIAGRAM OF TEST SETUP | |
| SUMMARY OF TEST RESULTS | |
| | |
| FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE | 9 |
| APPLICABLE STANDARD | 9 |
| TEST RESULT | 9 |
| FCC §15.203 - ANTENNA REQUIREMENT | 10 |
| APPLICABLE STANDARD | 10 |
| ANTENNA CONNECTOR CONSTRUCTION | 10 |
| FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS | 11 |
| APPLICABLE STANDARD | |
| MEASUREMENT UNCERTAINTY | |
| EUT Setup | |
| EMI Test Receiver Setup | |
| TEST PROCEDURE | 12 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | |
| TEST RESULTS SUMMARY | |
| TEST DATA | |
| FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS | 16 |
| APPLICABLE STANDARD | |
| MEASUREMENT UNCERTAINTY | |
| EUT SETUP | |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP | 17 |
| TEST PROCEDURE | |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | |
| TEST EQUIPMENT LIST AND DETAILS | |
| TEST DATA | |
| | |
| FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH | |
| APPLICABLE STANDARD | |
| TEST PROCEDURE | 27 27 |

| TEST DATA | 27 |
|---|----|
| FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER | 34 |
| APPLICABLE STANDARD | 34 |
| Test Procedure | |
| TEST EQUIPMENT LIST AND DETAILS. | 34 |
| Test Data | |
| FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE | 45 |
| APPLICABLE STANDARD | 45 |
| TEST PROCEDURE | 45 |
| TEST EQUIPMENT LIST AND DETAILS. | |
| TEST DATA | 45 |
| FCC §15.247(e) - POWER SPECTRAL DENSITY | 49 |
| APPLICABLE STANDARD | 49 |
| TEST PROCEDURE | 49 |
| TEST EQUIPMENT LIST AND DETAILS. | |
| TEST DATA | 40 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Galaxy Microsystems Ltd.*'s product, model number: *Galapad7(G2) (FCC ID: Y3GGALAPAD7G2)* (the "EUT") in this report was a *Galapad 7*, which was measured approximately: 19.5 cm (L) x 12.5 cm (W) x 1.0 cm (H), rated input voltage: DC 3.8 V from lithium battery or DC 5V from adapter.

Report No.: R2DG130508007-00A

Adapter information: GALAPAD Model: LFS0502000D-A8S

Input: AC 100-240V, 50/60Hz, 500mA max

Output: DC 5V, 2.0A

* All measurement and test data in this report was gathered from production sample serial number: 130508007 (Assigned by BACL.Dongguan). The EUT was received on 2013-05-09.

Objective

This report is prepared on behalf of *Galaxy Microsystems Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: *Y3GGALAPAD7G2*. FCC Part 15C DSS submissions with FCC ID: *Y3GGALAPAD7G2* for Bluetooth.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 55

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No.: R2DG130508007-00A

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at http://ts.nist.gov/standards/scopes/5 000690.htm

FCC Part 15.247 Page 5 of 55

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4G band, 11 channels are provided to testing:

Report No.: R2DG130508007-00A

| Channel Frequency (MHz) | | Channel | Frequency (MHz) |
|-------------------------|------|---------|--------------------|
| 1 | 2412 | 7 | 2442 |
| 2 | 2417 | 8 | 2447 |
| 3 | 2422 | 9 | 2452 |
| 4 | 2427 | 10 | 2457 |
| 5 | 2432 | 11 | 2462 |
| 6 | 2437 | / | / |

For 802.11b, 802.11g, and 802.11n20 modes were tested with Channel 1, 6 and 11.


The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all date rates bandwidths, and modulations.

EUT Exercise Software

The software "adb.exe" was used, which was provided by the manufacturer.

Equipment Modifications

1. As shown on below, paste the copper on the position of the point 1, 2, 3, 4, 5.



FCC Part 15.247 Page 6 of 55

2. Add an cord on the USB cable.

Support Equipment List and Details


| Manufacturer Description | | Model | Serial Number | |
|--------------------------|--|--------|--------------------------|--|
| DELL Monitor | | U3011t | CN-OPH5NY-74445-16T-290L | |
| Kinston Micro SD Card | | 4G | N/A | |

Report No.: R2DG130508007-00A

External Cable

| Cable Description | Length (m) | From Port | То |
|--------------------------------|------------|-------------|-----|
| Shielded Detachable HDMI Cable | 1.5 | LCD Monitor | EUT |
| Shielded Detachable USB Cable | 1.0 | Adapter | EUT |

Block Diagram of Test Setup



FCC Part 15.247 Page 7 of 55

SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|-------------------------------------|--|------------|
| FCC §15.247 (i) & §1.1310 & §2.1093 | RF Exposure | Compliance |
| §15.203 | Antenna Requirement | Compliance |
| §15.207 (a) | AC Line Conducted Emissions | Compliance |
| §15.247(d) | Spurious Emissions at Antenna Port | Compliance |
| \$15.205, \$15.209, \$15.247(d) | Spurious Emissions | Compliance |
| §15.247 (a)(2) | 6 dB Emission Bandwidth | Compliance |
| §15.247(b)(3) | Maximum Peak Output Power | Compliance |
| §15.247(d) | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e) | Power Spectral Density | Compliance |

Report No.: R2DG130508007-00A

FCC Part 15.247 Page 8 of 55

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Report No.: R2DG130508007-00A

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: R1DG130508007-20

FCC Part 15.247 Page 9 of 55

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: R2DG130508007-00A

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has an internal PIFA antenna, which was permanently attached to the EUT, and the maximum gain is 1.6dBi, please refer to the internal photos.

Result: Compliance.

FCC Part 15.247 Page 10 of 55

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG130508007-00A

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of
$$U_{\text{cispr}}$$

| Measurement | $U_{ m cispr}$ |
|---|----------------|
| Conducted disturbance at mains port using AMN (150 kHz to 30 MHz) | 3.4 dB |

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 11 of 55

Report No.: R2DG130508007-00A

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W | |
|------------------|--------|--|
| 150 kHz – 30 MHz | 9 kHz | |

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$
$$C_f = A_C + VDF$$

Herein.

V_C(cord. Reading): corrected voltage amplitude

V_R: reading voltage amplitude A_c: attenuation caused by cable loss VDF: voltage division factor of AMN

C_f: Correction Factor

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 12 of 55

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|----------------------|----------|------------------|---------------------|-------------------------|
| R&S | EMI TEST RECIEVER | ESCS 30 | 830245/006 | 2013-1-10 | 2014-1-9 |
| R&S | L.I.S.N | ESH3-Z5 | 843331/015 | 2012-9-17 | 2013-9-16 |
| R&S | L.I.S.N | ESH3-Z5 | 100113 | 2012-11-29 | 2013-11-28 |
| BACL | Test Software | BACL-EMC | V1.0-2010 | N/A | N/A |

Report No.: R2DG130508007-00A

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

7.58dB at 0.560 MHz in the Line conducted mode

Test Data

Environmental Conditions

| Temperature: | 28.3 °C |
|--------------------|-----------|
| Relative Humidity: | 61 % |
| ATM Pressure: | 100.2 kPa |


The testing was performed by Leon Chen on 2013-07-15.

FCC Part 15.247 Page 13 of 55

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting


120 V, 60 Hz, Line:



| Frequency (MHz) | Cord. Reading (dBµV) | Correction Factor (dB) | Limit (dBµV) | Margin (dB) | Detector (PK/AV/QP) |
|--------------------|----------------------------|------------------------------|-----------------|----------------|------------------------|
| 0.170 | 44.27 | 0.45 | 64.96 | 20.69 | QP |
| 0.170 | 30.84 | 0.45 | 54.96 | 24.12 | AV |
| 0.240 | 42.03 | 0.39 | 62.10 | 20.07 | QP |
| 0.240 | 33.59 | 0.39 | 52.10 | 18.51 | AV |
| 0.430 | 41.21 | 0.32 | 57.25 | 16.04 | QP |
| 0.430 | 34.70 | 0.32 | 47.25 | 12.55 | AV |
| 0.560 | 44.94 | 0.31 | 56.00 | 11.06 | QP |
| 0.560 | 38.42 | 0.31 | 46.00 | 7.58 | AV |
| 0.650 | 40.76 | 0.31 | 56.00 | 15.24 | QP |
| 0.650 | 32.94 | 0.31 | 46.00 | 13.06 | AV |
| 4.020 | 45.75 | 0.43 | 56.00 | 10.25 | QP |
| 4.020 | 34.73 | 0.43 | 46.00 | 11.27 | AV |

FCC Part 15.247 Page 14 of 55

120 V, 60 Hz, Neutral:



Report No.: R2DG130508007-00A

| Frequency (MHz) | Cord. Reading (dBµV) | Correction Factor (dB) | Limit (dBµV) | Margin (dB) | Detector (PK/AV/QP) |
|--------------------|----------------------------|------------------------------|-----------------|----------------|------------------------|
| 0.170 | 45.05 | 0.26 | 64.96 | 19.91 | QP |
| 0.170 | 30.15 | 0.26 | 54.96 | 24.81 | AV |
| 0.360 | 40.66 | 0.22 | 58.73 | 18.07 | QP |
| 0.360 | 27.71 | 0.22 | 48.73 | 21.02 | AV |
| 0.560 | 48.38 | 0.21 | 56.00 | 7.62 | QP |
| 0.560 | 35.77 | 0.21 | 46.00 | 10.23 | AV |
| 1.170 | 37.97 | 0.24 | 56.00 | 18.03 | QP |
| 1.170 | 27.78 | 0.24 | 46.00 | 18.22 | AV |
| 1.550 | 40.27 | 0.25 | 56.00 | 15.73 | QP |
| 1.550 | 28.58 | 0.25 | 46.00 | 17.42 | AV |
| 4.000 | 44.33 | 0.35 | 56.00 | 11.67 | QP |
| 3.980 | 35.51 | 0.35 | 46.00 | 10.49 | AV |

FCC Part 15.247 Page 15 of 55

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG130508007-00A

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 2, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 2 – Values of U_{cispr}

| Measurement | | | | | |
|--|--------|--|--|--|--|
| Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz) | 6.3 dB | | | | |
| Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz) | 5.2 dB | | | | |
| Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz) | 5.5 dB | | | | |


EUT Setup

Below 1GHz:



FCC Part 15.247 Page 16 of 55

Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|------------------|---------|-----------|--------|----------|
| 30MHz – 1000 MHz | 120 kHz | 300 kHz | 120kHz | QP |
| Above 1 CHz | 1MHz | 3 MHz | / | PK |
| Above 1 GHz | 1MHz | 10 Hz | / | Ave. |

Test Procedure

For the radiated emissions test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 17 of 55

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: R2DG130508007-00A

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-------------------|----------------------|------------|------------------|---------------------|-------------------------|
| R&S | EMI TEST RECEIVER | ESCI | 100224 | 2013-5-6 | 2014-5-5 |
| Sunol Sciences | Antenna | ЈВ3 | A060611-1 | 2012-9-6 | 2015-9-5 |
| HP | HP AMPLIFIER | 8447E | 2434A02181 | N/A | N/A |
| R&S | Spectrum analyzer | FSEM 30 | 849016/001 | 2012-9-4 | 2013-9-3 |
| ETS LINDGREN | horn antenna | 3115 | 000 527 35 | 2012-9-6 | 2015-9-5 |
| Mini-Circuit | Amplifier | ZVA-213-S+ | 54201245 | N/A | N/A |
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2012-9-16 | 2013-9-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

8.92 dB at **2483.5 MHz** in the **Horizontal** polarization for 802.11g Mode

Test Data

Environmental Conditions

| Temperature: | 22.6~22.8° C |
|--------------------|--------------|
| Relative Humidity: | 67~68 % |
| ATM Pressure: | 99.8~99.9kPa |

The testing was performed by Leon Chen from 2013-05-10 to 2013-07-01.

FCC Part 15.247 Page 18 of 55

Mode: Transmitting 802.11b Mode

| 002.1 | lb Mode | eceiver | Dv A | ntenna | Cala | A1°C* | C | FCC 1: | 5 247 | |
|--------------|-----------------------|------------------------|----------------|----------------|--------------|-------------------|---------------------|----------------|----------------|--|
| Frequency | | | | | Cable loss | Amplifier Gain | Corrected Amplitude | | l | |
| (MHz) | Reading (dBµV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB) | (dB) | (dB) | (dBµV/m) | Limit (dBµV/m) | Margin (dB) | |
| | Low Channel: 2412 MHz | | | | | | | | | |
| 2412 | 76.08 | PK | Н | 25.67 | 3.93 | 0.00 | 105.68 | N/A | N/A | |
| 2412 | 71.4 | AV | Н | 25.67 | 3.93 | 0.00 | 101.00 | N/A | N/A | |
| 2412 | 70.25 | PK | V | 25.67 | 3.93 | 0.00 | 99.85 | N/A | N/A | |
| 2412 | 65.43 | AV | V | 25.67 | 3.93 | 0.00 | 95.03 | N/A | N/A | |
| 2390 | 25.63 | PK | Н | 25.61 | 3.84 | 0.00 | 55.08 | 74.00 | 18.92 | |
| 2390 | 13.61 | AV | Н | 25.61 | 3.84 | 0.00 | 43.06 | 54.00 | 10.94 | |
| 4824 | 41.57 | PK | Н | 30.64 | 4.73 | 27.26 | 49.68 | 74.00 | 24.32 | |
| 4824 | 36.23 | AV | Н | 30.64 | 4.73 | 27.26 | 44.34 | 54.00 | 9.66 | |
| 7236 | 33.14 | PK | Н | 34.17 | 6.56 | 26.36 | 47.51 | 74.00 | 26.49 | |
| 7236 | 20.57 | AV | Н | 34.17 | 6.56 | 26.36 | 34.94 | 54.00 | 19.06 | |
| 9648 | 33.28 | PK | Н | 36.06 | 8.70 | 26.06 | 51.98 | 74.00 | 22.02 | |
| 9648 | 19.81 | AV | Н | 36.06 | 8.70 | 26.06 | 38.51 | 54.00 | 15.49 | |
| 3298 | 34.45 | PK | Н | 28.15 | 4.60 | 27.40 | 39.80 | 74.00 | 34.20 | |
| 3298 | 20.98 | AV | H | 28.15 | 4.60 | 27.40 | 26.33 | 54.00 | 27.67 | |
| 219.35 | 32.84 | QP | Н | 11.55 | 1.79 | 21.47 | 24.71 | 46.00 | 21.29 | |
| 2.127 | 76.01 | DIZ | | dle Chann | | | 106.53 | 37/4 | 37/4 | |
| 2437 | 76.81 | PK | H | 25.74 | 3.98 | 0.00 | 106.53 | N/A | N/A | |
| 2437 | 72.45 | AV | H | 25.74 | 3.98 | 0.00 | 102.17 | N/A | N/A | |
| 2437 | 70.85 | PK | V | 25.74 | 3.98 | 0.00 | 100.57 | N/A | N/A | |
| 2437 | 66.46 | AV | | 25.74 | 3.98 | 0.00 | 96.18 | N/A | N/A | |
| 4874 4874 | 41.56 36.47 | PK AV | H H | 30.77 | 4.76 | 27.26 27.26 | 49.83 44.74 | 74.00 54.00 | 24.17 9.26 | |
| 7311 | 33.4 | PK | Н | 30.77 34.35 | 4.76 6.70 | 26.51 | | 74.00 | 26.06 | |
| 7311 | 20.68 | AV | Н | 34.35 | 6.70 | 26.51 | 47.94 35.22 | 54.00 | 18.78 | |
| 9748 | 33.26 | PK | H | 36.30 | 8.60 | 25.68 | 52.48 | 74.00 | 21.52 | |
| 9748 | 19.78 | AV | H | 36.30 | 8.60 | 25.68 | 39.00 | 54.00 | 15.00 | |
| 1927 | 34.4 | PK | H | 24.45 | 3.45 | 27.09 | 35.21 | 74.00 | 38.79 | |
| 1927 | 20.9 | AV | Н | 24.45 | 3.45 | 27.09 | 21.71 | 54.00 | 32.29 | |
| 3298 | 34.46 | PK | Н | 28.15 | 4.60 | 27.40 | 39.81 | 74.00 | 34.19 | |
| 3298 | 21.03 | AV | Н | 28.15 | 4.60 | 27.40 | 26.38 | 54.00 | 27.62 | |
| 218.75 | 31.65 | OP | Н | 11.52 | 1.79 | 21.47 | 23.49 | 46.00 | 22.51 | |
| 37,2 | | | | gh Channe | | | | | | |
| 2462 | 77.27 | PK | Н | 25.80 | 3.93 | 0.00 | 107.00 | N/A | N/A | |
| 2462 | 72.67 | AV | Н | 25.80 | 3.93 | 0.00 | 102.40 | N/A | N/A | |
| 2462 | 71.23 | PK | V | 25.80 | 3.93 | 0.00 | 100.96 | N/A | N/A | |
| 2462 | 66.82 | AV | V | 25.80 | 3.93 | 0.00 | 96.55 | N/A | N/A | |
| 2483.5 | 27.57 | PK | Н | 25.86 | 3.80 | 0.00 | 57.23 | 74.00 | 16.77 | |
| 2483.5 | 15.19 | AV | Н | 25.86 | 3.80 | 0.00 | 44.85 | 54.00 | 9.15 | |
| 4924 | 41.77 | PK | Н | 30.90 | 4.70 | 27.27 | 50.10 | 74.00 | 23.90 | |
| 4924 | 36.54 | AV | H | 30.90 | 4.70 | 27.27 | 44.87 | 54.00 | 9.13 | |
| 7386 | 33.43 | PK | H | 34.53 | 6.84 | 26.66 | 48.14 | 74.00 | 25.86 | |
| 7386 | 20.69 | AV | H | 34.53 | 6.84 | 26.66 | 35.40 | 54.00 | 18.60 | |
| 9848 | 33.55 | PK | Н | 36.54 | 8.49 | 25.49 | 53.09 | 74.00 | 20.91 | |
| 9848 | 19.97 | AV | Н | 36.54 | 8.49 | 25.49 | 39.51 | 54.00 | 14.49 | |
| 3298 | 34.62 | PK | Н | 28.15 | 4.60 | 27.40 | 39.97 | 74.00 | 34.03 | |
| 3298 | 21.13 | AV | Н | 28.15 | 4.60 | 27.40 | 26.48 | 54.00 | 27.52 | |
| 220.42 | 31.86 | QP | Н | 11.59 | 1.80 | 21.47 | 23.78 | 46.00 | 22.22 | |

FCC Part 15.247 Page 19 of 55

802 11g Mode

| 802.11g M | | eceiver | Ry A | ntenna | Cable | Amplifian | Connected | FCC 1 | 5.247 |
|-----------------------|----------------|------------|--------|----------------|--------------|-------------------|---------------------|----------------|----------------|
| Frequency (MHz) | Reading | Detector | Polar | Factor | loss | Amplifier Gain | Corrected Amplitude | Limit | Margin |
| | (dBµV) | (PK/QP/AV) | (H/V) | (dB) | (dB) | (dB) | (dBµV/m) | (dBµV/m) | (dB) |
| Low Channel: 2412 MHz | | | | | | | | | |
| 2412 | 75.53 | PK | Н | 25.67 | 3.93 | 0.00 | 105.13 | N/A | N/A |
| 2412 | 64.15 | AV | Н | 25.67 | 3.93 | 0.00 | 93.75 | N/A | N/A |
| 2412 | 69.83 | PK | V | 25.67 | 3.93 | 0.00 | 99.43 | N/A | N/A |
| 2412 | 58.45 | AV | V | 25.67 | 3.93 | 0.00 | 88.05 | N/A | N/A |
| 2390 | 28.53 | PK | Н | 25.61 | 3.84 | 0.00 | 57.98 | 74.00 | 16.02 |
| 2390 | 14.44 | AV | Н | 25.61 | 3.84 | 0.00 | 43.89 | 54.00 | 10.11 |
| 4824 | 40.12 | PK | Н | 30.64 | 4.73 | 27.26 | 48.23 | 74.00 | 25.77 |
| 4824 | 24.21 | AV | Н | 30.64 | 4.73 | 27.26 | 32.32 | 54.00 | 21.68 |
| 7236 | 33.02 | PK | Н | 34.17 | 6.56 | 26.36 | 47.39 | 74.00 | 26.61 |
| 7236 | 20.23 | AV | Н | 34.17 | 6.56 | 26.36 | 34.60 | 54.00 | 19.40 |
| 9648 | 32.87 | PK | Н | 36.06 | 8.70 | 26.06 | 51.57 | 74.00 | 22.43 |
| 9648 | 19.78 | AV | Н | 36.06 | 8.70 | 26.06 | 38.48 | 54.00 | 15.52 |
| 3298 | 34.05 | PK | Н | 28.15 | 4.60 | 27.40 | 39.40 | 74.00 | 34.60 |
| 3298 | 20.39 | AV | Н | 28.15 | 4.60 | 27.40 | 25.74 | 54.00 | 28.26 |
| 219.35 | 32.35 | QP | Н | 11.55 | 1.79 | 21.47 | 24.22 | 46.00 | 21.78 |
| 2427 | 76.44 | DIZ | | dle Channe | | | 106.16 | NT/A | NT/A |
| 2437 2437 | 76.44 64.72 | PK AV | H H | 25.74 25.74 | 3.98 | 0.00 | 106.16 94.44 | N/A N/A | N/A N/A |
| 2437 | 70.32 | PK | V | 25.74 | 3.98 3.98 | 0.00 | 100.04 | N/A N/A | N/A N/A |
| 2437 | 58.78 | AV | V | 25.74 | 3.98 | 0.00 | 88.50 | N/A N/A | N/A |
| 4874 | 40.29 | PK | H | 30.77 | 4.76 | 27.26 | 48.56 | 74.00 | 25.44 |
| 4874 | 24.31 | AV | Н | 30.77 | 4.76 | 27.26 | 32.58 | 54.00 | 21.42 |
| 7311 | 32.95 | PK | Н | 34.35 | 6.70 | 26.51 | 47.49 | 74.00 | 26.51 |
| 7311 | 20.24 | AV | Н | 34.35 | 6.70 | 26.51 | 34.78 | 54.00 | 19.22 |
| 9748 | 32.72 | PK | Н | 36.30 | 8.60 | 25.68 | 51.94 | 74.00 | 22.06 |
| 9748 | 19.78 | AV | Н | 36.30 | 8.60 | 25.68 | 39.00 | 54.00 | 15.00 |
| 1927 | 34.02 | PK | Н | 24.45 | 3.45 | 27.09 | 34.83 | 74.00 | 39.17 |
| 1927 | 20.45 | AV | Н | 24.45 | 3.45 | 27.09 | 21.26 | 54.00 | 32.74 |
| 3298 | 33.16 | PK | Н | 28.15 | 4.60 | 27.40 | 38.51 | 74.00 | 35.49 |
| 3298 | 20.34 | AV | Н | 28.15 | 4.60 | 27.40 | 25.69 | 54.00 | 28.31 |
| 218.75 | 31.76 | QP | Н | 11.52 | 1.79 | 21.47 | 23.60 | 46.00 | 22.4 |
| | _ | T | | gh Channel: | | | | T | T |
| 2462 | 76.72 | PK | Н | 25.80 | 3.93 | 0.00 | 106.45 | N/A | N/A |
| 2462 | 64.93 | AV | Н | 25.80 | 3.93 | 0.00 | 94.66 | N/A | N/A |
| 2462 | 70.63 | PK | V | 25.80 | 3.93 | 0.00 | 100.36 | N/A | N/A |
| 2462 | 58.97 | AV | V | 25.80 | 3.93 | 0.00 | 88.70 | N/A | N/A |
| 2483.5 | 29.31 | PK | Н | 25.86 | 3.80 | 0.00 | 58.97 | 74.00 | 15.03 |
| 2483.5 4924 | 15.42 | AV PK | H H | 25.86 | 3.80 4.70 | 0.00 27.27 | 45.08 48.66 | 54.00 74.00 | 8.92 |
| 4924 | 40.33 | AV | Н | 30.90 30.90 | 4.70 | 27.27 | 32.74 | 54.00 | 25.34 21.26 |
| 7386 | 33.23 | PK | Н | 34.53 | 6.84 | 26.66 | 47.94 | 74.00 | 26.06 |
| 7386 | 20.52 | AV | Н | 34.53 | 6.84 | 26.66 | 35.23 | 54.00 | 18.77 |
| 9848 | 32.97 | PK | Н | 36.54 | 8.49 | 25.49 | 52.51 | 74.00 | 21.49 |
| 9848 | 19.89 | AV | Н | 36.54 | 8.49 | 25.49 | 39.43 | 54.00 | 14.57 |
| 3298 | 34.13 | PK | Н | 28.15 | 4.60 | 27.40 | 39.48 | 74.00 | 34.52 |
| 3298 | 20.62 | AV | Н | 28.15 | 4.60 | 27.40 | 25.97 | 54.00 | 28.03 |
| 220.42 | 31.24 | OP | Н | 11.59 | 1.80 | 21.47 | 23.16 | 46.00 | 22.84 |

Report No.: R2DG130508007-00A

FCC Part 15.247 Page 20 of 55

802.11 n20 Mode

| T | Re | eceiver | Rx A | ntenna | Cable | Amplifier | Corrected | FCC 1: | 5.247 | |
|--------------------|-----------------------|------------------------|----------------|--------------------|-------------------|--------------|--------------------|-------------------|-------------|--|
| Frequency (MHz) | Reading (dBµV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB) | loss (dB) | Gain (dB) | Amplitude (dBμV/m) | Limit (dBµV/m) | Margin (dB) | |
| | Low Channel: 2412 MHz | | | | | | | | | |
| 2412 | 76.92 | PK | Н | 25.67 | 3.93 | 0.00 | 106.52 | N/A | N/A | |
| 2412 | 65.91 | AV | Н | 25.67 | 3.93 | 0.00 | 95.51 | N/A | N/A | |
| 2412 | 69.89 | PK | V | 25.67 | 3.93 | 0.00 | 99.49 | N/A | N/A | |
| 2412 | 58.47 | AV | V | 25.67 | 3.93 | 0.00 | 88.07 | N/A | N/A | |
| 2390 | 30.95 | PK | Н | 25.61 | 3.84 | 0.00 | 60.4 | 74.00 | 13.6 | |
| 2390 | 14.03 | AV | Н | 25.61 | 3.84 | 0.00 | 43.48 | 54.00 | 10.52 | |
| 4824 | 40.26 | PK | Н | 30.64 | 4.73 | 27.26 | 48.37 | 74.00 | 25.63 | |
| 4824 | 26.02 | AV | Н | 30.64 | 4.73 | 27.26 | 34.13 | 54.00 | 19.87 | |
| 7236 | 34.69 | PK | Н | 34.17 | 6.56 | 26.36 | 49.06 | 74.00 | 24.94 | |
| 7236 | 21.26 | AV | Н | 34.17 | 6.56 | 26.36 | 35.63 | 54.00 | 18.37 | |
| 9648 | 31.25 | PK | Н | 36.06 | 8.7 | 26.06 | 49.95 | 74.00 | 24.05 | |
| 9648 | 20.17 | AV | Н | 36.06 | 8.7 | 26.06 | 38.87 | 54.00 | 15.13 | |
| 3298 | 34.12 | PK | Н | 28.15 | 4.6 | 27.4 | 39.47 | 74.00 | 34.53 | |
| 3298 | 19.64 | AV | Н | 28.15 | 4.6 | 27.4 | 24.99 | 54.00 | 29.01 | |
| 219.35 | 32.01 | QP | Н | 11.55 | 1.79 | 21.47 | 23.88 | 46.00 | 22.12 | |
| | | | | dle Chann | | | T | T | 1 | |
| 2437 | 75.24 | PK | Н | 25.74 | 3.98 | 0.00 | 104.96 | N/A | N/A | |
| 2437 | 64.06 | AV | Н | 25.74 | 3.98 | 0.00 | 93.78 | N/A | N/A | |
| 2437 | 68.24 | PK | V | 25.74 | 3.98 | 0.00 | 97.96 | N/A | N/A | |
| 2437 | 54.93 | AV | V | 25.74 | 3.98 | 0.00 | 84.65 | N/A | N/A | |
| 4874 | 41.06 | PK | Н | 30.77 | 4.76 | 27.26 | 49.33 | 74.00 | 24.5 | |
| 4874 | 23.58 | AV | Н | 30.77 | 4.76 | 27.26 | 31.85 | 54.00 | 21.58 | |
| 7311 | 33.26 | PK | H | 34.35 | 6.7 | 26.51 | 47.8 | 74.00 | 26.44 | |
| 7311 | 21.05 | AV | Н | 34.35 | 6.7 | 26.51 | 35.59 | 54.00 | 19.13 | |
| 9748 | 33.09 | PK | H | 36.3 | 8.6 | 25.68 | 52.31 | 74.00 | 22.19 | |
| 9748 | 20.17 | AV | H | 36.3 | 8.6 | 25.68 | 39.39 | 54.00 | 15.4 | |
| 1927 | 33.26 | PK | Н | 24.45 | 3.45 | 27.09 | 34.07 | 74.00 | 39.38 | |
| 1927 | 21.54 | AV | H | 24.45 | 3.45 | 27.09 | 22.35 | 54.00 | 32.81 | |
| 3298 | 32.15 | PK | Н | 28.15 | 4.6 | 27.4 | 37.5 | 74.00 | 34.98 | |
| 3298 | 19.29 | AV OP | H H | 28.15 | 4.6 | 27.4 | 24.64 | 54.00 | 28.23 | |
| 218.75 | 29.47 | QP | | 11.52 gh Channe | 1.79 1: 2462 N | 21.47 | 21.31 | 46.00 | 20.72 | |
| 2462 | 76.23 | PK | H | 25.8 | 3.93 | 0.00 | 105.96 | N/A | N/A | |
| 2462 | 66.84 | AV | H | 25.8 | 3.93 | 0.00 | 96.57 | N/A | N/A | |
| 2462 | 70.16 | PK | V | 25.8 | 3.93 | 0.00 | 99.89 | N/A | N/A | |
| 2462 | 61.03 | AV | V | 25.8 | 3.93 | 0.00 | 90.76 | N/A | N/A | |
| 2483.5 | 31.25 | PK | Н | 25.86 | 3.8 | 0.00 | 60.91 | 74.00 | 12.09 | |
| 2483.5 | 16.66 | AV | Н | 25.86 | 3.8 | 0.00 | 46.32 | 54.00 | 9.98 | |
| 4924 | 40.95 | PK | Н | 30.9 | 4.7 | 27.27 | 49.28 | 74.00 | 24.31 | |
| 4924 | 25.16 | AV | Н | 30.9 | 4.7 | 27.27 | 33.49 | 54.00 | 21.36 | |
| 7386 | 34.02 | PK | Н | 34.53 | 6.84 | 26.66 | 48.73 | 74.00 | 26.2 | |
| 7386 | 20.95 | AV | Н | 34.53 | 6.84 | 26.66 | 35.66 | 54.00 | 18.95 | |
| 9848 | 31.58 | PK | Н | 36.54 | 8.49 | 25.49 | 51.12 | 74.00 | 21.69 | |
| 9848 | 20.06 | AV | Н | 36.54 | 8.49 | 25.49 | 39.6 | 54.00 | 14.84 | |
| 3298 | 33.25 | PK | Н | 28.15 | 4.6 | 27.4 | 38.6 | 74.00 | 34.7 | |
| 3298 | 21.06 | AV | Н | 28.15 | 4.6 | 27.4 | 26.41 | 54.00 | 28.05 | |
| 220.42 | 31.02 | QP | Н | 11.59 | 1.8 | 21.47 | 22.94 | 46.00 | 19.72 | |


^{*}Within measurement uncertainty!

FCC Part 15.247 Page 21 of 55


Conducted Spurious Emissions at Antenna Port

Report No.: R2DG130508007-00A

802.11b Low Channel




802.11b Middle Channel



FCC Part 15.247 Page 22 of 55


802.11b High Channel

Report No.: R2DG130508007-00A



Date: 01.JUL.2013 14:09:04


802.11g Low Channel




FCC Part 15.247 Page 23 of 55

802.11g Middle Channel

Report No.: R2DG130508007-00A




802.11g High Channel




FCC Part 15.247 Page 24 of 55

802.11n20 Low Channel

Report No.: R2DG130508007-00A




802.11n20 Middle Channel



FCC Part 15.247 Page 25 of 55

802.11n20 High Channel

Report No.: R2DG130508007-00A



FCC Part 15.247 Page 26 of 55

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: R2DG130508007-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|---------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2012-9-16 | 2013-9-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 24.3~29.7° C |
|--------------------|---------------|
| Relative Humidity: | 56~70 % |
| ATM Pressure: | 99.5~100.5kPa |

The testing was performed by Leon Chen from 2013-05-10 to 2013-08-02.

Test Result: Pass.

Please refer to the following tables and plots.


FCC Part 15.247 Page 27 of 55

| Channel | Frequency | 6 dB Bandwidth | Limit |
|---------|-----------|----------------|-------|
| Channel | (MHz) | (MHz) | (kHz) |
| | 8 | 02.11b mode | |
| Low | 2412 | 8.63 | >500 |
| Middle | 2437 | 9.59 | >500 |
| High | 2462 | 9.63 | >500 |
| | 8 | 02.11g mode | |
| Low | 2412 | 15.46 | >500 |
| Middle | 2437 | 15.06 | >500 |
| High | 2462 | 15.10 | >500 |
| | 80: | 2.11n20 mode | |
| Low | 2412 | 2412 16.56 >50 | |
| Middle | 2437 | 16.40 | >500 |
| High | 2462 | 16.72 | >500 |

FCC Part 15.247 Page 28 of 55


Report No.: R2DG130508007-00A

802.11b Low Channel



Date: 10.MAY.2013 16:17:57

802.11b Middle Channel




Date: 10.MAY.2013 17:05:36

FCC Part 15.247 Page 29 of 55


Report No.: R2DG130508007-00A

802.11b High Channel



Date: 10.MAY.2013 17:09:26

802.11g Low Channel




Date: 10.MAY.2013 17:34:54

FCC Part 15.247 Page 30 of 55


802.11g Middle Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:42:16

802.11g High Channel




Date: 10.MAY.2013 17:44:57

FCC Part 15.247 Page 31 of 55


802.11n20 Low Channel

Report No.: R2DG130508007-00A



Date: 2.AUG.2013 14:55:30


802.11n20 Middle Channel



Date: 2.AUG.2013 14:54:27

FCC Part 15.247 Page 32 of 55

Report No.: R2DG130508007-00A



Date: 2.AUG.2013 14:56:34

FCC Part 15.247 Page 33 of 55

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: R2DG130508007-00A

Test Procedure

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
- 3. Add a correction factor to the display.



- 4. According to KDB 558074 D01 DTS Meas Guidance v02, Section 8.2.1 Option 1:
 - 4.1 Set the analyzer span to a minimum of 1.5 times the EBW.
 - 4.2 Set the RBW = 1 MHz.
 - 4.3 Set the VBW = 3 MHz.
 - 4.4 Ensure that the number of measurement points in the sweep $\geq 2 \text{ x span/RBW}$
 - 4.5 Sweep time = auto couple.
 - 4.6 Detector = power averaging (RMS) or sample detector when RMS not available.
 - 4.7 Employ trace averaging in power averaging (RMS) mode over a minimum of 100 traces.
 - 4.8 Use the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges.

Note: EBW means 26dB bandwidth.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2012-9-16 | 2013-9-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 34 of 55

. Test Data

Environmental Conditions

| Temperature: | 24.3~29.7°C | |
|--------------------|---------------|--|
| Relative Humidity: | 62~70 % | |
| ATM Pressure: | 99.5~100.5kPa | |

The testing was performed by Leon Chen from 2013-05-10 to 2013-07-15.

Test Mode: Transmitting

| Channel | Frequency | Conducted Output Power | Limit | Result | |
|----------------|-----------|---------------------------|-------|--------|--|
| | (MHz) | (dBm) | (dBm) | | |
| 802.11b mode | | | | | |
| Low | 2412 | 14.86 | 30 | PASS | |
| Middle | 2437 | 14.84 | 30 | PASS | |
| High | 2462 | 14.98 | 30 | PASS | |
| 802.11g mode | | | | | |
| Low | 2412 | 14.56 | 30 | PASS | |
| Middle | 2437 | 14.69 | 30 | PASS | |
| High | 2462 | 14.54 | 30 | PASS | |
| 802.11n20 mode | | | | | |
| Low | 2412 | 14.27 | 30 | PASS | |
| Middle | 2437 | 14.14 | 30 | PASS | |
| High | 2462 | 14.45 | 30 | PASS | |


Report No.: R2DG130508007-00A

Please refer to the following plots

FCC Part 15.247 Page 35 of 55


802.11b 26dB, Low Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 16:18:10

802.11b RF Output Power, Low Channel




Date: 15.JUL.2013 14:18:01

FCC Part 15.247 Page 36 of 55


802.11b 26dB, Middle Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:05:51

802.11b RF Output Power, Middle Channel




Date: 15.JUL.2013 14:16:33

FCC Part 15.247 Page 37 of 55


802.11b 26dB, High Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:09:40

802.11b RF Output Power, High Channel




Date: 15.JUL.2013 14:17:20

FCC Part 15.247 Page 38 of 55


802.11g 26dB, Low Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:35:08

802.11g RF Output Power, Low Channel




Date: 10.MAY.2013 17:35:25

FCC Part 15.247 Page 39 of 55


802.11g 26dB, Middle Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:42:29

802.11g RF Output Power, Middle Channel




Date: 10.MAY.2013 17:42:46

FCC Part 15.247 Page 40 of 55


802.11g RF 26dB, High Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:45:11

802.11g RF Output Power, High Channel




Date: 10.MAY.2013 17:45:28

FCC Part 15.247 Page 41 of 55


802.11n20 26dB, Low Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:48:13

802.11n20 RF Output Power, Low Channel




Date: 10.MAY.2013 17:48:30

FCC Part 15.247 Page 42 of 55


802.11n20 26dB, Middle Channel

Report No.: R2DG130508007-00A



Date: 12.MAY.2013 16:18:51

802.11n20 RF Output Power, Middle Channel




Date: 12.MAY.2013 16:19:08

FCC Part 15.247 Page 43 of 55


802.11n20 26dB, High Channel

Report No.: R2DG130508007-00A



Date: 12.MAY.2013 16:21:34

802.11n20 RF Output Power, High Channel



Date: 12.MAY.2013 16:21:50

FCC Part 15.247 Page 44 of 55

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: R2DG130508007-00A

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2012-9-16 | 2013-9-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 24.3~29.7°C |
|--------------------|---------------|
| Relative Humidity: | 56~70 % |
| ATM Pressure: | 99.5~100.5kPa |

The testing was performed by Leon Chen from 2013-05-10 to 2013-08-02.


Test Result: Compliance

Please refer to following table and plots.

FCC Part 15.247 Page 45 of 55


802.11b: Band Edge, Left Side

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 16:18:56

802.11b: Band Edge, Right Side




Date: 10.MAY.2013 17:10:26

FCC Part 15.247 Page 46 of 55


802.11g: Band Edge, Left Side

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:35:55

802.11g: Band Edge, Right Side




Date: 10.MAY.2013 17:45:58

FCC Part 15.247 Page 47 of 55


802.11n20 Band Edge, Left Side

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:49:00

802.11n20 Band Edge, Right Side



Date: 2.AUG.2013 14:58:51

FCC Part 15.247 Page 48 of 55

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: R2DG130508007-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. According to KDB 558074 D01 DTS Meas Guidance v02, set the RBW = 3 kHz, VBW = 30 kHz, Set the span to 1.5 times the DTS channel bandwidth.
- 4. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2012-9-16 | 2013-9-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 26~28.5° C | |
|--------------------|---------------|--|
| Relative Humidity: | 64~70 % | |
| ATM Pressure: | 99.5~100.1kPa | |

The testing was performed by Leon Chen from 2013-06-13 to 2013-06-27.

FCC Part 15.247 Page 49 of 55

Test Mode: Transmitting

Test Result: Pass

| Channel | PSD | Limit | Result | |
|----------------|------------|------------|--------|--|
| Channel | (dBm/3kHz) | (dBm/3kHz) | | |
| 802.11b mode | | | | |
| Low | -9.58 | 8 | PASS | |
| Middle | -8.14 | 8 | PASS | |
| High -8.57 | | 8 | PASS | |
| 802.11g mode | | | | |
| Low | -11.28 | 8 | PASS | |
| Middle | -11.71 | 8 | PASS | |
| High -11.65 | | 8 | PASS | |
| 802.11n20 mode | | | | |
| Low | -12.54 | 8 | PASS | |
| Middle | -11.11 | 8 | PASS | |
| High -11.77 | | 8 | PASS | |


Report No.: R2DG130508007-00A

Please refer to the following plots

FCC Part 15.247 Page 50 of 55


Report No.: R2DG130508007-00A

Power Spectral Density, 802.11b Low Channel



Date: 15.JUL.2013 14:12:37


Power Spectral Density, 802.11b Middle Channel



Date: 15.JUL.2013 14:12:07


FCC Part 15.247 Page 51 of 55

Power Spectral Density, 802.11b High Channel



Date: 15.JUL.2013 14:13:25


Power Spectral Density, 802.11g Low Channel



Date: 10.MAY.2013 17:35:34


FCC Part 15.247 Page 52 of 55

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:42:56

Power Spectral Density, 802.11g High Channel




Date: 10.MAY.2013 17:45:37

FCC Part 15.247 Page 53 of 55


Power Spectral Density, 802.11n20 Low Channel

Report No.: R2DG130508007-00A



Date: 10.MAY.2013 17:48:38

Power Spectral Density, 802.11n20 Middle Channel




Date: 12.MAY.2013 16:19:17

FCC Part 15.247 Page 54 of 55

Power Spectral Density, 802.11n20 High Channel

Report No.: R2DG130508007-00A



Date: 12.MAY.2013 16:21:59

***** END OF REPORT *****

FCC Part 15.247 Page 55 of 55