

FCC TEST REPORT

FCC ID : Y3VT-00

Applicant : **Legend Lifestyle Products Corp.**

Address : 8th Fl., No298, Rueiguang Rd., Neihu, Taipei, Taiwan

Equipment Under Test (EUT) :

Product description : Torque tool

Model No. : T-00

Standards : FCC Part 15 Subpart C, Section15.249

Date of Test : Feb.18, 2011

Test Engineer : **Olic huang/ Engineer**



Reviewed By : **Philo Zhong/Manager**



Test Result :	PASS *
----------------------	---------------

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District,
Shenzhen 518105, China

Tel : +86-755-27553488

Fax: +86-755-27553868

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
3 TEST SUMMARY	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF E.U.T.	5
4.3 DETAILS OF E.U.T.....	5
4.4 DESCRIPTION OF SUPPORT UNITS.....	5
4.5 STANDARDS APPLICABLE FOR TESTING	5
4.6 TEST FACILITY	6
4.7 TEST LOCATION	6
5 EQUIPMENT USED DURING TEST.....	7
6 CONDUCTED EMISSION TEST.....	9
6.1 TEST EQUIPMENT	9
6.2 TEST PROCEDURE.....	9
6.3 CONDUCTED TEST SETUP	10
6.4 EUT OPERATING CONDITION	10
6.5 CONDUCTED EMISSION LIMITS.....	11
6.6 CONDUCTED EMISSION TEST RESULT	11
7 RADIATION EMISSION TEST	12
7.1 TEST EQUIPMENT	12
7.2 MEASUREMENT UNCERTAINTY	12
7.3 TEST PROCEDURE.....	12
7.4 RADIATED TEST SETUP	13
7.5 SPECTRUM ANALYZER SETUP	13
7.6 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	14
7.7 SUMMARY OF TEST RESULTS	14
7.8 EUT OPERATING CONDITION	15
7.9 RADIATED EMISSIONS LIMIT	15
7.10 RADIATED EMISSIONS TEST RESULT	16
8 PERIODIC OPERATION	19
9 ANTENNA REQUIREMENT.	22
10 20-DB BANDWIDTH.....	22
11 BAND EDGE.....	23
11.1 TEST EQUIPMENT	23
11.2 TEST PROCEDURE.....	23
11.3 BAND EDGE.....	23
11.4 BAND EDGE TEST RESULT	24
11.5 BAND EDGE TEST RECORD.....	24
12 PHOTOGRAPHS OF TESTING	25
12.1 RADIATION EMISSION TEST VIEW FOR 30MHZ-1000MHZ.....	25
12.2 RADIATION EMISSION TEST VIEW FOR 1GHZ-25GHZ	25

13 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....26

13.1 EUT - FRONT VIEW26

13.2 EUT - FRONT VIEW (CONTROL PANEL)26

13.3 EUT - BACK VIEW27

13.4 PCB1 - FRONT VIEW27

13.5 PCB1 - BACK VIEW28

13.6 PCB2 – MODULATION VIEW28

14 FCC LABEL.....29

3 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 25GHz)	FCC 15.249 FCC 15.209	ANSI C63.4: 2003	N/A	PASS
Conducted Emission (150KHz to 30MHz)	FCC 15.249 FCC 15.207	ANSI C63.4: 2003	Class B	N/A
Periodic Operation	FCC 15.249	ANSI C63.4: 2003	N/A	Comply
20dB-Bandwidth	FCC 15.249	ANSI C63.4: 2003	N/A	Comply

4 General Information

4.1 Client Information

Applicant: **Legend Lifestyle Products Corp.**
Address of Applicant: 8th Fl., No298, Rueiguang Rd., Neihu, Taipei, Taiwan

Manufacturer: **Zhuhai Cybertech Ventures Inc.**
Address of Manufacturer: #6, Jing Heng 2th, RD Taiwan Industrial Yard, Tangjia Town, Zhuhai, Guangdong, China

4.2 General Description of E.U.T.

Product description: Torque tool
Model No.: T-00

4.3 Details of E.U.T.

Power Supply: DC 1.5V*4,AAA
Working Frequency: 2440MHz

4.4 Description of Support Units

The EUT has been tested as an independent unit.

4.5 Standards Applicable for Testing

The customer requested FCC tests for a Torque tool. The standards used were FCC Part 15 Subpart C, FCC Part 15 Subpart C, Section15.209, FCC Part 15 Subpart C,Section15.207, FCC Part 15 Subpart C,Section15.203.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **IC – Registration No.: 7760A**

Waltek Services(Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration 7760A, Aug. 03, 2010

- **FCC – Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, June 24, 2008.

4.7 Test Location

The Emission test was performed at:-

Waltek Services(Shenzhen) Co., Ltd. at 1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District, Shenzhen, China.

5 Equipment Used during Test

Equipment Name	Manufacturer Model	Equipment No	Internal No	Specification	Cal. Date	Due Date	Cert. No	Uncertainty
EMC Analyzer	Agilent/ E7405A	MY451149 43	W2008001	9k-26.5GHz	Aug-03 -10	Aug-02 -11	Wws200 81596	±1dB
Trilog Broadband Antenne	SCHWARZB ECK MESS-ELEK TROM/ VULB9163	336	W2008002	30-3000 MHz	Aug-03 -10	Aug-02 -11		±1dB
Broad-band Horn Antenna	SCHWARZB ECK MESS-ELEK TROM/ BBHA 9120D(1201)	667	W2008003	1-18GHz	Aug-03 -10	Aug-02 -11		f<10 GHz: ±1dB 10GHz<f<18 GHz: ±1.5dB
Broadband Preamplifier	SCHWARZB ECK MESS-ELEK TROM/ BBV 9718	9718-148	W2008004	0.5-18GHz	Aug-03 -10	Aug-02 -11		±1.2dB
10m Coaxial Cable with N-male Connectors	SCHWARZB ECK MESS-ELEK TROM/ AK 9515 H	-	-	-	Aug-03 -10	Aug-02 -11		-
10m 50 Ohm Coaxial Cable with N-plug, individual length, usable up to 3(5)GHz, Connector	SCHWARZB ECK MESS-ELEK TROM/ AK 9513				Aug-03 -10	Aug-02 -11		
Positioning Controller	C&C LAB/ CC-C-IF				N/A	N/A		
Color Monitor	SUNSP0/ SP-14C				N/A	N/A		
Test Receiver	ROHDE&SC HWARZ/ ESPI	101155	W2005001	9k-3GHz	Aug-03 -10	Aug-02 -11	Wws200 80942	±1dB
EMI Receiver	Beijingkehua n	KH3931		9k-1GHz	Aug-03 -10	Aug-02 -11		
Two-Line V-Network	ROHDE&SC HWARZ/ ENV216	100115	W2005002	50Ω/50μH	Aug-03 -10	Aug-02 -11	Wws200 80941	±10%
Absorbing Clamp	ROHDE&SC HWARZ/ MDS-21	100205	W2005003	impedance 50 Ω loss : 17 dB	Aug-03 -10	Aug-02 -11	Wws200 80943	±1dB
10m 50	SCHWARZB				Aug-03	Aug-02		

Equipment Name	Manufacturer Model	Equipment No	Internal No	Specification	Cal. Date	Due Date	Cert. No	Uncertainty
Ohm Coaxial Cable with N-plug, individual length, usable up to 3(5)GHz, Connectors	ECK MESS-ELEKTROM/ AK 9514				-10	-11		
Digital Power Analyzer	Em Test AG/Switzerland/ DPA 500	V07451 03095	W2008012	Power: 2000VA Vol-range: 0-300V Freq_range: 10-80Hz	Aug-03 -10	Aug-02 -11	Wwd200 81185	Voltage distinguish: 0.025% Power_freq distinguish: 0.02Hz
Power Source	Em Test AG/Switzerland/ ACS 500	V07451 03096	W2008013	Vol-range: 0-300V Power_freq: 10-80Hz				
Electrostatic Discharge Simulator	Em Test AG/Switzerland/DITO	V07451 03094	W2008005	Contact discharge: 500V-10KV Air discharge: 500V-16.5KV	Aug-03 -10	Aug-02 -11	Wwc200 82400	7.5A current will be changed in $V_m=1.5V$
RF Generator	TESEQ GmbH/ NSG4070	25781	W2008008	Freq-range: 9K-1GHz RF voltage: -60 dBm-+10dBm	Aug-03 -10	Aug-02 -11	Wws200 81890	Power_freq distinguish: 0.1Hz RF electric distinguish: 0.1 B
CDN M-Type	TESEQ GmbH/ CDN M016	25112	W2008009	Voltage correct factor 9.5 dB	Aug-03 -10	Aug-02 -11	Wwc200 82396	150K-80MHz: $\pm 1dB$ 80-230MHz: -2-+3dB
EM-Clamp	TESEQ GmbH/ KEMZ 801	25453	W2008010	Freq_range: 0.15-1000 MHz	Aug-03 -10	Aug-02 -11	Wwc200 82397	0.3-400 MHz: $\pm 4dB$ Other freq: $\pm 5dB$
Attenuator 6dB	TESEQ GmbH/ ATN6050	25365			Aug-03 -10	Aug-02 -11	Wws200 81597	
All Modules Generator	SCHAFFNER/ 6150	34579	W2008006	voltage: 200V-4.4KV Pulse current: 100A-2.2KA	Aug-03 -10	Aug-02 -11	Wwc200 82401	voltage: $\pm 10\%$ Pulse current: $\pm 10\%$
Capacitive Coupling Clamp	SCHAFFNER/ CDN 8014	25311			Aug-03 -10	Aug-02 -11	Wwc200 82398	-
Signal and Data Line Coupling Network	SCHAFFNER/ CDN 117	25627	W2008011	1.2/50 μ S	Aug-03 -10	Aug-02 -11	Wwc200 82399	-

6 Conducted Emission Test

Product Name:	Torque tool
Test Requirement:	FCC 15.249 and FCC 15.207
Test Method:	Based on ANSI C63.4: 2003
Test Date:	N/A
Frequency Range:	150 kHz to 30MHz
Class:	Class B
Detector:	Peak for pre-scan (9 kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

6.1 Test Equipment


Please refer to Section 5 this report.

6.2 Test Procedure

1. The EUT was tested according to ANSI C63.4: 2003. The frequency spectrum from 150kHz to 30MHz was investigated.
2. The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.3 Conducted Test Setup


The conducted emission tests were performed using the setup accordance with the ANSI C63.4:2003, The specification used in this report was the FCC 15.249 limits.



6.4 EUT Operating Condition

Operating condition is according to ANSI C63.4: 2003.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.



6.5 Conducted Emission Limits

66-56 dB μ V between 0.15MHz & 0.5MHz

56 dB μ V between 0.5MHz & 5MHz

60 dB μ V between 5MHz & 30MHz

Note: In the above limits, the tighter limit applies at the band edges.

6.6 Conducted Emission Test Result

Note: This equipment operates from 6.0VDC vehicle battery power, so this test is not performed.

7 Radiation Emission Test

Product Name:	Torque tool
Test Requirement:	FCC 15.249 and FCC 15.209
Test Method:	Based on ANSI C63.4: 2003
Test Date:	Feb.18, 2011
Frequency Range:	30MHz to 25GHz
Measurement Distance:	3m
Detector:	Peak for pre-scan (120kHz resolution bandwidth) Quasi-Peak if maximised peak within 6dB of limit

7.1 Test Equipment

Please refer to Section 5 this report.

7.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase centre variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on ANSI C63.4: 2003, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at waltek EMC Lab is +/-5.03 dB.

7.3 Test Procedure

1. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combinations.
2. All data was recorded in the peak & average detection mode.
3. The EUT was under normal mode during the final qualification test and the configuration was used to represent the worst case results.
4. This is a handheld device, The radiation emission should be tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-tested, It was found that the worse radiation emission was got at the X position. So the data shown was the X position only.

7.4 Radiated Test Setup

The radiated emission tests were performed in the 3m Semi-Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003, The specification used in this report was the FCC 15.249 and FCC 15.209 limits.



7.5 Spectrum Analyzer Setup

According to FCC 15.249 Rules, the system was tested to 25000 MHz.

Below 1GHz

Start Frequency.....	30 MHz
Stop Frequency.....	1000 MHz
Sweep Speed	Auto
IF Bandwidth.....	120 KHz
Video Bandwidth.....	100KHz
Quasi-Peak Adapter Bandwidth	120 KHz
Quasi-Peak Adapter Mode	Normal
Resolution Bandwidth	100KHz

Above 1GHz

Start Frequency..... 1000 MHz
 Stop Frequency..... 25000 MHz
 Sweep Speed Auto
 IF Bandwidth..... 1 MHz
 Video Bandwidth..... 1 MHz
 Resolution Bandwidth 1MHz

7.6 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dBμV means the emission is 7dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$

7.7 Summary of Test Results

According to the data in section 7.10, the EUT complied with the FCC 15.249 standards.

7.8 EUT Operating Condition

Same as section 6.4 of this report.

7.9 Radiated Emissions Limit

A. FCC 15.249 for RF Limit

Fundamental Frequency	Field Strength of Fundamental		Field Strength of Harmonics	
	mV/m	dBuV/m	uV/m	dBuV/m
902-928MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25GHz	250	108	2500	68

- Note:**
- (1) $\text{RF Voltage(dBuV)} = 20 \log \text{RF Voltage(uV)}$
 - (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
 - (3) The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
 - (4) Above 1GHz, do a Peak and average measurements for all emissions, Limit for peak is 94dBuV/m, According to Part 15.35(b) and average is 54BuV/m.

B. Frequencies in restricted band are complied to limit on FCC 15.249 and FCC 15.209.

Frequency(MHZ)	Distance(m)	Field strength(dBuV/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

- Note:**
- (1) $\text{RF Voltage(dBuV)} = 20 \log \text{RF Voltage(uV)}$
 - (2) In the Above Table, the tighter limit applies at the band edges.
 - (3) Distance refers to the distance in meters between the measuring instrument antenna.

7.10 Radiated Emissions Test Result

Formula of conversion factors: the field strength at 3m was established by adding
The meter reading of the spectrum analyzer (which is set to read in units of dBuV)
To the antenna correction factor supplied by the antenna manufacturer. The antenna
Correction factors are stated in terms of dB. The gain of the pressetor was accounted
For in the spectrum analyser meter reading.

Example:

Freq(MHz) Meter Reading +ACF=FS

33 20dBuV+10.36dB=30.36dBuV/m @3m

Radiated Emission Test Data

Test Voltage: DC 6.0V

Test Mode: TX On

Temperature: 25.5 °C

Humidity: 51%RH

Test Result: PASS

Remarks: 30-1000MHz radiation test no significant emissions above the equipment noise floor
were detected.

1GHz-25GHz Radiated Emission Data

Frequency (MHz)	Detector	Antenna Polarization	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Turntable Angle (°)
2440.00	AV	Vertical	80.82	94.00	13.18	1.0	90
2440.00	AV	Horizontal	75.25	94.00	18.75	1.1	120
4880.00	AV	Vertical	43.49	54.00	10.51	1.2	45
7320.00	AV	Vertical	42.58	54.00	11.42	1.1	90
9760.00	AV	Vertical	41.21	54.00	12.79	1.0	90
12200.00	AV	Vertical	40.92	54.00	13.08	1.1	120
14640.00	AV	Vertical	39.91	54.00	14.09	1.0	45
17080.00	AV	Vertical	39.85	54.00	14.15	1.1	120
19520.00	AV	Vertical	37.59	54.00	16.41	1.4	180
21960.00	AV	Vertical	38.57	54.00	15.43	1.1	90
24400.00	AV	Vertical	38.54	54.00	15.46	1.2	60
4880.00	AV	Horizontal	35.85	54.00	18.15	1.1	180
7320.00	AV	Horizontal	36.44	54.00	17.56	1.2	45
9760.00	AV	Horizontal	36.55	54.00	17.45	1.5	45
12200.00	AV	Horizontal	34.59	54.00	19.41	1.0	180
14640.00	AV	Horizontal	33.59	54.00	20.41	1.1	45
17080.00	AV	Horizontal	34.55	54.00	19.45	1.1	60
19520.00	AV	Horizontal	33.26	54.00	20.74	1.1	120
21960.00	AV	Horizontal	32.44	54.00	21.56	1.2	90
24400.00	AV	Horizontal	31.19	54.00	22.81	1.1	90
2440.00	PK	Vertical	104.52	114.00	25.41	1.0	20
2440.00	PK	Horizontal	98.56	114.00	30.98	1.1	30
4880.00	PK	Vertical	51.26	74.00	22.74	1.0	120
7320.00	PK	Vertical	50.35	74.00	23.65	1.1	120
9760.00	PK	Vertical	48.98	74.00	25.02	1.0	90
12200.00	PK	Vertical	48.69	74.00	25.31	1.0	90
14640.00	PK	Vertical	47.68	74.00	26.32	1.0	45
17080.00	PK	Vertical	47.62	74.00	26.38	1.2	60
19520.00	PK	Vertical	45.36	74.00	28.64	1.1	60
21960.00	PK	Vertical	46.34	74.00	27.66	1.1	100
24400.00	PK	Vertical	46.31	74.00	27.69	1.2	120
4880.00	PK	Horizontal	43.62	74.00	30.38	1.1	45

7320.00	PK	Horizontal	44.21	74.00	29.79	1.1	90
9760.00	PK	Horizontal	44.32	74.00	29.68	1.1	180
12200.00	PK	Horizontal	42.36	74.00	31.64	1.2	120
14640.00	PK	Horizontal	41.36	74.00	32.64	1.1	45
17080.00	PK	Horizontal	42.32	74.00	31.68	1.2	180
19520.00	PK	Horizontal	41.03	74.00	32.97	1.1	120
21960.00	PK	Horizontal	40.21	74.00	33.79	1.0	90
24400.00	PK	Horizontal	38.96	74.00	35.04	1.1	90

Note1: Above 1GHz,do a Peak and average measurements for all emissions,Limit for peak is 94dBuV/m,According to the paragraph in IC RSS-210,RSS-Gen 7.2.1 and average is 54BuV/m.

Note2: $AV = \text{Peak} + 20\log_{10}(\text{duty cycle}) = \text{Peak} - 7.65$

So the Radiated Emission Test Data as the table follow.For more details of the calculation , please refer the section 8 of the Periodic operation .And The maximum permitted unwanted emission level is 50 dB below the maximum permitted fundamental level.

The formula of calculate $AV = \text{Peak} + 20\log_{10}(\text{duty cycle})$

8 Periodic Operation

The duty cycle was determined by the following equation:

To calculate the actual field intensity, The duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

Duty Cycle(%)=

Total On interval in a complete pulse train/ Length of a complete pulse train * %


Duty Cycle Correction Factor(dB)=20 * Log₁₀(Duty Cycle(%))

Pulse Train	Number of Pulse	T(ms)	Total Time(ms)
Pulse 1	1	22	22
Pulse 2	1	40	40
Pulse 3	1	40	40


Total On interval in a complete pulse train	246msec
Length of a complete pulse train	102msec
Duty Cycle(%)	41.46%
Duty Cycle Correction Factor(dB)	-7.65

Refer to the duty cycle plot (as below), This device does meet the FCC requirement.


Length of a complete pulse train:




Pulse 1:



Pulse 2:



Pulse 3:



9 Antenna Requirement.

According to the FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna to the intentional radiator shall be considered sufficient to comply with the provisions of this section. This product has a permanent antenna, fulfill the requirement of this section

10 20-dB Bandwidth


Product Name: Torque tool
Test Voltage: DC 6.0V
Test Mode: TX On
Temperature: 25.5°C
Humidity: 51%RH

Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. The bandwidth of the fundamental frequency was measure by spectrum analyser with 100KHz RBW and 100KHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power 20dB.

Test Result

Please refer the graph as below:



11 Band Edge

11.1 Test Equipment

Please refer to Section 5 this report.

11.2 Test Procedure

1. The EUT, peripherals were put on the turntable which table size is 1mX1.5m, table high 0.8m. All set up is according to FCC 15.249 and FCC 15.209.
2. The bandwidth of the fundamental frequency was measure by spectrum analyser with 1MHz RBW and 1MHz VBW.


11.3 Band Edge

Requirements: FCC15.247, the emission power at the START and STOP frequencies shall be at least 50dB below the level of the fundamental or to the general radiated emission limits in FCC15.209.

11.4 Band Edge Test Result

Product Name: Torque tool
Test Item: Band Edge Test
Test Voltage: DC 6.0V
Test Mode: TX On
Temperature: 25.5°C
Humidity: 51%RH


11.5 Band Edge Test Record




- Note:**
- (1) The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in FCC 15.249 and FCC 15.209.
 - (2) This device does meet the FCC requirement.

12 Photographs of Testing

12.1 Radiation Emission Test View For 30MHz-1000MHz



12.2 Radiation Emission Test View For 1GHz-25GHz



13 Photographs - Constructional Details

13.1 EUT - Front View




13.2 EUT - Front View (control panel)




13.3 EUT - Back View




13.4 PCB1 - Front View



13.5 PCB1 - Back View



13.6 PCB2 – Modulation View



14 FCC Label

The Label must not be a stick-on paper. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Proposed Label Location on EUT
EUT Bottom View/proposed FCC Mark Location

