



# ELECTRONICS TESTING CENTER(ETC), TAIWAN

## EMC TESTING DEPARTMENT II

NO. 34, LIN 5, DINGFU VIL., LINKOU DIST., NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.

*According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance  $\leq 50$  mm are determined by:*

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

The max. average power of channel, including tune-up tolerance(mW) is **12 mW** @ **697.900MHz** (With Tune-up tolerance),

The min. test separation distance (mm) is **5 mm**,

So,  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 2.0 < 3.0$  (With Tune-up tolerance).

Therefore, standalone SAR measurements are not required for both head and body.

Signature S. S. Liou

Name/Title: S. S. Liou / Section Manager, EMC Testing Department II

TEL: +886-2-2602-3052

Email: ssliou@etc.org.tw