

# FCC PART 74

## Measurement and Test Report

### For

**inMusic Brands, Inc.**

**200 Scenic View Drive, Cumberland, RI 02864, U.S.A**

**FCC ID: Y40-DA35**

<b>FCC Rules:</b>	<u>FCC Part 74</u>
<b>Product Description:</b>	<u>UHF transmitter</u>
<b>Tested Model:</b>	<u>DA35</u>
<b>Report No.:</b>	<u>STRD1703236I</u>
<b>Tested Date:</b>	<u>2017-03-29 to 2017-05-05</u>
<b>Issued Date:</b>	<u>2017-05-06</u>
<b>Tested By:</b>	<u>Iven Guo / Engineer</u>
<b>Reviewed By:</b>	<u>Silin Chen / EMC Manager</u>
<b>Approved &amp; Authorized By:</b>	<u>Jandy So / PSQ Manager</u>
<b>Prepared By:</b>	

*Iven Guo*  
*Silin Chen*  
*Jandy So*



**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd

## **TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT EXERCISE SOFTWARE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>3. RF OUTPUT POWER.....</b>	<b>8</b>
3.1 STANDARD APPLICABLE.....	8
3.2 TEST PROCEDURE.....	8
3.3 ENVIRONMENTAL CONDITIONS.....	8
3.4 TEST RESULT/PLOTS.....	8
<b>4. MODULATION CHARACTERISTICS.....</b>	<b>11</b>
4.1 STANDARD APPLICABLE.....	11
4.2 TEST PROCEDURE.....	11
4.3 ENVIRONMENTAL CONDITIONS.....	11
4.4 TEST RESULTS/PLOTS.....	11
<b>5. OCCUPIED BANDWIDTH.....</b>	<b>14</b>
5.1 STANDARD APPLICABLE.....	14
5.2 TEST PROCEDURE.....	14
5.3 ENVIRONMENTAL CONDITIONS.....	14
5.4 TEST RESULTS/PLOTS.....	14
<b>6. RADIATED SPURIOUS EMISSION.....</b>	<b>18</b>
6.1 STANDARD APPLICABLE.....	18
6.2 TEST PROCEDURE.....	18
6.3 ENVIRONMENTAL CONDITIONS.....	20
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	20
<b>7. SPURIOUS EMISSION AT ANTENNA TERMINAL.....</b>	<b>28</b>
7.1 STANDARD APPLICABLE.....	28
7.2 TEST PROCEDURE.....	28
7.3 ENVIRONMENTAL CONDITIONS.....	28
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	28
<b>8. FREQUENCY STABILITY.....</b>	<b>32</b>
8.1 STANDARD APPLICABLE.....	32
8.2 TEST PROCEDURE.....	32
8.3 ENVIRONMENTAL CONDITIONS.....	32
8.4 TEST RESULTS/PLOTS.....	32

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: inMusic Brands, Inc.  
Address of applicant: 200 Scenic View Drive, Cumberland, RI 02864, U.S.A

Manufacturer: inMusic Brands, Inc.  
Address of manufacturer: 200 Scenic View Drive, Cumberland, RI 02864, U.S.A

General Description of EUT	
Product Name:	UHF transmitter
Trade Name:	DENON PROFESSIONAL
Model No.:	DA35
Adding Model(s):	/
Rated Voltage:	Battery DC 3V
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Items	Description
RF Output Power:	Max. 10.98dBm (Conducted) Max. 11.72dBm (ERP)
Frequency Range:	584MHz - 594.85MHz
Modulation:	FM
Antenna Type:	Integral Antenna
Antenna Gain:	0 dBi
For more information refer to the circuit diagram form and the user's manual.	

*The test data gathered are from a production sample, provided by the manufacturer.*

## 1.2 Test Standards

The following report is prepared on behalf of the inMusic Brands, Inc. in accordance with Part 74 Subpart H of the Federal Communication Commissions rules.

The objective is to determine compliance with the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

Measurements contained in this report were also conducted with ANSI/TIA-603-D: 2010, Telecommunications Industry Association Land Mobile FM or PM Communications Equipment Measurement and Performance Standards, ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted with Low Channel, Middle Channel and High Channel, accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.5 EUT Exercise Software

The EUT exercise program used during the testing was designed to exercise the system components. The test software is started while the whole system is on.

Test Mode List		
Test Mode	Description	Remark
TM1	transmitter	Low, Middle, High Channels

Test Conditions					
	Normal	LTLV	LTHV	HTHV	HTLV
Temperature ( °C )	20	-30	-30	50	50
Voltage ( V )	3.0	2.6	3.4	2.6	3.4

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	---	$\pm 1 \times 10^{-7}$
Frequency Stability	2.3%	$\pm 5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.2\text{dB}$

## 1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

## 2. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§74.861(e)(1)(ii)	Output Power Measurement	Compliant
§74.861(e)(3)	Modulation Characteristics	Compliant
§74.861(e)(5)	Occupied Bandwidth Emission	Compliant
§74.861(e)(6)	Radiated Spurious Emission	Compliant
§2.1051	Spurious Emission at Antenna Port	Compliant
§74.86(e)(4)	Frequency Stability	Compliant

### 3. RF OUTPUT POWER

#### 3.1 Standard Applicable

According to FCC 74.861(e)(1)(ii), for low power auxiliary station operating in the 470-608, and 614-698 MHz bands, the power of the measured unmodulated carrier power and the output of the transmitter power amplifier (antenna input power) may not exceed 250mW.

#### 3.2 Test Procedure

1. The maximum peak output power was measured with a Spectrum Analyzer connected to the antenna terminal while EUT was operating in unmodulated situation.
2. Power was supplied to the battery input connector a power supply. The power supply was set for +3.0VDC. The Spectrum Analyzer was connected at antenna terminal to measure RF power of the carrier.
3. A Multimeter was connected in series with final RF Stage to measure the current; A Multimeter was used to measure final RF Stage supply voltage. Then the voltage v.s. current of the final RF Stage can be showed.

#### 3.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### 3.4 Test Result/Plots

ERP power


Channel	Measured Value	Antenna Gain	ERP	Limit
	dBm	dBi	dBm	dBm
Low	11.53	0	11.53	24
Middle	11.71	0	11.71	24
High	11.72	0	11.72	24

Conducted power


Channel	Frequency (MHz)	RF Stage Voltage (Vdc)	Collected Current (mA)	Output Power (dBm)	Limit (dBm)
Low	584.00	3.00	0.35	10.98	24
Middle	589.25	3.00	0.35	10.87	24
High	594.85	3.00	0.35	10.93	24




### Low Channel (584.00MHz)



### Middle Channel (589.25MHz)



*High Channel (594.85MHz)*

## 4. MODULATION CHARACTERISTICS

---

### 4.1 Standard Applicable

According to FCC 2.1047 (a), for Voice Modulated Communication Equipment, the frequency response of the audio modulating circuit over a range of 100Hz to 5000Hz shall be measured. For equipment required to have an audio low-pass filter, the frequency response of the filter or of all circuitry installed between the modulation limiter and the modulated stage shall be measured.

According to §74.861(e)(3), any form of modulation may be used. A maximum deviation of  $\pm 75$  kHz is permitted when frequency modulation is employed.

### 4.2 Test Procedure



- 1) Position the EUT as shown in figure 1, adjust the audio input frequency to 100 Hz and the input level from 0V to maximum permitted input voltage with recording each carrier frequency deviation responding to respective input level.
- 2) Repeat step 1 with changing the input frequency for 100, 300, 1000, 2500 and 3000 Hz in sequence.

### 4.3 Environmental Conditions



Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 4.4 Test Results/Plots

### Middle Channel (589.25MHz)



### Audio Low Pass Filter Characteristic Curve



## 5. OCCUPIED BANDWIDTH

### 5.1 Standard Applicable

According to FCC 2.1049 (c) (1), for radiotelephone transmitter, other than single sideband or independent sideband transmitter, when modulated by a 2.5 kHz tone at an input level 16 dB greater than that necessary to produce 50 percent modulation.

According to §74.861(e)(5), the operating bandwidth shall not exceed 200 kHz.

According to FCC 74.861(e)(6), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

1. On any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB.
2. On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB.
3. On any frequency removed from the operating frequency by more than 250 percent up to and the authorized bandwidth shall be attenuated below the un-modulated carrier by at least 43 plus 10 Log (output power in watts) dB.

### 5.2 Test Procedure

According to TIA-603 for additional Test Set-Up procedures, the occupied bandwidth of emission was measured with a Spectrum Analyzer connected to the antenna terminal while EUT was operating in 2.5kHz tone at an input level 16 dB greater than that necessary to produce 50 percent modulation. Then mark the -26dB Bandwidth and record it.


### 5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


### 5.4 Test Results/Plots

Test Channel	Frequency (MHz)	-26dB Bandwidth (kHz)	99% Bandwidth (kHz)	Limit (kHz)
Low	584.00	126.959	75.4317	200
Middle	589.25	126.803	75.4833	200
High	594.85	126.403	75.4994	200


### Low Channel (584.00MHz)




### Middle Channel (589.25MHz)



### High Channel 3 (594.85MHz)




### Emission Mask (584.00MHz)






### Emission Mask (589.25MHz)



### Emission Mask (594.85MHz)



## 6. RADIATED SPURIOUS EMISSION

---

### 6.1 Standard Applicable

According to FCC 2.1053, measurements shall be made to detect spurious emission that may be radiated directly from the cabinet, control circuits, power leads, or intermediated circuit elements under normal condition of installation and operation. Information submitted shall include the relative radiated power of spurious emission with reference to the rated power output of the transmitter assuming all emissions are radiated from a halfwave dipole antenna.

According to FCC74.861 (e)(6), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

4. On any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB.
5. On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB.
6. On any frequency removed from the operating frequency by more than 250 percent up to and the authorized bandwidth shall be attenuated below the un-modulated carrier by at least 43 plus 10 Log (output power in watts) dB.

### 6.2 Test Procedure



The setup of EUT is according with per TIA/EIA Standard 603 and ANSI C63.4-2014 measurement procedure.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB =  $43 + 10 \text{ Log}_{10} (\text{power in Watts})$



Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=300KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

### 6.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	52%
ATM Pressure:	1022 mbar

### 6.4 Summary of Test Results/Plots

According to the data below, the FCC Part 74.861 standards, and had the worst margin of:

**-28.56 dB at 739.6605 MHz in the Vertical polarization Transmitting 584 MHz Mode, 30 MHz to 1 GHz**

### Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: UHF transmitter

Tested Model: DA35

Operating Condition: Transmitting Low Channel (584.00MHz)


Comment: DC 3V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	236.6447	-72.29	20.52	-51.77	-13.00	-38.77	ERP
2	440.1963	-69.48	24.31	-45.17	-13.00	-32.17	ERP
3	584.7894	-18.27	27.73	9.46	/	/	ERP
4	752.7432	-72.38	30.27	-42.11	-13.00	-29.11	ERP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	252.0627	-71.94	21.18	-50.76	-13.00	-37.76	ERP
2	400.4319	-72.30	24.47	-47.83	-13.00	-34.83	ERP
3	584.7894	-16.14	27.73	11.59	/	/	ERP
4	739.6605	-72.36	30.80	-41.56	-13.00	-28.56	ERP

### Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: UHF transmitter

Tested Model: DA35

Operating Condition: Transmitting Middle Channel (589.25MHz)


Comment: DC 3V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	253.8367	-72.53	21.26	-51.27	-13.00	-38.27	ERP
2	443.2943	-70.20	24.39	-45.81	-13.00	-32.81	ERP
3	589.2537	-18.63	28.12	9.49	/	/	ERP
4	734.4913	-72.81	30.49	-42.32	-13.00	-29.32	ERP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	204.2377	-72.14	16.09	-56.05	-13.00	-43.05	ERP
2	339.5888	-71.59	23.18	-48.41	-13.00	-35.41	ERP
3	499.4247	-72.14	25.11	-47.03	-13.00	-34.03	ERP
4	589.2537	-16.39	28.12	11.73	/	/	ERP



### Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: UHF transmitter

Tested Model: DA35

Operating Condition: Transmitting High Channel (594.85MHz)


Comment: DC 3V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	247.6819	-72.78	21.02	-51.76	-13.00	-38.76	ERP
2	393.4724	-72.10	24.19	-47.91	-13.00	-34.91	ERP
3	594.9737	-19.56	28.87	9.31	/	/	ERP
4	696.8567	-71.50	29.23	-42.27	-13.00	-29.27	ERP

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	204.9551	-73.84	16.24	-57.60	-13.00	-44.60	ERP
2	420.5803	-71.57	23.70	-47.87	-13.00	-34.87	ERP
3	594.9737	-17.11	28.87	11.76	/	/	ERP
4	677.5798	-71.97	30.35	-41.62	-13.00	-28.62	ERP

### Spurious Emission Above 1GHz

Frequency	SG Reading	Angle	Height	Polar	Correct (dB)	Result dBm	Limit dBm	Margin dB
MHz	dBm	Degree	Meter	H/V				
Low Channel (584.00MHz)								
1168.00	-36.54	175	1.6	H	8.42	-28.12	-13	-15.12
1168.00	-35.36	175	1.5	V	8.42	-26.94	-13	-13.94
1752.00	-34.37	171	1.5	H	9.18	-25.19	-13	-12.19
1752.00	-29.54	186	1.4	V	9.18	-20.36	-13	-7.36
2336.00	-44.89	130	1.7	H	11.98	-32.91	-13	-19.91
2336.00	-42.06	125	1.8	V	11.98	-30.08	-13	-17.08
Middle Channel (589.25MHz)								
1178.50	-37.05	205	1.5	H	8.41	-28.64	-13	-15.64
1178.50	-33.19	303	1.6	V	8.41	-24.78	-13	-11.78
1767.75	-36.31	195	1.3	H	9.23	-27.08	-13	-14.08
1767.75	-31.54	114	1.7	V	9.23	-22.31	-13	-9.31
2357.00	-41.53	181	1.3	H	11.6	-29.93	-13	-16.93
2357.00	-44.08	213	1.8	V	11.6	-32.48	-13	-19.48
High Channel (594.85MHz)								
1189.70	-37.62	140	1.6	H	8.4	-29.22	-13	-16.22
1189.70	-35.31	139	1.4	V	8.4	-26.91	-13	-13.91
1784.55	-35.51	297	1.4	H	9.32	-26.19	-13	-13.19
1784.55	-31.46	270	1.4	V	9.32	-22.14	-13	-9.14
2379.40	-44.08	217	1.3	H	12.01	-32.07	-13	-19.07
2379.40	-41.86	221	1.7	V	12.01	-29.85	-13	-16.85

Note: Testing is carried out with frequency rang 30MHz to the tenth harmonics, which above 4<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 7. SPURIOUS EMISSION AT ANTENNA TERMINAL

### 7.1 Standard Applicable

According to §2.1051, the radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in §2.1049 as appropriate.

According to FCC74.861 (e)(6), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

On any frequency removed from the operating frequency by more than 250 percent up to and the authorized bandwidth shall be attenuated below the un-modulated carrier by at least 43 plus 10 Log (output power in watts) dB.

### 7.2 Test Procedure

Connect a suitable artificial antenna properly, set the Low, Middle and High Transmitting Channel, observed the spurious emissions from antenna port, and then mark the higher-level emission for comparing with the FCC rules.



### 7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar



### 7.4 Summary of Test Results/Plots

Refer to the attached plots.



# Low Channel



### Middle Channel



### High Channel



## 8. FREQUENCY STABILITY

---

### 8.1 Standard Applicable

According to FCC 2.1055(a)(1), the frequency stability shall be measure with variation of ambient temperature from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ , and according to FCC 2.1055(d)(2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC 74.861, the frequency tolerance of the transmitter shall be 0.005 percent.

### 8.2 Test Procedure

1. Setup the configuration of the ambient temperature form  $-30^{\circ}\text{C}$  to  $50^{\circ}\text{C}$  with sufficient time. And measure the different power of the EUT with an artificial power from highest to end point voltage.
2. Set frequency counter center frequency to the right frequency needs to be measured.

### 8.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

### 8.4 Test Results/Plots



Test conditions		Frequency Error		
		584.0 MHz	589.25 MHz	594.85 MHz
T <sub>min</sub> (-30°C)	V <sub>min</sub> (2.6V)	583.9828	589.2375	594.8375
	V <sub>max</sub> (3.4V)	583.9857	589.2353	594.8395
T(-20°C)	V <sub>nom</sub> (3.0V)	583.9839	589.2327	594.8423
T(-10°C)	V <sub>nom</sub> (3.0V)	583.9863	589.2339	594.8357
T(0°C)	V <sub>nom</sub> (3.0V)	583.9872	589.2367	594.8419
T(10°C)	V <sub>nom</sub> (3.0V)	583.9885	589.2313	594.8357
T <sub>nom</sub> (20°C)	V <sub>nom</sub> (3.0V)	583.9896	589.2359	594.8362
T(30°C)	V <sub>nom</sub> (3.0V)	583.9837	589.2387	594.8409
T(40°C)	V <sub>nom</sub> (3.0V)	583.9819	589.2393	594.8435
T <sub>max</sub> (50°C)	V <sub>min</sub> (2.6V)	583.9865	589.2401	594.8427
	V <sub>max</sub> (3.4V)	583.9887	589.2398	594.8398
Max. frequency error (ppm)		-30.99	-31.74	-24.04
Limit (ppm)		±50ppm		
End Point		DC 3.0V		

\*\*\*\*\* END OF REPORT \*\*\*\*\*