ION AUDIO LLC

TRANSACTIVE AIR

Model Number: LGAC

FCC ID: Y4O-LGAC

Prepared for : ION AUDIO LLC
200 SCENIC VIEW DRIVE, SUITE 201,
CUMBERLAND, Rhode Island 02864, United States

Prepared By : EST Technology Co., Ltd.
Santun Management Zone, Houjie District, Dongguan,
Guangdong, China
Tel: 86-769-83081888-808
Fax: 86-769-83081878

Report Number: ESTE-R1207004
Date of Test : June 19~ July 14, 2012
Date of Report : 17 July, 2012

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2 , ｜H｜2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2 , ｜H｜2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$E \text{ (V/m)} = (30*P*G)0.5/d$ Power Density: $Pd \text{ (W/m2)} = E2/377$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$Pd = (30*P*G) / (377*d2)$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Antenna gain (dBi)	Antenna gain (Linear)	Power Density (S) (mW/cm2)	Limited of Power Density (S) (mW/cm2)	Test Result
GFSK	2402	-9.051	0.125	2.5	1.7785	**0.000044**	1	Compiles
GFSK	2441	-8.375	0.145	2.5	1.7785	**0.000051**	1	Compiles
GFSK	2480	-7.039	0.197	2.5	1.7785	**0.000069**	1	Compiles
π/4-DQPSK	2402	-11.200	0.075	2.5	1.7785	**0.000026**	1	Compiles
π/4-DQPSK	2441	-10.340	0.092	2.5	1.7785	**0.000032**	1	Compiles
π/4-DQPSK	2480	-8.807	0.131	2.5	1.7785	**0.000046**	1	Compiles
8-DPSK	2402	-10.270	0.093	2.5	1.7785	**0.000032**	1	Compiles
8-DPSK	2441	-9.549	0.110	2.5	1.7785	**0.000039**	1	Compiles
8-DPSK	2480	-8.432	0.143	2.5	1.7785	**0.000050**	1	Compiles