

**IEEE C95.1
KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091**

RF EXPOSURE REPORT

For

Guitar Processor

Model: HEADRUSH PEDALBOARD

Data Applies To:N/A

Trade Name: HEADRUSH

Issued to

**inMusic Brands, Inc.
200 Scenic View Drive, Cumberland, RI 02864, U.S.A.**

Issued By

Compliance Certification Services Inc.

**Tainan Laboratory
No.8,Jiucengling, Xinhua Dist., Tainan City
712, Taiwan (R.O.C.)
TEL: 886-6-580-2201
FAX: 886-6-580-2202
<http://www.ccsrf.com>
E-Mail : service@ccsrf.com
Issued Date: December 15, 2016**





Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	December 15, 2016	Initial Issue	ALL	Daphne Liang



TABLE OF CONTENTS

1. LIMIT.....	4
2. EUT SPECIFICATION	4
3. TEST RESULTS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6

1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT SPECIFICATION

EUT	Guitar Processor		
Model	HEADRUSH PEDALBOARD		
Brand	HEADRUSH		
RF Module	SMS	Model:	AP6335
Frequency band (Operating)	<input checked="" type="checkbox"/> 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz 802.11a/n HT20: 5.180GHz ~ 5.240GHz / 5.745 ~ 5.825GHz 802.11n HT40: 5.190GHz ~ 5.230GHz / 5.755~ 5.795GHz 802.11ac VHT80: 5.210GHz / 5.775GHz <input checked="" type="checkbox"/> Others (Bluetooth 4.0: 2402MHz~2480MHz)		
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others		
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)		
Antenna Specification	PCB Antenna / Gain: 4.600 dBi (Numeric gain: 2.88) worst		
Maximum Average output power	IEEE 802.11b Mode :	11.610 dBm	(14.488 mW)
	IEEE 802.11g Mode :	16.380 dBm	(43.451 mW)
	IEEE 802.11n HT20 Mode :	16.270 dBm	(42.364 mW)
	Bluetooth 4.0 Mode :	2.350 dBm	(1.716 mW)
Maximum Tune up Power	IEEE 802.11b Mode :	11.710 dBm	(14.825 mW)
	IEEE 802.11g Mode :	16.480 dBm	(44.463 mW)
	IEEE 802.11n HT20 Mode :	16.370 dBm	(43.351 mW)
	Bluetooth 4.0 Mode :	2.450 dBm	(1.758 mW)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A		

3. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P / 1000) \times G}{377 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	2437	14.825	2.88	20	0.0085	1	Pass

IEEE 802.11g Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mld	2437	44.463	2.88	20	0.0255	1	Pass

IEEE 802.11n HT20 Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Low	2412	43.351	2.88	20	0.0248	1	Pass

Bluetooth 4.0 Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	2442	1.758	2.88	20	0.0010	1	Pass