

**FCC PART 15C TEST REPORT FOR CERTIFICATION**  
**On Behalf of**

**INMUSIC BRANDS INC**

**BLUETOOTH MIXER**

**Model Number: BLACK&BLUE**

**Additional Model: RA08**

**FCC ID: Y4O-RA08**

Prepared for:	INMUSIC BRANDS INC
	200 SCENIC VIEW DRIVE, SUITE 201, CUMBERLAND,
	RI 02864, U.S.A.
Prepared By:	EST Technology Co., Ltd.
	San Tun Management Zone, Houjie District, Dongguan, China
	Tel: 86-769-83081888-808




Report Number:	ESTE-R1709018
Date of Test:	June 26~July 01, 2017
Date of Report:	July 03, 2017

# TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT) .....	5
2. SUMMARY OF TEST .....	6
2.1. Summary of test result.....	6
2.2. Test Facilities .....	7
2.3. Measurement uncertainty .....	8
2.4. Assistant equipment used for test .....	8
2.5. Block Diagram .....	8
2.6. Test mode .....	9
2.7. Channel List for Bluetooth.....	9
2.8. Test Equipment.....	10
3 POWER LINE CONDUCTED EMISSION TEST.....	11
3.1 Limit .....	11
3.2 Test Procedure .....	11
3.3. Test Result.....	11
3.4. Test data .....	12
4 RADIATED EMISSION TEST .....	16
4.1 Limit.....	16
4.2. Block Diagram of Test setup.....	17
4.3. Test Procedure .....	18
4.4. Test Result.....	18
4.5. Test Data .....	19
5 BAND EDGE COMPLIANCE TEST .....	26
5.1 Limit .....	26
5.2 Block Diagram of Test setup.....	26
5.3 Test Procedure .....	26
5.4 Test Result.....	26
5.5 Test Data .....	27
6 6dB Bandwidth Test.....	31
6.1 Limit .....	31
6.2 Test Procedure .....	31
6.3 Test Result.....	31
6.4 Test Data .....	32
7 OUTPUT POWER TEST .....	38
7.1 Limit .....	38
7.2 Test Procedure .....	38
7.3 Test Result.....	39
7.4 Test Data .....	40
8 POWER SPECTRAL DENSITY TEST .....	46
8.1 Limit .....	46
8.2 Test Procedure .....	46
8.3 Test Result.....	46

8.4	Test Data .....	47
9	ANTENNA REQUIREMENTS .....	53
9.1	Limit .....	53
9.2	Result.....	53

## EST Technology Co., Ltd.

<b>Applicant:</b>	INMUSIC BRANDS INC		
<b>Address:</b>	200 SCENIC VIEW DRIVE, SUITE 201, CUMBERLAND, RI 02864, U.S.A.		
<b>Manufacturer:</b>	INMUSIC BRANDS INC		
<b>Address:</b>	200 SCENIC VIEW DRIVE, SUITE 201, CUMBERLAND, RI 02864, U.S.A.		
<b>E.U.T:</b>	BLUETOOTH MIXER		
<b>Model Number:</b>	BLACK&BLUE		
<b>Additional Model:</b>	RA08 Note: The two models have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction, except the different model number.		
<b>Power Supply:</b>	AC 100-240V~50/60Hz		
<b>Test Voltage:</b>	AC 120V/60Hz AC 240V/60Hz		
<b>Trade Name:</b>	RANE	<b>Serial No.:</b>	-----
<b>Date of Receipt:</b>	June 25, 2017	<b>Date of Test:</b>	June 25~July 01, 2017
<b>Test Specification:</b>	FCC Rules and Regulations Part 15 Subpart C:2016 ANSI C63.10:2013		
<b>Test Result:</b>	<p>The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p>This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.</p>		
<b>Prepared by:</b>		<b>Reviewed by:</b>	
 Winni / Assistant		 Tony / Engineer	
		<b>Date:</b> July 03, 2017 <b>Approved by:</b>  Iceman Hu / Manager	
<b>Other Aspects:</b>			
None.			
Abbreviations: OK/P=passed    fail/F=failed    n.a/N=not applicable    E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

Product Name	:	BLUETOOTH MIXER		
FCC ID	:	Y4O-RA08		
Model Number	:	BLACK&BLUE		
Operation frequency	:	2402MHz~2480MHz		
Number of channel	:	79	40	
Antenna	:	External antenna		
		BLUETOOTH A	BLUETOOTH B	BLUETOOTH C
		5 dBi gain	5 dBi gain	5 dBi gain
		Three modules can work simultaneously		
Modulation	:	Dual-mode Bluetooth 4.2 BT BDR: GFSK BT EDR: $\pi/4$ -DQPSK BT EDR: 8-DPSK		Dual-mode Bluetooth 4.2 BLE: GFSK
Sample Type	:	Prototype production		

## 2. SUMMARY OF TEST

### 2.1. Summary of test result

Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10:2013	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.10:2013 KDB 558074	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note: KDB 558074 D01 DTS Meas Guidance v04		

## 2.2. Test Facilities

EMC Lab	:	<p>Certificated by CNAS, CHINA Registration No.: L5288 Date of registration: December 07, 2015</p> <p>Certificated by FCC, USA Registration No.: 989591 Date of registration: November 15, 2016</p> <p>Certificated by Industry Canada Registration No.: 9405A-1 Date of registration: December 30, 2015</p> <p>Certificated by VCCI, Japan Registration No.: R-3663 &amp; C-4103 Date of registration: July 25, 2014</p> <p>Certificated by TUV Rheinland, Germany Registration No.: UA 50195514 0001 Date of registration: February 07, 2015</p> <p>Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011</p> <p>Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L1-18 Date of registration: April 28, 2011</p> <p>Certificated by Siemic, Inc. Registration No.: SLCN021 Date of registration: November 8, 2011</p> <p>Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011</p>
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	San Tun Management Zone, Houjie Town, Dongguan, Guangdong, China



### 2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.54dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.62
Uncertainty for Radiation Emission test (1GHz to 18GHz)	4.86
Uncertainty for radio frequency	$7 \times 10^{-8}$
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

### 2.4. Assistant equipment used for test

2.4.1. N/A

### 2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into Bluetooth test mode by software before test.



(EUT: BLUETOOTH MIXER)



## 2.6. Test mode

A special test software was used to control EUT work in Continuous TX mode(100% duty cycle), and select test channel, wireless mode and data rate.

Mode	Channel	Frequency
BT 4.0-BLE GFSK	Low	2402MHz
	Middle	2440MHz
	High	2480MHz

## 2.7. Channel List for Bluetooth

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2404
3	2406	4	2408
5	2410	6	2412
7	2414	8	2416
9	2418	10	2420
11	2422	12	2424
13	2426	14	2428
15	2430	16	2432
17	2434	18	2436
19	2438	20	2440
21	2442	22	2444
23	2446	24	2448
25	2450	26	2452
27	2454	28	2456
29	2458	30	2460
31	2462	32	2464
33	2466	34	2468
35	2470	36	2472
37	2474	38	2476
39	2478	40	2480

## 2.8. Test Equipment

### 2.8.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	June 17,17	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	101260	June 17,17	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	June 17,17	1 Year

### 2.8.2. For radiated emission test(9 kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI	100435	June 17,17	1 Year
Loop Antenna	ETS-LINDGREN	6502	00071730	June 08,17	1 Year
RF Cable	MIYAZAKI	5D-2W	966 Chamber No.1	June 17,17	1 Year

### 2.8.3. For radiated emissions test (30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June 17,17	1 Year
Spectrum Analyzer	Agilent	E4411B	MY50140697	June 17,17	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June 08,17	1 Year
Signal Amplifier	Agilent	310N	187037	June 17,17	1 Year
RF Cable	MIYAZAKI	5D-2W	966 Chamber No.1	June 17,17	1 Year

### 2.8.4. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA9120D1002	June 08,17	1 Year
Board-Band Horn Antenna	SCHWARZBECK	BBHA 9170	9170-497	June 08,17	1 Year
Signal Amplifier	SCHWARZBECK	BBV9718	9718-212	June 17,17	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June 17,17	1 Year
Spectrum Analyzer	Rohde &Schwarz	FSV	103173	June 17,17	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	June 17,17	1 Year

### 3 POWER LINE CONDUCTED EMISSION TEST

#### 3.1 Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

#### 3.2 Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

#### 3.3. Test Result


**PASS.** (All emissions not reported below are too low against the prescribed limits.)

## 3.4. Test data



Site no : 844 Shield Room Data no. : 117  
 Env. / Ins. : Temp:24.0'C Humi:53% Press:101.50kPa LINE Phase : NEUTRAL  
 Limit : FCC PART 15B QP  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 240V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : TX Mode


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.152	9.46	9.81	15.74	35.01	55.91	20.90	Average
2	0.152	9.46	9.81	29.46	48.73	65.91	17.18	QP
3	0.168	9.52	9.81	12.53	31.86	55.08	23.22	Average
4	0.168	9.52	9.81	27.80	47.13	65.08	17.95	QP
5	0.263	9.60	9.82	14.55	33.97	51.34	17.37	Average
6	0.263	9.60	9.82	24.49	43.91	61.34	17.43	QP
7	0.369	9.59	9.82	19.48	38.89	48.52	9.63	Average
8	0.369	9.59	9.82	28.49	47.90	58.52	10.62	QP
9	0.679	9.63	9.81	6.98	26.42	46.00	19.58	Average
10	0.679	9.63	9.81	16.73	36.17	56.00	19.83	QP
11	0.914	9.61	9.82	7.44	26.87	46.00	19.13	Average
12	0.914	9.61	9.82	16.10	35.53	56.00	20.47	QP



Site no : 844 Shield Room Data no. : 119  
 Env. / Ins. : Temp:24.0°C Humi:53% Press:101.50kPa LINE Phase : LINE  
 Limit : FCC PART 15B QP  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 240V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : TX Mode


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	9.61	9.81	14.13	33.55	56.00	22.45	Average
2	0.150	9.61	9.81	29.09	48.51	66.00	17.49	QP
3	0.280	9.61	9.83	12.50	31.94	50.81	18.87	Average
4	0.280	9.61	9.83	22.31	41.75	60.81	19.06	QP
5	0.365	9.61	9.82	16.80	36.23	48.61	12.38	Average
6	0.365	9.61	9.82	26.57	46.00	58.61	12.61	QP
7	0.679	9.59	9.81	8.42	27.82	46.00	18.18	Average
8	0.679	9.59	9.81	17.29	36.69	56.00	19.31	QP
9	1.310	9.63	9.82	6.36	25.81	46.00	20.19	Average
10	1.310	9.63	9.82	14.85	34.30	56.00	21.70	QP
11	10.019	9.66	9.88	8.80	28.34	50.00	21.66	Average
12	10.019	9.66	9.88	15.88	35.42	60.00	24.58	QP





Site no : 844 Shield Room Data no. : 121  
 Env. / Ins. : Temp:24.0'C Humi:53% Press:101.50kPa LINE Phase : LINE  
 Limit : FCC PART 15B QP  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.154	9.61	9.81	14.13	33.55	55.78	22.23	Average
2	0.154	9.61	9.81	28.77	48.19	65.78	17.59	QP
3	0.167	9.61	9.81	10.13	29.55	55.12	25.57	Average
4	0.167	9.61	9.81	26.33	45.75	65.12	19.37	QP
5	0.186	9.61	9.80	8.57	27.98	54.20	26.22	Average
6	0.186	9.61	9.80	23.98	43.39	64.20	20.81	QP
7	0.360	9.61	9.82	16.80	36.23	48.74	12.51	Average
8	0.360	9.61	9.82	24.89	44.32	58.74	14.42	QP
9	0.654	9.59	9.81	4.18	23.58	46.00	22.42	Average
10	0.654	9.59	9.81	14.87	34.27	56.00	21.73	QP
11	9.966	9.66	9.90	5.40	24.96	50.00	25.04	Average
12	9.966	9.66	9.90	12.72	32.28	60.00	27.72	QP



Site no : 844 Shield Room Data no. : 123  
 Env. / Ins. : Temp:24.0'C Humi:53% Press:101.50kPa LINE Phase : NEUTRAL  
 Limit : FCC PART 15B QP  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	9.46	9.81	15.13	34.40	56.00	21.60	Average
2	0.150	9.46	9.81	30.36	49.63	66.00	16.37	QP
3	0.175	9.54	9.80	9.97	29.31	54.72	25.41	Average
4	0.175	9.54	9.80	25.29	44.63	64.72	20.09	QP
5	0.360	9.59	9.82	18.45	37.86	48.74	10.88	Average
6	0.360	9.59	9.82	26.43	45.84	58.74	12.90	QP
7	0.406	9.59	9.82	9.23	28.64	47.73	19.09	Average
8	0.406	9.59	9.82	16.31	35.72	57.73	22.01	QP
9	0.464	9.59	9.81	2.85	22.25	46.63	24.38	Average
10	0.464	9.59	9.81	14.92	34.32	56.63	22.31	QP
11	0.595	9.61	9.82	3.37	22.80	46.00	23.20	Average
12	0.595	9.61	9.82	14.60	34.03	56.00	21.97	QP



## 4 RADIATED EMISSION TEST

### 4.1 Limit

#### 4.1.1 15.209 limits

Frequency (MHz)	Field Strength( $\mu\text{V/m}$ )	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

- Remark : (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$   
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.


#### 4.1.2 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )


All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

## 4.2. Block Diagram of Test setup


9kHz~30MHz



30~1000MHz



Above 1GHz



### 4.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 9kHz~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,

PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

### 4.4. Test Result

**PASS.**

All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2402MHz 、 2440MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


#### 4.5. Test Data

9 kHz – 30 MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

30-1000 MHz



Site no : 1# 966 Chamber Data no. : 55  
 Env. / Ins. : Temp:25.1';Humi:54.2%;Press:101.52kPaLINE Phase : VERTICAL  
 Limit : FCC PART 15 B(3M)  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : TX Mode  
 BLUETOOTH A+B+C

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.970	17.72	0.67	2.16	20.55	40.00	19.45	QP
2	53.280	6.11	0.91	9.60	16.62	40.00	23.38	QP
3	154.160	10.71	1.66	3.80	16.17	43.50	27.33	QP
4	364.650	14.65	2.63	0.63	17.91	46.00	28.09	QP
5	567.380	19.63	3.18	0.59	23.40	46.00	22.60	QP
6	725.490	21.85	3.75	0.86	26.46	46.00	19.54	QP



Site no : 1# 966 Chamber Data no. : 56  
 Env. / Ins. : Temp:25.1'; Humi:54.2%; Press:101.52kPa LINE Phase : HORIZONTAL  
 Limit : FCC PART 15 B(3M)  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : TX Mode  
           BLUETOOTH A+B+C

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.970	17.72	0.67	0.97	19.36	40.00	20.64	QP
2	120.210	11.16	1.41	1.77	14.34	43.50	29.16	QP
3	130.880	11.33	1.47	1.27	14.07	43.50	29.43	QP
4	320.030	13.57	2.40	6.44	22.41	46.00	23.59	QP
5	399.570	16.05	2.67	10.26	28.98	46.00	17.02	QP
6	562.530	19.68	3.26	0.62	23.56	46.00	22.44	QP



## 1000-18000MHz

Site no. : 1# 966 Chamber Data no. : 29  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2402MHz  
 BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	93.00	92.59	74.00	-18.59	Peak
2	4804.00	31.25	11.77	35.64	39.12	46.50	74.00	27.50	Peak
3	7206.00	36.52	11.54	33.95	33.34	47.45	74.00	26.55	Peak
4	8990.00	37.41	11.46	34.40	34.02	48.49	74.00	25.51	Peak
5	10724.00	39.22	11.30	34.14	31.45	47.83	74.00	26.17	Peak
6	13240.00	39.46	11.46	32.88	29.85	47.89	74.00	26.11	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 30  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2402MHz  
 BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	97.25	96.84	74.00	-22.84	Peak
2	4804.00	31.25	11.77	35.64	38.14	45.52	74.00	28.48	Peak
3	7206.00	36.52	11.54	33.95	33.17	47.28	74.00	26.72	Peak
4	8004.00	37.01	11.40	34.96	35.97	49.42	74.00	24.58	Peak
5	10146.00	38.36	11.51	34.58	32.96	48.25	74.00	25.75	Peak
6	14107.00	41.55	10.91	33.16	27.91	47.21	74.00	26.79	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 31  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2440MHz  
 BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	27.60	6.67	34.85	96.70	96.12	74.00	-22.12	Peak
2	4880.00	31.37	12.07	35.76	40.52	48.20	74.00	25.80	Peak
3	7320.00	36.55	11.57	34.14	34.22	48.20	74.00	25.80	Peak
4	7987.00	36.98	11.41	35.00	34.58	47.97	74.00	26.03	Peak
5	9925.00	38.14	11.61	34.97	33.54	48.32	74.00	25.68	Peak
6	13750.00	40.78	11.20	33.02	28.48	47.44	74.00	26.56	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 32  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2440MHz  
 BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	27.60	6.67	34.85	92.58	92.00	74.00	-18.00	Peak
2	4880.00	31.37	12.07	35.76	38.14	45.82	74.00	28.18	Peak
3	7320.00	36.55	11.57	34.14	35.57	49.55	74.00	24.45	Peak
4	7834.00	36.68	11.47	34.96	36.43	49.62	74.00	24.38	Peak
5	10316.00	38.65	11.41	34.51	31.55	47.10	74.00	26.90	Peak
6	14294.00	41.71	10.92	33.42	28.09	47.30	74.00	26.70	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 33  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2480MHz  
 BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	93.54	92.72	74.00	-18.72	Peak
2	4960.00	31.49	12.44	36.01	39.26	47.18	74.00	26.82	Peak
3	7440.00	36.54	11.61	34.22	34.86	48.79	74.00	25.21	Peak
4	8344.00	36.67	11.43	34.57	34.34	47.87	74.00	26.13	Peak
5	11285.00	39.33	11.08	33.32	30.49	47.58	74.00	26.42	Peak
6	13784.00	40.88	11.16	33.05	28.71	47.70	74.00	26.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 1# 966 Chamber Data no. : 34  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2480MHz  
 BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	96.87	96.05	74.00	-22.05	Peak
2	4960.00	31.49	12.44	36.01	39.36	47.28	74.00	26.72	Peak
3	7440.00	36.54	11.61	34.22	34.72	48.65	74.00	25.35	Peak
4	8684.00	37.32	11.45	33.66	33.87	48.98	74.00	25.02	Peak
5	11336.00	39.30	11.04	33.44	31.58	48.48	74.00	25.52	Peak
6	13784.00	40.88	11.16	33.05	27.23	46.22	74.00	27.78	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

**18000MHz – 25000MHz**

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

## 5 BAND EDGE COMPLIANCE TEST

### 5.1 Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits

### 5.2 Block Diagram of Test setup



### 5.3 Test Procedure

1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto.

AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto.

### 5.4 Test Result


Pass (The testing data was attached in the next pages.)

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2402MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.




## 5.5 Test Data



Site no. : 1# 966 Chamber                      Data no. : 35  
 Dis. / Ant. : 3m ANT 1-18G                      Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2402MHz  
               BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2323.98	27.73	6.54	34.60	43.77	43.44	74.00	30.56	Peak
2	2390.00	27.64	6.62	34.62	38.57	38.21	74.00	35.79	Peak
3	2400.00	27.61	6.62	34.64	52.89	52.48	74.00	21.52	Peak
4	2402.08	27.61	6.62	34.64	97.14	96.73	74.00	-22.73	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 36  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2402MHz  
               BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2345.10	27.70	6.56	34.57	39.42	39.11	74.00	34.89	Peak
2	2390.00	27.64	6.62	34.62	37.52	37.16	74.00	36.84	Peak
3	2400.00	27.61	6.62	34.64	50.47	50.06	74.00	23.94	Peak
4	2402.08	27.61	6.62	34.64	92.84	92.43	74.00	-18.43	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 1# 966 Chamber                      Data no. : 37  
 Dis. / Ant. : 3m ANT 1-18G                      Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2480MHz  
               BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.95	27.58	6.71	35.11	93.11	92.29	74.00	-18.29	Peak
2	2483.50	27.58	6.71	35.11	39.54	38.72	74.00	35.28	Peak
3	2499.55	27.57	6.73	35.24	40.20	39.26	74.00	34.74	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 1# 966 Chamber                      Data no. : 38  
 Dis. / Ant. : 3m ANT 1-18G                      Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa  
 Engineer : Viking  
 EUT : BLUETOOTH MIXER  
 Power : AC 120V/60Hz  
 M/N : BLACK&BLUE  
 Test Mode : GFSK TX 2480MHz  
               BLUETOOTH A+B+C

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2479.95	27.58	6.71	35.11	96.83	96.01	74.00	-22.01	Peak
2	2483.50	27.58	6.71	35.11	45.05	44.23	74.00	29.77	Peak
3	2496.00	27.57	6.73	35.24	44.96	44.02	74.00	29.98	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 6 6dB Bandwidth Test

### 6.1 Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

### 6.2 Test Procedure

- 1, The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
- 2, Follow the test procedure as described in KDB 558074
  - (1). Set resolution bandwidth (RBW) = 100 kHz.
  - (2). Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
  - (3). Detector = Peak.
  - (4). Trace mode = max hold.
  - (5). Sweep = auto couple.
  - (6). Allow the trace to stabilize.
  - (7). Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


### 6.3 Test Result

EUT: BLUETOOTH MIXER			
M/N: BLACK&BLUE			
Test date: 2017-06-26		Tested by: Viking	Test site: RF Site
Test Mode	CH	6dB bandwidth ( MHz )	Limit (KHz)
BLUETOOTH A			
BT 4.0-BLE GFSK	CH1	0.752	>500
	CH20	0.753	>500
	CH40	0.748	>500
BLUETOOTH B			
BT 4.0-BLE GFSK	CH1	0.746	>500
	CH20	0.761	>500
	CH40	0.753	>500
BLUETOOTH C			
BT 4.0-BLE GFSK	CH1	0.759	>500
	CH20	0.760	>500
	CH40	0.758	>500
Conclusion : PASS			


## 6.4 Test Data

## BLUETOOTH A


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz




Test Mode: BT 4.0-BLE GFSK 2480MHz




## BLUETOOTH B


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz




Test Mode: BT 4.0-BLE GFSK 2480MHz




## BLUETOOTH C

Test Mode: BT 4.0-BLE GFSK 2402MHz




Test Mode: BT 4.0-BLE GFSK 2440MHz





Test Mode: BT 4.0-BLE GFSK 2480MHz



## 7 OUTPUT POWER TEST

### 7.1 Limit

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

### 7.2 Test Procedure

- 1, The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
- 2, Follow the test procedure as described in KDB 558074
  - (1). Set the RBW  $\geq$  DTS bandwidth.
  - (2). Set VBW  $\geq$  3 x RBW.
  - (3). Set span  $\geq$  3 x RBW.
  - (4). Sweep time = auto couple.
  - (5). Detector = peak.
  - (6). Trace mode = max hold.
  - (7). Allow trace to fully stabilize.
  - (8). Use peak marker function to determine the peak amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.


## 7.3 Test Result

<b>EUT: BLUETOOTH MIXER</b>			
<b>M/N: BLACK&amp;BLUE</b>			
<b>Test date: 2017-06-26</b>		<b>Test site: RF Site</b>	<b>Tested by: Viking</b>
<b>Pass</b>			
<b>Test Mode</b>	<b>CH</b>	<b>Peak output Power ( dBm )</b>	<b>Limit (dBm)</b>
<b>BLUETOOTH A</b>			
<b>BT 4.0-BLE GFSK</b>	<b>CH1</b>	<b>-2.41</b>	<b>30</b>
	<b>CH20</b>	<b>-3.05</b>	<b>30</b>
	<b>CH40</b>	<b>-3.05</b>	<b>30</b>
<b>BLUETOOTH B</b>			
<b>BT 4.0-BLE GFSK</b>	<b>CH1</b>	<b>-2.74</b>	<b>30</b>
	<b>CH20</b>	<b>-3.14</b>	<b>30</b>
	<b>CH40</b>	<b>-2.95</b>	<b>30</b>
<b>BLUETOOTH C</b>			
<b>BT 4.0-BLE GFSK</b>	<b>CH1</b>	<b>-6.74</b>	<b>30</b>
	<b>CH20</b>	<b>-7.08</b>	<b>30</b>
	<b>CH40</b>	<b>-6.63</b>	<b>30</b>
<b>Conclusion : PASS</b>			


## 7.4 Test Data

## BLUETOOTH A


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz




Test Mode: BT 4.0-BLE GFSK 2480MHz






## BLUETOOTH B


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz




Test Mode: BT 4.0-BLE GFSK 2480MHz




## BLUETOOTH C


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



## 8 POWER SPECTRAL DENSITY TEST

### 8.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

### 8.2 Test Procedure

- 1, The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
- 2, Follow the test procedure as described in KDB 558074
  - (1). Set analyzer center frequency to DTS channel center frequency.
  - (2). Set the span to 1.5 times the DTS bandwidth.
  - (3). Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
  - (4). Set the VBW  $\geq 3 \text{ RBW}$ .
  - (5). Detector = peak.
  - (6). Sweep time = auto couple.
  - (7). Trace mode = max hold.
  - (8). Allow trace to fully stabilize.
  - (9). Use the peak marker function to determine the maximum amplitude level.
  - (10). If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 8.3 Test Result


EUT: BLUETOOTH MIXER			
M/N: BLACK&BLUE			
Test date: 2017-06-26		Test site: RF Site	Tested by: Viking
Pass			
Test Mode	CH	Power density (dBm/3kHz)	Limit (dBm/3kHz)
BLUETOOTH A			
BT 4.0-BLE GFSK	CH1	-16.27	8
	CH20	-16.97	8
	CH40	-17.33	8
BLUETOOTH B			
BT 4.0-BLE GFSK	CH1	-17.23	8
	CH20	-17.23	8
	CH40	-17.55	8
BLUETOOTH C			
BT 4.0-BLE GFSK	CH1	-20.89	8
	CH20	-21.51	8
	CH40	-21.22	8
Conclusion : PASS			




## 8.4 Test Data

## BLUETOOTH A


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz




Test Mode: BT 4.0-BLE GFSK 2480MHz




## BLUETOOTH B


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz




Test Mode: BT 4.0-BLE GFSK 2480MHz




## BLUETOOTH C

Test Mode: BT 4.0-BLE GFSK 2402MHz




Test Mode: BT 4.0-BLE GFSK 2440MHz





Test Mode: BT 4.0-BLE GFSK 2480MHz



## **9 ANTENNA REQUIREMENTS**

### **9.1 Limit**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **9.2 Result**

The antennas used for this product are external antenna (EUT uses RP-SMA antenna) and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 5 dBi.