

TEST REPORT



Applicant:	SHENZHEN QI SHENGLONG INDUSTRIALIST CO.,LTD
Address:	5F.,Blk 6A, Jing Nan Industry,Bai Ge long,Buji,Shenzhen,China

Manufacturer or Supplier	DONGGUAN FEIHAO INDUSTRIALIST CO.,LTD	
Address	No.8, Fengyi Road, Dakan Village, Huangjiang, DongGuan, China	
Product:	Bluetooth Digital Watch	
Brand Name:	N/A	
Model:	HB-216	
Additional Model & Model Difference:	See Section 3.1	
Date of tests:	Oct. 8 ~Oct. 18, 2012	

the tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C (Section 15.249)**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Grace Ren Project Engineer / EMC Department	Approved by Sam Tung Manager / EMC Department
	 Date: Oct. 19, 2012

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS	4
2 MEASUREMENT UNCERTAINTY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF EUT	5
3.2 DESCRIPTION OF TEST MODES	6
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4 DESCRIPTION OF SUPPORT UNITS	7
4. TEST TYPES AND RESULTS	8
4.1 CONDUCTED EMISSION MEASUREMENT	8
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	8
4.1.2 TEST INSTRUMENTS	8
4.1.3 TEST PROCEDURES.....	9
4.1.4 DEVIATION FROM TEST STANDARD.....	9
4.1.5 TEST SETUP	10
4.1.6 EUT OPERATING CONDITIONS	10
4.1.7 TEST RESULTS.....	11
4.2 RADIATED EMISSION MEASUREMENT	13
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	13
4.2.2 TEST INSTRUMENTS	14
4.2.3 TEST PROCEDURES.....	15
4.2.4 DEVIATION FROM TEST STANDARD.....	15
4.2.5 TEST SETUP.....	16
4.2.6 EUT OPERATING CONDITIONS	16
4.2.7 TEST RESULTS.....	17
4.3 20dB BANDWIDTH MEASUREMENT.....	25
4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT	25
4.3.2 TEST INSTRUMENTS	25
4.3.3 TEST PROCEDURE	26
4.3.4 DEVIATION FROM TEST STANDARD.....	26
4.3.5 TEST SETUP	27
4.3.6 EUT OPERATING CONDITIONS	27
4.3.7 TEST RESULTS.....	28
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	32
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	33



**BUREAU
VERITAS**

Test Report No.: FC120925N004

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FC120925N004	Original release	Oct. 19, 2012



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.249)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
§15.203	Antenna Requirement	PASS	Compliant
§15.207 (a)	Conducted Emission	PASS	Compliant
§15.205	Restricted Band of Operation	PASS	Compliant
§15.209 §15.249(a)	Radiated Emission	PASS	Compliant
§15.215(c)	20dB Bandwidth Test	PASS	Compliant

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44dB
Radiated emissions	30MHz ~ 200MHz	3.19dB
	200MHz ~1000MHz	3.21dB
	1GHz ~ 18GHz	2.26dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth Digital Watch
MODEL NO.	HB-216
FCC ID	Y56QSLHB216
NOMINAL VOLTAGE	DC 3.7V by battery or DC 5V by USB
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, $\pi/4$ DPSK
OPERATING FREQUENCY	2402MHz ~ 2480MHz
ANTENNA TYPE	Integral PCB Antenna; 0dBi gain
I/O PORTS	USB Charging Port
DATA CABLE SUPPLIED	N/A

NOTE:

- 1 Additional model **DP-558** is identical with the test model **HB-216** except the model name of the product for marketing purpose.
- 2 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 3 For the test results, the EUT had been tested with all conditions. But only the worst case was showed in test report.



3.2 DESCRIPTION OF TEST MODES

The EUT was tested under following modes. And the final worst mode were marked in boldface and recorded in this report.

Condition	Configuration
1	Device powered by battery
2	Device powered by USB charging cable

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case was found when positioned on Y axis for radiated emission.

Following channel(s) was (were) selected for the test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE	PACKET TYPE
Low, Middle, High	FHSS	GFSK	1M	DH1/3/5
Low, Middle, High	FHSS	$\pi/4$ DPSK	2M	DH1/3/5
Low, Middle, High	FHSS	8DPSK	3M	DH1/3/5

CHANNEL NUMBER	TESTED CHANNEL	TESTED FREQUENCY
0	Low	2402 MHz
39	Mid.	2441 MHz
78	High	2480 MHz

After estimating all the combination of every test mode, the result shown as below is the worst case

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE	PACKET TYPE
Low, Middle, High	FHSS	GFSK	1M	DH5

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.249)

ANSI C63.4-2003

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Verification). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

◆ FOR CONDUCTED EMISSION MEASUREMENT

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	5P2PM2X	12400120329	N/A

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line :Unshielded, Detachable 1.5m;DC Line: Unshielded, Undetachable 1.8m



4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
EMI Test Receiver Rohde&Schwarz	ESU 26	100005	May 15,12	May 14,13
Artificial Mains Network Rohde&Schwarz	ENV216	101173	May 15,12	May 14,13
Artificial Mains Network Rohde&Schwarz	ESH2-Z5	100071	May 15,12	May 14,13
Test software	ADT_Cond_V7.3.7	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA

2. The test was performed in Dongguan Shielded Room 553.

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.




4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18122	10.54	42.31	25.74	52.85	36.28	64.43	54.43	-11.58	-18.15
2	0.24775	10.43	34.2	18.52	44.63	28.95	61.83	51.83	-17.2	-22.88
3	0.31031	10.39	27.64	13.37	38.03	23.76	59.96	49.96	-21.93	-26.2
4	3.17634	9.95	23.62	16.37	33.57	26.32	56	46	-22.43	-19.68
5	20.77134	10.33	30.09	22.3	40.42	32.63	60	50	-19.58	-17.37
6	25.06452	10.53	28.95	21.05	39.48	31.58	60	50	-20.52	-18.42


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.1576	10.7	30.88	11.38	41.58	22.08	65.59	55.59	-24.01	-33.51
2	0.18122	10.51	41.63	24.83	52.14	35.34	64.43	54.43	-12.29	-19.09
3	0.24025	10.37	34.66	17.31	45.03	27.68	62.09	52.09	-17.05	-24.4
4	3.15251	9.63	23.52	16.09	33.15	25.72	56	46	-22.85	-20.28
5	20.482	10.22	29.37	21.93	39.59	32.15	60	50	-20.41	-17.85
6	23.38713	10.42	28.59	21.53	39.01	31.95	60	50	-20.99	-18.05

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

**4.2.2 TEST INSTRUMENTS**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer ROHDE & SCHWARZ	E4446A	MY46180622	May 02, 12	May 01, 13
Test Receiver ROHDE & SCHWARZ	ESVD	847398/003	May 15,12	May 14,13
Bilog Antenna TESEQ	CBL 6111D	27089	July 16,12	July 15,13
Horn Antenna EMCO	3117	00085519	Nov.07,11	Nov.07,12
10m Semi-anechoic Chamber ETS-LINDGREN	21.4m*12.1m*8.8m	NSEMC006	Mar 24,12	Mar 23,13
RF Cable IMRO	IMRO-400	10m Cable 1#10m	May 16,12	May 15,13
RF Cable IMRO	IMRO-400	10m Cable 2#3m	May 16,12	May 15,13
Signal Amplifier SONOMA	310N	186955	Mar. 14,12	Mar. 13,13
Signal Amplifier HP	8449B	3008A00409	May 31,12	May 30,13
RF Cable DRAKA	M06/25-RG102	10m Cable 2#	May 16,12	May 15,13
Test software ADT	ADT_Radiated_V7. 6.15	N/A	N/A	N/A

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.
 2. The test was performed in Dongguan Chamber 10m.
 3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.2.7 TEST RESULTS


BELOW 1GHz WORST-CASE DATA: GFSK DH5

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	DC 5V from PC	DETECTOR FUNCTION	Quasi-Peak

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	60.62	8.03	13.53	21.56	40	-18.44	100	113
2	88.11	9.46	15.96	25.42	43.5	-18.08	100	6
3	144.71	12.58	13.06	25.64	43.5	-17.86	100	22
4	199.69	10.4	14.36	24.76	43.5	-18.74	100	64
5	287	14.82	17.85	32.67	46	-13.33	100	37
6	408.28	18.2	4.72	22.92	46	-23.08	100	140

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	47.69	10.83	27.1	37.93	40	-2.07	100	0
2	88.11	9.46	17.72	27.18	43.5	-16.32	100	316
3	181.9	10.32	15.63	25.95	43.5	-17.55	100	0
4	287	14.82	6.52	21.34	46	-24.66	100	358
5	333.9	15.85	6.38	22.23	46	-23.77	100	0
6	432.53	18.75	2.53	21.28	46	-24.72	100	272

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





BUREAU
VERITAS

Test Report No.: FC120925N004

ABOVE 1GHz DATA: GFSK DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.8 PK	74.0	-27.2	1.05 H	158	10.39	36.41
2	2390.00	16.7 AV	54.0	-37.3	1.05 H	158	-19.71	36.41
3	*2402.00	75.1 PK	114.0	-38.9	2.00 H	55	38.58	36.52
4	*2402.00	45.0 AV	94.0	-49.0	2.00 H	55	8.48	36.52
5	4804.00	65.3 PK	74.0	-8.7	2.00 H	45	16.05	49.25
6	4804.00	35.2 AV	54.0	-18.8	2.00 H	45	-14.05	49.25
7	7206.00	57.7 PK	74.0	-16.3	1.90 H	210	11.18	46.52
8	7206.00	27.6 AV	54.0	-26.4	1.90 H	210	-18.92	46.52
9	9608.00	55.8 PK	74.0	-18.2	2.00 H	150	10.90	44.90
10	9608.00	25.7 AV	54.0	-28.3	2.00 H	150	-19.20	44.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.9 PK	74.0	-27.1	1.10 V	85	10.49	36.41
2	2390.00	16.8 AV	54.0	-37.2	1.10 V	85	-19.61	36.41
3	*2402.00	77.4 PK	114.0	-36.6	1.05 V	270	40.88	36.52
4	*2402.00	47.3 AV	94.0	-46.7	1.05 V	270	10.78	36.52
5	4804.00	68.9 PK	74.0	-5.1	1.00 V	245	19.65	49.25
6	4804.00	38.8 AV	54.0	-15.2	1.00 V	245	-10.45	49.25
7	7206.00	57.1 PK	74.0	-16.9	1.00 V	170	10.58	46.52
8	7206.00	27.0 AV	54.0	-27.0	1.00 V	170	-19.52	46.52
9	9608.00	56.0 PK	74.0	-18.0	1.05 V	70	11.10	44.90
10	9608.00	25.9 AV	54.0	-28.1	1.05 V	70	-19.00	44.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1\text{dB}$.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	79.1 PK	114.0	-34.9	1.36 H	110	42.23	36.87
2	*2441.00	49.0 AV	94.0	-45.0	1.36 H	110	12.13	36.87
3	4882.00	66.0 PK	74.0	-8.0	2.00 H	190	16.77	49.23
4	4882.00	35.9 AV	54.0	-18.1	2.00 H	190	-13.33	49.23
5	7323.00	56.5 PK	74.0	-17.5	1.90 H	180	9.89	46.61
6	7323.00	26.4 AV	54.0	-27.6	1.90 H	180	-20.21	46.61
7	9764.00	56.5 PK	74.0	-17.5	2.00 H	136	11.69	44.81
8	9764.00	26.4 AV	54.0	-27.6	2.00 H	136	-18.41	44.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	77.3 PK	114.0	-36.7	1.00 V	210	40.43	36.87
2	*2441.00	47.2 AV	94.0	-46.8	1.00 V	210	10.33	36.87
3	4882.00	69.3 PK	74.0	-4.7	1.00 V	324	20.07	49.23
4	4882.00	39.2 AV	54.0	-14.8	1.00 V	324	-10.03	49.23
5	7323.00	57.2 PK	74.0	-16.8	1.03 V	170	10.59	46.61
6	7323.00	27.1 AV	54.0	-26.9	1.03 V	170	-19.51	46.61
7	9764.00	56.2 PK	74.0	-17.8	1.05 V	145	11.39	44.81
8	9764.00	26.1 AV	54.0	-27.9	1.05 V	145	-18.71	44.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + 20log(duty cycle).



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	77.1 PK	114.0	-36.9	1.00 H	185	39.89	37.21
2	*2480.00	47.0 AV	94.0	-47.0	1.00 H	185	9.79	37.21
3	2483.50	48.2 PK	74.0	-25.8	1.14 H	158	10.96	37.24
4	2483.50	18.1 AV	54.0	-35.9	1.14 H	158	-19.14	37.24
5	4960.00	61.9 PK	74.0	-12.1	1.00 H	50	12.69	49.21
6	4960.00	31.8 AV	54.0	-22.2	1.00 H	50	-17.41	49.21
7	7440.00	57.8 PK	74.0	-16.2	1.05 H	126	11.10	46.70
8	7440.00	27.7 AV	54.0	-26.3	1.05 H	126	-19.00	46.70
9	9920.00	57.6 PK	74.0	-16.4	1.00 H	314	12.89	44.71
10	9920.00	27.5 AV	54.0	-26.5	1.00 H	314	-17.21	44.71
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	78.5 PK	114.0	-35.5	1.14 V	140	41.29	37.21
2	*2480.00	48.4 AV	94.0	-45.6	1.14 V	140	11.19	37.21
3	2483.50	48.9 PK	74.0	-25.1	1.05 V	178	11.66	37.24
4	2483.50	18.8 AV	54.0	-35.2	1.05 V	178	-18.44	37.24
5	4960.00	67.8 PK	74.0	-6.2	1.10 V	320	18.59	49.21
6	4960.00	37.7 AV	54.0	-16.3	1.10 V	320	-11.51	49.21
7	7440.00	58.0 PK	74.0	-16.0	1.05 V	196	11.30	46.70
8	7440.00	27.9 AV	54.0	-26.1	1.05 V	196	-18.80	46.70
9	9920.00	56.4 PK	74.0	-17.6	1.05 V	332	11.69	44.71
10	9920.00	26.3 AV	54.0	-27.7	1.05 V	332	-18.41	44.71

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



BT_8DPSK DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	47.4 PK	74.0	-26.6	2.00 H	275	10.99	36.41
2	2390.00	17.3 AV	54.0	-36.7	2.00 H	275	-19.11	36.41
3	*2402.00	76.2 PK	114.0	-37.8	2.00 H	55	39.68	36.52
4	*2402.00	46.1 AV	94.0	-47.9	2.00 H	55	9.58	36.52
5	4804.00	61.7 PK	74.0	-12.3	1.06 H	277	12.45	49.25
6	4804.00	31.6 AV	54.0	-22.4	1.06 H	277	-17.65	49.25
7	7206.00	58.4 PK	74.0	-15.6	1.35 H	242	11.88	46.52
8	7206.00	28.3 AV	54.0	-25.7	1.35 H	242	-18.22	46.52
9	9608.00	56.6 PK	74.0	-17.4	1.20 H	48	11.70	44.90
10	9608.00	26.5 AV	54.0	-27.5	1.20 H	48	-18.40	44.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	47.2 PK	74.0	-26.8	1.06 V	175	10.79	36.41
2	2390.00	17.1 AV	54.0	-36.9	1.06 V	175	-19.31	36.41
3	*2402.00	76.0 PK	114.0	-38.0	1.40 V	155	39.48	36.52
4	*2402.00	45.9 AV	94.0	-48.1	1.40 V	155	9.38	36.52
5	4804.00	66.3 PK	74.0	-7.7	1.35 V	246	17.05	49.25
6	4804.00	36.2 AV	54.0	-17.8	1.35 V	246	-13.05	49.25
7	7206.00	58.5 PK	74.0	-15.5	1.20 V	176	11.98	46.52
8	7206.00	28.4 AV	54.0	-25.6	1.20 V	176	-18.12	46.52
9	9608.00	56.8 PK	74.0	-17.2	1.40 V	54	11.90	44.90
10	9608.00	26.7 AV	54.0	-27.3	1.40 V	54	-18.20	44.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



BUREAU
VERITAS

Test Report No.: FC120925N004

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	78.8 PK	114.0	-35.2	1.25 H	190	41.93	36.87
2	*2441.00	48.7 AV	94.0	-45.3	1.25 H	190	11.83	36.87
3	4882.00	61.6 PK	74.0	-12.4	1.20 H	225	12.37	49.23
4	4882.00	31.5 AV	54.0	-22.5	1.20 H	225	-17.73	49.23
5	7323.00	57.3 PK	74.0	-16.7	1.35 H	142	10.69	46.61
6	7323.00	27.2 AV	54.0	-26.8	1.35 H	142	-19.41	46.61
7	9764.00	56.6 PK	74.0	-17.4	1.10 H	75	11.79	44.81
8	9764.00	26.5 AV	54.0	-27.5	1.10 H	75	-18.31	44.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	78.9 PK	114.0	-35.1	1.03 V	245	42.03	36.87
2	*2441.00	48.8 AV	94.0	-45.2	1.03 V	245	11.93	36.87
3	4882.00	68.5 PK	74.0	-5.5	1.03 V	252	19.27	49.23
4	4882.00	38.4 AV	54.0	-15.6	1.03 V	252	-10.83	49.23
5	7323.00	57.8 PK	74.0	-16.2	1.00 V	243	11.19	46.61
6	7323.00	27.7 AV	54.0	-26.4	1.00 V	243	-18.91	46.61
7	9764.00	56.7 PK	74.0	-17.3	1.00 V	52	11.89	44.81
8	9764.00	26.6 AV	54.0	-27.4	1.00 V	52	-18.21	44.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	76.8 PK	114.0	-37.2	1.00 H	140	39.59	37.21
2	*2480.00	46.7 AV	94.0	-47.3	1.00 H	140	9.49	37.21
3	2483.50	47.8 PK	74.0	-26.2	1.00 H	122	10.56	37.24
4	2483.50	17.7 AV	54.0	-36.3	1.00 H	122	-19.54	37.24
5	4960.00	61.3 PK	74.0	-12.7	1.00 H	65	12.09	49.21
6	4960.00	31.2 AV	54.0	-22.8	1.00 H	65	-18.01	49.21
7	7440.00	57.6 PK	74.0	-16.4	1.05 H	137	10.90	46.70
8	7440.00	27.5 AV	54.0	-26.5	1.05 H	137	-19.20	46.70
9	9920.00	57.9 PK	74.0	-16.1	1.10 H	310	13.19	44.71
10	9920.00	27.8 AV	54.0	-26.2	1.10 H	310	-16.91	44.71
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	78.2 PK	114.0	-35.8	1.05 V	240	40.99	37.21
2	*2480.00	48.1 AV	94.0	-45.9	1.05 V	240	10.89	37.21
3	2483.50	47.3 PK	74.0	-26.7	1.00 V	190	10.06	37.24
4	2483.50	17.2 AV	54.0	-36.8	1.00 V	190	-20.04	37.24
5	4960.00	68.6 PK	74.0	-5.4	1.04 V	250	19.39	49.21
6	4960.00	38.5 AV	54.0	-15.5	1.04 V	250	-10.71	49.21
7	7440.00	58.9 PK	74.0	-15.1	1.00 V	230	12.20	46.70
8	7440.00	28.8 AV	54.0	-25.2	1.00 V	230	-17.90	46.70
9	9920.00	56.8 PK	74.0	-17.2	1.00 V	85	12.09	44.71
10	9920.00	26.7 AV	54.0	-27.3	1.00 V	85	-18.01	44.71

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



4.3 20dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer ROHDE & SCHWARZ	E4446A	MY46180622	May 02, 12	May 01, 13
Horn Antenna EMCO	3117	00085519	Nov.07,11	Nov.07,12
10m Semi-anechoic Chamber ETS-LINDGREN	21.4m*12.1m*8.8m	NSEMC006	Mar 24,12	Mar 23,13
RF Cable IMRO	IMRO-400	10m Cable 2#3m	May 16,12	May 15,13
Signal Amplifier EMCI	EMC 012645	980077	Nov 07,11	Nov 07,12
RF Cable DRAKA	M06/25-RG102	10m Cable 2#	May 16,12	May 15,13
Test software ADT	ADT_Radiated_V7. 6.15	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA

2. The test was performed in Dongguan Chamber 10m.

4.3.3 TEST PROCEDURE


The EUT was placed on a turn table which was 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on a antenna tower. At the frequency band of 30MHz to 1GHz, The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 to 4 m for horizontal and vertical polarizations.

The spectrum analyzer was receiving the maximum emission level. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.7 TEST RESULTS

GFSK DH5

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2402	0.94
Middle	2441	0.94
High	2480	0.94

Test Data: Low channel







BUREAU
VERITAS

Test Report No.: FC120925N004

Test Data: Middle channel



Test Data: High channel



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: DGservice@cn.bureauveritas.com

8DPSK DH5

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2402	1.26
Middle	2441	1.26
High	2480	1.25

Test Data: Low channel







BUREAU
VERITAS

Test Report No.: FC120925N004

Test Data: Middle channel



Test Data: High channel



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: DGservice@cn.bureauveritas.com



Test Report No.: FC120925N004

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



**BUREAU
VERITAS**

Test Report No.: FC120925N004

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---