

FCC PART 15.247
EMI MEASUREMENT AND TEST REPORT
For

Fuzhou Smart Digital Science & Technology Co., Ltd.
No.8 Building, Hongshan Science & Technology Zone, Gulou District, Fuzhou, Fujian, China

FCC ID: Y5VMW0812

May 9, 2011

This Report Concerns: Original Report	Equipment Type: AOC TABLET
Test Engineer: Jack Liu	
Report No.: BST11050058Y-1ER-3	
Receive EUT Date/Test Date: April 29, 2011/ May 4-7, 2011	
Reviewed By:	Christina 
Prepared By:	<div style="display: flex; align-items: center;"><div>Shenzhen BST Technology Co.,Ltd. 3F, Weames Technology Building, No. 10 Kefa Road, Science Park, Nanshan District, Shenzhen, Guangdong, China Tel: 0755-26747751 ~ 3 Fax: 0755-26747751 ~ 3 ext.826</div></div>

Note: The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of Shenzhen BST Technology Co.,Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	4
1.1.	Report information	4
1.2.	Measurement Uncertainty	4
2.	PRODUCT DESCRIPTION	5
2.1.	EUT Description	5
2.2.	Block Diagram of EUT Configuration.....	5
2.3.	Support Equipment List	5
2.4.	Test Conditions	6
3.	FCC ID LABEL.....	6
4.	TEST RESULTS SUMMARY	7
	Modifications	7
5.	TEST EQUIPMENT USED	8
6.	§15.247 (I) AND §1.1307 (B) (1), §2.1093 – RF EXPOSURE	9
6.1.	Standard Applicable.....	9
6.2.	Test Result	9
7.	§15.203 - ANTENNA REQUIREMENT	10
7.1.	Standard Applicable.....	10
7.2.	Antenna Connector Construction.....	10
8.	§15.207 - CONDUCTED EMISSIONS.....	11
8.1.	Applicable Standard.....	11
8.2.	Test Procedure	11
8.3.	Conducted Power line Emission Limits.....	11
8.4.	Block Diagram of Test Setup.....	11
8.5.	Conducted Power Line Test Result.....	12
9.	§15.209, §15.205, §15.247(D) - SPURIOUS EMISSIONS	14
9.1.	Test Equipment	14
9.2.	Test Procedure	14
9.3.	Radiated Test Setup	14
9.4.	Radiated Emission Limit.....	14
9.5.	Radiated Emission Test Result	15
10.	§15.247(A) (2) – 6DB BANDWIDTH TESTING.....	24
10.1.	Test Equipment	24
10.2.	Test Procedure	24
10.3.	Applicable Standard.....	24
10.4.	Test Result:Pass.	24
11.	§15.247(B) (3) - MAXIMUM PEAK OUTPUT POWER	28
11.1.	Test Equipment	28
11.2.	Test Procedure	28
11.3.	Applicable Standard.....	28
11.4.	Test Result	29

12. §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE30

12.1. Test Equipment30

12.2. Test Procedure30

12.3. Applicable Standard.....30

12.4. Test Result30

13. §15.247(E) - POWER SPECTRAL DENSITY35

13.1. Test Equipment35

13.2. Test Procedure35

13.3. Applicable Standard.....35

13.4. Test Result35

1. GENERAL INFORMATION

1.1. Report information

1.1.1.This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BST approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BST in any way guarantees the later performance of the product/equipment.

1.1.2.The sample/s mentioned in this report is/are supplied by Applicant, BST therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BST, unless the applicant has authorized BST in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of emitel (Shenzhen) Limited

(FCC Registered Test Site Number: 746887) on

Building 2, 171 Meihua Road, Futian District, Shenzhen, 518049 China

The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

Available upon request.

2. PRODUCT DESCRIPTION

2.1. EUT Description

Applicant : Fuzhou Smart Digital Science & Technology Co., Ltd.
 Address : No.8 Building, Hongshan Science & Technology Zone, Gulou District, Fuzhou, Fujian, China
 Manufacturer : Fuzhou Smart Digital Science & Technology Co., Ltd.
 Address : No.8 Building, Hongshan Science & Technology Zone, Gulou District, Fuzhou, Fujian, China
 EUT Description : AOC TABLET
 Trade Name : AOC
 Modulation : 802.11b: DSSS
 802.11g: OFDM
 Model Number : MW0812
 Power Supply : DC 5V (Powered by Adapter) or DC 3.7V (Li-ion battery)
 Antenna connected : Unique Antenna
 Antenna gain : 0dBi(2.4GHz)

2.2. Block Diagram of EUT Configuration




Figure 1 EUT SETUP

2.3. Support Equipment List

Table 2 Ancillary Equipment

Name	Model No	S/N	Manufacturer	Used “ ”
Adapter Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 5V, 2.5A	DSA-15P-05	--	DVE	

2.4. Test Conditions

Temperature: 23~25

Relative Humidity: 50~63 %

3. FCC ID LABEL

FCC ID: Y5VMW0812

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference, and**
- 2. This device must accept any interference received, including interference that may cause undesired operation.**

Label Location on EUT

EUT Bottom View/ FCC ID Label Location



4. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.247

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247 (i) , §1.1307 (b) (1), §2.1093	RF Exposure	PASS
§15.203	Antenna Requirement	PASS
§15.207 (a)	Conducted Emissions	PASS
§15.247(d)	Spurious Emissions at Antenna Port	PASS
§15.205	Restricted Bands	PASS
§15.209, §15.205, §15.247(d)	Spurious Emissions	PASS
§15.247 (a)(2)	6 dB Bandwidth	PASS
§15.247(b)(3)	Maximum Peak Output Power	PASS
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	PASS
§15.247(e)	Power Spectral Density	PASS

Modifications

No modification was made.

5. TEST EQUIPMENT USED

Equipment/Facilities	Manufacturer	Model #	Serial no.	Date of Cal.	Cal. Interval
Cable	Resenberger	N/A	NO.1	Mar 10 , 2011	1 Year
Cable	SCHWARZBECK	N/A	NO.2	Mar 10 , 2011	1 Year
Cable	SCHWARZBECK	N/A	NO.3	Mar 10 , 2011	1 Year
LISN	Rohde & Schwarz	ESH3-Z5	100305	Mar 10 , 2011	1 Year
50 Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Mar 10 , 2011	1 Year
EMI Test Receiver	Rohde & Schwarz	ESP13	100180	Oct.11,2010	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSP40	100273	Sep.10,2010	1 Year
3m Semi-Anechoic Chamber	Albatross Projects	9mx6mx6m	N/A	Feb.20,2011	1 Year
Signal Generator	FLUKE	PM5418 + Y/C	LO747012	Feb.20,2011	1 Year
Signal Generator	FLUKE	PM5418TX	LO738007	Feb.20,2011	1 Year
Loop Antenna	SCHWARZBECK	FMZB1516	113	Jan.30,2011	1 Year
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	9161-4079	Sep.22,2010	1 Year
Broad-Band Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-564	Sep.22,2010	1 Year
Ultra Broadband Antenna	Rohde & Schwarz	HL-562	100110	June.15,2010	1 Year
AMN	Rohde & Schwarz	ESH3-Z5	100196	Oct.11,2010	1 Year
AMN	Rohde & Schwarz	ESH3-Z5	100197	Oct.11,2010	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
Power Meter	Rohde & Schwarz	NRVD	100041	Feb.20,2011	1 Year
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	Feb.20,2011	1 Year
Coaxial Cable with N-connectors	SCHWARZBECK	AK9515H	95549	Sep.22,2010	1 Year
Radio Communication Test Set	Rohde & Schwarz	CMS 54	846621/024	Feb.20,2011	1 Year
Modulation Analyzer	Hewlett-Packard	8901B	2303A00362	Feb.20,2011	1 Year
Absorbing clamp	Rohde & Schwarz	MDS-21	N/A	Oct.11,2010	1 Year

6. §15.247 (I) AND §1.1307 (B) (1), §2.1093 – RF EXPOSURE

6.1. Standard Applicable

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

According to FCC Exclusion list, In the following table, f_{GHz} is mid-band frequency in GHz, and d is the distance to a person's body, excluding hands, wrists, feet, and ankles.

Exposure category	<u>low threshold</u>	<u>high threshold</u>
general population	$(60/f_{\text{GHz}}) \text{ mW}, d < 2.5 \text{ cm}$ $(120/f_{\text{GHz}}) \text{ mW}, d \geq 2.5 \text{ cm}$	$(900/f_{\text{GHz}}) \text{ mW}, d < 20 \text{ cm}$
occupational	$(375/f_{\text{GHz}}) \text{ mW}, d < 2.5 \text{ cm}$ $(900/f_{\text{GHz}}) \text{ mW}, d \geq 2.5 \text{ cm}$	$(2250/f_{\text{GHz}}) \text{ mW}, d < 20 \text{ cm}$

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

6.2. Test Result

Measurement Result:

The Max peak output power is $19.7\text{mW} < 24.9\text{mW}$.

The SAR measurement is not required.

7. §15.203 - ANTENNA REQUIREMENT

7.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.2. Antenna Connector Construction

The antenna used in this product is a unique antenna. The antenna is permanently attached. Refer to the product photo.

8. §15.207 - CONDUCTED EMISSIONS

8.1. Applicable Standard

The specification used was with the FCC Part 15.207 limits.

8.2. Test Procedure


During the conducted emission test, the EUT was connected to the outlet of the LISN. Maximizing procedure was performed on the six (6) highest emissions of the EUT. All data was recorded in the Quasi-peak and average detection mode.

8.3. Conducted Power line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHz)	Class A QP/AV	Class B QP/AV
0.15-0.5	79/66	65-56/56-46
0.5-5.0	73/60	56-46
5.0-3.0	73/60	60-50

Note: In the above table, the tighter limit applies at the band edges.


8.4. Block Diagram of Test Setup



8.5. Conducted Power Line Test Result

Pass.

The worst test mode: Wi-Fi TX 2437MHz



Condition:


: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	Line	Limit		
			dBuV	dB		
1	0.22	15.28	52.88	-37.60	Average	LINE
2	0.30	15.91	50.24	-34.33	Average	LINE
3	0.92	8.78	46.00	-37.22	Average	LINE
4	1.97	9.11	46.00	-36.89	Average	LINE
5 Max	5.39	14.47	50.00	-35.53	Average	LINE

Condition:

: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	Line	Limit		
			dBuV	dB		
1	0.22	26.48	62.83	-36.35	Peak	LINE
2	0.30	29.06	60.24	-31.18	Peak	LINE
3	0.71	26.18	56.00	-29.82	Peak	LINE
4	3.16	24.95	56.00	-31.05	Peak	LINE
5 Max	4.80	29.00	56.00	-27.00	Peak	LINE



Condition:

: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over		Pol/Phase
	MHz	dBuV	Line	Limit	Remark	
1	0.22	13.15	52.88	-39.73	Average	NEUTRAL
2	0.38	11.34	48.25	-36.91	Average	NEUTRAL
3 Max	0.38	11.34	48.25	-36.91	Average	NEUTRAL
4	0.75	9.54	46.00	-36.46	Average	NEUTRAL
5	1.88	8.31	46.00	-37.69	Average	NEUTRAL
6	5.56	13.45	50.00	-36.55	Average	NEUTRAL

Condition:

: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over		Pol/Phase
	MHz	dBuV	Line	Limit	Remark	
1	0.31	28.04	59.93	-31.89	Peak	NEUTRAL
2	0.58	25.12	56.00	-30.88	Peak	NEUTRAL
3 Max	0.92	25.61	56.00	-30.39	Peak	NEUTRAL
4	1.66	24.45	56.00	-31.55	Peak	NEUTRAL
5	5.56	28.64	60.00	-31.36	Peak	NEUTRAL

9. §15.209, §15.205, §15.247(D) - Spurious Emissions


9.1. Test Equipment

Please refer to section 2 this report.

9.2. Test Procedure

The out of band emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part Subpart C limits. The EUT was tested in 3 orthogonal planes.

9.3. Radiated Test Setup



For the accrual test configuration, please refer to the related items-photos of Testing.

9.4. Radiated Emission Limit

CARRIER FREQUENCY WILL NOT EXCEEDS 48.0 dBuV/m AT 3M. OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

Frequency (MHz)	Distance (m)	Field Strength (dBuV/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
ABOVE 960	3	54.0

9.5. Radiated Emission Test Result**Pass.**

Date of Test:	May 4, 2011	Temperature:	25°C
EUT:	AOC TABLET	Humidity:	52%
Model No.:	MW0812	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Low 2412MHz	Test Engineer:	Jack

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2400.000	37.59	43.58	-7.46	30.13	36.12	54	74	-23.87	-37.88	Vertical
2412.020	106.42	112.43	-7.43	98.99	105.00	-	-	-	-	Vertical
4824.036	50.21	56.22	-0.19	50.02	56.03	54	74	-3.98	-17.97	Vertical
7236.052	41.97	47.96	3.05	45.02	51.01	54	74	-8.98	-22.99	Vertical
2400.000	37.52	43.48	-7.46	30.06	36.02	54	74	-23.94	-37.98	Horizontal
2412.020	105.59	111.56	-7.43	98.16	104.13	-	-	-	-	Horizontal
4824.036	49.22	55.22	-0.19	49.03	55.03	54	74	-4.97	-18.97	Horizontal
7236.052	41.13	47.15	3.05	44.18	50.20	54	74	-9.82	-23.80	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

Date of Test:	May 4, 2011	Temperature:	25°C
EUT:	AOC TABLET	Humidity:	52%
Model No.:	MW0812	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Middle 2437MHz	Test Engineer:	Jack

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2437.018	106.08	112.10	-7.36	98.72	104.74	-	-	-	-	Vertical
4874.032	50.41	56.45	0.09	50.50	56.54	54	74	-3.50	-17.46	Vertical
7311.048	41.56	47.56	3.22	44.78	50.78	54	74	-9.22	-23.22	Vertical
2437.018	105.51	111.55	-7.36	98.15	104.19	-	-	-	-	Horizontal
4874.032	49.16	55.20	0.09	49.25	55.29	54	74	-4.75	-18.71	Horizontal
7311.048	40.78	46.82	3.22	44.00	50.04	54	74	-10.00	-23.96	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

Date of Test:	May 4, 2011	Temperature:	25°C
EUT:	AOC TABLET	Humidity:	52%
Model No.:	MW0812	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel High 2462MHz	Test Engineer:	Jack

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2462.020	105.77	111.79	-7.35	98.42	104.44	-	-	-	-	Vertical
2483.500	38.21	44.22	-7.37	30.84	36.85	54	74	-23.16	-37.15	Vertical
4924.038	49.75	55.79	0.34	50.09	56.13	54	74	-3.91	-17.87	Vertical
7386.054	41.51	47.55	3.39	44.90	50.94	54	74	-9.10	-23.06	Vertical
2462.020	105.44	111.45	-7.35	98.09	104.10	-	-	-	-	Horizontal
2483.500	38.54	44.55	-7.37	31.17	37.18	54	74	-22.83	-36.82	Horizontal
4924.038	48.93	54.96	0.34	49.27	55.30	54	74	-4.73	-18.70	Horizontal
7386.054	39.39	45.37	3.39	42.78	48.76	54	74	-11.22	-25.24	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

Date of Test:	May 4, 2011	Temperature:	25°C
EUT:	AOC TABLET	Humidity:	52%
Model No.:	MW0812	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Low 2412MHz	Test Engineer:	Jack

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2400.000	38.92	44.95	-7.46	31.46	37.49	54	74	-22.54	-36.51	Vertical
2412.016	105.11	111.16	-7.43	97.68	103.73	-	-	-	-	Vertical
4824.028	50.69	56.74	-0.19	50.50	56.55	54	74	-3.50	-17.45	Vertical
2400.000	37.72	43.71	-7.46	30.26	36.25	54	74	-23.74	-37.75	Horizontal
2412.016	104.82	110.86	-7.43	97.39	103.43	-	-	-	-	Horizontal
4824.028	49.36	55.40	-0.19	49.17	55.21	54	74	-4.83	-18.79	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

Date of Test:	May 4, 2011	Temperature:	25°C
EUT:	AOC TABLET	Humidity:	52%
Model No.:	MW0812	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Middle 2437MHz	Test Engineer:	Jack

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2437.018	105.04	111.07	-7.36	97.68	103.71	-	-	-	-	Vertical
4874.030	49.88	55.91	0.09	49.97	56.00	54	74	-4.03	-18.00	Vertical
2437.018	104.90	110.95	-7.36	97.54	103.59	-	-	-	-	Horizontal
4874.030	48.78	54.82	0.09	48.87	54.91	54	74	-5.13	-19.09	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

Date of Test:	May 4, 2011	Temperature:	25°C
EUT:	AOC TABLET	Humidity:	52%
Model No.:	MW0812	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel High 2462MHz	Test Engineer:	Jack

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain


Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2462.017	105.44	111.46	-7.35	98.09	104.11	-	-	-	-	Vertical
2483.500	39.19	45.18	-7.37	31.82	37.81	54	74	-22.18	-36.19	Vertical
4924.031	49.90	55.92	0.34	50.24	56.26	54	74	-3.76	-17.74	Vertical
2462.017	104.57	110.60	-7.35	97.22	103.25	-	-	-	-	Horizontal
2483.500	39.56	45.61	-7.37	32.19	38.24	54	74	-21.81	-35.76	Horizontal
4924.031	49.12	55.16	0.34	49.46	55.50	54	74	-4.54	-18.50	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.


Antenna port conducted spurious emissions

802.11b mode:


Low channel



Middle channel




High channel




802.11g mode:


Low channel



Middle channel



High channel



10. §15.247(A) (2) – 6DB BANDWIDTH TESTING

10.1. Test Equipment

Please refer to Section 4 this report.

10.2. Test Procedure

1. Set EUT in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=100KHz, VBW RBW, Span=50MHz, Sweep=auto.
4. Mark the peak frequency and -6dB(upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

10.3. Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


10.4. Test Result: Pass.

Please refer to the following tables


Channel Frequency (MHz)	Data Rate (Mbps)	6dB Bandwidth (kHz)	Limit (kHz)	Ref. Plot
802.11b Mode				
2412	1	11000	> 500	PLOT 1
2437	1	11200	> 500	PLOT 2
2462	1	11200	> 500	PLOT 3
802.11g Mode				
2412	6	16400	> 500	PLOT 4
2437	6	16400	> 500	PLOT 5
2462	6	16400	> 500	PLOT 6

802.11b Mode:


Low Channel



Middle Channel




High Channel




802.11g Mode:


Low Channel



Middle Channel



High Channel



11. §15.247(B) (3) - Maximum Peak Output Power

11.1. Test Equipment

Please refer to Section 4 this report.

11.2. Test Procedure

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz.
3. Set VBW = 3 MHz.
4. Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 RBW. Otherwise use peak detector mode.
5. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to “free run”.
6. Trace average 100 traces in power averaging mode.
7. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer’s band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.

11.3. Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

11.4. Test Result**Pass****802.11b Mode:**

Channel	Frequency (MHz)	Data Rate (Mbps)	Conducted Power (dBm)	Limit (dBm)
Low	2412	1	12.46	30
Mid	2437	1	12.34	30
High	2462	1	12.06	30

802.11g Mode:

Channel	Frequency (MHz)	Data Rate (Mbps)	Conducted Power (dBm)	Limit (dBm)
Low	2412	6	12.95	30
Mid	2437	6	12.46	30
High	2462	6	12.55	30

12. §15.247(D) – 100 KHZ Bandwidth of Frequency Band Edge

12.1.Test Equipment

Please refer to Section 4 this report.

12.2.Test Procedure

- 1, Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2, Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3,Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
Note: For Rdstricted Band
RBW=1MHz
VBW=1 MHz
- 4, Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5,Repeat above procedures until all measured frequencies were complete.

12.3.Applicable Standard



In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

12.4.Test Result



Pass.

Conducted test

802.11b Mode:



802.11g Mode:



Radiated test**802.11b_Channel Low_Hor**

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2310.000	0.188	38.250	38.439	-35.561	74.000	PEAK
2		2326.547	0.226	41.172	41.398	-32.602	74.000	PEAK
3		2390.000	0.358	40.335	40.693	-33.307	74.000	PEAK
4	*	2410.659	0.424	93.847	94.271	N/A	N/A	PEAK

802.11b_Channel Low_Ver

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2310.000	0.188	38.445	38.634	-35.366	74.000	PEAK
2		2325.708	0.224	41.828	42.052	-31.948	74.000	PEAK
3		2390.000	0.358	40.349	40.707	-33.293	74.000	PEAK
4	*	2412.335	0.429	95.754	96.184	N/A	N/A	PEAK

802.11b_Channel High_Hor

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2463.633	0.605	94.449	95.054	N/A	N/A	PEAK
2		2483.500	0.672	40.496	41.169	-32.831	74.000	PEAK
3		2493.972	0.708	40.842	41.551	-32.449	74.000	PEAK
4		2500.000	0.737	38.308	39.044	-34.956	74.000	PEAK

802.11b_Channel High_Ver

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2463.633	0.605	96.915	97.520	N/A	N/A	PEAK
2		2483.500	0.672	41.986	42.659	-31.341	74.000	PEAK
3		2491.098	0.699	41.201	41.900	-32.100	74.000	PEAK
4		2500.000	0.737	38.510	39.246	-34.754	74.000	PEAK

802.11g_Channel Low_Hor

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2310.000	0.188	38.351	38.540	-35.460	74.000	PEAK
2		2338.004	0.251	40.879	41.130	-32.870	74.000	PEAK
3		2390.000	0.358	52.565	52.923	-21.077	74.000	PEAK
4	*	2410.659	0.424	90.746	91.170	N/A	N/A	PEAK

802.11g_Channel Low_Ver

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1		2310.000	0.188	38.621	38.810	-35.190	74.000	PEAK
2		2339.681	0.256	40.262	40.517	-33.483	74.000	PEAK
3		2390.000	0.358	54.260	54.618	-19.382	74.000	PEAK
4	*	2413.174	0.433	93.338	93.771	N/A	N/A	PEAK
5		2390.000	0.358	42.653	43.011	-10.989	54.000	AVERAGE

802.11g_Channel High_Hor

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2462.994	0.602	91.485	92.088	N/A	N/A	PEAK
2		2483.500	0.672	53.049	53.722	-20.278	74.000	PEAK
3		2483.500	0.672	41.860	42.533	-11.467	54.000	AVERAGE
4		2491.417	0.700	43.920	44.620	-29.380	74.000	PEAK
5		2500.000	0.737	39.545	40.281	-33.719	74.000	PEAK

802.11g_Channel High_Ver

		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Detector Type
1	*	2460.759	0.594	92.386	92.980	N/A	N/A	PEAK
2		2483.500	0.672	54.226	54.899	-19.101	74.000	PEAK
3		2483.500	0.672	42.580	43.253	-10.747	54.000	AVERAGE
4		2486.307	0.683	50.363	51.046	-22.954	74.000	PEAK
5		2500.000	0.737	41.073	41.809	-32.191	74.000	PEAK

13. §15.247(E) - Power Spectral Density

13.1. Test Equipment

Please refer to Section 4 this report.

13.2. Test Procedure

- 1, Set EUT in the transmitting mode.
- 2, Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3, Set the spectrum analyzer as RBW=3KHz, VBW=10KHz, Span=1.5MHz, Sweep=500S.
- 4, Record the max. reading
- 5, Repeat the above procedure until the measurements for all frequencies are completed.

13.3. Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


13.4. Test Result

PASS


Channel Frequency (MHz)	Data Rate (Mbps)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	RESULT
802.11b Mode				
2412	1	-17.85	8	Compliant
2437	1	-17.33	8	Compliant
2462	1	-16.98	8	Compliant
802.11g Mode				
2412	6	-20.82	8	Compliant
2437	6	-22.24	8	Compliant
2462	6	-21.24	8	Compliant


802.11b Mode:

Low Channel




Middle Channel






802.11g Mode:



Middle Channel



High Channel

