

## FCC REPORT

**Applicant:** Guangdong Coagent Electronics S&T Co., Ltd.

**Address of Applicant:** Section C, Xi'nan Industrial Zone, Sanshui District, Foshan City  
China

**Equipment Under Test (EUT)**

Product Name: Car DVD/TV/Radio/Bluetooth/GPS

Model No.: See section 5.2

Trade Mark: CASKA/KOGND

**FCC ID:** Y7QSSHBS07

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.249:2012

**Date of sample receipt:** July 02, 2013


**Date of Test:** July 02-17, 2013

**Date of report issued:** July 17, 2013

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue stamp with the text "GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD." around the perimeter and "GTS GLOBAL TESTING" in the center. A handwritten signature in black ink is written over the stamp.

**Robinson Lo**  
**Laboratory Manager**

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

## 2 Version

Version No.	Date	Description
00	July 17, 2013	Original

Prepared By:

*Sam. Gao*

Date:

July 17, 2013

Project Engineer

Check By:

*Hans. Hu*

Date:

July 17, 2013

Reviewer

## 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
5 GENERAL INFORMATION .....	5
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF EUT .....	5
5.3 TEST MODE .....	7
5.4 DESCRIPTION OF SUPPORT UNITS .....	7
5.5 TEST FACILITY .....	7
5.6 TEST LOCATION .....	7
5.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	7
6 TEST INSTRUMENTS LIST .....	8
7 TEST RESULTS AND MEASUREMENT DATA.....	9
7.1 ANTENNA REQUIREMENT:.....	9
7.2 RADIATED EMISSION METHOD .....	10
7.2.1 Field Strength of The Fundamental Signal .....	12
7.2.2 Spurious emissions.....	13
7.2.3 Bandedge emissions.....	17
7.3 20dB OCCUPY BANDWIDTH .....	18
8 TEST SETUP PHOTO .....	20
9 EUT CONSTRUCTIONAL DETAILS .....	21

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

*N/A: not applicable.*

## 5 General Information

### 5.1 Client Information

Applicant:	Guangdong Coagent Electronics S&T Co., Ltd.
Address of Applicant:	Section C, Xi'nan Industrial Zone, Sanshui District, Foshan City China
Manufacturer:	Guangdong Coagent Electronics S&T Co., Ltd.
Address of Manufacturer:	Section C, Xi'nan Industrial Zone, Sanshui District, Foshan City China

### 5.2 General Description of EUT

Product Name:	Car DVD/TV/Radio/Bluetooth/GPS
Model No.:	CA109-R, CA1624-R, CA191-R, CA262-R, CA009-R4, CA083-R4, CA115-R4, CA163-R4, CA262-R4, CA325-R4, CA355-R4, CA371-R4, CA013-R5, CA1624-R5, CA069-R8, CA191-R8, CA322-R8, CA323-R8, CA350-R8, CA108-RA8, CA355-RA8, RQ285-RA8, CA017-Q4, CA019-Q4, CA028-Q4, CA033-Q4, CA087-Q4, CA112-Q4, CA115-Q4, CA123-Q4, CA126-Q4, CA146-Q4, CA163-Q4, CA1634-Q4, CA187-Q4, CA191-Q4, CA197-Q4, CA220-Q4, CA229-Q4, CA237-Q4, CA260-Q4, CA262-Q4, CA277-Q4, CA279-Q4, CA293-Q4, CA310-Q4, CA322-Q4, CA323-Q4, CA325-Q4, CA341-Q4, CA345-Q4, CA350-Q4, CA371-Q4, RQ301-Q4, CA109-QA4, CA182-QA4, CA350-QA4, CA036-Q5, CA109-Q5, CA146-Q5, CA189-Q5, CA278-Q5, CA310-Q5, CA325-Q5, CA371-Q5, RQ193-Q5, RQ292-Q5, CA126-QA8, CA036-Q8, CA037-Q8, CA067-Q8, CA069-Q8, CA112-Q8, CA115-Q8, CA156-Q8, CA1624-Q8, CA309-Q8, CA314-Q8, CA315-Q8, CA322-Q8, CA341-Q8, CA353-Q8, RQ315-US8, RQ046-UT8, CA123-BR, CA1624-BR, CA189-BR, CA220-BR, CA309-BR, CA310-BR, CA322-BR, CA112-A, CA146-A, CA163-A, CA182-A, CA188-A, CA193-A, CA197-A, CA229-A, CA238-A, CA244-A, CA260-A, CA277-A, CA278-A, CA279-A, CA293-A, CA309-A, CA310-A, CA314-A, CA315-A, CA323-A, CA325-A, CA350-A, CA051-H, CA112-H, CA132-H, CA1624-H, CA163-H, CA169-H, CA197-H, CA279-H, CA311-H, CA6049-H, CA108-AB, CA192-AB
Test Model No.:	CA109-R
Remark:	All above models are identical in the same interior structure, electrical circuits, components and appearance. The only difference is the model name for the marketing requirement.
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, Pi/4QPSK, 8DPSK
Antenna Type:	Integral
Antenna gain:	0dBi
Power supply:	DC 12V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

## 5.3 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode with GFSK modulation.
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

### Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	86.16	88.96	84.35

### Final Test Mode:

The EUT was tested in GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation is the worst case.

According to ANSI C63.4 standards, the test results are both the "worst case" and "worst setup":

Y axis (see the test setup photo)

## 5.4 Description of Support Units

N/A

## 5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

## 5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

## 5.7 Other Information Requested by the Customer

None.


## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 29 2013	Mar. 28 2014
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	Dec. 6, 2012	Dec. 05 2013
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 02 2013	Jul. 01 2014
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 24 2013	Feb. 23 2014
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2013	June 27 2014
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 29 2013	Mar. 28 2014
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	Mar. 30 2013	Mar. 29 2014
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 30 2013	Mar. 29 2014
11	Coaxial cable	GTS	N/A	GTS210	Mar. 30 2013	Mar. 29 2014
12	Coaxial Cable	GTS	N/A	GTS212	Mar. 30 2013	Mar. 29 2014
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 02 2013	Jul. 01 2014
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 02 2013	Jul. 01 2014
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2013	June 27 2014
16	Band filter	Amindeon	82346	GTS219	Mar. 30 2013	Mar. 29 2014





## 7 Test results and Measurement Data

### 7.1 Antenna requirement:

<b>Standard requirement:</b>	FCC Part15 C Section 15.203
<b>15.203 requirement:</b> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
<b>E.U.T Antenna:</b> <p><i>The antenna is Integral, the best case gain of the antenna is 0dBi</i></p>	
	

## 7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.00		Quasi-peak Value
	88MHz-216MHz		43.50		Quasi-peak Value
	216MHz-960MHz		46.00		Quasi-peak Value
	960MHz-1GHz		54.00		Quasi-peak Value
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	Below 1GHz				
					
	Above 1GHz				

	 <p>The diagram illustrates the test setup. An EUT (Equipment Under Test) is placed on a Turn Table at a height of 0.8m. The Turn Table is 3m away from an Antenna Tower. The Antenna Tower has a Horn Antenna at a height of 4m. A Spectrum Analyzer is connected to the Antenna Tower via an Amplifier. The distance from the ground to the Horn Antenna is 1m.</p>
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

## Measurement data:

## 7.2.1 Field Strength of The Fundamental Signal

### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	89.62	27.58	5.39	34.01	88.58	114.00	-25.42	Horizontal
2402.00	90.00	27.58	5.39	34.01	88.96	114.00	-25.04	Vertical
2441.00	87.27	27.48	5.43	33.96	86.22	114.00	-27.78	Horizontal
2441.00	89.15	27.48	5.43	33.96	88.10	114.00	-25.90	Vertical
2480.00	83.86	27.52	5.47	33.92	82.93	114.00	-31.07	Horizontal
2480.00	84.26	27.52	5.47	33.92	83.33	114.00	-30.67	Vertical

### Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	80.46	27.58	5.39	34.01	79.42	94.00	-14.58	Horizontal
2402.00	81.46	27.58	5.39	34.01	80.42	94.00	-13.58	Vertical
2441.00	77.46	27.48	5.43	33.96	76.41	94.00	-17.59	Horizontal
2441.00	79.14	27.48	5.43	33.96	78.09	94.00	-15.91	Vertical
2480.00	74.12	27.52	5.47	33.92	73.19	94.00	-20.81	Horizontal
2480.00	75.75	27.52	5.47	33.92	74.82	94.00	-19.18	Vertical

According to the following transmitter output power ( $P_t$ ) formula:

$$P_t = (E \times d)^2 / (30 \times g_t)$$

$P_t$  = transmitter output power in watts

$g_t$  = numeric gain of the transmitting antenna (unitless)

$E$  = electric field strength in V/m

$d$  = measurement distance in meters (m).

According to the above test data,  $E_{max} = 88.96 \text{ dBuV/m} = 0.0281 \text{ V/m}$ ,  $d = 3 \text{ m}$ ,  $g_t = 1.0$

$$P_t = (E \times d)^2 / (30 \times g_t) = (0.0281 \times 3)^2 / (30 \times 1.0) = 0.000150 \text{ W} = 0.150 \text{ mW}$$

## 7.2.2 Spurious emissions

### ■ Below 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
47.83	39.36	14.25	0.18	32.05	21.74	40.00	-18.26	Vertical
57.80	38.16	15.47	0.18	31.97	21.84	40.00	-18.16	Vertical
97.46	38.15	12.32	0.22	31.71	18.98	43.50	-24.52	Vertical
143.83	39.69	12.86	0.31	31.95	20.91	43.50	-22.59	Vertical
300.37	39.65	12.51	0.64	32.30	20.50	46.00	-25.50	Vertical
543.27	38.65	18.53	1.05	31.47	26.76	46.00	-19.24	Vertical
49.88	36.62	14.86	0.18	32.01	19.65	40.00	-20.35	Horizontal
68.15	40.44	9.63	0.18	31.89	18.36	40.00	-21.64	Horizontal
142.32	40.79	9.43	0.31	31.93	18.60	43.50	-24.90	Horizontal
508.26	35.88	19.67	1.00	31.58	24.97	46.00	-21.03	Horizontal
696.86	34.65	23.04	1.33	31.69	27.33	46.00	-18.67	Horizontal
922.52	34.69	25.33	1.78	31.47	30.33	46.00	-15.67	Horizontal

## ■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	45.48	31.78	8.60	24.17	61.69	74.00	-12.31	Vertical
7206.00	30.46	38.01	14.14	25.45	57.16	74.00	-16.84	Vertical
9608.00	30.64	36.15	11.66	26.46	51.99	74.00	-22.01	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	40.98	31.78	8.60	24.17	57.19	74.00	-16.81	Horizontal
7206.00	29.50	38.01	14.14	25.45	56.20	74.00	-17.80	Horizontal
9608.00	28.20	36.15	11.66	26.46	49.55	74.00	-24.45	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

### Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	32.61	31.78	8.60	24.17	48.82	54.00	-5.18	Vertical
7206.00	18.94	38.01	14.14	25.45	45.64	54.00	-8.36	Vertical
9608.00	20.52	36.15	11.66	26.46	41.87	54.00	-12.13	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	30.50	31.78	8.60	24.17	46.71	54.00	-7.29	Horizontal
7206.00	16.85	38.01	14.14	25.45	43.55	54.00	-10.45	Horizontal
9608.00	18.43	36.15	11.66	26.46	39.78	54.00	-14.22	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

### Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “\*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle channel
---------------	----------------

## Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	30.08	38.35	14.27	25.36	57.34	74.00	-16.66	Vertical
7323.00	30.97	36.41	11.72	26.78	52.32	74.00	-21.68	Vertical
9764.00	30.41	31.86	8.67	24.10	46.84	74.00	-27.16	Vertical
12205.00	*					74.00		Vertical
14646.00	*					74.00		Vertical
4882.00	28.86	38.35	14.27	25.36	56.12	74.00	-17.88	Horizontal
7323.00	29.94	36.41	11.72	26.78	51.29	74.00	-22.71	Horizontal
9764.00	28.35	31.86	8.67	24.10	44.78	74.00	-29.22	Horizontal
12205.00	*					74.00		Horizontal
14646.00	*					74.00		Horizontal

## Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	18.53	38.35	14.27	25.36	45.79	54.00	-8.21	Vertical
7323.00	19.86	36.41	11.72	26.78	41.21	54.00	-12.79	Vertical
9764.00	21.41	31.86	8.67	24.10	37.84	54.00	-16.16	Vertical
12205.00	*					54.00		Vertical
14646.00	*					54.00		Vertical
4882.00	17.60	38.35	14.27	25.36	44.86	54.00	-9.14	Horizontal
7323.00	19.42	36.41	11.72	26.78	40.77	54.00	-13.23	Horizontal
9764.00	17.55	31.86	8.67	24.10	33.98	54.00	-20.02	Horizontal
12205.00	*					54.00		Horizontal
14646.00	*					54.00		Horizontal

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “\*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest channel
---------------	-----------------

## Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	27.88	39.05	14.42	25.21	56.14	74.00	-17.86	Vertical
7440.00	29.51	36.56	11.79	27.03	50.83	74.00	-23.17	Vertical
9920.00	29.88	31.91	8.71	24.03	46.47	74.00	-27.53	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	26.09	39.05	14.42	25.21	54.35	74.00	-19.65	Horizontal
7440.00	28.69	36.56	11.79	27.03	50.01	74.00	-23.99	Horizontal
9920.00	28.67	31.91	8.71	24.03	45.26	74.00	-28.74	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

## Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	16.84	39.05	14.42	25.21	45.10	54.00	-8.90	Vertical
7440.00	18.81	36.56	11.79	27.03	40.13	54.00	-13.87	Vertical
9920.00	18.65	31.91	8.71	24.03	35.24	54.00	-18.76	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	16.70	39.05	14.42	25.21	44.96	54.00	-9.04	Horizontal
7440.00	17.84	36.56	11.79	27.03	39.16	54.00	-14.84	Horizontal
9920.00	18.52	31.91	8.71	24.03	35.11	54.00	-18.89	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “\*”, means this data is the too weak instrument of signal is unable to test.



## 7.2.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest channel
---------------	----------------

### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	49.59	27.56	5.38	30.18	52.35	74.00	-21.65	Horizontal
2400.00	53.78	27.57	5.39	30.18	56.56	74.00	-17.44	Horizontal
2390.00	52.69	27.59	5.38	30.18	55.48	74.00	-18.52	Vertical
2400.00	56.78	27.58	5.39	30.18	59.57	74.00	-14.43	Vertical

### Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	32.47	27.58	5.39	30.18	35.26	54.00	-18.74	Horizontal
2400.00	35.78	27.58	5.39	30.18	38.57	54.00	-15.43	Horizontal
2390.00	34.59	27.58	5.39	30.18	37.38	54.00	-16.62	Vertical
2400.00	37.48	27.58	5.39	30.18	40.27	54.00	-13.73	Vertical

Test channel:	Highest channel
---------------	-----------------

### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	51.57	27.54	5.47	29.93	54.65	74.00	-19.35	Horizontal
2500.00	48.47	27.56	5.49	29.93	51.59	74.00	-22.41	Horizontal
2483.50	54.67	27.53	5.47	29.93	57.74	74.00	-16.26	Vertical
2500.00	51.47	27.55	5.49	29.93	54.58	74.00	-19.42	Vertical


### Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.24	27.54	5.47	29.93	41.32	54.00	-12.68	Horizontal
2500.00	34.59	27.55	5.49	29.93	37.70	54.00	-16.30	Horizontal
2483.50	39.47	27.54	5.47	29.93	42.55	54.00	-11.45	Vertical
2500.00	36.47	27.55	5.49	29.93	39.58	54.00	-14.42	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

## 7.3 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.4:2003
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

### Measurement Data


Worst case GFSK modulation

Test channel	20dB bandwidth(MHz)	Result
Lowest	0.838	Pass
Middle	0.854	Pass
Highest	0.844	Pass


Test plot as follows:



Lowest channel





Middle channel




Highest channel

## 8 Test Setup Photo



Radiated Emission







## 9 EUT Constructional Details









































































-----end-----