序号	名 称	描述	单位	子项数量	位置码	生产厂家
1	电阻	电阻, 6. 2K ohm, ±5%, 1/16W, 0402, ,	PCS		R202	
2	电阻	电阻,33 ohm, ±5%,1/16W,0402,,	PCS	3	R100 R204 R205	
3	电容	电容, 1. 8pF, ±0. 25pF, 50V, C0G, 0402, ,	PCS	4	C406 C407 C409 C410	
4		电感, Inductor, 22nH, ±	DOG			0 1 1
4	电感	5%, DCR=0. 8ohm, 200mA, 0402, , SDCL1005C22NJT(f), Sunlord,	PCS	2	L400 L401	Sunlord
_	上民	电感, Inductor, 1.8nH, ±	DCC	1	1.404	C 1 1
5	电感	0.3nH, DCR=0.1ohm, 300mA, 0402, , SDCL1005C1N8STDF, Sunlord, ,	PCS	1	L404	Sunlord
6	电阻	电阻,510 ohm, ±5%, 1/16W, 0402, ,	PCS	2	R302 R305	
7	电阻	电阻, 1.5K ohm, ±1%, 1/16W, 0402, ,	PCS	2	R303 R304	
8	电阻	电阻, 0 ohm, ±5%, 1/10W, 0603,	PCS	2	L300 L305	
					R206 R207 R211 R306 R307	
					R319 R320 R382 C423 R720	
9	电阻	电阻,0 ohm, ±5%,1/16W,0402,,	PCS		C711 R810 R809 R808 R807	
					L412 R716 R718 R730 R711	
					R709 R710	
10	电阻	电阻, Resistor, O. 36 ohm, ±1%, 1/4W, 0805, WWO8PR360FTL, WALSIN,	PCS		R209	WALSIN
11	电阻	电阻, 1K ohm, ±5%, 1/16W, 0402, ,	PCS		R203 R308 R309 R312	
12	电阻	电阻, 100K ohm, ±5%, 1/16W, 0402, ,	PCS		R301 R380 R340 R601	
13	电容	电容, Capacitor, 470pF, ±10%, 50V, X7R, 0402, C0402X7R471K500NT, EYANG,	PCS		C205	EYANG
		集成电路, 1. 2W, Class-D Audio Amplifier, UTQFN-9, 1. 463×				
14	Audio Amplifier	1. 463mm, , , , SN2010B, SIEN,	PCS	1	U301	SIEN
	- 1	ESD保护二极管, ESD protection diodes, Vrwm=7V, SOD-				
15	ESD保护二极管	523, CESD7VOD5, CHANGJIANG,	PCS	1	D200	CHANGJIANG
					C203 C204 C206 C207 C208	
16	电容	电容, Capacitor, 1uF, ±10%, 6.3V, X5R, 0402, C0402X5R105K6R3NT, EYANG,	PCS	9	C217 C218 C223 C402	EYANG
					C213 C215 C216 C219 C220	
17	电容	电容, Capacitor, 2. 2uF, ±10%, 10V, X5R, 0603, C0603X5R225K100NT, EYANG,	PCS	1 1 ()	C221 C222 C307 C341 C500	EYANG
		电容, Capacitor, 10uF, ±			C201 C209 C212 C308 C318	
18	电容	20%, 6. 3V, X5R, 0805 (T=1. 25mm) C0805X5R106M6R3NT, EYANG,	PCS	6	C319	EYANG
		20%, G. 57, Note, Good (1 1. 20mm) Coolonott Completely, Ellitte,			C303 C305 C315 C317 C320	
19	电容	电容, Capacitor, 47pF, ±5%, 50V, COG, 0402, CO402COG470J500NT, EYANG,	PCS		C321 C322 C324 C344 C345	EYANG
13	七年	电台, Capacitor, 47pr, 上5%, 50%, Cod, 0402, C0402C00470J500M1, E1MNd,	105		C425	LIANG
20	电容	电容, Capacitor, 3. 3pF, ±0. 25pF, 50V, COG, 0402, CO402COG3R3C500NT, EYANG,	PCS		C431 C432	EYANG
					C202 C309 C300 C370 C609	
21	电容	电容, Capacitor, 100nF, ±10%, 10V, X5R, 0402, C0402X5R104K100NT, EYANG,	PCS	()	C718 C715 C707 C708	EYANG
22	电容	电容, Capacitor, 1nF, ±10%, 50V, X7R, 0402, C0402X7R102K500NT, EYANG,	PCS		C403 C418 C716	EYANG
23	电容	电容, Capacitor, 1pF, ±0. 25pF, 50V, COG, 0402, C0402COG1ROC500NT, EYANG,	PCS		C709	EYANG
24	电容	电容, Capacitor, 2. 7pF, ±0. 25pF, 50V, COG, 0402, C0402COG2R7C500NT, EYANG,	PCS		C710	EYANG

25	电容	电容, Capacitor, 100pF, ±5%, 50V, COG, 0402, CO402COG101J500NT, EYANG,	PCS	11	C110 C306 C304 C316 C323 C346 C400 C405 C413 C414 C420	EYANG
26	电容	电容, Capacitor, 22pF, ±5%, 50V, COG, 0402, CO402COG220J500NT, EYANG,	PCS	5	C232 C233 C429 C508 C511	EYANG
27	电容	电容, Capacitor, 27pF, ±5%, 50V, COG, 0402, CO402COG270J500NT, EYANG,	PCS	4	C426 C427 C428 C424	EYANG
28	电容	电容, Capacitor, 33pF, ±5%, 50V, COG, 0402, CO402COG330J500NT, EYANG,	PCS	5	C229 C314 C312 C313 C419	EYANG
29	电容	电容, Capacitor, 4.7pF, ±0.25pF, 50V, COG, 0402, CO402COG4R7C500NT, EYANG,	PCS	1	C401	EYANG
30	电容	电容, Capacitor, 22uF, ± 20%, 6. 3V, X5R, 0805 (T=1. 25mm), C0805X5R226M6R3NT, EYANG,	PCS	1	C421	EYANG
31	电容	电容, 22nF, ±10%, 10V, X7R, 0402, ,	PCS	4	C301 C302 C310 C311	
32	USB连接器	USB连接器, MINI USB connector,,10pin,0.4pitch,H=3.7mm,,DIP+SMT TYPE,MUB06-CK42001,星擎,	PCS	1	J301	星擎
32A	I/0连接器	I/O连接器,I/O connector,10pin,O.4pitch,H=3.7mm,,WKUBIOO4-011,JTCONN,	PCS	1	Ј301	JTCONN
32B	I/0连接器	I/O连接器,I/O connector,10pin,O.4pitch,H=3.7mm,,O5-10002,信为通,	PCS	1	Ј301	信为通
32C	USB连接器	USB连接器,USB Connector,,10pin,08pitch,H=3.7mm,,SMT type with post,MIN-210D211,大为,	PCS	1	Ј301	大为
32D	USB连接器	USB连接器, MINI USB connector,,10pin,0.4pitch,H=3.7mm,,WITHOUT POST,UAF04-10374-S107,Linkconn,	PCS	1	Ј301	Linkconn
33	Front-end Module	集成电路,Front-end Module,28-pins LGA,6×6×1.1mm,,,非加密,RDA6232,RDA,	PCS	1	U401	RDA
34	磁珠	磁珠,Chip ferrite beads,600ohm± 25%,DCR=0.2ohm,1000mA,0603,MHC1608S601LBP,INPAQ,,	PCS	1	B301	INPAQ
34A	磁珠	磁珠,Chip ferrite beads,600ohm± 25%,DCR=150mohm,1000mA,0603,UPZ1608E601,Sunlord,,	PCS	1	B301	Sunlord
35	Radio Transceiver	集成电路,Single-chip Radio Transceiver,5×4×0.9mm,28 pin QFN,,,,SR528,SPREADTRUM,	PCS	1	U404	SPREADTRUM
36	场效应管	场效应管,P-channel MOSFET with schottky diode,DFN 2×2×0.75mm,20V(D-S),MC3117,MegaPower,	PCS	1	Q201	MegaPower
37	滤波器	滤波器, SAW filter for GSM900/1800MHz, 1.4×1.8mm, 10pin, SF18- 1842EAUBA1, KYOCERA(京瓷),	PCS	1	U405	KYOCERA
37A	滤波器	滤波器,EGSM900/DCS1800, Dual Band Rx SAW Filter,942.5/1842.5MHz,1.8×1.4×HO.55mm,10pin,,, SFR942PY002,WISOL,	PCS	1	U405	WISOL
37B	滤波器	滤波器, SAW filter, for GSM900/1800 Rx, 942.5MHz, 1.8×1.35× TO.5mm, , , SAWEN942MCN0F00, MURATA,	PCS	1	U405	MURATA
37C	滤波器	滤波器,EGSM900/DCS1800, Dual Band Rx SAW Filter,942.5/1842.5MHz,1.8×1.4×HO.65mm,10pin,,,EFCH9418TDL1, Panasonic,	PCS	1	U405	Panasonic
38	Baseband Process	集成电路, GSM/GPRS Baseband Process, LFBGA, 9×9mm, 200-ball, 0.50 pitch, , , SC6620, SPREADTRUM,	PCS	1	U100	SPREADTRUM
39	FLASH Memory	SC2112,集成电路-GD25Q32BWIG,GigaDevice OR FM25Q32A- 1AIA4,Fidelix,NOR;3.OV;32Mbit;Quad SPI;104/12OMhz;WSON,	PCS	1	U500	WSON

40		集成电路,Single Chip for Bluetooth & FM Radio Tuner,4×4mm 32pin QFN,,,,RDA5876,RDA Microelectronics,	PCS	1	U701	RDA
41	电感	电感, Inductor, 6. 2nH, ± 0. 3nH, 300mA, DCR=0. 22ohm, 0402, , LQG15HS6N2S02D, MURATA,	PCS	2	L402 L407	MURATA
42	主板PCB	主板PCB,,F190,V1.2,4Layers,85×37×0.8mm,红板,	PCS	1		红板
43	RF屏蔽罩	RF屏蔽罩, RF shielding cover, F190, T=0.2mm, 洋白铜, 22.60×12.50×1.40mm, 久润,	PCS	1		久润
44	晶振	晶振, Quartz Crystal, 32.768KHz, 20ppm, 12.5pF,,,SSP-T7-F,SEIKO,	PCS	1	X201	SEIKO
44A	晶振	晶振, Crystal,, 32.768KHz, ±20ppm, 12.5pF,,, MC-146 32.768K-AGO, SEIKO EPSON,	PCS	1	X201	SEIKO
45	晶振	晶振, Crystal, 26MHz, ±10ppm, 7.3pf, 3.2×2.5×0.6mm,, XTL571100-S362-001, SIWARD(希华),	PCS	1	X400	SIWARD
45A	晶振	晶振, Crystal, 26MHz, ±10ppm, 9.0pF, 3.2×2.5×T0.7mm,, 7M26000056, TXC,	PCS	1	X400	TXC
46	发光二极管	发光二极管, LED, super blue, 1.6x0.8x0.4mm,,,,20mA,,HB336G- TRB(J4F1),HB336G-TRB(J4F2),HB336G-TRB(K4F1),HB336G-TRB(K4F2),HB336G- TRB(K5F1),BRIGHT,	PCS	4	D810 D809 D808 D807	BRIGHT
46A	发光二极管	发光二极管, LED, Blue, 0.8×1.6×0.35mm,,,,,,LTST-C193TBKT-5A,LITEON,	PCS	4	D810 D809 D808 D807	LITEON
47	电容	电容, 1.5pF, ±0.25pF, 50V, COG, 0402, ,	PCS	4	C411 C412 C415 C416	
48	T-F卡座	T-F卡座,T-Flash card connector,,8pin,1.1pitch,13.6×14.5×H1.6,	PCS	1	J506	Linkconn
48A	T-F卡座	T-F卡座,T-Flash card connector,,8pin,1.1pitch,H=1.5,,,TFS07-8K30000,SINGEEN,	PCS	1	J506	SINGEEN
48B	T-F卡座	T-F卡座, T-flash connector,, 8pin, 1.1pitch, H=1.6mm,,, WKTFH010-S05, JTCONN PRECISION,	PCS	1	J506	JTCONN
49	电感	电感, Inductor, 2. 4nH, ± 0. 3nH, 300mA, DCR=0. 15ohm, 0402, , LQG15HS2N4S02D, MURATA,	PCS	1	L703	MURATA
50	电池连接器	电池连接器,Battery connector,,3Pin,3.0Pitch,8.4×3.5×H5.4mm,,侧压,02-032112K,信为通,	PCS	1	J202	信为通
50A	电池连接器	电池连接器, Battery connector,, 3Pin, 3. OPitch, 8.4×3.5×H5.4mm,, WITHOUT POST, PAN30-03543-S106, LCN,	PCS	1	J202	LCN
51	SIM卡连接器	SIM卡连接器, SIM card connector,,6pin,H=1.5mm,,SMT type without post,CAF99-06153-S127,Linkconn,	PCS	2	J502 J504	Linkconn
51A	SIM卡连接器	SIM卡连接器,SIM card connector,,6pin,2.54pitch,H=1.5mm,,SMT type without post,SIM-206B231,大为,	PCS	2	J502 J504	大为
52	板对板插座	板对板插座, BTB connector socket, 40pin, 0. 4pitch, 10. 22×3. 75×H0. 90mm, 母座, DRKBF034009, 特雷卡,	PCS	1	J603	特雷卡
52A	板对板插座	板对板插座, BTB connector socket,, 40pin, 0.4pitch, H=0.9mm,,,10.20×3.76×0.90mm,5.016A0-040-1R0, FAF	PCS	1	J603	FAF
53	Hall effect Switch	集成电路,Hall effect Switch,,1.65V-3.3V, H=0.6mm,,,BU52031NVX,ROHM,	PCS	1	U606	ROHM

53A	Hall effect Switch	集成电路, Hall ICs, SSON004X1216, Vsupply=1.65-3.30V,,, BU52051NVX, ROHM,	PCS	1	U606	ROHM
54	BB屏蔽罩	BB屏蔽罩, BB shielding, F902, T=0.2mm, 洋白铜, 19.52×24.36×1.80mm, 联飞,,	PCS	1		联飞
55	电容	电容, Capacitor, 0. 5pF, ±0. 25pF, 50V, COG, 0402, CO402COGOR5C50ONT, EYANG,	PCS	1	C422	EYANG
56	二极管	二极管, Schottky barrier Diodes, SOD-523, 30V/200mA, RB520S-30, 江苏长电, (MB COST DOWN)	PCS	1	D301	江苏长电
57	磁珠	磁珠,Chip ferrite beads,600ohm±25%,DCR=0.35ohm,500mA,0603,HPZ1608D601-R50T(f),Sunlord,(MB COST DOWN)	PCS	2	R325 R326	Sunlord
58	滤波器	滤波器,GSM850 Rx SAW Filter,881.5MHz,1.4×1.1×H0.55mm,5pin,, SFH881PQ102,WISOL,,	PCS	1	U410	WISOL
58A	滤波器	滤波器,SAW Filter,881.5MHz,1.35×1.05×T0.5mm,,,SAFEA881MFL0F00,Murata,	PCS	1	U410	Murata
58B	滤波器	滤波器,GSM850 Rx SAW Filter,881.5MHz,1.4×1.1×H0.5mm,5pin,, EFCH881MTDA1,Panasonic,,	PCS	1	U410	Panasonic
58D	滤波器	滤波器,SAW Filter,881.5MHz,1.35×1.05× TO.6mm,,,SAFEB881MFL0F00R12,Murata	PCS	1	U410	Murata
59	电感	电感, Inductor, 6.8nH, ± 5%, DCR=0.32ohm, 300mA, 0402, , SDCL1005C6N8JT(f), Sunlord, (MB COST DOWN)	PCS	1	L403	Sunlord
60	滤波器	滤波器,PCS1900 Rx SAW Filter,1960MHz,1.4×1.1×H0.55mm,5pin,, SFHG60MQ102,WISOL,,	PCS	1	U400	WISOL
60A	滤波器	滤波器,SAW Filter,,1960MHz,,,,SAFEA1G96FA0F00,Murata,拓展	PCS	1	U400	Murata
60B	滤波器	滤波器,SAW filter,PB,F.O.S,1930-1990MHz,1.9600,,,SAFEB1G96FA0F00,Murata,	PCS	1	U400	Murata
60C	滤波器	滤波器,PCS1900 Rx SAW Filter,1960MHz,1.4×1.1×H0.5mm,5pin,, EFCH1960TDA1,Panasonic,,	PCS	1	U400	Panasonic