Request for Modular Approval

Date:	October 17, 2019				
Subje	ect: Manufacturer's Declaration for \boxtimes - Modular Approval \square - Split Modu \square - Limited Modular Approval \square - Limited Split				
Confi	dentiality Request for:				
	8 Basic Requirements – FCC Part 15.212(a)(1) For Hamp Monked (NO(*)), the Limited Models Proprietion Months Eilled Out on the Eilled Out o	allaiu a Da a			
	For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the F Modular Approval Requirement		ment Met		
1.	The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	□ - NO(*)		
	Details: The module contains a metal shield which covers all RF components and circuitry. The shield is located on the top side of the board. See photo provided with this application.				
2.	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)	⊠ - YES	□ - NO(*)		
	Details: Data to the modulation circuit is buffered on the module; please refer to the operational description document filed with this application for full description.				
3.	The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	⊠ - YES	□ - NO(*)		
	Details: The module contains its own power supply regulation and the rf reference oscillator is contained within the module. Please refer to the schematics and operational description documents filed with this application for full description.				
4.	The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	⊠ - YES	□ - NO(*)		
	Details: The module connects to its antenna via using an UFL type connector. This antenna connector is a non-standard connector. The antenna tested was a PIFA type and the data sheet is included in the application.				
	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)		
Details: Test data contained in this application is for the device tested as a stand-alone device connected externally to a PC. See test set-up photographs filed with this application.					

	Modular Approval Requirement	Require	ment Met
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This	⊠ - YES	□ - NO(*)
	exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)		
	Details: The module is appropriately labeled (refer to the label and label location drawings contained within this application). Information to the integrator of this device regarding the labeling requirements for the host system is contained in the instructions provided with the module.		
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: The module complies with FCC Part 15C requirements. Instructions to the OEM installer installation manual filed with this application.>	are provided	in the
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
Details: The module meets the requirements for a mobile/portable device that may be used at separation distances of more than			

12mm from the human body. Refer to the RF Exposure test report submitted with this application.

Limited Module Description – When Applicable
* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA).
This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control
over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the
LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the
end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of
the end product is always ensured should be provided here.

Details: N/A

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement		Requirement Met	
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	□ - Provided in Separate Cover Letter	□ - N/A
	Details: <example a="" adjusted="" application.="" be="" by="" cannot="" cover="" device="" filed="" firmware="" letter="" modified="" of="" or="" the="" this="" with="" –=""></example>	he end user as described in a	separate
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	☐ - Provided in Separate Cover Letter	⊠ - N/A
	Details: N/A		

Split Modular Requirements			
Requirement	Provided in Manual		
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	☐ - Provided in Separate Cover Letter	⊠ - N/A	
Details: N/A			

OTM 1				
OEM Integration Manual Guidance – KDB 996369 D03 Section 2				
Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures				
for thi	rd-parties to use and/or into	egrate the module into a host device.		
Dogwinsmont				
Requirement				
		⊠ - No,		
		If No, and LMA applies, the applicant		
T 4: 11:4 116	□ - YES	not make the following detailed info public. However there still needs to be basic integration instructions for a users manual and		
Is this module intended for sale to third parties?		the information below must still be included in the operational		
sale to time parties:		description. If the applicant wishes to k		
		this will require a separate statement co		
		module is not for sale to third partie		
Itome	required to be in the manu	instructions are internal confide al – See KDB 996369 D03, Section 2	ential documents.	
		rmation to be in the installation manual	. Modular transmitter	
		r all these items indicating clearly when		
		dicate "Not Applicable". Also if a modu		
		rties, the user instructions may not need		
		tion, but this should include a cover let	ter as cited above.	
List of applicable FCC rules. K a. Only list rules re	lated to the transmitter.			
Summarize the specific operation		3260 D02 Section 2.2		
		oss, reduction of power for point to point		
	ional installation info	oss, reduction of power for point to point		
3. Limited Module Procedures. KI				
		es to verify the host meets the necessary		
limiting conditio			□ - All Items shown to	
h When RE exposure evaluation is necessary state how control will be maintained such 1			the left are provided in	
4. Trace antenna designs. KDB 99		or new nosts, etc.	the Modular Integration	
		nectors, isolation requirements, tests for	Guide (or UM) for Full	
		lures for ensuring compliance. If	Modular Approval	
		ntial must be identified and information	(MA) or LMA.	
	perational description.		☐ - An LMA applies	
5. RF exposure considerations. KI	*		and is approved ONLY	
		ow host manufacturers to use the	for use by the grantee in	
module. Two types of instructions are necessary: first to the host manufacturer to define conditions (mobile, portable – xx cm from body) and second additional text their own products, and				
	vided to the end user in the ho		not intended for sale to	
6. Antennas. KDB 996369 D03, S		-	3 rd parties as provided in	
		d all applicable professional installer	a separate cover letter. Therefore the	
		shall also identify the antenna types	information shown to	
		ni-directional" is not considered a type)	the left is found in the	
7. Label and compliance information. KDB 996369 D03, Section 2.8 a. Advice to host integrators that they need to provide a physical or e-label stating theory of operation.				
	D: " with their finished produ			
8. Information on test modes and a				
		ation by host integrators including		
	cessary for stand-alone and sin			
	tion on how to configure test			
9. Additional testing, Part 15 Subp	part B disclaimer. KDB 99636	D9 D03, Section 2.10		
Sincerely,				
Sincerery,				

By: /Vice President__ (Signature/Title¹)

Jay Moulton, RF Exposure Lab (Print name)

¹ - Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.