

# RF EXPOSURE REPORT

REPORT NO.: SA130912C02A

MODEL NO.: AK1

FCC ID: YA7-ATVT1240

**RECEIVED:** Oct. 07, 2013

**ISSUED:** Oct. 09, 2013

APPLICANT: ATrack Technology Inc.

ADDRESS: 3F., No. 88, Sec. 1, Neihu Rd., Neihu Dist., Taipei

City 11493 Taiwan (R.O.C.)

**ISSUED BY:** Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan,

R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: SA130912C02A Reference No.: 131007C19



# **TABLE OF CONTENTS**

RE	ELEASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE	5
	2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	
	2.2 MPE CALCULATION FORMULA	5
	2.3 CLASSIFICATION	5
	2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Report No.: SA130912C02A Reference No.: 131007C19



# **RELEASE CONTROL RECORD**

ISSUE NO.	NO. REASON FOR CHANGE	
SA130912C02A	Original release	Oct. 09, 2013

Report No.: SA130912C02A 3 of 6 Report Format Version 5.0.0

Reference No.: 131007C19



#### 1. CERTIFICATION

**PRODUCT:** Vehicle telematics

MODEL: AK1

**BRAND**: ATrack

**APPLICANT:** ATrack Technology Inc.

**TEST SAMPLE:** Identical Prototype

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

**IEEE C95.1** 

The above equipment (Model: AK1) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: , DATE: Oct. 09, 2013

Gina Liu / Specialist

APPROVED BY : , DATE : Oct. 09, 2013

Gordon Lin / Assistant Manager



#### 2. RF EXPOSURE

### 2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	AVERAGE TIME (minutes)					
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE								
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

#### 2.2 MPE CALCULATION FORMULA

Pd = (Pout\*G) / (4\*pi\*r2)

where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Report No.: SA130912C02A Reference No.: 131007C19



### 2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Frequency Band		Conducted Bm) Antenna Gain		E.I.R.P.	Power Density	Limit	
(MHz)	Mode	Burst Avg. Power	Time Avg. Power	(dBi)	(mW)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
GSM850	GPRS8	35	26	0	398.11	0.079	0.55
GSM1900	GPRS8	32	23	0	199.53	0.040	1

Report No.: SA130912C02A 6 of 6 Report Format Version 5.0.0

Reference No.: 131007C19