

<b>Prüfbericht-Nr.:</b> <i>Test Report No.:</i>	<b>501938571 001</b>	<b>Auftrags-Nr.:</b> <i>Order No.:</i>	<b>114082189</b>	Seite 1 von 32 <i>Page 1 of 32</i>
<b>Kunden-Referenz-Nr.:</b> <i>Client Reference No.:</i>	<b>N/A</b>	<b>Auftragsdatum:</b> <i>Order date:</i>	<b>26-Sep-2018</b>	
<b>Auftraggeber:</b> <i>Client:</i>	InnoComm Mobile Technology Corporation 3F, No. 6, Hsin Ann Rd., Hsinchu Science Park, Hsinchu, Taiwan, R.O.C.			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Wireless audio module			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type No.:</i>	<b>WB10</b>			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	FCC Part 15C (BLE)			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247(DTS)			
<b>Wareneingangsdatum:</b> <i>Date of receipt:</i>	08-Oct-2018			
<b>Prüfmuster-Nr.:</b> <i>Test sample No.:</i>	A000817010-002			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	8-Oct-2018 - 28-Oct-2018			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	EMC/RF Laboratory Taipei			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TUV Rheinland Taiwan Ltd.			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>geprüft von / tested by:</b>		<b>kontrolliert von / reviewed by:</b>		
2018-10-29 Mars Y. J. Lin / Project Engineer		2018-10-29 Ryan W. T. Chen / Project Manager		
<b>Datum</b> <i>Date</i>	<b>Datum</b> <i>Date</i>	<b>Datum</b> <i>Date</i>	<b>Datum</b> <i>Date</i>	
<b>Sonstiges / Other:</b> The module has both modes with heat sink and without heat sink. Both models of this report are evaluated, taking the Worst case test.				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: 1 = sehr gut      2 = gut      3 = befriedigend      4 = ausreichend      5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n)      F(ail) = entspricht nicht o.g. Prüfgrundlage(n)      N/A = nicht anwendbar      N/T = nicht getestet Legend: 1 = very good      2 = good      3 = satisfactory      4 = sufficient      5 = poor P(ass) = passed a.m. test specification(s)      F(ail) = failed a.m. test specification(s)      N/A = not applicable      N/T = not tested				
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

## TEST SUMMARY

### **5.1.1 ANTENNA REQUIREMENT**

*RESULT: Passed*

### **5.1.2 PEAK OUTPUT POWER**

*RESULT: Passed*

### **5.1.3 6dB BANDWIDTH**

*RESULT: Passed*

### **5.1.4 POWER DENSITY**

*RESULT: Passed*

### **5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100kHz BANDWIDTH**

*RESULT: Passed*

### **5.1.6 SPURIOUS EMISSION**

*RESULT: Passed*

### **5.2.1 MAINS CONDUCTED EMISSIONS**

*RESULT: Passed*

### **6.1.1 ELECTROMAGNETIC FIELDS**

*RESULT: Passed*

## Contents

<b>1.</b>	<b>GENERAL REMARKS .....</b>	<b>5</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS.....</b>	<b>5</b>
<b>2.</b>	<b>TEST SITES .....</b>	<b>6</b>
<b>2.1</b>	<b>TEST LABORATORY .....</b>	<b>6</b>
<b>2.2</b>	<b>TEST FACILITY.....</b>	<b>6</b>
<b>2.3</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>	<b>7</b>
<b>2.4</b>	<b>TRACEABILITY .....</b>	<b>8</b>
<b>2.5</b>	<b>CALIBRATION .....</b>	<b>8</b>
<b>2.6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>3.</b>	<b>GENERAL PRODUCT INFORMATION.....</b>	<b>9</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE .....</b>	<b>9</b>
<b>3.2</b>	<b>SYSTEM DETAILS AND RATINGS.....</b>	<b>9</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES.....</b>	<b>10</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>	<b>10</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS.....</b>	<b>10</b>
<b>4.</b>	<b>TEST SET-UP AND OPERATION MODES.....</b>	<b>11</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION .....</b>	<b>11</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE.....</b>	<b>11</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>11</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>	<b>12</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>12</b>
<b>5.</b>	<b>TEST RESULTS .....</b>	<b>14</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES.....</b>	<b>14</b>
5.1.1	<i>Antenna Requirement .....</i>	<i>14</i>
5.1.2	<i>Peak Output Power .....</i>	<i>15</i>
5.1.3	<i>6dB Bandwidth .....</i>	<i>16</i>
5.1.4	<i>Power Density .....</i>	<i>19</i>
5.1.5	<i>Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth.....</i>	<i>22</i>
5.1.6	<i>Spurious Emission .....</i>	<i>26</i>
<b>5.2</b>	<b>MAINS EMISSIONS.....</b>	<b>27</b>
5.2.1	<i>Mains Conducted Emissions.....</i>	<i>27</i>
<b>6.</b>	<b>SAFETY HUMAN EXPOSURE .....</b>	<b>28</b>

**Prüfbericht - Nr.: 501938571 001***Test Report No.***Seite 4 von 32***Page 4 of 32*

<b>6.1</b>	<b>RADIO FREQUENCY EXPOSURE COMPLIANCE .....</b>	<b>28</b>
6.1.1	<i>Electromagnetic Fields.....</i>	<i>28</i>
<b>7.</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP.....</b>	<b>29</b>
<b>8.</b>	<b>LIST OF TABLES .....</b>	<b>32</b>
<b>9.</b>	<b>LIST OF PHOTOGRAPHS.....</b>	<b>32</b>

## 1. General Remarks

### 1.1 Complementary Materials

These attachments are integral parts of this test report:

**Appendix P: Photo Documentation internal view**  
(File Name: 501938571 001 Appendix P)

**Appendix D: Test Result of Radiated Emissions**  
(File Name: 501938571 001 Appendix D)

Test Specifications

The following standards were applied.

**Table 1: Applied Standard and Test Levels**

Radio
FCC CFR47 Part 15: Subpart C Section 15.247 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v05

## 2. Test Sites

### 2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.  
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,  
Taichung City 428  
Taiwan (R.O.C.)

### 2.2 Test Facility

TUV Rheinland Taiwan Ltd.  
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

FCC RegistrationNo.: 340738  
IC Canada Registration No.: 9465A-1  
TAF Accredited NCC Test Lab. No.:0759  
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th



**Testing Laboratory**  
**0759**

## 2.3 List of Test and Measurement Instruments

**Table 2: List of Test and Measurement Equipment**

Kind of Equipment	Manu-facturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMC	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESR7	101062	2018/09/12	2019/09/12
Spectrum Analyzer	R&S	FSV 40	100921	2018/04/21	2019/04/21
Spectrum Analyzer	Agilent	N9010A	MY53470241	2018/04/25	2019/04/24
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	2018/07/29	2019/07/29
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2017/11/19	2018/11/19
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	060558	2017/11/19	2018/11/19
Bilog Antenna	TESEQ	CBL6111D	29804	2018/06/23	2019/06/23
Horn Antenna	ETS-Lindgren	3117	138160	2018/05/03	2019/05/03
Horn Antenna (18GHz~40GHz)	COM-POWER	AH840	101031	2018/11/02	2019/11/02
EMI Test Receiver	R&S	ESCI7	100797	2017/12/28	2018/12/27
Temp. & Humid. Chamber	Giant Force	GCT-099-40-S	MAF0103-007	2018/07/13	2019/07/12
LISN (1 phase)	R&S	ENV216	101243	2018/06/02	2019/06/02
LISN	R&S	ENV216	101262	2018/06/16	2019/06/16
Test Software	Audix	e3	Ver. 9	N/A	N/A
Test Software	Agilent	300328 testsystem	V1.9.1	N/A	N/A
Power sensor	Agilent	U2021XA	MY53480013	2018/03/11	2019/03/10

## 2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

## 2.5 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular schedule using in house standards or comparisons.

## 2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements .

**Table 3: Emission Measurement Uncertainty**

Parameter	Uncertainty
Radio Frequency	± 0.1 ppm
RF power, conducted	± 1.5 dB
RF power density, conducted	± 3 dB
spurious emissions, conducted	± 3 dB
all emissions, radiated	± 6 dB
Temperature	± 1 °C
Humidity	± 5 %
DC and low frequency voltages	±3 %



## 3. General Product Information

### 3.1 Product Function and Intended Use

The EUT is a Wireless audio module. It contains both Bluetooth and WiFi compatible module enabling the user to communicate data through a Wireless interface.  
For details refer to the User Guide, Data Sheet and Circuit Diagram.

### 3.2 System Details and Ratings

**Table 4: Basic Information of EUT**

Item	EUT information
Kind of Equipment/Test Item	Wireless audio module
Type Identification	WB10
FCC ID	YAIWB10

**Table 5: Technical Specification of EUT**

Technical Specification	Value
Operating Frequencies	2402~2480MHz
Channel Spacing	2 MHz
Channel number	39
Operation Voltage	5Vdc
Modulation	GFSK
Antenna gain	3.69 dBi

### **3.3 Independent Operation Modes**

Basic operation modes are:

- A. Transmitting
  - 1. Low channel
  - 2. Middle channel
  - 3. High channel
- B. Receiving

### **3.4 Noise Generating and Noise Suppressing Parts**

Refer to the Circuit Diagram.

### **3.5 Submitted Documents**

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

## 4. Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 3.3 as appropriate.

The samples were used as follows:  
A000817010-002

Full test was applied on all test modes, but only worst case was shown

### 4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:


Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

## 4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.


## 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m

**Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement**



## 5. Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:****Passed**

Test standard : FCC Part 15.247(b)(4), Part 15.203

Requirement : use of approved antennas only with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.69 dBi. The antenna is a PCB Antenna with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

## 5.1.2 Peak Output Power

### RESULT:

**Passed**

Test standard : FCC Part 15.247(b)(3)  
 Basic standard : ANSI C63.10:2013, KDB558074  
 Limit : 1 Watt  
 Kind of test site : Shielded room

### Test setup

Test Channel : Low/ Middle/ High  
 Operation Mode : A

Ambient temperature : 20-24 °C  
 Relative humidity : 50-65 %  
 Atmospheric pressure : 100-103 kPa

**Table 6: Test result of Peak Output Power**

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2402	-4.78	0.000333	1
Middle Channel	2440	-4.59	0.000348	1
High Channel	2480	-4.17	0.000383	1

Pmax: 0.3828 mW

### 5.1.3 6dB Bandwidth

**RESULT:****Passed**

Test standard : FCC Part 15.247(a)(2)  
Basic standard : ANSI C63.10:2013, KDB558074  
Kind of test site : Shielded room

**Test setup**

Test Channel : Low/ Middle/ High  
Operation Mode : A

Ambient temperature : 20-24°C  
Relative humidity : 50-65%  
Atmospheric pressure : 100-103 kPa


**Table 7: Test result of 6dB Bandwidth**

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low Channel	2402	664.1	>500	Pass
Mid Channel	2440	665.3	>500	Pass
High Channel	2480	665.3	>500	Pass



## Test Plot of 6dB Bandwidth

### Low Channel



### Middle Channel



**High Channel**


### 5.1.4 Power Density

**RESULT:****Passed**

Test standard : FCC Part 15.247(e)  
Basic standard : ANSI C63.10:2013, KDB558074  
Kind of test site : Shielded room

**Test setup**


Test Channel : Low/ Middle/ High  
Operation Mode : A  
Ambient temperature : 20-24°C  
Relative humidity : 50-65%  
Atmospheric pressure : 100-103 kPa

**Table 8: Test result of Power Density**


Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2402	-17.60	8
Middle Channel	2440	-17.30	8
High Channel	2480	-16.95	8


## Test Plot of Power Density

### Low Channel



### Middle Channel





### 5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

**RESULT:****Passed**

Test standard	:	FCC part 15.247(d)
Basic standard	:	ANSI C63.10:2013, KDB558074
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

**Test setup**

Test Channel	:	Low/ Middle/ High for Conducted Spurious Emissions Low/ High for Frequency Band Edge
Operation Mode	:	A
Ambient temperature	:	20-24°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa


All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.

Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.





## Test Plot 100kHz Conducted Emissions

### Low Channel



### Middle Channel




**High Channel**





## Test Plot 100kHz RBW of Band Edge

### Low Channel



### High Channel



### 5.1.6 Spurious Emission

**RESULT:****Passed**

Test standard : FCC part 15.247(d), FCC 15.205, FCC 15.209  
Basic standard : ANSI C63.10: 2013  
Limits : Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i5, 8.10 (Table 7), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen 5, 8.9 (Table 5 and 6).

Emission radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in FCC15.247(d) and RSS-247 i2, 5.5

Kind of test site : 3m Semi-Anechoic Chamber

**Test setup**

Test Channel : Low/ Middle/ High  
Operation mode : A

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic.

For details refer to Appendix D.

Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix D. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

**Prüfbericht - Nr.: 501938571 001***Test Report No.***Seite 27 von 32***Page 27 of 32*

## 5.2 Mains Emissions

### 5.2.1 Mains Conducted Emissions

**RESULT:****Passed**

Test standard : FCC Part 15.207  
FCC Part 15.107

Limits : Mains Conducted emissions as defined in  
above test standards must comply with the  
mains conducted emission limits specified

Kind of test site : Shielded Room

**Test setup**

Test Channel : Normal link  
Operation mode : Normal link

Ambient temperature : 20-24 °C  
Relative humidity : 50-65 %  
Atmospheric pressure : 100-103 kPa

Remark: For details refer to Appendix D.

## 6. Safety Human exposure

### 6.1 Radio Frequency Exposure Compliance

#### 6.1.1 Electromagnetic Fields

**RESULT:****Passed**

Test standard : FCC KDB Publication 447498 D01 v06

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied.

**Maximum Exposure:**

Power to Antenna (mW)	0.383 mW
Power to Antenna (dBm)	-4.2 dBm
Antenna Gain	3.69 dBi
Power+Ant Gain	0.9 mW
Distance	20 cm
S=	0.000 mW/cm <sup>2</sup>


Limit FCC:

**1500-100,000 MHz 1.0 mW/cm<sup>2</sup>**


---End---

## 7. Photographs of the Test Set-Up

**Photograph 1: Set-up for Spurious Emissions (Front View)**




**Photograph 2: Set-up for Spurious Emissions (Back View 1)**






**Photograph 3: Set-up for Spurious Emissions (Back View 2)**



**Photograph 4: Set-up for Conducted testing**



**Photograph 5: Set-up for AC Mains (Front View)**



**Photograph 6: Set-up for AC Mains (Back View)**



## 8. List of Tables

Table 1: Applied Standard and Test Levels .....	5
Table 2: List of Test and Measurement Equipment .....	7
Table 3: Emission Measurement Uncertainty.....	8
Table 4: Basic Information of EUT .....	9
Table 5: Technical Specification of EUT .....	9
Table 6: Test result of Peak Output Power .....	15
Table 7: Test result of 6dB Bandwidth .....	16
Table 8: Test result of Power Density .....	19

## 9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....	29
Photograph 2: Set-up for Spurious Emissions (Back View 1) .....	29
Photograph 3: Set-up for Spurious Emissions (Back View 2) .....	30
Photograph 4: Set-up for Conducted testing .....	30
Photograph 3: Set-up for AC Mains (Front View).....	31
Photograph 4: Set-up for AC Mains (Back View) .....	31