# FCC §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: RDG180712002-00C

### **Applicable Standard**

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### **Limits for Occupational/Controlled Exposure**

Limits for occupational/Controlled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)					
0.3-1.34	614	1.63	*(100)	6					
1.34-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6					
30-300	61.4	0.163	1.0	6					
300-1500	/	/	f/300	6					
1500-100,000	/	/	5.0	6					

f = frequency in MHz

#### Result

#### **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 22, 74 and 90 Page 9 of 30

<sup>\* =</sup> Plane-wave equivalent power density

## Worst case as below:

Frequency	Antenna Gain		Tune up Conducted Power		Evaluation Distance	Power Density	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	$(mW/cm^2)$	(mW/cm <sup>2</sup> )
2412-2472	2.5	1.78	14.5	28.18	60	0.001	1.00
400-470	3.5	2.24	44	25118.86	60	1.24	1.33

Report No.: RDG180712002-00C

#### Note:

Simultaneous transmitting consideration: DTS and DMR

The ratio=MPE/limit<sub>DTS</sub>+MPE/limit<sub>DMR</sub>=0.001/1.00+1.24/1.33=0.933 < 1.0, simultaneous exposure is not required.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 60 cm from nearby persons to antenna.

**Result: Compliance** 

FCC Part 22, 74 and 90 Page 10 of 30