



FCC PART 90 and RSS-119 TEST REPORT

FCC Part 90 and RSS-119

Report Reference No.....: WE10040015

FCC ID.....: YAMRD98XU1

IC.....: 8913A-RD98XU1

Compiled by

(position+printed name+signature)...: File administrators Xiankun Ding

Xiankun Ding

Supervised by

(position+printed name+signature)...: Test Engineer Wenliang Li

Wenliang Li

Approved by

(position+printed name+signature)...: Manager Jimmy Li

Jimmy Li

Date of issue.....: July 11, 2010

Testing Laboratory Name.....: Shenzhen Huatongwei International Inspection Co., Ltd

Address.....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name.....: Hytera Communications Corporation Ltd.

Address.....: HYT Tower, Hi-Tech Industrial Park North, Nanshan District, Shenzhen China. 518057

Test specification:

Standard.....: FCC Part 90: PRIVATE LAND TWO-WAY RADIO SERVICES

RSS-119 Issue 10: Land Mobile and Fixed Radio Transmitters and Receivers Operating in the Frequency Range 27.41-960 MHz

TRF Originator.....: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF.....: Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Digital Base Station Repeater

Trade Mark.....:



Model/Type reference.....: RD982 U(1)/ RD985 U(1)/ RD986 U(1)/ RD988 U(1)

Listed Models.....: /

Modulation/Channel Separation.....: FM&4FSK/12.5KHz&25KHz

Ratings.....: DC 13.60 V

Rated Power.....: 5Watt(36.99dBm)-50Watt(46.99dBm) Continuous

Result.....: **Positive**

TEST REPORT

Test Report No. : WE10040015	July 11, 2010 Date of issue
-------------------------------------	--------------------------------

Equipment under Test : Digital Base Station Repeater

Model /Type : RD982 U(1)/ RD985 U(1)/ RD986 U(1)/ RD988 U(1)

Listed Models : /

Applicant : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

Manufacturer : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

Test Result according to the standards on page 4:	Positive
--	-----------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS</u>	<u>4</u>
<u>2.</u>	<u>SUMMARY</u>	<u>5</u>
2.1.	General Remarks	5
2.2.	Product Description	5
2.3.	Equipment Under Test	5
2.4.	Short description of the Equipment under Test (EUT)	6
2.5.	EUT Configuration	6
2.6.	EUT operation mode	6
2.7.	EUT configuration	6
2.8.	Related Submittal(s) / Grant (s)	6
2.9.	Modifications	6
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
3.1.	Address of the test laboratory	7
3.2.	Test Facility	7
3.3.	Environmental conditions	8
3.4.	Configuration of Tested System	8
3.5.	Description of Tested Modes	8
3.6.	Statement of the measurement uncertainty	8
3.7.	Test Description	9
3.8.	Equipments Used during the Test	9
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
4.1.	Conducted Emissions Test	11
4.2.	Occupied Bandwidth and Emission Mask Test	13
4.3.	Transmitter Radiated Spurious Emission	28
4.4.	Spurious Emission on Antenna Port	34
4.5.	Modulation Characteristics	72
4.6.	Frequency Stability Test	77
4.7.	Maximum Transmitter Power	79
4.8.	Transmitter Frequency Behavior	89
4.9.	Receiver Radiated Spurious Emission	93
4.10.	Receiver Conducted Spurious Emission	101
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>111</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>115</u>

1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 90: PRIVATE LAND TWO-WAY RADIO SERVICES.

RSS-119 Issue 10 April 2010: Spectrum Management and Telecommunications Radio Standards Specification Land Mobile and Fixed Radio Transmitters and Receivers Operating in the Frequency Range 27.41-960 MHz.

TIA/EIA 603: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

ANSI C63.4-2009: American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample : Apr 23, 2010

Testing commenced on : Apr 23, 2010

Testing concluded on : July 11 2010

2.2. Product Description

The Hytera Communications Corporation Ltd.'s Model: RD982 U(1)/ RD985 U(1)/ RD986 U(1)/ RD988 U(1) or the "EUT" as referred to in this report; more general information as follows:

Name of EUT	Digital Base Station Repeater	
Model Number	RD982 U(1)/ RD985 U(1)/ RD986 U(1)/ RD988 U(1)	
FCC ID	YAMRD98XU1	
IC	8913A-RD98XU1	
Rated Output Power	5Watt(36.99dBm)-50Watt(46.99dBm) Continuous	
Operation Type	The repeater cannot operate on multi-channels	
Modulation Type	FM for Analog Voice	
	4FSK for Digital Voice/Digital Data	
Emission Designator	Analog	16K0F3E for 25KHz Channel Separation
		11K0F3E for 12.5KHz Channel Separation
	Digital	7K60FXD for Digital Data only
		7K60FXW for Digital Data & Digital Voice
Channel Separation	Analog Voice	12.5KHz&25KHz
	Digital Voice/Data	12.5KHz
Antenna Type	External	
Frequency Range	From 400MHz to 470MHz	
Maximum Transmitter Power	Analog	53.95 W for 25 KHz Channel Separation
		53.58 W for 12.5 KHz Channel Separation
	Digital	52.84 W for 12.5 KHz Channel Separation

Note: The product has the same digital working characters when operating in both two digitized voice/data mode (7K60FXD and 7K60FXW). So only one set of test results for digital modulation modes are provided in this test report.

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 13.60 V

Test frequency list

Modulation Type	Test Channel	Test Frequency
Analog/FM	Bottom Channel	400MHz
	Middle Channel	435MHz
	Top Channel	470MHz
Digital/4FSK	Bottom Channel	401MHz
	Middle Channel	436MHz
	Top Channel	469MHz

2.4. Short description of the Equipment under Test (EUT)

400-470MHz U frequency band Digital Base Station Repeater (RD982 U (1)/ RD985 U (1)/ RD986 U (1)/ RD988 U (1)).

The Digital Base Station Repeater (RD982 U (1)/ RD985 U (1)/ RD986 U (1)/ RD988 U (1)) can only operates on one signal channel.

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

2.5. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.6. EUT operation mode

The EUT has been tested under typical operating condition. Using software provided by the client to control the EUT for staying in transmitting and receiving mode for testing.

2.7. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

● Power Cable

Length (m) : 3

Shield : Unshield

Detachable : Detachable

○ Multimeter

Manufacturer : /

Model No. : /

2.8. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **YAMRD98XU1** and IC: **8913A-RD98XU1** filing to comply with FCC Part 90 Rules and RSS-119.

2.9. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: August 02, 2007. Valid time is until March 29, 2012.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time to Sep 30, 2011.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date July 01, 2009.

IC-Registration No.: 5377

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377 on February 13th, 2009.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

NEMKO-Aut. No.: ELA125

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025:2005 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10; the Authorization is valid through July 07, 2011.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) and Shielded Room (8m×4m×3m) of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: December 20, 2009. Valid time is until December 19, 2012.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: December 20, 2009. Valid time is until December 19, 2011.

DNV

Shenzhen Huatongwei International Inspection Co Ltd has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025(2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until 09 July, 2010.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	<u>15-35 ° C</u>
Humidity:	<u>30-60 %</u>
Atmospheric pressure:	<u>950-1050mbar</u>

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

No.	Product	Manufacturer	Model No.	Serial No.	FCC ID
1	Notebook PC	HP	I9100L	59NP00972	FCC DoC

3.5. Discription of Tested Modes

The EUT (Digital Base Station Repeater) has been tested under normal operating condition. Three channels (the top, the middle and the bottom) are chosen for testing at each channel separation (12.5 KHz/ 25KHz).

3.6. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.24 dB	(1)
Radiated Emission	1~18GHz	5.16 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.39 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.7. Test Description

FCC Rules	RSS-119	Description of Test	Test Result
§ 15.107	RSS-Gen	Conducted Emission	N/A
§ 15.109	RSS-Gen	Receiver Radiated Spurious Emssion	Complies
§ 15.109	RSS-Gen	Receiver Conducted Spurious Emssion	Complies
§ 90.205	§ 5.4	Maximum Transmitter Power	Complies
§ 90.207	§ 5.13	Modulation Characteristic	Complies
§ 90.209	§ 5.5	Occupied Bandwidth	Complies
§ 90.210	§ 5.8	Emission Mask	Complies
§ 90.213	§ 5.3	Frequency Stability	Complies
§ 90.214	§ 5.9	Transmitter Frequency Behavior	Complies
§ 90.210	§ 5.8	Transmitter Radiated Spurious Emssion	Complies
§ 90.210	§ 5.8	Spurious Emssion On Antenna Port	Complies
§ 2.1091	RSS-102	RF Exposure Evaluation	Complies

3.8. Equipments Used during the Test

AC Power Conducted Emission				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	11/2010
EMI Test Receiver	Rohde&Schwarz	ESCS 30	100038	11/2010
Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	11/2010
EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	11/2010

Modulation Characteristic				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Modulation Analyzer	HP	8901B	3104A03367	11/2010
Signal Generator	Rohde&Schwarz	SMT03	100059	11/2010
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	11/2010

Frequency Stability				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Communication Test Set	HP	HP8920B	US35010135	11/2010
Signal Generator	Rohde&Schwarz	SMT03	100059	11/2010
Climate Chamber	ESPEC	EL-10KA	05107008	11/2010

Transmitter Radiated Spurious Emission & Occupied Bandwidth & Emission Mask & Receiver Radiated Spurious Emission				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Ultra-Broadband Antenna	Rohde&Schwarz	HL562	100015	11/2010
EMI Test Receiver	Rohde&Schwarz	ESI 26	100009	11/2010
RF Test Panel	Rohde&Schwarz	TS / RSP	335015/ 0017	N/A
Turntable	ETS	2088	2149	N/A
Antenna Mast	ETS	2075	2346	N/A
EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	11/2010
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	11/2010
Vector Signal Generator	ROHDE & SCHWARZ	SMU200A	1141.2205.02	11/2010
ESG Vector Signal Generator	Agilent	E4438C	MY4271533	11/2010

Maximum Transmitter Power & Spurious Emission On Antenna Port				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Receiver	Rohde&Schwarz	ESI 26	100009	11/2010
Attenuator	R&S	ESH3-22	100449	11/2010
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	11/2010
High-Pass Filter	Anritsu	MP526B	6220875256	11/2010
High-Pass Filter	Anritsu	MP526D	6220878392	11/2010

Transient Frequency Behavior				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Signal Generator	Rohde&Schwarz	SMT03	100059	11/2010
Storage Oscilloscope	Tektronix	TDS3054B	B033027	11/2010
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	11/2010


4. TEST CONDITIONS AND RESULTS

4.1. Conducted Emissions Test

TEST APPLICABLE

The EUT was tested according to ANSI C63.4 - 2009. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm / 50 u Henry as specified by section 5.1 of ANSI C63.4 - 2009. Cables and peripherals were moved to find the maximum emission levels for each frequency.

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4-2009.
- 2 Support equipment, if needed, was placed as per ANSI C63.4-2009.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4-2009.
- 4 If a EUT received DC power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

TEST RESULTS


N/A (As to the EUT was powered by battery)

4.2. Occupied Bandwidth and Emission Mask Test

TEST APPLICABLE

- (a). Occupied Bandwidth: The EUT was connected to the audio signal generator and the spectrum analyzer via the main RF connector, and through an appropriate attenuator. The EUT was controlled to transmit its maximum power. Then the bandwidth of 99% power can be measured by the spectrum analyzer.
- (b). Emission Mask B: For transmitters that are equipped with an audio low-pass filter pursuant to §90.211(a), the power of any emission must be below the unmodulated carrier power (P) as follows:
- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
 - (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
 - (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.
- (c). Emission Mask D, 12.5 kHz channel bandwidth equipment: For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:
- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
 - (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
 - (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

TEST CONFIGURATION



TEST PROCEDURE


- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 The EUT was modulated by 2.5 KHz Sine wave audio signal; the level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing) and 5 kHz (25 kHz channel spacing).
- 3 Set EUT as normal operation.
- 4 Set SPA Center Frequency = fundamental frequency, RBW=300Hz, VBW= 3 KHz, span =50 KHz.
- 5 Set SPA Max hold. Mark peak, Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.
- 6 Set SPA Center Frequency=fundamental frequency, RBW=300Hz, VBW=3 KHz span=50 KHz for 25 KHz channel spacing, while RBW=100Hz, VBW=300Hz, span=50 KHz for 12.5 channel spacing.

TEST RESULTS**4.2.1 Occupied Bandwidth**


Modulation type	Channel Sparation	Test Channel	Test Frequency	99% Occupied Bandwidth	26dB Occupied Band width
FM	25KHz	Bottom	400MHz	15.13KHz	16.73KHz
		Middle	435MHz	15.03KHz	15.84KHz
		Top	470MHz	15.13KHz	15.84KHz
	12.5KHz	Bottom	400MHz	9.20KHz	10.52KHz
		Middle	435MHz	9.20KHz	10.52KHz
		Top	470MHz	9.92KHz	10.52KHz
4FSK	12.5KHz	Bottom	401MHz	7.62KHz	9.82KHz
		Middle	436MHz	7.82KHz	9.31KHz
		Top	469MHz	7.62KHz	9.42KHz
Limit		20kHz for 25KHz Channel Separation			
		11.25KHz for 12.5KHz Channel Separation			
Test Results		Compliance			

Plots of 99% and 26dB Bandwidth Measurement


Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
FM	25 KHz	400.00	15.13	16.73	20	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
FM	25 KHz	435.00	15.13	15.84	20	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
FM	25 KHz	470.00	15.03	15.84	20	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
FM	12.5 KHz	400.00	9.20	10.52	11.25	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
FM	12.5 KHz	435.00	9.20	10.52	11.25	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
FM	12.5 KHz	470.00	9.92	10.52	11.25	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
4FSK	12.5 KHz	401.00	7.62	9.82	11.25	Complicance



Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
4FSK	12.5 KHz	436.00	7.82	9.31	11.25	Compliance



Modulation Type	Channel Separation	Freq.(MHz)	99% Bandwidth (KHz)	26dB Bandwidth (KHz)	FCC Limit (KHz)	Results
4FSK	12.5 KHz	469.00	7.62	9.42	11.25	Compliance



4.2.2 Emission Mask

Modulation type	Channel Sparation	Test Channel	Test Frequency	FCC Applicable Mask	RBW
FM	25KHz	Bottom	400MHz	B	300Hz
		Middle	435MHz	B	300Hz
		Top	470MHz	B	300Hz
	12.5KHz	Bottom	400MHz	D	100Hz
		Middle	435MHz	D	100Hz
		Top	470MHz	D	100Hz
4FSK	12.5KHz	Bottom	401MHz	D	100Hz
		Middle	436MHz	D	100Hz
		Top	469MHz	D	100Hz
Test Results		Compliance			


Photos of Emission Mask Measurement

Referred as the attached plot hereinafter

Note: The blue curve represents unmodulated signal.


The black curve represents modulated signal.

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Audio Freq. (KHz)	Results
FM	25 KHz	400.00	B	300Hz	2.5	Compliance




25 kHz Channel Spacing, 400.00 MHz, 2500 Hz Audio Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Audio Freq. (KHz)	Results
FM	25 KHz	435.00	B	300Hz	2.5	Compliance




25 kHz Channel Spacing, 435.00 MHz, 2500 Hz Audio Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Audio Freq. (KHz)	Results
FM	25 KHz	470.00	B	300Hz	2.5	Compliance




25 kHz Channel Spacing, 470.00 MHz, 2500 Hz Audio Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Audio Freq. (KHz)	Results
FM	12.5 KHz	400.00	D	100Hz	2.5	Compliance




12.5 kHz Channel Spacing, 400.00 MHz, 2500 Hz Audio Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Audio Freq. (KHz)	Results
FM	12.5 KHz	435.00	D	100Hz	2.5	Compliance




12.5 kHz Channel Spacing, 435.00 MHz, 2500 Hz Audio Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Audio Freq. (KHz)	Results
FM	12.5 KHz	470.00	D	100Hz	2.5	Compliance




12.5 kHz Channel Spacing, 470.00 MHz, 2500 Hz Audio Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Results
4FSK	12.5 KHz	401.00	D	100Hz	Compliance




12.5 kHz Channel Spacing, 401.00 MHz, 4FSK Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Results
4FSK	12.5 KHz	436.00	D	100Hz	Compliance



12.5 kHz Channel Spacing, 436.00 MHz, 4FSK Modulation Only

Modulation Type	Channel Separation	Freq.(MHz)	FCC Applicable Mask	RBW	Results
4FSK	12.5 KHz	469.00	D	100Hz	Compliance



12.5 kHz Channel Spacing, 469.00 MHz, 4FSK Modulation Only

4.3. Transmitter Radiated Spurious Emission

TEST APPLICABLE



According to the TIA/EIA 603 test method, and according to Section 90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with 12.5 KHz channel bandwidth:



- 1 On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 KHz removed from f_0 : Zero dB
 - 2 On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 5.625 KHz but no more than 12.5 KHz: At least 7.27dB
 - 3 On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 12.5 KHz: At least $50 + 10 \log(P)$ dB or 70 dB, which ever is lesser attenuation.
- For transmitters designed to transmit with 25 KHz channel separation and equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as following:

- 1 On any frequency removed from the assigned frequency by more than 50 percent, but no more than 100 percent of the authorized bandwidth: At least 25 dB.
- 2 On any frequency removed from the assigned frequency by more than 100 percent, but no more than 250 percent of the authorized bandwidth: At least 35 dB.
- 3 On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log(P)$ dB.

TEST CONFIGURATION

Below 1GHz



Above 1GHz**TEST PROCEDURE**

- 1 On a test site, the EUT shall be placed on a turntable and in the position closest to the normal use as declared by the user.
- 2 The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- 3 The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- 4 The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- 5 The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- 6 The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- 7 The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- 8 The maximum signal level detected by the measuring receiver shall be noted.
- 9 The measurement shall be repeated with the test antenna set to horizontal polarization.
- 10 Replace the antenna with a proper Antenna (substitution antenna).
- 11 The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- 12 The substitution antenna shall be connected to a calibrated signal generator.

- 13 If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- 14 The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- 15 The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- 16 The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- 17 The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization

TEST RESULTS

The Transmitter Radiated Spurious Emission was performed to the Rated high power (50Watt) and Rated low power (5Watt) the datum that reported below is the worst case (Rated high power) of the two rated power conditions.

Modulation Type: FM

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 9 (25 kHz bandwidth only):
On any frequency removed from the center of the assigned channel by more than 250 percent at least:

Low: $43 + 10 \log (\text{Pwatts}) = 43 + 10 \log (51.40) = 60.11 \text{ dB}$

High: $43 + 10 \log (\text{Pwatts}) = 43 + 10 \log (53.95) = 60.32 \text{ dB}$

Calculation: Limit (dBm) = EL-43-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,
In this application, the EL is 46.99 dBm.

Limit (dBm) = $46.99 - 43 - 10 \log_{10} (53.95) = -13 \text{ dBm}$

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 9 (25 kHz bandwidth only): On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (51.40) = 67.11 \text{ dB}$

High: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (53.58) = 67.29 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) = EL-50-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,
In this application, the EL is 46.99 dBm.

Limit (dBm) = $46.99 - 50 - 10 \log_{10} (53.58) = -20 \text{ dBm}$

Modulation Type: 4FSK

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 9 (12.5 kHz Bandwidth only):

On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (49.77) = 66.97 \text{ dB}$

High: $50 + 10 \log (\text{Pwatts}) = 50 + 10 \log (52.84) = 67.23 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) = EL-50-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,
In this application, the EL is 46.99 dBm.

Limit (dBm) = $46.99 - 50 - 10 \log_{10} (52.84) = -20 \text{ dBm}$

Note: 1. In general, the worse case attenuation requirement shown above was applied.

2. The measurement frequency range from 30MHz to 5GHz.

3. *** means that the emission level is too low to be measured or at least 20 dB down than the limit.

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Bottom	H	800.000	-34.18	3200.000	-32.46	-13dBm
			V	800.000	-27.65	3200.000	-30.32	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
800.000	-66.43	H	32.25	-34.18	-13	21.18
2400.000	-41.39	H	8.12	-33.27	-13	20.27
3200.000	-43.86	H	11.40	-32.46	-13	19.46
...	...	H		...		
800.000	-59.90	V	32.25	-27.65	-13	14.65
2400.000	-36.95	V	8.12	-28.83	-13	15.83
3200.000	-43.72	V	11.40	-30.32	-13	17.32
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Middle	H	870.000	-38.14	2160.000	-37.35	-13dBm
			V	870.000	-35.64	3480.000	-34.83	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
870.000	-71.04	H	32.90	-38.14	-13	25.14
2610.000	-46.26	H	8.91	-37.35	-13	24.35
3480.000	-50.79	H	12.20	-38.59	-13	25.59
...	...	H		...		
870.000	-68.54	V	32.90	-35.64	-13	22.64
2610.000	-45.38	V	8.91	-36.47	-13	23.47
3480.000	-47.03	V	12.20	-34.83	-13	21.83
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Top	H	940.000	-37.06	3290.000	-30.49	-13dBm
			V	940.000	-36.01	3290.000	-28.96	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
940.000	-70.76	H	33.70	-37.06	-13	24.06
3290.000	-41.99	H	11.50	-30.49	-13	17.49
3760.000	-47.01	H	12.20	-34.81	-13	21.81
...	...	H		...		
940.000	-69.71	V	33.70	-36.01	-13	23.01
3290.000	-40.46	V	11.50	-28.96	-13	15.96
3760.000	-42.20	V	12.20	-30.00	-13	17.00
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Bottom	H	800.000	-34.24	3200.000	-32.41	-20dBm
			V	800.000	-27.70	2400.000	-27.94	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
800.000	-66.49	H	32.25	-34.24	-20	14.24
2400.000	-41.26	H	8.12	-33.14	-20	13.14
3200.000	-43.81	H	11.40	-32.41	-20	12.41
...	...	H		...		
800.000	-59.95	V	32.25	-27.70	-20	7.70
2400.000	-36.06	V	8.12	-27.94	-20	7.94
3200.000	-41.72	V	11.40	-30.32	-20	10.32
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Middle	H	870.000	-37.86	3480.000	-37.89	-20dBm
			V	870.000	-35.13	2610.000	-36.41	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
870.000	-70.76	H	32.90	-37.86	-20	17.86
2610.000	-46.98	H	8.91	-38.07	-20	18.07
3480.000	-50.09	H	12.20	-37.89	-20	17.89
...	...	H		...		
870.000	-68.03	V	32.90	-35.13	-20	15.13
2610.000	-45.32	V	8.91	-36.41	-20	16.41
3480.000	-48.79	V	12.20	-36.59	-20	16.59
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Top	H	940.000	-37.54	3290.000	-30.79	-20dBm
			V	940.000	-35.68	3760.000	-27.06	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
940.000	-71.24	H	33.70	-37.54	-20	17.54
3290.000	-42.29	H	11.50	-30.79	-20	10.79
3760.000	-45.53	H	12.20	-33.33	-20	13.33
...	...	H		...		
940.000	-69.36	V	33.70	-35.68	-20	15.68
3290.000	-41.43	V	11.50	-29.93	-20	9.93
3760.000	-39.26	V	12.20	-27.06	-20	7.06
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Bottom	H	802.000	-32.96	3208.000	-30.56	-20dBm
			V	802.000	-26.86	2406.000	-25.56	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
802.000	-65.21	H	32.25	-32.96	-20	12.96
2406.000	-42.69	H	8.12	-34.57	-20	14.57
3208.000	-41.96	H	11.40	-30.56	-20	10.56
...	...	H		...		
802.000	-59.11	V	32.25	-26.86	-20	6.86
2406.000	-34.68	V	8.12	-25.56	-20	5.56
3208.000	-41.04	V	11.40	-29.64	-20	9.64
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Middle	H	872.000	-36.71	3924.000	-36.31	-20dBm
			V	872.000	-33.51	3924.000	-34.18	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
872.000	-69.61	H	32.90	-36.71	-20	16.71
3052.000	-48.96	H	12.20	-36.76	-20	16.76
3924.000	-48.45	H	12.14	-36.31	-20	16.31
...	...	H		...		
872.000	-66.41	V	32.90	-33.51	-20	13.51
3052.000	-46.67	V	12.20	-34.47	-20	14.47
3924.000	-46.32	V	12.14	-34.18	-20	14.18
...	...	V		...		

Modulation Type	Channel Sparation	Test Channel	Polar	Maximum Radiated Spurious Emissions Below 1GHz		Maximum Radiated Spurious Emissions Above1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Top	H	938.000	-38.99	3283.000	-29.93	-20dBm
			V	938.000	-37.93	3752.000	-28.71	
Test Results				Compliance				

Frequency (MHz)	Reading Level (dBm)	Antenna Polarization	Transd (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
938.000	-72.69	H	33.70	-38.99	-20	18.99
3283.000	-41.43	H	11.50	-29.93	-20	9.93
3752.000	-45.76	H	12.20	-33.56	-20	13.56
...	...	H		...		
938.000	-71.63	V	33.70	-37.93	-20	17.93
3283.000	-40.49	V	11.50	-28.99	-20	8.99
3752.000	-40.91	V	12.20	-28.71	-20	8.71
...	...	V		...		

4.4. Spurious Emission on Antenna Port

TEST APPLICABLE


The same as Section 4.3

TEST PROCEDURE

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set to 100 kHz. Sufficient scans were taken to show any out of band emission up to 10th. Harmonic for the lower and the highest frequency range. Set RBW 100 kHz, VBW 300 kHz in the frequency band 30MHz to 1GHz, while set RBW=1MHz. VBW=3MHz from the 1GHz to 10th Harmonic.

The audio input was set to 0 to get the unmodulated carrier, the resulting picture is print out for each channel separation.

TEST CONFIGURATION



TEST RESULTS

Modulation Type: FM

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 9 (25 kHz bandwidth only): On any frequency removed from the center of the assigned channel by more than 250 percent at least:

Low: $43 + 10 \log (P_{\text{watts}}) = 43 + 10 \log (51.40) = 60.11 \text{ dB}$

High: $43 + 10 \log (P_{\text{watts}}) = 43 + 10 \log (53.95) = 60.32 \text{ dB}$

Calculation: Limit (dBm) = EL - 43 - 10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,

In this application, the EL is 46.99 dBm.

Limit (dBm) = 46.99 - 43 - 10log10 (53.95) = -13 dBm

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 9 (25 kHz bandwidth only): On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log (P_{\text{watts}}) = 50 + 10 \log (51.40) = 67.11 \text{ dB}$

High: $50 + 10 \log (P_{\text{watts}}) = 50 + 10 \log (53.58) = 67.29 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) = EL - 50 - 10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,

In this application, the EL is 46.99 dBm.

Limit (dBm) = 46.99 - 50 - 10log10 (53.58) = -20 dBm

Modulation Type: 4FSK

FCC Part 22.359, 74.462, 80.211 and 90.210 and RSS Gen, RSS 119 Issue 9 (12.5 kHz Bandwidth only):
On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz at least:

Low: $50 + 10 \log(P_{\text{watts}}) = 50 + 10 \log(49.77) = 66.97 \text{ dB}$

High: $50 + 10 \log(P_{\text{watts}}) = 50 + 10 \log(52.84) = 67.23 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) = EL-50-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,

In this application, the EL is 46.99 dBm.

Limit (dBm) = 46.99-50-10log10 (52.84) = -20 dBm

Note: 1. In general, the worse case attenuation requirement shown above was applied.

2. The measurement frequency range from 30MHz to 5GHz.

For Rated High Power (50Watt)


Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz	
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)
FM	25KHz	Bottom	400	773.45	-25.30	4879.76	-37.71
		Middle	435	952.87	-25.68	4599.20	-37.12
		Top	470	765.38	-25.44	2939.88	-36.77
	12.5KHz	Bottom	400	800.87	-26.25	2234.47	-37.14
		Middle	435	965.21	-25.92	2827.66	-37.21
		Top	470	943.19	-24.58	4703.41	-36.81
4FSK	12.5KHz	Bottom	401	794.06	-25.35	2963.93	-37.40
		Middle	436	912.62	-25.60	3717.43	-36.93
		Top	469	704.85	-26.05	4695.39	-35.44
Limit		-13dBm for 25KHz Channel Separation					
		-20dBm for 12.5KHz Channel Separation					
Test Results		Compliance					

For Rated Low Power (5Watt)


Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz	
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)
FM	25KHz	Bottom	400	46.83	-31.68	2803.61	-36.13
		Middle	435	30.00	-34.56	3765.53	-35.62
		Top	470	471.17	-34.91	4278.56	-36.99
	12.5KHz	Bottom	400	402.43	-34.56	2971.94	-36.10
		Middle	435	436.07	-31.66	2947.90	-35.24
		Top	470	472.47	-35.64	2907.82	-37.10
4FSK	12.5KHz	Bottom	401	47.60	-33.44	2675.35	-37.07
		Middle	436	367.52	-35.37	2426.85	-37.18
		Top	469	386.59	-35.07	2523.05	-37.04
Limit		-13dBm for 25KHz Channel Separation					
		-20dBm for 12.5KHz Channel Separation					
Test Results		Compliance					

Plots of Spurious Emission on Antenna Port Measurement**For Rated High Power (50Watt)**



Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Bottom	400	773.45	-25.30	4879.76	-37.71	-13dBm
Test Results				Compliance				




Date: 27.JUN.2010 16:28:06




Date: 27.JUN.2010 16:27:32





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Middle	435	952.87	-25.68	4599.20	-37.12	-13dBm
Test Results				Compliance				




Date: 27.JUN.2010 16:35:21




Date: 27.JUN.2010 16:34:46





Modulation Type	Channel SpARATION	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Top	470	765.38	-25.44	2939.88	-36.77	-13dBm
Test Results				Compliance				




Date: 27.JUN.2010 16:41:32




Date: 27.JUN.2010 16:41:05





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Bottom	400	800.87	-26.25	2234.47	-37.14	-20dBm
Test Results				Compliance				




Date: 27.JUN.2010 16:19:43




Date: 27.JUN.2010 16:20:23





Modulation Type	Channel SpARATION	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Middle	435	965.21	-25.92	2827.66	-37.21	-20dBm
Test Results				Compliance				




Date: 27.JUN.2010 16:28:40




Date: 27.JUN.2010 16:29:18





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Top	470	943.19	-24.58	4703.41	-36.81	-20dBm
Test Results				Compliance				




Date: 27.JUN.2010 16:36:00




Date: 27.JUN.2010 16:36:31





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Bottom	401	794.06	-25.35	29639.27	-37.40	-20dBm
Test Results				Compliance				




Date: 3.JUL.2010 19:24:21




Date: 3.JUL.2010 19:24:53





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Middle	436	912.62	-25.60	3717.43	-36.93	-20dBm
Test Results				Compliance				





Date: 3.JUL.2010 19:36:58





Date: 3.JUL.2010 19:36:36




Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Top	469	704.85	-26.05	4695.39	-35.44	-20dBm
Test Results				Compliance				






For Rated Low Power (5Watt)



Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Bottom	400	46.83	-31.68	2803.61	-36.13	-13dBm
Test Results				Compliance				




Date: 11.JUL.2010 10:46:26




Date: 11.JUL.2010 10:46:49





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Middle	435	30.00	-34.56	3765.53	-35.62	-13dBm
Test Results				Compliance				




Date: 11.JUL.2010 10:45:51




Date: 11.JUL.2010 10:43:44





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Top	470	471.17	-34.91	4278.56	-36.99	-13dBm
Test Results				Compliance				




Date: 11.JUL.2010 10:38:05




Date: 11.JUL.2010 10:37:44





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Bottom	400	402.43	-34.56	2971.94	-36.10	-20dBm
Test Results				Compliance				




Date: 11.JUL.2010 10:53:10




Date: 11.JUL.2010 10:29:21





Modulation Type	Channel SpARATION	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Middle	435	436.07	-31.66	2947.90	-35.24	-20dBm
Test Results				Compliance				




Date: 11.JUL.2010 10:28:22




Date: 11.JUL.2010 10:27:39





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Top	470	472.47	-35.64	2907.82	-37.10	-20dBm
Test Results				Compliance				




Date: 11.JUL.2010 10:21:04




Date: 11.JUL.2010 10:21:43





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Bottom	401	47.60	-33.44	2675.35	-37.07	-20dBm
Test Results				Compliance				




Date: 11.JUL.2010 11:32:29




Date: 11.JUL.2010 11:32:52





Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Middle	436	367.52	-35.37	2426.85	-37.18	-20dBm
Test Results				Compliance				




Date: 11.JUL.2010 11:37:46




Date: 11.JUL.2010 11:37:21





Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Top	469	386.59	-35.07	2523.05	-37.04	-20dBm
Test Results				Compliance				



Date: 11.JUL.2010 11:39:28



Date: 11.JUL.2010 11:39:54



4.5. Modulation Characteristics

TEST APPLICABLE

According to CFR 47 section 2.1047(a), for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000 Hz shall be measured.

TEST PROCEDURE


Modulation Limit

- 1 Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1 KHz using this level as a reference (0dB) and vary the input level from -20 to +20 dB. Record the frequency deviation obtained as a function of the input level.
- 2 Repeat step 1 with input frequency changing to 300, 1004, and 2500 Hz in sequence.

Audio Frequency Response

- 1 Configure the EUT as shown in figure 1.
- 2 Adjust the audio input for 20% of rated system deviation at 1 KHz using this level as a reference (0dB).
- 3 Vary the Audio frequency from 100 Hz to 10 KHz and record the frequency deviation.
- 4 Audio Frequency Response = $20 \log_{10} (\text{Deviation of test frequency} / \text{Deviation of 1 KHz reference})$.

TEST CONFIGURATION




TEST RESULTS

Modulation Type: FM


25 KHz Channel Separation

Modulation Level(dB)	Peak Freq. Deviation At 300 Hz(KHz)	Peak Freq. Deviation At 1004 Hz(KHz)	Peak Freq. Deviation At 1500 Hz(KHz)	Peak Freq. Deviation At 2500 Hz(KHz)
-20	0.31	0.46	0.57	0.76
-15	0.36	0.61	0.80	1.16
-10	0.45	0.96	1.33	2.03
-5	0.59	1.49	2.15	3.36
0	0.87	2.44	3.67	4.84
+5	1.36	4.20	4.89	4.84
+10	2.24	4.86	4.89	4.84
+15	3.88	4.85	4.87	4.83
+20	4.59	4.71	4.80	4.84



12.5 KHz Channel Separation

Modulation Level(dB)	Peak Freq. Deviation At 300 Hz(KHz)	Peak Freq. Deviation At 1004 H(KHz)	Peak Freq. Deviation At 1500 Hz(KHz)	Peak Freq. Deviation At 2500 Hz(KHz)
-20	0.30	0.38	0.44	0.57
-15	0.33	0.47	0.58	0.80
-10	0.37	0.65	0.86	1.26
-5	0.46	0.96	1.35	2.06
0	0.60	1.53	2.20	2.41
+5	0.89	2.43	2.45	2.41
+10	1.41	2.39	2.43	2.41
+15	2.32	2.42	2.44	2.40
+20	2.15	2.34	2.39	2.40



Modulation type: 4FSK

Channel bandwidth: 12.5 kHz

It is not applicable for devices which operate with the digitized voice/data modulation type.

b). Audio Frequency Response:**Rule Part No.: Part 2.1407(a) (b)****Method of Measurement:**

The audio frequency response was measured in accordance with TIA/EIA Specification 603 with no exception. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 300-3000Hz shall be submitted and Audio Post Limiter Low Pass Filter Response from 3.0 KHz to 50KHz. However, the audio frequency response should test from 100Hz to 5.0 KHz according to FCC Part 90.

Modulation Type: FM

The audio frequency response curve is show below.and


Test Audio Level (1 KHz and 20% maximum deviation) for 25 KHz channel separation is 28mv and 19mv for 12.5 KHz channel separation.

Note:

- 1 Not applicable to new standard. However, tests are conducted under FCC's recommendation.
- 2 The Audio Frequency Response is identical for 12.5 KHz and 25 KHz channel separation


For 25 KHz

Frequency (KHz)	Frequency Deviation (KHz)	1KHz Reference Deviation (KHz)	Audio Frequency Response (dB)
0.1	0.06	1.00	-24.4
0.2	0.05	1.00	-26.0
0.3	0.20	1.00	-13.8
0.4	0.42	1.00	-7.5
0.5	0.51	1.00	-5.8
0.6	0.64	1.00	-3.7
0.7	0.75	1.00	-2.3
0.8	0.82	1.00	-1.7
0.9	0.93	1.00	-0.6
1.0	1.00	1.00	0
1.2	1.17	1.00	1.4
1.4	1.29	1.00	2.2
1.6	1.47	1.00	3.3
1.8	1.61	1.00	4.1
2.0	1.78	1.00	5.0
2.2	1.91	1.00	5.6
2.4	2.15	1.00	6.6
2.6	2.21	1.00	6.9
2.7	2.29	1.00	7.2
2.8	2.37	1.00	7.5
3.0	2.56	1.00	8.2
3.5	0.06	1.00	-24.4
4.0	0.07	1.00	-23.0
4.5	0.06	1.00	-24.4
5.0	0.06	1.00	-24.4



For 12.5 KHz

Frequency (KHz)	Frequency Deviation (KHz)	1KHz Referece Deviation (KHz)	Audio Frequency Response (dB)
0.1	0.02	0.49	-27.6
0.2	0.02	0.49	-27.6
0.3	0.13	0.49	-11.5
0.4	0.20	0.49	-7.8
0.5	0.25	0.49	-5.8
0.6	0.31	0.49	-3.9
0.7	0.36	0.49	-2.7
0.8	0.42	0.49	-1.3
0.9	0.47	0.49	-0.4
1.0	0.49	0.49	0
1.2	0.58	0.49	1.5
1.4	0.65	0.49	2.5
1.6	0.79	0.49	4.1
1.8	0.88	0.49	5.1
2.0	0.93	0.49	5.6
2.2	1.07	0.49	6.8
2.4	1.14	0.49	7.3
2.6	1.25	0.49	8.1
2.7	1.33	0.49	8.7
2.8	1.36	0.49	8.9
3.0	1.41	0.49	9.1
3.5	0.03	0.49	-24.3
4.0	0.02	0.49	-27.6
4.5	0.02	0.49	-27.6
5.0	0.02	0.49	-27.6

**Modulation type: 4FSK**

Channel bandwidth: 12.5 kHz

It is not applicable for devices which operate with the digitized voice/data modulation type.

4.6. Frequency Stability Test


TEST APPLICABLE

- 1 According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to +60°C centigrade.
- 2 According to FCC Part 2 Section 2.1055 (a) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
- 3 Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- 4 According to §90.213, the frequency stability limit is 2.5 ppm for 12.5KHz channel separation and 5 ppm for 25KHz channel separation.

TEST PROCEDURE

The EUT was set in the climate chamber and connected to an external DC power supply. The RF output was directly connected to Spectrum Analyzer ESI 26. The coupling loss of the additional cables was recorded and taken in account for all the measurements. After temperature stabilization (approx. 20 min for each stage), the frequency for the lower, the middle and the highest frequency range was recorded. For Frequency stability Vs. Voltage the EUT was connected to a DC power supply and the voltage was adjusted in the required ranges. The result was recorded.

TEST CONFIGURATION



TEST LIMITS

According to 90.213, Transmitters used must have minimum frequency stability as specified in the following table.

Frequency Range (MHz)	Channel Bandwidth (KHz)	Frequency Tolerance (ppm)		
		Fixed and Base Stations	Mobile Stations	
			> 2 W	≤ 2 W
150-174 MHz	6.25	1.0	2.0	2.0
	12.5	2.5	5.0	5.0
	25	5.0	5.0	50.0*
421-512 MHz	6.25	0.5	1.0	1.0
	12.5	1.5	2.5	2.5
	25	2.5	5.0	5.0

- Stations operating in the 154.45 to 154.49 MHz or the 173.2 to 173.4 MHz bands must have a frequency stability of 5 ppm.
- Paging transmitters operating on paging-only frequencies must operate with frequency stability of 5 ppm in the 150-174 MHz band and 2.5 ppm in the 421-512 MHz band.

TEST RESULTS

Modulation Type	Channel Separation	Test conditions		Frequency error (ppm)		
		Voltage(V)	Temp(°C)	Bottom Channel	Middle Channel	Top Channel
Analog/FM	25KHz	13.60	-30	-1.10	-1.09	-1.03
			-20	-0.97	-0.88	-0.91
			-10	-0.66	-0.79	-0.77
			0	-0.57	-0.60	-0.61
			10	-0.53	-0.52	-0.50
			20	-0.53	-0.52	-0.50
			30	-0.50	-0.52	-0.50
			40	-0.51	-0.44	-0.46
			50	-0.47	-0.45	-0.43
		11.0 (85% Rated)	20	-0.95	-0.87	-0.84
		15.6 (115% Rated)	20	-0.46	-0.60	-0.53
Limit		2.5 ppm				
Conclusion		Complies				

Modulation Type	Channel Separation	Test conditions		Frequency error (ppm)		
		Voltage(V)	Temp(°C)	Bottom Channel	Middle Channel	Top Channel
Analog/FM	12.5KHz	13.60	-30	-1.05	-1.00	-0.99
			-20	-0.91	-0.82	-0.86
			-10	-0.65	-0.60	-0.61
			0	-0.51	-0.49	-0.50
			10	-0.46	-0.47	-0.48
			20	-0.45	-0.66	-0.58
			30	-0.45	-0.51	-0.49
			40	-0.42	-0.47	-0.44
			50	-0.42	-0.47	-0.44
		11.0 (85% Rated)	20	-0.90	-0.79	-0.81
		15.6 (115% Rated)	20	-0.41	-0.48	-0.42
Limit			1.5 ppm			
Conclusion			Complies			

Modulation Type	Channel Separation	Test conditions		Frequency error (ppm)		
		Voltage(V)	Temp(°C)	Bottom Channel	Middle Channel	Top Channel
Digital/4FSK	12.5KHz	13.60	-30	-1.02	-1.01	-0.99
			-20	-0.92	-0.84	-0.82
			-10	-0.60	-0.58	-0.55
			0	-0.44	-0.47	-0.44
			10	-0.43	-0.40	-0.41
			20	-0.43	-0.40	-0.41
			30	-0.40	-0.41	-0.40
			40	-0.40	-0.40	-0.38
			50	-0.39	-0.38	-0.38
		11.0 (85% Rated)	20	-0.88	-0.86	-0.87
		15.6 (115% Rated)	20	-0.42	-0.41	-0.39
		Limit			1.5 ppm	
Conclusion			Complies			

4.7. Maximum Transmitter Power

TEST APPLICABLE

Per FCC «2.1046 and «90.205: Maximum ERP is dependent upon the station's antenna HAAT and required service area..

TEST PROCEDURE


Measurements shall be made to establish the radio frequency power delivered by the transmitter the standard output termination. The power output shall be monitored and recorded and no adjustment shall be made to the transmitter after the test has begun, except as noted bellow:

If the power output is adjustable, measurements shall be made for the highest and lowest power levels.

The EUT connect to the Receiver through 20 dB attenuator.

Measurement with Spectrum Analyzer ESI 26 conducted, external power supply with 13.60 V stabilized supply voltage.

TEST CONFIGURATION




The EUT was directly connected to a RF Communication Test Set by a 20 dB attenuator

TEST RESULTS


Modulation Type	Channel Separation	Test Channel	Test Frequency	Maximum Transmitter Power at Rated High Power Level(dBm)	Maximum Transmitter Power at Rated Low Power Level(dBm)
Analog/FM	25KHz	Bottom Channel	400MHz	47.32	38.06
		Middle Channel	435MHz	47.11	38.15
		Top Channel	470MHz	47.25	38.01
	12.5KHz	Bottom Channel	400MHz	47.29	38.06
		Middle Channel	435MHz	47.11	38.11
		Top Channel	470MHz	47.24	37.94
Digital/4FSK	12.5KHz	Bottom Channel	401MHz	47.23	38.31
		Middle Channel	436MHz	46.97	38.15
		Top Channel	469MHz	47.22	37.97
Limit		The limit is dependent upon the station's antenna HAAT and required service area.			
Test Results		Compliance			

Plots of Maximum Transmitter Power Measurement


Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	25 KHz	400.00	50	47.32	Varies	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	25 KHz	435.00	50	47.11	Varies	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	25 KHz	470.00	50	47.25	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	12.5 KHz	400.00	50	47.29	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	12.5 KHz	435.00	50	47.11	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	12.5 KHz	470.00	50	47.24	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
4FSK	12.5 KHz	401.00	50	47.23	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
4FSK	12.5 KHz	436.00	50	46.97	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
4FSK	12.5 KHz	469.00	50	47.22	Varies	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	25 KHz	400.00	5	38.06	Varies	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	25 KHz	435.00	5	38.15	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	25 KHz	470.00	5	38.01	Varies	Compliance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	12.5 KHz	400.00	5	38.06	Varies	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	12.5 KHz	435.00	5	38.11	Varies	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
FM	12.5 KHz	470.00	5	37.94	Varies	Complicance




Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
4FSK	12.5 KHz	401.00	5	38.31	Varies	Complicance



Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
4FSK	12.5 KHz	436.00	5	38.15	Varies	Compliance



Modulation Type	Channel Separation	Freq.(MHz)	Rated Power (Watt)	Measurement (dBm)	FCC Limit	Results
4FSK	12.5 KHz	469.00	50	37.97	Varies	Compliance



4.8. Transmitter Frequency Behavior

TEST APPLICABLE

Section 90.214

Transient frequencies must be within the maximum frequency difference limits during the time intervals indicated:


Time intervals ^{1, 2}	Maximum frequency difference ³	All equipment	
		150 to 174 MHz	421 to 512MHz
Transient Frequency Behavior for Equipment Designed to Operate on 25 KHz Channels			
t ₁ ⁴	± 25.0 KHz	5.0 ms	10.0 ms
t ₂	± 12.5 KHz	20.0 ms	25.0 ms
t ₃ ⁴	± 25.0 KHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 12.5 KHz Channels			
t ₁ ⁴	± 12.5 KHz	5.0 ms	10.0 ms
t ₂	± 6.25 KHz	20.0 ms	25.0 ms
t ₃ ⁴	± 12.5 KHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 6.25 KHz Channels			
t ₁ ⁴	±6.25 KHz	5.0 ms	10.0 ms
t ₂	±3.125 KHz	20.0 ms	25.0 ms
t ₃ ⁴	±6.25 KHz	5.0 ms	10.0 ms

- t_{on} is the instant when a 1 KHz test signal is completely suppressed, including any capture time due to phasing.
 t_1 is the time period immediately following t_{on} .
 t_2 is the time period immediately following t_1 .
 t_3 is the time period from the instant when the transmitter is turned off until t_{off} .
 t_{off} is the instant when the 1 KHz test signal starts to rise.
- During the time from the end of t_2 to the beginning of t_3 , the frequency difference must not exceed the limits specified in § 90.213.
- Difference between the actual transmitter frequency and the assigned transmitter frequency.
- If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.

TEST PROCEDURE

TIA/EIA-603 2.2.19

TEST CONFIGURATION




TEST RESULTS


Please refer to the following plots.

Modulation Type: FM


Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation-----Off – On




Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation-----On - Off



Transmitter Frequency Behaviour @ 25 KHz Channel Separation-----Off – On




Transmitter Frequency Behaviour @ 25 KHz Channel Separation-----On - Off




Modulation Type: 4FSK

Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation-----Off – On



Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation-----On - Off



4.9. Receiver Radiated Spurious Emission

TEST APPLICABLE


The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$


Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



TEST PROCEDURE

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- 3 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4 Repeat above procedures until all frequency measurements have been completed.

RECEIVER RADIATED SPOUIOUS LIMIT

For unintentional device, according to § 15.109(a) and RSS-Gen, except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

TEST RESULTS


The Radiated Measurement are performed to the three channels (the top channel, the middle channel and the bottom channel), the datum recorded below is the worst case for each channel separation; and the EUT shall be scanned from 30 MHz to the 5th harmonic of the highest oscillator frequency in the digital devices or 1 GHz whichever is higher.

Modulation Type	Channel Separation	Test Frequency (MHz)	Polar.	Maximum Radiated Emissions		FCC Limit (dBuV/m)
				Frequency (MHz)	Datum (dBuV/m)	
FM	25 KHz	400.00	H	928.08	25.20	46
			V	916.41	25.70	
Test Results			Compliance			

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength

Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09


***MEASUREMENT RESULT: "HTW0515405_red"***

5/15/2010 8:06PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	17.30	-10.7	40.0	22.7	Peak	100.0	355.00	VERTICAL
86.372745	11.20	-20.5	40.0	28.8	Peak	100.0	355.00	VERTICAL
164.128257	10.10	-23.3	43.5	33.4	Peak	100.0	270.00	VERTICAL
288.537074	12.50	-17.1	46.0	33.5	Peak	100.0	18.00	VERTICAL
533.466934	18.00	-11.8	46.0	28.0	Peak	100.0	169.00	VERTICAL
916.412826	25.70	-3.8	46.0	20.3	Peak	100.0	169.00	VERTICAL

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09

***MEASUREMENT RESULT: "HTW0515406_red"***

5/15/2010 9:12PM


Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	18.40	-10.7	40.0	21.6	Peak	100.0	318.00	HORIZONTAL
76.653307	18.10	-22.0	40.0	21.9	Peak	300.0	153.00	HORIZONTAL
98.036072	13.50	-19.8	43.5	30.0	Peak	300.0	79.00	HORIZONTAL
288.537074	17.70	-17.1	46.0	28.3	Peak	100.0	129.00	HORIZONTAL
517.915832	18.60	-11.9	46.0	27.4	Peak	100.0	271.00	HORIZONTAL
928.076152	25.20	-3.5	46.0	20.8	Peak	100.0	360.00	HORIZONTAL

Modulation Type	Channel Separation	Test Frequency (MHz)	Polar.	Maximum Radiated Emissions		FCC Limit (dBuV/m)
				Frequency (MHz)	Datum (dBuV/m)	
FM	12.5 KHz	400.00	H	950.40	25.80	46
			V	933.91	25.90	
Test Results			Compliance			

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength

Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09


***MEASUREMENT RESULT: "HTW0515404_red"***

5/15/2010 8:04PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	17.20	-10.7	40.0	22.8	Peak	100.0	237.00	VERTICAL
88.316633	13.10	-20.3	43.5	30.4	Peak	100.0	22.00	VERTICAL
134.969940	11.30	-20.7	43.5	32.2	Peak	100.0	284.00	VERTICAL
269.098196	12.60	-18.1	46.0	33.4	Peak	100.0	5.00	VERTICAL
537.354709	18.10	-11.8	46.0	27.9	Peak	100.0	170.00	VERTICAL
933.907816	25.90	-3.4	46.0	20.1	Peak	100.0	284.00	VERTICAL

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09

***MEASUREMENT RESULT: "HTW0515403_red"***


5/15/2010 8:00PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	17.80	-10.7	40.0	22.2	Peak	100.0	253.00	HORIZONTAL
76.653307	19.10	-22.0	40.0	20.9	Peak	300.0	136.00	HORIZONTAL
98.036072	14.00	-19.8	43.5	29.5	Peak	300.0	89.00	HORIZONTAL
269.098196	19.90	-18.1	46.0	26.1	Peak	100.0	100.00	HORIZONTAL
531.523046	17.70	-11.8	46.0	28.3	Peak	100.0	223.00	HORIZONTAL
951.402806	25.80	-3.4	46.0	20.2	Peak	100.0	177.00	HORIZONTAL

Modulation Type	Channel Separation	Test Frequency (MHz)	Polar.	Maximum Radiated Emissions		FCC Limit (dBuV/m)
				Frequency (MHz)	Datum (dBuV/m)	
4FSK	12.5 KHz	469.00	H	939.74	26.30	46
			V	926.13	25.00	
Test Results			Compliance			

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09


***MEASUREMENT RESULT: "HTW0515407_red"***

5/15/2010 9:14PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	17.90	-10.7	40.0	22.1	Peak	300.0	18.00	HORIZONTAL
76.653307	18.70	-22.0	40.0	21.3	Peak	300.0	125.00	HORIZONTAL
101.923848	13.70	-19.7	43.5	29.8	Peak	300.0	105.00	HORIZONTAL
269.098196	18.30	-18.1	46.0	27.7	Peak	100.0	103.00	HORIZONTAL
539.298597	17.40	-11.8	46.0	28.6	Peak	300.0	267.00	HORIZONTAL
939.739479	26.30	-3.2	46.0	19.7	Peak	100.0	43.00	HORIZONTAL

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09

***MEASUREMENT RESULT: "HTW0515408_red"***

5/15/2010 9:17PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	19.50	-10.7	40.0	20.5	Peak	100.0	116.00	VERTICAL
80.541082	9.90	-21.4	40.0	30.1	Peak	100.0	89.00	VERTICAL
119.418838	11.00	-18.8	43.5	32.5	Peak	100.0	122.00	VERTICAL
269.098196	13.30	-18.1	46.0	32.7	Peak	100.0	203.00	VERTICAL
537.354709	18.50	-11.8	46.0	27.5	Peak	100.0	190.00	VERTICAL
926.132265	25.00	-3.5	46.0	21.0	Peak	100.0	76.00	VERTICAL

4.10. Receiver Conducted Spurious Emssion


TEST APPLICABLE

The same as Section 4.3

TEST PROCEDURE

The spectrum analyzer was connected to the RF output power of the EUT, the EUT was setup in receiving mode; The RBW of the spectrum analyzer was set to 100 kHz and the VBW set to 300 KHz below the test frequency 1GHz. While the RBW of the spectrum analyzer was set to the 1MHz and VBW set to the 3MHz from 1GHz to the 10th harmonic.

TEST CONFIGURATION





LIMIT

The power at the antenna terminal shall not exceed 2.0 nanowatts (-57dBm).



TEST RESULTS

The Receiver Conducted Spurious Emssions Measurement is performed to the three channels (the top channel, the middle channel and the bottom channel), the datums recorded below were for the three channels; and the EUT shall be scanned from 30 MHz to the 6GHz.



Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Bottom	400	982.51	-86.09	5398.80	-77.51	-57dBm
Test Results				Compliance				





Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Middle	435	951.40	-85.99	5709.42	-76.79	-57dBm
Test Results				Compliance				





Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	25KHz	Top	470	745.35	-86.08	5619.24	-78.23	-57dBm
Test Results				Compliance				





Modulation Type	Channel SpARATION	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Bottom	400	933.91	-85.94	5398.80	-77.51	-57dBm
Test Results				Compliance				





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Middle	435	815.33	-86.65	5829.66	-76.06	-57dBm
Test Results				Compliance				





Modulation Type	Channel Sparation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
FM	12.5KHz	Top	470	799.78	-85.80	5939.88	-77.61	-57dBm
Test Results				Compliance				



Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Bottom	401	739.52	-85.08	5408.82	-75.89	-57dBm
Test Results				Compliance				



Modulation Type	Channel SpARATION	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Middle	436	517.92	-84.69	5959.92	-75.34	-57dBm
Test Results				Compliance				



Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	Maximum Conducted Spurious Emissions Below 1GHz		Maximum Conducted Spurious Emissions Above 1GHz		FCC Limit
				Frequency (MHz)	Datum (dBm)	Frequency (MHz)	Datum (dBm)	
4FSK	12.5KHz	Top	469	694.81	-85.28	5619.24	-75.52	-57dBm
Test Results				Compliance				

