

# FCC PART 22, 74, 80

# **TEST REPORT**

For

# **Hytera Communications Corporation Limited**

Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, 518057 China

FCC ID: YAMMD78XGU2

Report Type:

Product Type:

Class II Permissive Change

Digital Mobile Radio

Kiangguang . Kong

Report Number: RDG170907003-00A1

**Report Date:** 2017-09-27

Xiangguang Kong

Reviewed By: EMC Engineer

**Prepared By:** Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone,

Shenzhen, Guangdong, China Tel: +86-755-33320018

Fax: +86-755-33320008 www.baclcorp.com.cn

**Note**: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

# TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
MEASUREMENT UNCERTAINTY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
EXTERNAL I/O CABLE	
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	8
§1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	9
APPLICABLE STANDARD	
RESULT	
FCC §2.1046 & § 22.727 & §74.461 & §80.215 - RF OUTPUT POWER	
Applicable Standard	
TEST PROCEDURE  TEST DATA	
FCC §2.1047 - MODULATION CHARACTERISTIC	
APPLICABLE STANDARD	
TEST PROCEDURE	
	12
FCC §2.1049 & § 22.359 & § 22.731 & §74.462 & § 80.205 & § 80.211 – OCCUPIED BANDWIDTH & EMISSION MASK	38
APPLICABLE STANDARD	38
TEST PROCEDURE	
Test Data	39
FCC §2.1051 & §22.861 & §74.462 & § 80.211 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	56
APPLICABLE STANDARD	56
TEST PROCEDURE	
Test Data	56
FCC §2.1053 & §22.861 & §74.462 & § 80.211 - RADIATED SPURIOUS EMISSIONS	66
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST DATA	
FCC §2.1055 & § 22.355 & §74.464 & § 80.209 - FREQUENCY STABILITY	70
APPLICABLE STANDARD	
TEST PROCEDURE	
Test Data	70

### **GENERAL INFORMATION**

### **Product Description for Equipment under Test (EUT)**

The Hytera Communications Corporation Limited's product, model number: MD782G U(2) (FCC ID: YAMMD78XGU2) in this report is a Digital Mobile Radio which was measured approximately: 196 mm (L) x 174 mm (W) x 60 mm (H), rated input voltage: DC 13.60V.

Report No.: RDG170907003-00A1

Notes: This series products model:  $MD782\ U(2)$  and  $MD782G\ U(2)$  are electrically identical. Model  $MD782G\ U(2)$  was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

\* All measurement and test data in this report was gathered from production sample serial number: 170907003 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-09-07.

### **Objective**

This test report is prepared on behalf of *Hytera Communications Corporation Limited* in accordance with Part 2, and Part 22, 74, 80 of the Federal Communication Commissions rules.

This is a CIIPC application of the device; the differences between the original device and the current one are as follows:

- (1). Adding standars FCC Part 22, 74, 80.
- (2) Changing the model number to "MD782G U(2),MD782 U(2)".

#### **Related Submittal(s)/Grant(s)**

No Related Submittal(s)/Grant(s).

#### **Test Methodology**

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 22 – Public Mobile Service

Part 74 – Experimental Radio, Auxiliary, Special Broadcast and other Program Distributonal Service

Part 80 – Stantions in the Maritme Service

Applicable Standards: TIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 22, 74, 80 Page 3 of 75

### **Measurement Uncertainty**

Parameter	uncertainty
Occupied Channel Bandwidth	±5%
RF output power, conducted	±1.5dB
Unwanted Emission, conducted	±1.5dB
All emissions, radiated	±4.88dB
Temperature	±1 °C
Supply voltages	±0.4%

Report No.: RDG170907003-00A1

### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP(Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 22, 74, 80 Page 4 of 75

# **SYSTEM TEST CONFIGURATION**

### **Description of Test Configuration**

The system was configured for testing in a test mode which has been done in the factory.

Report No.: RDG170907003-00A1

#### **EUT Exercise Software**

No exercise software was used.

### **Special Accessories**

No special accessory was used.

# **Equipment Modifications**

No modification was made to the EUT tested.

## **Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
N/A	Load	N/A	N/A
TDK-Lambda	DC Power Supply	Z60-14-L-C	LOC-645A242-0004

### **External I/O Cable**

Cable Description	Length (m)	From Port	То
Un-Shileding Detachable DC Power Cable	2.0	DC Power Supply	EUT

FCC Part 22, 74, 80 Page 5 of 75

# **Block Diagram of Test Setup**



FCC Part 22, 74, 80 Page 6 of 75

# SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§1.1307(b), §2.1091	Maximum Permissible exposure (MPE)	Compliance
\$2.1046; \$ 22.727; \$74.461; \$ 80.215	RF Output Power	Compliance
§2.1047	Modulation Characteristic	Compliance
\$2.1049; § 22.359; § 22.731; §74.462; § 80.205; § 80.211	Occupied Bandwidth & Emission Mask	Compliance
\$2.1051; \$22.861; \$74.462; \$ 80.211	Spurious Emission at Antenna Terminal	Compliance
\$2.1053; \$22.861; \$74.462; \$ 80.211	Spurious Radiated Emissions	Compliance
§2.1055; § 22.355; §74.464; § 80.209	Frequency Stability	Compliance

Report No.: RDG170907003-00A1

FCC Part 22, 74, 80 Page 7 of 75

# TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date			
	Radiated Emission Test							
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28			
Rohde & Schwarz	Signal Generator	FSIQ26	8386001028	2017-04-24	2018-04-24			
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-17	2017-12-16			
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-02-14	2018-02-14			
НР	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19			
Anritsu	Signal Generator	68369B	004114	2016-12-05	2017-12-05			
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07			
COM POWER	Dipole Antenna	AD-100	041000	NCR	NCR			
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17			
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19			
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19			
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19			
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22			
		RF Conducted T	`est					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2016-12-05	2017-12-05			
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2016-11-22	2017-11-22			
TDK-Lambda	DC Power Supply	Z60-14-L-C	LOC-645A242- 0004	NCR	NCR			
HP Agilent	RF Communication Test Set	HP8920	3325U00859	2017-05-07	2018-05-07			
Ducommun technologies	RF Cable	RG-214	3	2017-05-22	2017-11-22			
WEINSCHEL	30dB Attenuator	53-30-43	PG633	2017-05-22	2017-11-22			

Report No.: RDG170907003-00A1

FCC Part 22, 74, 80 Page 8 of 75

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

# §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### **Applicable Standard**

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Controlled Exposure

Report No.: RDG170907003-00A1

	Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)			
0.3-1.34	614	1.63	*(100)	6			
1.34-30	1824/f	4.89/f	*(900/f <sup>2</sup> )	6			
30-300	61.4	0.163	1.0	6			
300-1500	/	/	f/300	6			
1500-100,000	/	/	5.0	6			

f = frequency in MHz

#### Result

#### **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency	Ante	nna Gain	<b>Conducted Power</b>	Evaluation	Power	Strictest
Range (MHz)	(dBi)	(numeric)	(mW)	Distance (cm)	Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
450-520	5.5	3.55	22500	100	0.636	1.5

Note: The rated max tune-up output power is 46.53dBm(45W), 50% duty cycle was used in evaluation, so the power is 22500mW

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 100cm from nearby persons.

Result: Compliance

FCC Part 22, 74, 80 Page 9 of 75

<sup>\* =</sup> Plane-wave equivalent power density

# FCC §2.1046 & § 22.727 & §74.461 & §80.215 - RF OUTPUT POWER

Report No.: RDG170907003-00A1

### **Applicable Standard**

FCC §2.1046, § 22.727, §74.461, § 80.215

#### **Test Procedure**

Conducted RF Output Power:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer Setting:

R B/W Video B/W 100 kHz 300 kHz

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-09-11.

Test Mode: Transmitting

Test Result: Compliance. Please refer to following table.

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power	Conducted Output Power (dBm)	Conducted Output Power (W)	Note
		453.2125	Н	46.16	41.30	For Part 74
Disital	10.5		L	36.18	4.15	FOR Part 74
Digital	1 12.5	4545	Н	46.17	41.40	For Part 22
		434.3	L	36.21	4.18	For Part 22

FCC Part 22, 74, 80 Page 10 of 75

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power	Conducted Output Power (dBm)	Conducted Output Power (W)	Note	
		453.2125	High	46.19	41.59	For Part 74	
	12.5	433.2123	Low	36.37	4.34	Por Fait 74	
	12.3	454.5	High	46.19	41.59	For Part 22	
			434.3	Low	36.43	4.40	FOI Part 22
A = 1 =		453.2125	High	46.18	41.50	For Part 74	
Analog			Low	36.31	4.28	FOI Fait /4	
	25	454.5	High	46.19	41.59	For Part 22	
		25	434.3	Low	36.37	4.34	FOR Part 22
		450 2125	High	46.22	41.88	For Part 80	
		458.2125	Low	36.44	4.41	FOI Part 80	

Note: The high rated power is 45W, Limit is 36W-54W. The low rated power is 5W, Limit is 4W-6W.

FCC Part 22, 74, 80 Page 11 of 75

# FCC §2.1047 - MODULATION CHARACTERISTIC

### **Applicable Standard**

#### FCC§2.1047:

(a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.

Report No.: RDG170907003-00A1

(b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

### **Test Procedure**

Test Method: TIA/EIA-603 2.2.3

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-09-25.

Test Mode: Transmitting

Result: Compliance.

FCC Part 22, 74, 80 Page 12 of 75

# **Analog Modulation:**


## MODULATION LIMITING

Report No.: RDG170907003-00A1

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz

	Instant	aneous	Stead	y-state	
Audio Frequency (Hz)	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	FCC Limit [kHz]
300	2.343	0.073	2.340	0.071	2.5
400	2.347	0.086	2.343	0.085	2.5
500	2.351	0.105	2.344	0.104	2.5
600	2.347	0.118	2.342	0.115	2.5
700	2.335	0.128	2.330	0.124	2.5
800	2.327	0.137	2.324	0.133	2.5
900	2.316	0.159	2.311	0.156	2.5
1000	2.306	0.170	2.302	0.168	2.5
1200	2.281	0.187	2.275	0.185	2.5
1400	2.286	0.225	2.281	0.221	2.5
1600	2.308	0.249	2.301	0.245	2.5
1800	2.340	0.290	2.335	0.285	2.5
2000	2.368	0.312	2.362	0.310	2.5
2100	2.364	0.333	2.358	0.329	2.5
2200	2.354	0.354	2.349	0.348	2.5
2300	2.328	0.366	2.321	0.356	2.5
2400	2.392	0.367	2.385	0.355	2.5
2500	2.369	0.386	2.361	0.381	2.5
2600	2.242	0.403	2.236	0.398	2.5
2700	2.207	0.406	2.201	0.399	2.5
2800	2.169	0.407	2.165	0.401	2.5
2900	2.113	0.424	2.107	0.415	2.5
3000	2.055	0.418	2.049	0.413	2.5

FCC Part 22, 74, 80 Page 13 of 75



FCC Part 22, 74, 80 Page 14 of 75


# **Audio Frequency Response**

Report No.: RDG170907003-00A1

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-9.84
400	-7.70
500	-5.45
600	-3.93
700	-2.81
800	-2.00
900	-0.97
1000	0.00
1200	1.05
1400	2.71
1600	3.59
1800	5.03
2000	5.65
2100	6.29
2200	6.79
2300	7.00
2400	7.15
2500	7.62
2600	7.92
2700	7.94
2800	8.04
2900	8.41
3000	8.31


FCC Part 22, 74, 80 Page 15 of 75



FCC Part 22, 74, 80 Page 16 of 75

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-38.55	0.0
4.0	-47.37	-12.5
5.0	-62.53	-22.2
6.0	-60.98	-30.1
7.0	-75.04	-36.8
8.0	-79.50	-42.6
9.0	-79.05	-47.7
10.0	-91.47	-52.3
12.0	-96.62	-60.2
14.0	-87.75	-66.9
16.0	-87.04	-72.7
18.0	-95.33	-77.8
20.0	-85.85	-82.5



FCC Part 22, 74, 80 Page 17 of 75


## MODULATION LIMITING

Report No.: RDG170907003-00A1

Carrier Frequency: 453.2125 MHz, Channel Separation= 25 kHz

	Instant	aneous	Steady	y-state	
Audio Frequency (Hz)	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	FCC Limit [kHz]
300	4.663	0.110	4.658	0.108	5.000
400	4.661	0.149	4.659	0.146	5.000
500	4.686	0.172	4.683	0.170	5.000
600	4.693	0.213	4.690	0.212	5.000
700	4.672	0.227	4.668	0.223	5.000
800	4.667	0.257	4.664	0.254	5.000
900	4.634	0.289	4.632	0.286	5.000
1000	4.589	0.325	4.586	0.322	5.000
1200	4.592	0.361	4.590	0.358	5.000
1400	4.534	0.431	4.531	0.429	5.000
1600	4.620	0.477	4.616	0.475	5.000
1800	4.856	0.558	4.855	0.556	5.000
2000	4.997	0.601	4.994	0.598	5.000
2100	4.998	0.643	4.995	0.640	5.000
2200	4.987	0.676	4.985	0.674	5.000
2300	4.940	0.691	4.936	0.689	5.000
2400	4.837	0.707	4.836	0.704	5.000
2500	4.696	0.744	4.688	0.740	5.000
2600	4.527	0.771	4.520	0.768	5.000
2700	4.325	0.778	4.322	0.774	5.000
2800	4.143	0.783	4.140	0.781	5.000
2900	4.003	0.821	4.000	0.815	5.000
3000	3.870	0.807	3.865	0.801	5.000

FCC Part 22, 74, 80 Page 18 of 75



FCC Part 22, 74, 80 Page 19 of 75


# **Audio Frequency Response**

Report No.: RDG170907003-00A1

Carrier Frequency: 453.2125 MHz, Channel Separation= 25 kHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-9.90
400	-7.62
500	-5.38
600	-3.99
700	-2.90
800	-1.96
900	-0.83
1000	0.00
1200	1.27
1400	2.95
1600	3.86
1800	5.28
2000	6.02
2100	6.59
2200	7.10
2300	7.24
2400	7.35
2500	7.74
2600	8.08
2700	8.06
2800	8.11
2900	8.46
3000	8.34


FCC Part 22, 74, 80 Page 20 of 75



Page 21 of 75 FCC Part 22, 74, 80

Carrier Frequency: 453.2125 MHz, Channel Separation= 25 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-43.06	0.0
4.0	-53.14	-7.5
5.0	-64.13	-13.3
6.0	-66.11	-18.1
7.0	-76.48	-22.1
8.0	-79.42	-25.6
9.0	-84.82	-28.6
10.0	-86.52	-31.4
15.0	-95.44	-41.9
20.0	-86.78	-50.0
30.0	-86.14	-50.0
40.0	-88.46	-50.0
50.0	-91.37	-50.0
60.0	-90.15	-50.0
70.0	-85.48	-50.0



FCC Part 22, 74, 80 Page 22 of 75


## MODULATION LIMITING

Report No.: RDG170907003-00A1

Carrier Frequency: 454.5 MHz, Channel Separation=12.5 kHz

	Instant	aneous	Stead	y-state	
Audio Frequency (Hz)	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	FCC Limit [kHz]
300	2.398	0.069	2.405	0.078	2.5
400	2.423	0.092	2.277	0.090	2.5
500	2.319	0.100	2.277	0.100	2.5
600	2.425	0.125	2.320	0.120	2.5
700	2.399	0.124	2.378	0.140	2.5
800	2.360	0.143	2.378	0.140	2.5
900	2.360	0.165	2.354	0.162	2.5
1000	2.341	0.186	2.228	0.165	2.5
1200	2.236	0.203	2.208	0.201	2.5
1400	2.230	0.241	2.346	0.238	2.5
1600	2.343	0.266	2.278	0.252	2.5
1800	2.407	0.295	2.282	0.290	2.5
2000	2.292	0.307	2.417	0.317	2.5
2100	2.317	0.338	2.292	0.346	2.5
2200	2.388	0.360	2.287	0.364	2.5
2300	2.371	0.383	2.296	0.373	2.5
2400	2.458	0.372	2.312	0.350	2.5
2500	2.334	0.392	2.428	0.396	2.5
2600	2.308	0.408	2.270	0.404	2.5
2700	2.155	0.421	2.165	0.404	2.5
2800	2.145	0.412	2.223	0.396	2.5
2900	2.170	0.430	2.161	0.411	2.5
3000	2.120	0.413	2.094	0.409	2.5

FCC Part 22, 74, 80 Page 23 of 75



FCC Part 22, 74, 80 Page 24 of 75


# **Audio Frequency Response**

Report No.: RDG170907003-00A1

Carrier Frequency: 454.5 MHz, Channel Separation=12.5 kHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-9.74
400	-7.66
500	-5.42
600	-3.88
700	-2.76
800	-1.96
900	-0.95
1000	0.00
1200	1.08
1400	2.73
1600	3.61
1800	5.06
2000	5.68
2100	6.32
2200	6.82
2300	7.04
2400	7.19
2500	7.65
2600	7.94
2700	7.97
2800	8.07
2900	8.43
3000	8.34


FCC Part 22, 74, 80 Page 25 of 75



FCC Part 22, 74, 80 Page 26 of 75

Carrier Frequency: 454.5 MHz, Channel Separation=12.5 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-38.35	0.0
4.0	-44.37	-12.5
5.0	-56.53	-22.2
6.0	-67.18	-30.1
7.0	-74.14	-36.8
8.0	-74.80	-42.6
9.0	-78.25	-47.7
10.0	-86.37	-52.3
12.0	-96.82	-60.2
14.0	-86.75	-66.9
16.0	-87.14	-72.7
18.0	-89.23	-77.8
20.0	-89.05	-82.5



FCC Part 22, 74, 80 Page 27 of 75


## MODULATION LIMITING

Report No.: RDG170907003-00A1

Carrier Frequency: 454.5 MHz, Channel Separation= 25 kHz

	Instant	aneous	Stead	y-state	
Audio Frequency (Hz)	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	FCC Limit [kHz]
300	4.710	0.117	4.703	0.104	5.000
400	4.605	0.156	4.625	0.152	5.000
500	4.653	0.167	4.641	0.175	5.000
600	4.760	0.218	4.724	0.229	5.000
700	4.608	0.233	4.706	0.230	5.000
800	4.635	0.254	4.730	0.261	5.000
900	4.699	0.305	4.606	0.282	5.000
1000	4.622	0.322	4.621	0.317	5.000
1200	4.566	0.356	4.657	0.365	5.000
1400	4.600	0.446	4.568	0.445	5.000
1600	4.573	0.473	4.573	0.491	5.000
1800	4.891	0.564	4.792	0.551	5.000
2000	4.986	0.617	4.975	0.594	5.000
2100	4.966	0.659	4.930	0.645	5.000
2200	4.965	0.683	4.958	0.671	5.000
2300	4.898	0.707	4.990	0.695	5.000
2400	4.774	0.723	4.810	0.710	5.000
2500	4.751	0.761	4.643	0.755	5.000
2600	4.560	0.786	4.475	0.774	5.000
2700	4.292	0.784	4.270	0.790	5.000
2800	4.098	0.780	4.084	0.797	5.000
2900	4.049	0.837	3.944	0.821	5.000
3000	3.794	0.813	3.909	0.807	5.000

FCC Part 22, 74, 80 Page 28 of 75



FCC Part 22, 74, 80 Page 29 of 75


# **Audio Frequency Response**

Report No.: RDG170907003-00A1

Carrier Frequency: 454.5 MHz, Channel Separation= 25 kHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-9.84
400	-7.58
500	-5.34
600	-3.94
700	-2.88
800	-1.92
900	-0.81
1000	0.00
1200	1.28
1400	2.97
1600	3.87
1800	5.29
2000	6.05
2100	6.58
2200	7.11
2300	7.25
2400	7.36
2500	7.74
2600	8.09
2700	8.07
2800	8.12
2900	8.48
3000	8.36

FCC Part 22, 74, 80 Page 30 of 75




FCC Part 22, 74, 80 Page 31 of 75

Audio frequency lows pass filter response

Carrier Frequency: 454.5 MHz, Channel Separation= 25 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-38.76	0.0
4.0	-51.64	-7.5
5.0	-61.43	-13.3
6.0	-68.51	-18.1
7.0	-75.48	-22.1
8.0	-84.82	-25.6
9.0	-84.42	-28.6
10.0	-81.32	-31.4
15.0	-94.44	-41.9
20.0	-86.58	-50.0
30.0	-85.94	-50.0
40.0	-91.56	-50.0
50.0	-86.87	-50.0
60.0	-90.45	-50.0
70.0	-85.48	-50.0



FCC Part 22, 74, 80 Page 32 of 75


## MODULATION LIMITING

Report No.: RDG170907003-00A1

Carrier Frequency: 458.2125 MHz, Channel Separation= 25 kHz

	Instantaneous		Steady-state		
Audio Frequency (Hz)	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	FCC Limit [kHz]
300	4.639	0.107	4.623	0.113	5.000
400	4.718	0.156	4.726	0.142	5.000
500	4.732	0.168	4.740	0.166	5.000
600	4.626	0.229	4.644	0.208	5.000
700	4.605	0.232	4.643	0.230	5.000
800	4.734	0.252	4.642	0.251	5.000
900	4.581	0.285	4.695	0.293	5.000
1000	4.512	0.332	4.554	0.318	5.000
1200	4.540	0.366	4.646	0.364	5.000
1400	4.588	0.437	4.487	0.444	5.000
1600	4.564	0.482	4.539	0.480	5.000
1800	4.813	0.574	4.928	0.573	5.000
2000	4.942	0.607	4.970	0.594	5.000
2100	4.984	0.659	4.973	0.656	5.000
2200	4.941	0.692	4.919	0.680	5.000
2300	4.865	0.688	4.853	0.706	5.000
2400	4.793	0.713	4.860	0.700	5.000
2500	4.630	0.750	4.731	0.747	5.000
2600	4.483	0.767	4.556	0.773	5.000
2700	4.248	0.784	4.290	0.790	5.000
2800	4.100	0.779	4.106	0.777	5.000
2900	4.028	0.828	3.936	0.820	5.000
3000	3.914	0.802	3.902	0.808	5.000

FCC Part 22, 74, 80 Page 33 of 75



FCC Part 22, 74, 80 Page 34 of 75


# **Audio Frequency Response**

Report No.: RDG170907003-00A1

Carrier Frequency: 458.2125 MHz, Channel Separation= 25 kHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-9.92
400	-7.64
500	-5.42
600	-4.01
700	-2.91
800	-1.98
900	-0.86
1000	0.00
1200	1.25
1400	2.93
1600	3.84
1800	5.27
2000	6.01
2100	6.58
2200	7.09
2300	7.23
2400	7.34
2500	7.73
2600	8.07
2700	8.06
2800	8.11
2900	8.46
3000	8.34

FCC Part 22, 74, 80 Page 35 of 75




limit2

FCC Part 22, 74, 80 Page 36 of 75

Report No.: RDG170907003-00A1

Carrier Frequency: 458.2125 MHz, Channel Separation= 25 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-39.46	0.0
4.0	-50.94	-7.5
5.0	-63.93	-13.3
6.0	-68.81	-18.1
7.0	-76.68	-22.1
8.0	-82.72	-25.6
9.0	-84.92	-28.6
10.0	-90.42	-31.4
15.0	-91.34	-41.9
20.0	-87.78	-50.0
30.0	-89.94	-50.0
40.0	-93.86	-50.0
50.0	-89.27	-50.0
60.0	-86.75	-50.0
70.0	-89.58	-50.0



FCC Part 22, 74, 80 Page 37 of 75

# FCC §2.1049 & § 22.359 & § 22.731 & §74.462 & § 80.205 & § 80.211 – OCCUPIED BANDWIDTH & EMISSION MASK

#### **Applicable Standard**

FCC §2.1049, § 22.359, § 22.731, §74.462, § 80.205, § 80.211

Emission Mask D - 12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

Report No.: RDG170907003-00A1

- 1) For any frequency removed from the center of the authorized bandwidth  $f_0$  to 5.625 kHz removed from  $f_0$ , 0dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 ( $f_d$  –2.88 kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 12.5 kHz at least: At least 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.

Emission Mask B - 25 kHz channel bandwidth equipment. For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log (P) dB$ .

Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 30 kHz or more. In the 60 kHz bands immediately outside and adjacent to the authorized frequency range or channel, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e., 30 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC Part 22, 74, 80 Page 38 of 75

#### **Test Procedure**

The resolution bandwidth of the spectrum analyzer was set at 100 Hz or 300 Hz and the spectrum was recorded in the frequency band  $\pm 50$  kHz from the carrier frequency.

Report No.: RDG170907003-00A1

#### **Test Data**

### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-09-11 and 2017-09-25.

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)	Note
	12.5	452 2125	High	7.53	8.89	For Part 74
Dicital	12.5	453.2125	Low	7.53	9.86	roi rait /4
Digital	12.5	454.5	High	7.05	9.21	F P 22
	12.5	454.5	Low	7.77	9.62	For Part 22

Emission Designator Per CFR 47 §2.201& §2.202§&, Bn=2M+2D

# For Digital Mode (Channel Spacing:12.5 kHz)

Emission Designator 7K60FXD and 7K60FXW

The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case,7.77 kHz. The emission mask was obtained from 47CFR 90.210(d).

FXD and FXW portion of the designator indicates digital information.


Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60FXD and 7K60FXW.

FCC Part 22, 74, 80 Page 39 of 75

# **Digital Modulation:**


Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power

Report No.: RDG170907003-00A1



Date: 11.SEP.2017 19:45:47


Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power



Date: 11.SEP.2017 19:37:54


FCC Part 22, 74, 80 Page 40 of 75

Frequency 453.2125 MHz: Emission Mask D,FCC part 74.462, Low Power



Date: 25.SEP.2017 23:14:43


Frequency 453.2125 MHz: Emission Mask D, FCC part 74.462, High Power



Date: 25.SEP.2017 23:11:38


FCC Part 22, 74, 80 Page 41 of 75

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, Low Power



Date: 11.SEP.2017 19:47:05


Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, High Power



Date: 11.SEP.2017 19:48:18


FCC Part 22, 74, 80 Page 42 of 75

Frequency 454.5 MHz: Emission Mask ,FCC part 22.359, Low Power



Date: 25.SEP.2017 23:19:21

Frequency 454.5 MHz: Emission Mask ,FCC part 22.359, High Power



Date: 25.SEP.2017 23:18:37

FCC Part 22, 74, 80 Page 43 of 75

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)	Note
	12.5	452 2125	High	10.02	10.34	For Part 74
A = 1 = -	12.5	453.2125	Low	10.02	10.34	For Part 74
	12.5	454.5	High	10.02	10.34	E D 22
	12.5	454.5	Low	10.02	10.34	For Part 22

Report No.: RDG170907003-00A1

Emission Designator Per CFR 47 §2.201& §2.202§&, Bn=2M+2D

### For FM Mode (Channel Spacing:12.5 kHz)

Emission Designator 11K0F3E. In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.  $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} \rightarrow 11K0$ 

F3E portion of the designator represents an FM voice transmission.


Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

FCC Part 22, 74, 80 Page 44 of 75

### **Analog Modulation 12.5k:**


Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power

Report No.: RDG170907003-00A1



Date: 25.SEP.2017 23:32:41


Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power



Date: 25.SEP.2017 23:33:11


FCC Part 22, 74, 80 Page 45 of 75

Frequency 453.2125 MHz: Emission Mask D, FCC part 74.462, Low Power



Date: 25.SEP.2017 23:23:30


Frequency 453.2125 MHz: Emission Mask D, FCC part 74.462, High Power



Date: 25.SEP.2017 23:24:06


FCC Part 22, 74, 80 Page 46 of 75

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, Low Power



Date: 25.SEP.2017 23:34:17


Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, High Power



Date: 25.SEP.2017 23:33:41


FCC Part 22, 74, 80 Page 47 of 75

Frequency 454.5 MHz: Emission Mask ,FCC part 22.359, Low Power



Date: 25.SEP.2017 23:20:37

Frequency 454.5 MHz: Emission Mask ,FCC part 22.359, High Power



Date: 25.SEP.2017 23:21:08

FCC Part 22, 74, 80 Page 48 of 75

Report No.: RDG170907003-00A1

Emission Designator Per CFR 47 §2.201& §2.202§&, Bn=2M+2D

#### For FM Mode (Channel Spacing:25 kHz)

Emission Designator 16K0F3E. In this case, the maximum modulating frequency is 3.0 kHz with a 5.0 kHz deviation.  $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 5.0 \text{ kHz}) = 16 \text{ kHz} \rightarrow 16K0$ 


F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 25 kHz channel spacing FM mode is 16K0F3E.

FCC Part 22, 74, 80 Page 49 of 75


#### **Analog Modulation 25k:**

### Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power



Date: 25.SEP.2017 23:29:28


### Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power



Date: 25.SEP.2017 23:28:53


FCC Part 22, 74, 80 Page 50 of 75

Frequency 453.2125 MHz: Emission Mask B,FCC Part 74.462, Low Power



Date: 25.SEP.2017 23:25:12


Frequency 453.2125 MHz: Emission Mask B, FCC Part 74.462, High Power



Date: 25.SEP.2017 23:24:52


FCC Part 22, 74, 80 Page 51 of 75

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, Low Power



Date: 25.SEP.2017 23:27:40


Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, High Power



Date: 25.SEP.2017 23:28:20


FCC Part 22, 74, 80 Page 52 of 75

Frequency 454.5 MHz: Emission Mask ,FCC part 22.359, Low Power



Date: 25.SEP.2017 23:26:45


Frequency 454.5 MHz: Emission Mask ,FCC part 22.359, High Power



Date: 25.SEP.2017 23:26:24


FCC Part 22, 74, 80 Page 53 of 75

### Frequency 458.2125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power



Date: 25.SEP.2017 23:30:01


### Frequency 458.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power



Date: 25.SEP.2017 23:30:31


FCC Part 22, 74, 80 Page 54 of 75

# Frequency 458.2125 MHz: Emission Mask B,FCC part 80.211(f), Low Power



Date: 25.SEP.2017 23:25:42

### Frequency 458.2125 MHz: Emission Mask B, FCC part 80.211(f), High Power



Date: 25.SEP.2017 23:26:00

FCC Part 22, 74, 80 Page 55 of 75

# FCC §2.1051 & §22.861 & §74.462 & § 80.211 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Report No.: RDG170907003-00A1

#### **Applicable Standard**

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) For any frequency removed from the center of the authorized bandwidth  $f_0$  to 5.625 kHz removed from  $f_0$ , 0 dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least 7.27 ( $f_d$  –2.88 kHz) dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 12.5 kHz: At least 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.

Emission Mask B - 25 kHz channel bandwidth equipment. For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log (P) dB$ .

#### **Test Procedure**

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10<sup>th</sup> harmonic.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.5 kPa


The testing was performed by Dylan Li on 2017-09-25.

Test Mode: Transmitting, please refer to the following plots.

FCC Part 22, 74, 80 Page 56 of 75


### **Digital Modulation:**

# 30MHz - 1 GHz, Channel Spacing 12.5 kHz, 453.2125 MHz



Date: 25.SEP.2017 22:58:04


1 GHz – 5 GHz, Channel Spacing 12.5 kHz, 453.2125 MHz



Date: 25.SEP.2017 23:03:59


FCC Part 22, 74, 80 Page 57 of 75

30MHz – 1 GHz, Channel Spacing 12.5 kHz, 454.5 MHz



Date: 25.SEP.2017 22:59:01

1 GHz – 5 GHz, Channel Spacing 12.5 kHz, 454.5 MHz




Date: 25.SEP.2017 23:03:35

FCC Part 22, 74, 80 Page 58 of 75

**Analog Modulation:** 


# Report No.: RDG170907003-00A1

30MHz - 1 GHz, Channel Spacing 12.5 kHz, 453.2125 MHz



Date: 25.SEP.2017 22:59:41


1 GHz - 5 GHz, Channel Spacing 12.5 kHz, 453.2125 MHz



Date: 25.SEP.2017 23:02:53


FCC Part 22, 74, 80 Page 59 of 75

30MHz - 1 GHz, Channel Spacing 12.5 kHz, 454.5 MHz



Date: 25.SEP.2017 23:00:21

1 GHz – 5 GHz, Channel Spacing 12.5 kHz, 454.5 MHz




Date: 25.SEP.2017 23:03:22

FCC Part 22, 74, 80 Page 60 of 75

### **Analog Modulation:**


30MHz – 1 GHz, Channel Spacing 25 kHz, 453.2125 MHz

Report No.: RDG170907003-00A1



Date: 25.SEP.2017 23:01:09


1 GHz - 5 GHz, Channel Spacing 25 kHz, 453.2125 MHz



Date: 25.SEP.2017 23:02:16


FCC Part 22, 74, 80 Page 61 of 75

30MHz - 1 GHz, Channel Spacing 25 kHz, 454.5 MHz



Date: 25.SEP.2017 23:00:49


1 GHz – 5 GHz, Channel Spacing 25 kHz, 454.5 MHz



Date: 25.SEP.2017 23:02:32


FCC Part 22, 74, 80 Page 62 of 75

30MHz – 1 GHz, Channel Spacing 25 kHz, 458.2125 MHz



Date: 25.SEP.2017 23:01:23

1 GHz – 5 GHz, Channel Spacing 25 kHz, 458.2125 MHz



Date: 25.SEP.2017 23:02:02

FCC Part 22, 74, 80 Page 63 of 75

# FCC §2.1053 & §22.861 & §74.462 & § 80.211 - RADIATED SPURIOUS EMISSIONS

Report No.: RDG170907003-00A1

#### **Applicable Standard**

FCC §2.1053, §22.861, §74.462, § 80.211

#### **Test Procedure**

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB =10 1g (TXpwr in Watts/0.001)-the absolute level

Spurious attenuation limit in dB = $50+10 \text{ Log}_{10}$  (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃	
Relative Humidity:	56 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Dylan Li on 2017-09-11.

Test Mode: Transmitting

FCC Part 22, 74, 80 Page 64 of 75

30MHz - 5GHz:

	Receiver	Turn	Rx An	tenna		Substitut	ed	Absolute		
Frequency (MHz)	Reading (dBµV)	Table Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
			A	nalog 453	3.2125MH	z-25 kHz				
906.425	50.24	88	2.1	V	-45.8	0.7	0	-46.5	-13	33.5
906.425	49.85	262	2.2	Н	-46.2	0.7	0	-46.9	-13	33.9
1359.64	44.11	165	2.1	Н	-63.8	1.60	8.30	-57.10	-13	41.10
1359.64	46.50	109	1.5	V	-61.7	1.60	8.30	-55.00	-13	42.00
1812.85	43.16	172	1.5	Н	-63.3	1.30	8.50	-56.10	-13	43.10
1812.85	44.73	13	1.9	V	-61.3	1.30	8.50	-54.10	-13	41.10
				Analog 4	54.5MHz-	25 kHz				
909	52.16	227	1.5	V	-43.8	0.7	0	-44.5	-13	31.5
909	51.27	41	2.0	Н	-44.7	0.7	0	-45.4	-13	32.4
1363.50	48.77	337	1.7	Н	-59.2	1.60	8.30	-52.50	-13	39.50
1363.50	46.30	239	1.4	V	-61.9	1.60	8.30	-55.20	-13	42.20
1818.00	44.46	265	2.2	Н	-62.0	1.30	8.50	-54.80	-13	41.80
1818.00	43.75	142	1.5	V	-62.3	1.30	8.50	-55.10	-13	42.10
			A	nalog 458	3.2125MH	z-25 kHz				
916.425	52.14	327	1.2	V	-43.9	0.7	0	-44.6	-13	31.6
916.425	50.29	177	1.6	Н	-45.7	0.7	0	-46.4	-13	33.4
1374.64	46.56	206	2.1	Н	-61.4	1.60	8.30	-54.70	-13	41.70
1374.64	46.02	117	1.7	V	-62.2	1.60	8.30	-55.50	-13	42.50
1832.85	43.57	42	1.1	Н	-62.9	1.30	8.50	-55.70	-13	42.70
1832.85	43.96	267	1.8	V	-62.1	1.30	8.50	-54.90	-13	41.90
			An	alog 453.	2125MHz	-12.5 kHz				
906.425	49.68	157	1.5	V	-46.3	0.7	0	-47.0	-20	27.0
906.425	48.67	220	2.2	Н	-47.3	0.7	0	-48.0	-20	28.0
1359.64	47.90	88	1.7	Н	-60.1	1.60	8.30	-53.40	-20	33.40
1359.64	45.86	114	1.3	V	-62.4	1.60	8.30	-55.70	-20	35.70
1812.85	43.44	347	1.6	Н	-63.0	1.30	8.50	-55.80	-20	35.80
1812.85	43.69	266	2.4	V	-62.4	1.30	8.50	-55.20	-20	35.20
			P	Analog 45	4.5MHz-1	2.5 kHz				
909	51.84	252	2.2	V	-44.2	0.7	0	-44.9	-20	24.9
909	50.95	61	1.8	Н	-45.1	0.7	0	-45.8	-20	25.8
1363.50	45.55	8	2.2	Н	-62.4	1.60	8.30	-55.70	-20	35.70
1363.50	44.81	127	1.6	V	-63.4	1.60	8.30	-56.70	-20	36.70
1818.00	44.12	321	2.2	Н	-62.3	1.30	8.50	-55.10	-20	35.10
1818.00	43.14	208	2.3	V	-62.9	1.30	8.50	-55.70	-20	35.70

Report No.: RDG170907003-00A1

FCC Part 22, 74, 80 Page 65 of 75

Frequency	Receiver Turn Table		N Receiver Table			Substituted			Limit	Margin
(MHz)	Reading (dBμV) Angle Degree	_	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		(dBm)	(dB)
			Г	igital 453	.2125MH	z-12.5 kH	Z			
906.425	51.86	224	2.3	V	-44.1	0.7	0	-44.8	-20	24.8
906.425	49.68	220	2.4	Н	-46.3	0.7	0	-47.0	-20	27.0
1359.64	45.77	321	2.5	Н	-62.2	1.60	8.30	-55.50	-20	35.50
1359.64	46.00	74	2.1	V	-62.2	1.60	8.30	-55.50	-20	35.50
1812.85	45.45	337	1.6	Н	-61.0	1.30	8.50	-53.80	-20	33.80
1812.85	43.81	172	2.1	V	-62.2	1.30	8.50	-55.00	-20	35.00
				Digital 4:	54.5MHz-	12.5 kHz				
909	51.22	157	1.1	V	-44.8	0.7	0	-45.5	-20	25.5
909	49.87	290	1.4	Н	-46.1	0.7	0	-46.8	-20	26.8
1363.50	46.92	344	1.2	Н	-61.0	1.60	8.30	-54.30	-20	34.30
1363.50	47.10	226	1.8	V	-61.1	1.60	8.30	-54.40	-20	34.40
1818.00	43.95	232	1.3	Н	-62.5	1.30	8.50	-55.30	-20	35.30
1818.00	43.21	269	2.0	V	-62.8	1.30	8.50	-55.60	-20	35.60

Report No.: RDG170907003-00A1

Absolute Level = Substituted Level - Cable loss + Antenna Gain Margin = Limit- Absolute Level

FCC Part 22, 74, 80 Page 66 of 75

# FCC §2.1055 & § 22.355 & §74.464 & § 80.209 - FREQUENCY STABILITY

Report No.: RDG170907003-00A1

#### **Applicable Standard**

FCC §2.1055, § 22.355, §74.464, § 80.209

#### **Test Procedure**

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃	
Relative Humidity:	56 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Dylan Li on 2017-09-26.

Test Mode: Transmitting

FCC Part 22, 74, 80 Page 67 of 75

Digital Modulation, Reference Frequency: 453.2125 MHz, Limit: ±2.5 ppm,12.5 kHz								
Test Eı	nvironment	Frequency Measure with Time Elapsed						
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)					
	Frequency Stability	y versus Input Temper	ature					
50	13.6	453.21246	-0.08826					
40	13.6	453.21241	-0.19858					
30	13.6	453.21237	-0.28684					
20	13.6	453.21241	-0.19858					
10	13.6	453.21245	-0.11032					
0	13.6	453.21239	-0.24271					
-10	13.6	453.21240	-0.22065					
-20	13.6	453.21237	-0.28684					
-30	13.6	453.21241	-0.19858					
	Frequency Stability versus Input Voltage							
20	11.0	453.21244	-0.13239					
20	15.6	453.21253	0.06619					

Digital Modulation, Reference Frequency: 454.5 MHz, Limit: ±2.5 ppm,12.5 kHz								
Test En	vironment	Frequency Measure with Time Elapsed						
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)					
	Frequency Stability	y versus Input Temper	ature					
50	13.6	454.49997	-0.06601					
40	13.6	454.49992	-0.17602					
30	13.6	454.49994	-0.13201					
20	13.6	454.49987	-0.28603					
10	13.6	454.49983	-0.37404					
0	13.6	454.49995	-0.11001					
-10	13.6	454.49985	-0.33003					
-20	13.6	454.49990	-0.22002					
-30	13.6	454.49988	-0.26403					
	Frequency Stability versus Input Voltage							
20	11.0	454.49990	-0.22002					
20	15.6	454.49983	-0.37404					

FCC Part 22, 74, 80 Page 68 of 75

Digital Modulation, Reference Frequency: 458.2125 MHz, Limit: ±2.5 ppm,12.5 kHz								
Test En	vironment	Frequency Measure with Time Elapsed						
Temperature (℃)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)					
	Frequency Stability	y versus Input Temper	ature					
50	13.6	458.21240	-0.21824					
40	13.6	458.21241	-0.19642					
30	13.6	458.21239	-0.24006					
20	13.6	458.21244	-0.13094					
10	13.6	458.21236	-0.30554					
0	13.6	458.21235	-0.32736					
-10	13.6	458.21241	-0.19642					
-20	13.6	458.21236	-0.30554					
-30	13.6	458.21243	-0.15277					
	Frequency Stability versus Input Voltage							
20	11.0	458.21241	-0.19642					
20	15.6	458.21247	-0.06547					

Analog Modulation, Reference Frequency: 453.2125 MHz, Limit: ±2.5 ppm,12.5 kHz			
Test Environment		Frequency Measure with Time Elapsed	
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)
	Frequency Stability	y versus Input Temper	rature
50	13.6	453.21245	-0.11032
40	13.6	453.21241	-0.19858
30	13.6	453.21238	-0.26478
20	13.6	453.21240	-0.22065
10	13.6	453.21244	-0.13239
0	13.6	453.21241	-0.19858
-10	13.6	453.21247	-0.06619
-20	13.6	453.21239	-0.24271
-30	13.6	453.21244	-0.13239
Frequency Stability versus Input Voltage			
20	11.0	453.21245	-0.11032
20	15.6	453.21239	-0.24271

FCC Part 22, 74, 80 Page 69 of 75

Analog Modulation, Reference Frequency: 454.5 MHz, Limit: ±2.5 ppm,12.5 kHz			
Test Environment		Frequency Measure with Time Elapsed	
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)
	Frequency Stability	y versus Input Temper	ature
50	13.6	454.49981	-0.41804
40	13.6	454.49989	-0.24202
30	13.6	454.49986	-0.30803
20	13.6	454.49990	-0.22002
10	13.6	454.49993	-0.15402
0	13.6	454.49991	-0.19802
-10	13.6	454.49989	-0.24202
-20	13.6	454.49991	-0.19802
-30	13.6	454.49986	-0.30803
Frequency Stability versus Input Voltage			
20	11.0	454.49992	-0.17602
20	15.6	454.49985	-0.33003

Analog Modulation, Reference Frequency: 458.2125 MHz, Limit: ±2.5 ppm,12.5 kHz			
Test Environment		Frequency Measure with Time Elapsed	
Temperature (℃)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)
	Frequency Stability	y versus Input Temper	ature
50	13.6	458.21241	-0.19642
40	13.6	458.21240	-0.21824
30	13.6	458.21239	-0.24006
20	13.6	458.21237	-0.28371
10	13.6	458.21233	-0.37101
0	13.6	458.21245	-0.10912
-10	13.6	458.21243	-0.15277
-20	13.6	458.21246	-0.08730
-30	13.6	458.21242	-0.17459
Frequency Stability versus Input Voltage			
20	11.0	458.21239	-0.24006
20	15.6	458.21243	-0.15277

FCC Part 22, 74, 80 Page 70 of 75

Analog Modulation, Reference Frequency: 453.2125 MHz, Limit: ±5.0 ppm, 25 kHz			
Test Environment		Frequency Measure with Time Elapsed	
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)
	Frequency Stability	y versus Input Temper	ature
50	13.6	453.21239	-0.24271
40	13.6	453.21235	-0.33097
30	13.6	453.21242	-0.17652
20	13.6	453.21241	-0.19858
10	13.6	453.21238	-0.26478
0	13.6	453.21244	-0.13239
-10	13.6	453.21241	-0.19858
-20	13.6	453.21240	-0.22065
-30	13.6	453.21237	-0.28684
Frequency Stability versus Input Voltage			
20	11.0	453.21240	-0.22065
20	15.6	453.21244	-0.13239

Analog Modulation, Reference Frequency: 454.5 MHz, Limit: ±5.0 ppm, 25 kHz				
Test Environment		Frequency Measure with Time Elapsed		
Temperature (℃)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)	
	Frequency Stability versus Input Temperature			
50	13.6	454.49989	-0.24202	
40	13.6	454.49986	-0.30803	
30	13.6	454.49990	-0.22002	
20	13.6	454.49986	-0.30803	
10	13.6	454.49983	-0.37404	
0	13.6	454.49987	-0.28603	
-10	13.6	454.49982	-0.39604	
-20	13.6	454.49989	-0.24202	
-30	13.6	454.49984	-0.35204	
Frequency Stability versus Input Voltage				
20	11.0	454.49992	-0.17602	
20	15.6	454.49985	-0.33003	

FCC Part 22, 74, 80 Page 71 of 75

Analog Modulation, Reference Frequency: 458.2125 MHz, Limit: ±5.0 ppm, 25 kHz				
Test Environment		Frequency Measure with Time Elapsed		
Temperature (°C)	Voltage Supplied (V <sub>DC</sub> )	Measured Frequency (MHz)	Frequency Error (ppm)	
	Frequency Stability versus Input Temperature			
50	13.6	458.21239	-0.24006	
40	13.6	458.21247	-0.06547	
30	13.6	458.21240	-0.21824	
20	13.6	458.21245	-0.10912	
10	13.6	458.21243	-0.15277	
0	13.6	458.21241	-0.19642	
-10	13.6	458.21234	-0.34918	
-20	13.6	458.21238	-0.26189	
-30	13.6	458.21236	-0.30554	
Frequency Stability versus Input Voltage				
20	11.0	458.21242	-0.17459	
20	15.6	458.21237	-0.28371	

\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 22, 74, 80 Page 72 of 75