



## MPE TEST REPORT

### FCC Per 47 CFR 2.1091(b)

Report Reference No. ....: WE11030059

FCC ID .....: YAMMD78XU2

Compiled by

( position+printed name+signature) ..: File administrators Eric Zhang

*Eric Zhang*

Supervised by

( position+printed name+signature) ..: Test Engineer Wenliang Li

*Wenliang Li*

Approved by

( position+printed name+signature) ..: Manager Jimmy Li

*Jimmy Li*

Date of issue .....: Apr 11, 2011

Testing Laboratory Name .....: Shenzhen Huatongwei International Inspection Co., Ltd

Address .....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name .....: Hytera Communications Corporation Ltd.

Address .....: HYT Tower, Hi-Tech Industrial Park North, Nanshan District, Shenzhen China. 518057

#### Test specification:

Standard .....: FCC Per 47 CFR 2.1091(b)

TRF Originator .....: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF .....: Dated 2006-06

#### Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....: Digital Mobile Radio

Trade Mark .....:



Manufacturer .....: Hytera Communications Corporation Ltd.

Model/Type reference .....: MD782 U(2)/ MD785 U(2)/ MD786 U(2)/ MD788 U(2)

Listed Models .....: /

Ratings .....: DC 13.60V

Modulation .....: FM&4FSK

Rated Power .....: 45 Watts(46.53 dBm)/5 Watts(36.99 dBm)

Channel Separation .....: 12.5KHz

Frequency Range .....: From 450 MHz to 520 MHz

Result .....: Positive

**M P E T E S T   R E P O R T**

<b>Test Report No. :</b> <b>WE11030059</b>	Apr 11, 2011 Date of issue
--	-------------------------------

Equipment under Test                      :            Digital Mobile Radio

Model /Type                                        :            MD782 U(2)/ MD785 U(2)/ MD786 U(2)/ MD788 U(2)

Listed Models                                        :            /

**Applicant**    :            **Hytera Communications Corporation Ltd.**

Address    :            HYT Tower,Hi-Tech Industrial Park North,Nanshan  
District,Shenzhen China.518057

**Manufacturer**    :            **Hytera Communications Corporation Ltd.**

Address    :            HYT Tower,Hi-Tech Industrial Park North,Nanshan  
District,Shenzhen China.518057

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

<b><u>1.</u></b>	<b><u>MEASUREMENT UNCERTAINTY .....</u></b>	<b><u>4</u></b>
<b><u>2.</u></b>	<b><u>METHOD OF MEASUREMENT .....</u></b>	<b><u>4</u></b>
<b>2.1.</b>	<b>EME measurements made on trunk mounted antennas</b>	<b>4</b>
2.1.1.	External vehicle EME measurement .....	4
2.1.2.	Internal vehicle EME measurement .....	4
<b>2.2.</b>	<b>EME measurements made on center roof mounted antennas</b>	<b>4</b>
2.2.1.	External vehicle EME measurement .....	4
2.2.2.	Internal vehicle EME measurement .....	4
<b><u>3.</u></b>	<b><u>APPROVED ACCESSORIES.....</u></b>	<b><u>5</u></b>
<b><u>4.</u></b>	<b><u>TEST RESULT .....</u></b>	<b><u>5</u></b>
<b><u>5.</u></b>	<b><u>CONCLUSION .....</u></b>	<b><u>7</u></b>
<b><u>6.</u></b>	<b><u>ANTENNA LOCATION DRAWING .....</u></b>	<b><u>8</u></b>
<b><u>7.</u></b>	<b><u>PROBE CALIBRATION CERTIFICATES.....</u></b>	<b><u>9</u></b>

## **1. Measurement Uncertainty**

The information below presents an estimate of the possible errors that are associated with the measurement system.

<b><u>Description</u></b>	<b><u>Error</u></b>
<b>NARDA Survey Meter</b>	<b><math>\pm 3\%</math></b>
<b>Repeatability Accuracy</b>	<b><math>\pm 7\%</math></b>

## **2. Method of measurement**

### **2.1. EME measurements made on trunk mounted antennas**

#### **2.1.1. External vehicle EME measurement**

(Antenna mounted in trunk center)

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 60 cm to the antenna, from the back of the vehicle in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters.

#### **2.1.2. Internal vehicle EME measurement**

(Antenna mounted in trunk center)

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged

- a) Head area
- b) Chest area
- c) Lower Trunk area

### **2.2. EME measurements made on center roof mounted antennas**

#### **2.2.1. External vehicle EME measurement**

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 110 cm from the vehicle-mounted antenna, in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters; this would be representative of a person standing next to a vehicle during a mobile radio transmission.

#### **2.2.2. Internal vehicle EME measurement**

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

### 3. Approved Accessories

**Antenna:**

Model: TQC-500DII  
Roof Mount 450-520 MHz  
Gain: 5.5 dBi

**Vehicle:**

Band: BYD  
Model: F6

### 4. Test Result

Measurement Information			
Measurement Freq.(MHz)	450.5000	485.0000	519.5000
Raw Data Power(W)	43.75	43.65	41.98
Controlled Limit(mW/cm <sup>2</sup> )	1.5017	1.6167	1.7317
Uncontrolled Limit(mW/cm <sup>2</sup> )	0.3003	0.3233	0.3463
Cal.	1.00	1.00	1.00
Antenna / gain(dBi)	Whip / 5.5	Whip / 5.5	Whip / 5.5
External Vehicle Power Density(50% duty)	average over body/2		
Internal Vehicle Power Density(50% duty)	average over (head/chest/leg)/2		

External Vehicle MPE Assessment at 450.5000 MHz						
Antenna Location	Antenna/ gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm <sup>2</sup> )
Trunk	Whip / 5.5	60	E	1.00	0.55	0.28
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	7.0	6	120	29.0	
2	40	11.0	7	140	22.6	
3	60	11.8	8	160	15.7	
4	80	18.2	9	180	14.7	
5	100	27.9	10	200	10.5	

External Vehicle MPE Assessment at 485.0000 MHz						
Antenna Location	Antenna/ gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm <sup>2</sup> )
Trunk	Whip / 5.5	60	E	1.00	0.50	0.25
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	7.8	6	120	30.5	
2	40	10.9	7	140	22.7	
3	60	15.9	8	160	17.5	
4	80	24.5	9	180	14.3	
5	100	30.0	10	200	11.2	

External Vehicle MPE Assessment at 519.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm <sup>2</sup> )
Trunk	Whip / 5.5	60	E	1.00	0.53	0.27
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	8.4	6	120	26.3	
2	40	12.5	7	140	23.7	
3	60	12.9	8	160	10.9	
4	80	17.2	9	180	10.0	
5	100	25.0	10	200	8.4	

External Vehicle MPE Assessment at 450.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm <sup>2</sup> )
Trunk	Whip / 5.5	110	E	1.00	0.42	0.21
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	5.9	6	120	12.0	
2	40	6.0	7	140	13.5	
3	60	6.4	8	160	10.2	
4	80	5.7	9	180	8.1	
5	100	9.2	10	200	5.5	

Internal Vehicle MPE Assessment at 450.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm <sup>2</sup> )	Pwr. Density of Higher Level (mW/cm <sup>2</sup> )
Trunk	Whip / 5.5	Highest Reading	E	1.00	0.400/0.030	0.200/0.015
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	11.3		7.2		3.3	
Front Sea	3.4		1.5		1.0	

Internal Vehicle MPE Assessment at 485.0000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm <sup>2</sup> )	Pwr. Density of Higher Level (mW/cm <sup>2</sup> )
Trunk	Whip / 5.5	Highest Reading	E	1.00	0.360/0.0020	0.180/0.001
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	3.3		3.8		1.1	
Front Sea	4.6		4.9		1.5	


Internal Vehicle MPE Assessment at 519.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm <sup>2</sup> )	Pwr. Density of Higher Level (mW/cm <sup>2</sup> )
Trunk	Whip / 5.5	Highest Reading	E	1.00	0.320/0.006	0.160/0.003
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	11.3		12.8		8.4	
Front Sea	6.7		11.0		5.1	

Internal Vehicle MPE Assessment at 519.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm <sup>2</sup> )	Pwr. Density of Higher Level (mW/cm <sup>2</sup> )
Roof	Whip / 5.5	Highest Reading	E	1.00	0.240/0.008	0.120/0.004
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	2.2		3.5		4.8	
Front Sea	1.2		1.2		1.3	


## 5. Conclusion

The measurement results comply with the FCC Limit Per 47 CFR 2.1091 (b) for the controlled RF Exposure.

## 6. Antenna Location Drawing











- 1 - Roof (center)  
2 - Trunk (center)





## 7. Probe Calibration Certificates

	<b>华南国家计量测试中心 广东省计量科学研究院</b> SOUTH CHINA NATIONAL CENTER OF METROLOGY GUANGDONG INSTITUTE OF METROLOGY		
<b>校准证书</b> CALIBRATION CERTIFICATE			
证书编号 WWD20101583 Certificate No.		第 1 页, 共 3 页 Page of	
委托方 Client	深圳华通威国际检验有限公司		
委托方地址 Add. of Client	深圳市南山区高新技术产业园科技南12路		
计量器具名称 Description	场强仪		
型号规格 Model/Type	FM5004/HI-6005		
制造厂 Manufacturer	AR		
出厂编号 Serial No.	300239/00064170	设备编号 Equipment No.	
接收日期 Date of Receipt	2010 年 10 月 28 日 Y M D		
结论 Conclusion	见校准结果页		
校准日期 Date of Calibration	2010 年 11 月 3 日 Y M D		
批准人 Approved Signatory			
核 验 Inspected by			
校 准 Calibrated by			
			
			
<p>本中心地址: 中国广州市广园中路松柏东街30号 邮政编码: 510405 电话: (8620)86594172 传真: (8620)86590743 投诉电话: (8620)26296063 E-mail: scm@scm.com.cn Add: No.30, Songbaidong Street, Guangyuanzhong Road, Guangzhou, P. R. China Post Code: 510405 Tel: (8620)86594172 Fax: (8620)86590743 Complaint Tel: (8620)26296063 101028n07-1</p>			



华南国家计量测试中心  
广东省计量科学研究所  
SOUTH CHINA NATIONAL CENTER OF METROLOGY  
GUANGDONG INSTITUTE OF METROLOGY



## 说 明

证书编号 WWD20101583  
Certificate No.

### DIRECTIONS

第 2 页, 共 3 页  
Page of

1. 本中心是国家质量监督检验检疫总局在华南地区设立的国家法定计量检定机构, 计量授权证书号是: (国) 法计 (2007) 01043号、(国) 法计 (2007) 01032号。本中心是中国合格评定国家认可委员会 (CNAS) 认可实验室, 认可证书号为: CNAS L0730。

This laboratory is the National Legal Metrological Verification Institution in southern China set up by the General Administration of Quality Supervision, Inspection and Quarantine of the People's Republic of China (AQSIQ) under authorization certificates No.(2007)01043 & (2007)01032. This laboratory is accredited by China National Accreditation Service for Conformity Assessment under Laboratory Accreditation Certification No. CNAS L0730.

2. 本中心所出具的数据均可溯源至国家计量基准和国际单位制 (SI)。

All data issued by this laboratory are traceable to national primary standards and International System of Units (SI).

3. 本次校准的技术依据:

Reference documents for the calibration:

IEEE 1309-2005 Calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 MHz 频率为9KHz~40GHz的电磁场传感器和探头(天线除外)的校准

JJG 561-1988 RJ-3型近区电场测量仪试行检定规程 V.R. of Model RJ-3 Near-Zone Electric-Field Measuring Instruments

4. 本次校准所使用的主要计量标准器具:

Major standards of measurement used in the calibration:

设备名称/型号 Name of Equipment /Model	编号 Serial No.	证书号/有效期 Certificate No. /Due Date	计量特性 Metrological Characteristic
场强标准 TEM Cell /8801	014	WWD20100034 /2011-01-12	$\pm 1$ dB
功率放大器 Power Amplifier /100W1000B	305581	WWS20100786 /2011-07-15	增益: $U_{rel}=1$ dB ( $k=2$ ) Gain: $U_{rel}=1$ dB ( $k=2$ )
信号发生器 Signal Generator /E8267C	US42340272	WWS20100376 /2011-04-18	电平: $U_{rel}=0.20$ dB 频率: $U_{rel}=1 \times 10^{-8}$ ( $k=2$ ) Level: $U_{rel}=0.20$ dB, Frequency: $U_{rel}=1 \times 10^{-8}$ ( $k=2$ )
电场探头/读出装置 Electromagnetic Field Meter/reader /EP183/8053A	000WJ40805&1420K211 37	XDdj2010-1988 /2011-09-24	$U=(0.94 \sim 1.3)$ dB, $k=2$

5. 校准地点、环境条件:

Place and environmental conditions of the calibration:

地点 无线电室 (Radio Lab.)	温度 $(20 \pm 5) ^\circ\text{C}$	相对湿度 $< 80\%$
Place	Temperature	RH

6. 被校准仪器限制使用条件:

Limiting condition of the instrument calibrated:


注: 1. 本证书校准结果只与受校准仪器有关。

2. 未经本中心书面批准, 不得部分复制此证书。

Note: 1. The results relate only to the items calibrated.

2. This certificate shall not be reproduced except in full, without the written approval of our laboratory.







华南国家计量测试中心  
广东省计量科学研究院  
SOUTH CHINA NATIONAL CENTER OF METROLOGY  
GUANGDONG INSTITUTE OF METROLOGY

## 校准结果

### RESULTS OF CALIBRATION



校准  
CNAS L0730

证书编号 WWD20101583  
Certificate No.

原始记录号 020101583  
Record No.

第 3 页, 共 3 页  
Page of

1 场强测量准确度 (见表1)  
Field Strength Measuring Accuracy (See Table 1)

表1 (Table 1)

探头 Probe	频率 Frequency	标准值 Reference Value	被检表示值 Indication Value	误差 (dB) Error	允许误差 MPE	结论 Conclusion
HI-6005	27 MHz	1 V/m	1.08 V/m	+0.67	±2.0 dB	合格(Pass)
	27 MHz	2 V/m	2.21 V/m	+0.87	±2.0 dB	合格(Pass)
	27 MHz	5 V/m	5.07 V/m	+0.12	±2.0 dB	合格(Pass)
	27 MHz	10 V/m	9.93 V/m	-0.06	±2.0 dB	合格(Pass)
	27 MHz	20 V/m	19.29 V/m	-0.31	±2.0 dB	合格(Pass)

2 频率响应 (见表2)  
Frequency Response (See Table 2)

表2 (Table 2)

探头 Probe	频率 Frequency	标准值 Reference Value	被检表示值 Indication Value	误差 (dB) Error	允许误差 MPE	结论 Conclusion
HI-6005	100 kHz	10 V/m	8.30 V/m	-1.62	N/A	合格(Pass)
	1 MHz	10 V/m	9.83 V/m	-0.15	N/A	合格(Pass)
	10 MHz	10 V/m	10.44 V/m	+0.37	N/A	合格(Pass)
	27 MHz	10 V/m	9.93 V/m	-0.06	±2.0 dB	合格(Pass)
	50 MHz	10 V/m	9.74 V/m	-0.23	±2.0 dB	合格(Pass)
	100 MHz	10 V/m	9.82 V/m	-0.16	±2.0 dB	合格(Pass)
	200 MHz	10 V/m	9.68 V/m	-0.28	±2.0 dB	合格(Pass)
	300 MHz	10 V/m	9.36 V/m	-0.57	±2.0 dB	合格(Pass)
	1 GHz	10 V/m	9.12 V/m	-0.80	±2.0 dB	合格(Pass)
	2 GHz	10 V/m	9.76 V/m	-0.21	±2.0 dB	合格(Pass)
	3 GHz	10 V/m	9.03 V/m	-0.89	N/A	合格(Pass)

说明(Note):

1 测量结果的扩展不确定度:  
Expanded uncertainty of measurement:  
 $U=1.5 \text{ dB}, k=2$   
(依据 JJF1059-1999 测量不确定度评定与表示)  
(In accordance with JJF1059-1999 Evaluation and Expression of Uncertainty in Measurement)

2 建议校准周期不超过1年。  
The period of calibration advised within one year.

.....End of Report.....