



FCC PART 22, 74, 80 and 90

TEST REPORT

For

Hytera Communications Corporation Limited

Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen,
518057 China

FCC ID: YAMRD98XSIU2

Report Type: Original Report	Product Type: Digital Repeater
Report Number: RDG171207019-00A	
Report Date: 2018-03-12	
Rocky Kang	
Reviewed By: RF Engineer	<i>Rocky Kang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "**".

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	10
APPLICABLE STANDARD	10
RESULT	10
FCC §2.1046 & § 22.727 & §74.461 & §80.215 & §90.205 - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST DATA	11
FCC §2.1047 - MODULATION CHARACTERISTIC	13
APPLICABLE STANDARD	13
TEST PROCEDURE	13
TEST DATA	13
FCC §2.1049 & §22.357 & § 22.731 & §74.462 & § 80.205 & § 80.207 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	24
FCC §2.1051 & §22.861 & §74.462 & § 80.211 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41
FCC §2.1053 & §22.861 & §74.462 & § 80.211 & §90.210 - RADIATED SPURIOUS EMISSIONS.....	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST DATA	49
FCC §2.1055 & § 22.355 & §74.464 & § 80.209 & §90.213 - FREQUENCY STABILITY	52

APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52
FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR.....	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST DATA	57

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Hytera Communications Corporation Limited's* product, model number: *RD982Si U(2)* (FCC ID: *YAMRD98XSIU2*) in this report is a *Digital Repeater*, which was measured approximately: 48.2 cm (L) x 36.8 cm (W) x 9.9 cm (H), rated input voltage: DC 13.6 V.

Type	Parameter	
Frequency Range(MHz)	450-512	
Rated Output power(Watts)	50 (High) / 5(Low)	
Modulation	FM/4FSK	
Channel Spacing(kHz)	FM	12.5/25
	4FSK	12.5

Notes: This series products model: RD985Si U(2), RD986Si U(2), RD988Si U(2) and RD982Si U(2) are identical schematics, and only are different for model number. Model RD982Si U(2) was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

** All measurement and test data in this report was gathered from production sample serial number: 171207019 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-12-07.*

Objective

This test report is prepared on behalf of *Hytera Communications Corporation Limited* in accordance with Part 2, and Part 22,74,80,90 of the Federal Communication Commissions rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 22 – Public Mobile Service

Part 74 – Experimental Radio, Auxiliary, Special Broadcast and other Program Distributonal Service

Part 80 – Stantions in the Maritme Service

Part 90 – Private Land Mobile Radio Service

Applicable Standards: TIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 1.5\text{dB}$
Unwanted Emission, conducted	$\pm 1.5\text{dB}$
All emissions, radiated	$\pm 4.88\text{dB}$
Temperature	± 1
Supply voltages	$\pm 0.4\%$

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 382179, the FCC Designation No. : CN5001.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode which has been done in the factory.

EUT Exercise Software

No exercise software was used.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
N/A	Load	100W/50	N/A
TDK-Lambda	DC power supply	Z60-14-L-C	N/A

External I/O Cable

Cable Description	Length (m)	From Port	To
DC Power Cable	3.0	DC power supply	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§1.1307(b), §2.1091	Maximum Permissible exposure (MPE)	Compliance
§2.1046; § 22.727; §74.461; § 80.215; §90.205	RF Output Power	Compliance
§2.1047	Modulation Characteristic	Compliance
§2.1049;§22.357;§ 22.731; §74.462; § 80.205; § 80.207;§90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliance
§2.1051; §22.861; §74.462; § 80.211;§90.210	Spurious Emission at Antenna Terminal	Compliance
§2.1053; §22.861; §74.462; § 80.211;§90.210	Spurious Radiated Emissions	Compliance
§2.1055; § 22.355; §74.464; § 80.209;§90.213	Frequency Stability	Compliance
§90.214	Transient Frequency Behavior	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017-12-29	2020-12-28
Rohde & Schwarz	Signal Generator	FSIQ26	8386001028	2017-04-24	2018-04-24
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2017-12-17	2020-12-17
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-02-14	2018-02-14
HP	Amplifier	HP8447E	1937A01046	2017-11-19	2018-05-21
Anritsu	Signal Generator	68369B	004114	2017-12-05	2018-12-05
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2017-12-07	2018-12-07
COM POWER	Dipole Antenna	AD-100	041000	NCR	NCR
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	104PEA	218124002	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	1	2017-11-19	2018-05-21
Ducommun technologies	RF Cable	RG-214	2	2017-11-22	2018-05-22
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSW13	103533	2017-06-15	2018-06-14
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2017-11-22	2018-11-22
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR
Rohde & Schwarz	Vector Signal Generator	SMW200A	102522	2017-06-15	2018-06-14
BEW	Coaxial Attenuator	TS300-6-40	N/A	2017-06-15	2018-06-14
MICABLE	RF Cable	D02	N/A	2017-06-15	2018-06-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for Occupational/Controlled Exposure

Limits for occupational/Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	6
1.34-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5.0	6

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Max average output power (mW)	Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)				
450-512	5.5	3.55	28117	80	1.24	1.50

Note: Max tune-up output power is 47.5dBm (56234 mW), the duty cycle is 50%. So the average power is 28117 mW.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 80cm from nearby persons.

Result: Compliance

FCC §2.1046 & § 22.727 & §74.461 & §80.215 & §90.205 - RF OUTPUT POWER

Applicable Standard

FCC §2.1046, § 22.727, §74.461, § 80.215 and §90.205

Test Procedure

Conducted RF Output Power:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer Setting:

R B/W	Video B/W
100 kHz	300 kHz

Test Data

Environmental Conditions

Temperature:	25
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-12-19.

Test Mode: Transmitting

Test Result: Compliance. Please refer to following table.

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	Output Power (dBm)	Output Power (W)	Remark
Analog	12.5	450.0125	High	47.20	52.48	For Part 74/90
			Low	37.26	5.32	
	12.5	453.2125	High	47.19	52.36	For Part 74/90
			Low	37.28	5.35	
	12.5	454.5	High	47.19	52.36	For Part 22
			Low	37.28	5.35	
	12.5	511.9875	High	47.19	52.36	For Part 22/90
			Low	37.24	5.30	

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	Output Power (dBm)	Output Power (W)	Remark
Analog	25	450.0125	High	47.21	52.60	For Part 74
			Low	37.22	5.27	
	25	454.5	High	47.14	51.76	For Part 22/80
			Low	37.24	5.30	
	25	465.0125	High	47.24	52.97	For Part 80
			Low	37.29	5.36	
	25	511.9875	High	47.21	52.60	For Part 22
			Low	37.25	5.31	

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	Output Power (dBm)	Output Power (W)	Remark
Digital	12.5	450.0125	High	47.24	52.97	For Part 74/90
			Low	37.27	5.33	
	12.5	453.2125	High	47.18	52.24	For Part 74/90
			Low	37.28	5.35	
	12.5	454.5	High	47.24	52.97	For Part 22
			Low	37.27	5.33	
	12.5	511.9875	High	47.25	53.09	For Part 22/90
			Low	37.22	5.27	

Note: The high rated power is 50W, limit is 40-60W
The low rated power is 5W, limit is 4-6W

FCC §2.1047 - MODULATION CHARACTERISTIC

Applicable Standard

FCC§2.1047, §74.463, §80.213 and §90.207:

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Procedure

Test Method: TIA/EIA-603 2.2.3

Test Data

Environmental Conditions

Temperature:	25
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2017-12-30.


Test Mode: Transmitting

Result: Compliance.

Analog Modulation:**MODULATION LIMITING**

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz


Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	1.633	0.063	1.638	0.066	2.5
400	1.954	0.098	1.959	0.101	2.5
500	2.122	0.101	2.130	0.104	2.5
600	2.179	0.112	2.187	0.115	2.5
700	2.216	0.130	2.223	0.133	2.5
800	2.233	0.144	2.239	0.148	2.5
900	2.256	0.159	2.262	0.162	2.5
1000	2.261	0.165	2.268	0.169	2.5
1200	2.298	0.203	2.302	0.206	2.5
1400	2.296	0.219	2.305	0.221	2.5
1600	2.293	0.236	2.301	0.239	2.5
1800	2.278	0.252	2.287	0.257	2.5
2000	2.256	0.276	2.263	0.281	2.5
2100	2.236	0.282	2.241	0.286	2.5
2200	2.210	0.291	2.219	0.297	2.5
2300	2.178	0.301	2.189	0.304	2.5
2400	2.126	0.321	2.134	0.326	2.5
2500	2.068	0.328	2.077	0.335	2.5
2600	1.997	0.341	2.005	0.346	2.5
2700	1.898	0.353	1.907	0.357	2.5
2800	1.777	0.370	1.786	0.375	2.5
2900	1.646	0.369	1.654	0.378	2.5
3000	1.494	0.359	1.503	0.366	2.5



Audio Frequency Response

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-12.04
400	-8.05
500	-5.81
600	-4.35
700	-2.81
800	-1.41
900	-0.54
1000	0.00
1200	1.80
1400	2.93
1600	4.35
1800	4.95
2000	5.94
2100	6.23
2200	6.48
2300	6.85
2400	7.14
2500	7.11
2600	6.88
2700	6.86
2800	6.72
2900	6.26
3000	5.78



Audio frequency lows pass filter response

Carrier Frequency: 453.2125 MHz, Channel Separation=12.5 kHz


Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-16.00	0.0
4.0	-74.90	-12.5
5.0	-90.20	-22.2
6.0	-87.40	-30.1
7.0	-84.20	-36.8
8.0	-86.40	-42.6
9.0	-87.30	-47.7
10.0	-85.80	-52.3
12.0	-87.60	-60.2
14.0	-88.00	-66.9
16.0	-91.00	-72.7
18.0	-91.10	-77.8
20.0	-88.00	-82.5



MODULATION LIMITING

Carrier Frequency: 465.0125 MHz, Channel Separation=25 kHz


Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	3.431	0.086	3.435	0.089	5
400	4.084	0.131	4.089	0.134	5
500	4.416	0.166	4.425	0.169	5
600	4.549	0.205	4.556	0.207	5
700	4.623	0.238	4.631	0.243	5
800	4.683	0.269	4.695	0.274	5
900	4.729	0.297	4.738	0.303	5
1000	4.750	0.325	4.763	0.331	5
1200	4.783	0.388	4.795	0.391	5
1400	4.833	0.447	4.841	0.452	5
1600	4.815	0.528	4.826	0.532	5
1800	4.765	0.561	4.774	0.565	5
2000	4.696	0.623	4.708	0.627	5
2100	4.646	0.646	4.653	0.651	5
2200	4.577	0.673	4.585	0.679	5
2300	4.502	0.697	4.513	0.705	5
2400	4.397	0.714	4.411	0.721	5
2500	4.263	0.715	4.275	0.725	5
2600	4.098	0.696	4.121	0.704	5
2700	3.903	0.691	3.915	0.698	5
2800	3.653	0.683	3.661	0.687	5
2900	3.368	0.648	3.377	0.654	5
3000	3.052	0.609	3.059	0.622	5



Audio Frequency Response

Carrier Frequency: 465.0125 MHz, Channel Separation=25 kHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-12.80
400	-8.61
500	-6.14
600	-4.48
700	-2.95
800	-1.68
900	-0.80
1000	0.00
1200	1.68
1400	2.89
1600	4.29
1800	4.93
2000	5.88
2100	6.21
2200	6.42
2300	6.82
2400	7.15
2500	7.08
2600	6.86
2700	6.82
2800	6.72
2900	6.29
3000	5.79



Audio frequency lows pass filter response

Carrier Frequency: 465.0125 MHz, Channel Separation=25 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-13.20	0.0
4.0	-77.70	-7.5
5.0	-80.60	-13.3
6.0	-89.80	-18.1
7.0	-87.10	-22.1
8.0	-88.20	-25.6
9.0	-93.90	-28.6
10.0	-89.90	-31.4
15.0	-93.60	-41.9
20.0	-90.80	-50.0
30.0	-89.40	-50.0
40.0	-90.10	-50.0
50.0	-96.50	-50.0
60.0	-96.70	-50.0
70.0	-92.60	-50.0



FCC §2.1049 & §22.357 & § 22.731 & §74.462 & § 80.205 & § 80.207 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK**Applicable Standard**

FCC §2.1049, §22.357, § 22.731, §74.462, § 80.205, § 80.207, §90.209 and §90.210

Test Procedure

The test was performed in according to ANSI/TIA-603-D Section 2.2.11.2.

Test Data**Environmental Conditions**

Temperature:	24~25
Relative Humidity:	50~56 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by Dylan Li from 2018-01-01 to 2018-03-10.

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)	Note
Analog	12.5	453.2125	High	9.94	10.34	For Part 74/90
	12.5		Low	9.94	10.34	
	12.5	454.5	High	9.94	10.26	For Part 22
	12.5		Low	9.94	10.26	
Digital	12.5	453.2125	High	7.53	9.29	For Part 74/90
	12.5		Low	7.53	9.78	
	12.5	454.5	High	7.61	8.89	For Part 22
	12.5		Low	7.85	9.78	

Emission designator is base on calculation instead of measurement

Emission Designator Per CFR 47 §2.201& §2.202&, $B_n = 2M + 2D$

For FM Mode (Channel Spacing: 12.5 kHz)

Emission Designator 11K0F3E In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation. $BW = 2(M+D) = 2(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz}$ 11K0*

F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.


For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1E


The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.85 kHz. The emission mask was obtained from 47CFR 90.210(d).

F1D and F1E portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1E.


Analog Modulation:**Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power**

Date: 1.JAN.2018 19:21:35

Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power


Date: 1.JAN.2018 19:20:38

Frequency 453.2125 MHz: Emission Mask D, High Power




Date: 1.JAN.2018 18:52:06

Frequency 453.2125 MHz: Emission Mask D, Low Power




Date: 1.JAN.2018 18:49:43

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, High Power




Date: 1.JAN.2018 19:18:30

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, Low Power




Date: 1.JAN.2018 19:19:18

Frequency 454.5 MHz: Emission Mask, High Power, FCC part 22.359




Date: 1.JAN.2018 18:56:26

Frequency 454.5 MHz: Emission Mask, Low Power, FCC part 22.359




Date: 1.JAN.2018 18:55:36

Frequency 453.2125 MHz: 99% Occupied & 26 dB Bandwidth, High Power




Date: 1.JAN.2018 20:46:29

Frequency 453.2125 MHz: Emission Mask D, High Power




Date: 1.JAN.2018 21:02:00

Frequency 453.2125 MHz: Emission Mask D, Low Power




Date: 1.JAN.2018 21:00:57

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, High Power




Date: 1.JAN.2018 20:48:27

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, Low Power




Date: 1.JAN.2018 20:50:04

Frequency 454.5 MHz: Emission Mask, High Power, FCC part 22.359



Date: 1.JAN.2018 20:59:11

Frequency 454.5 MHz: Emission Mask, Low Power, FCC part 22.359



Date: 15.JAN.2018 22:30:33

Modulation	Channel Separation (kHz)	Frequency (MHz)	Power Level	99% Occupied Bandwidth (kHz)	26 dB Emissions Bandwidth (kHz)	Note
Analog	25	454.5	High	15.06	15.71	For Part 22
	25		Low	15.06	15.71	
	25	465.0125	High	15.06	15.71	For Part 80
	25		Low	15.06	15.71	
	25	450.0125	High	15.06	15.71	For Part 74
	25		Low	15.06	15.71	

Emission designator is base on calculation instead of measurement

Emission Designator Per CFR 47 §2.201 & §2.202, $B_n = 2M + 2D$


For FM Mode (Channel Spacing: 25 kHz)

Emission Designator 16K0F3E In this case, the maximum modulating frequency is 5.0 kHz with a 3 kHz deviation. $BW = 2(M+D) = 2(5 \text{ kHz} + 3 \text{ kHz}) = 16 \text{ kHz}$ 16K0*

F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 25 kHz channel spacing FM mode is 16K0F3E.


Analog Modulation

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, High Power




Date: 1.JAN.2018 19:12:38

Frequency 454.5 MHz: 99% Occupied & 26 dB Bandwidth, Low Power




Date: 1.JAN.2018 19:11:36

Frequency 454.5 MHz: Emission Mask B, High Power




Date: 1.JAN.2018 19:02:30

Frequency 454.5 MHz: Emission Mask B, Low Power




Date: 1.JAN.2018 19:03:03

Frequency 465.0125 MHz: 99% Occupied & 26 dB Bandwidth, High Power




Date: 1.JAN.2018 19:10:04

Frequency 465.0125 MHz: 99% Occupied & 26 dB Bandwidth, Low Power




Date: 1.JAN.2018 19:10:47

Frequency 465.0125 MHz: Emission Mask B, High Power




Date: 1.JAN.2018 19:08:13

Frequency 465.0125 MHz: Emission Mask B, Low Power




Date: 1.JAN.2018 19:07:31

Frequency 450.0125 MHz: 99% Occupied & 26 dB Bandwidth, High Power




Date: 10.MAR.2018 17:27:33

Frequency 450.0125MHz: 99% Occupied & 26 dB Bandwidth, Low Power




Date: 10.MAR.2018 17:30:08

Frequency 450.0125 MHz: Emission Mask B, High Power



Date: 10.MAR.2018 17:43:04

Frequency 450.0125 MHz: Emission Mask B, Low Power



Date: 10.MAR.2018 17:45:31

FCC §2.1051 & §22.861 & §74.462 & § 80.211 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) For any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 , 0 dB.
- 2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.626 kHz but no more than 12.5 kHz, at least $7.27 (f_d - 2.88 \text{ kHz})$ dB.
- 3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

Emission Mask B—25 kHz channel bandwidth equipment. For transmitters designed to operate with a 25 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- 2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- 3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.

Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

Test Data

Environmental Conditions

Temperature:	24
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa


The testing was performed by Dylan Li from 2017-12-19 to 2018-03-10 .

Test Mode: Transmitting, please refer to the following plots.

Note: All test was performed under the high power.


Analog Modulation:

30MHz – 1 GHz, Channel Spacing 12.5 kHz, 453.2125 MHz, For FCC part 74/90




Date: 19.DEC.2017 22:20:29

1 GHz – 5 GHz, Channel Spacing 12.5 kHz, 453.2125 MHz, For FCC part 74/90




Date: 19.DEC.2017 22:25:33

30MHz – 1 GHz, Channel Spacing 12.5 kHz, 454.5 MHz, For FCC part 22




Date: 19.DEC.2017 22:20:44

1 GHz – 5 GHz, Channel Spacing 12.5 kHz, 454.5 MHz, For FCC part 22




Date: 19.DEC.2017 22:25:10

30MHz – 1 GHz, Channel Spacing 25 kHz, 454.5 MHz, For FCC part 22




Date: 19.DEC.2017 22:22:10

1 GHz – 5 GHz, Channel Spacing 25 kHz, 454.5 MHz, For FCC part 22




Date: 19.DEC.2017 22:23:48

30MHz – 1 GHz, Channel Spacing 25 kHz, 465.0125 MHz, For FCC part 80




Date: 19.DEC.2017 22:22:44


1 GHz – 5 GHz, Channel Spacing 25 kHz, 465.0125 MHz, For FCC part 80



Date: 19.DEC.2017 22:23:25

30MHz – 1 GHz, Channel Spacing 25 kHz, 450.0125 MHz, For FCC part 74


Date: 10.MAR.2018 17:06:50

1 GHz – 5 GHz, Channel Spacing 25 kHz, 450.0125 MHz, For FCC part 74

Date: 10.MAR.2018 17:08:25


Digital Modulation:

30MHz – 1 GHz, 453.2125 MHz, For FCC part 74/90




Date: 19.DEC.2017 22:15:19

1 GHz – 5 GHz, 453.2125 MHz, For FCC part 74/90




Date: 19.DEC.2017 22:27:01

30MHz – 1 GHz, 454.5 MHz, For FCC part 22



Date: 19.DEC.2017 22:16:43

1 GHz – 5 GHz, 454.5 MHz, For FCC part 22



Date: 19.DEC.2017 22:26:45

FCC §2.1053 & §22.861 & §74.462 & § 80.211 & §90.210 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §2.1053, §22.861, §74.462, § 80.211 and §90.210

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001)-the absolute level

Spurious attenuation limit in dB = 50 + 10 Log₁₀ (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

Spurious attenuation limit in dB = 43 + 10 Log₁₀ (power out in Watts) for EUT with a 25 kHz channel bandwidth.

Test Data

Environmental Conditions

Temperature:	24
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2018-01-09.

Test Mode: Transmitting

30MHz - 6GHz:

Frequency (MHz)	Receiver Reading (dBμV)	Turn Table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
Analog Modulation 453.2125MHz-12.5 kHz For part 74/90										
906.425	40.63	219	1.8	H	-55.1	0.70	0.0	-55.80	-20	35.80
906.425	41.18	266	1.7	V	-53.1	0.70	0.0	-53.80	-20	33.80
3625.70	51.46	340	1.2	H	-49.6	1.50	9.80	-41.30	-20	21.30
3625.70	49.36	191	2.3	V	-51.2	1.50	9.80	-42.90	-20	22.90
4078.91	47.55	305	1.5	H	-52.4	1.40	10.00	-43.80	-20	23.80
4078.91	45.28	294	2.3	V	-53.6	1.40	10.00	-45.00	-20	25.00
Digital Modulation 453.0125MHz For part 74/90										
906.425	41.12	296	2.2	H	-54.6	0.70	0.0	-55.30	-20	35.30
906.425	40.39	348	1.7	V	-53.9	0.70	0.0	-54.60	-20	34.60
3625.70	53.68	35	1.2	H	-47.4	1.50	9.80	-39.10	-20	19.10
3625.70	51.47	183	1.8	V	-49.1	1.50	9.80	-40.80	-20	20.80
4078.91	46.58	145	2.4	H	-53.4	1.40	10.00	-44.80	-20	24.80
4078.91	45.33	216	1.5	V	-53.5	1.40	10.00	-44.90	-20	24.90
Analog Modulation 454.5MHz-12.5 kHz For part 22										
909	41.25	83	1.4	H	-54.5	0.70	0.0	-55.20	-13	42.20
909	42.62	161	1.6	V	-51.6	0.70	0.0	-52.30	-13	39.30
3181.50	51.27	214	1.4	H	-47.4	1.60	9.60	-39.40	-13	26.40
3181.50	50.38	284	1.7	V	-48.6	1.60	9.60	-40.60	-13	27.60
3636.00	47.35	331	2.1	H	-53.7	1.50	9.80	-45.40	-13	32.40
3636.00	45.22	225	2.0	V	-55.3	1.50	9.80	-47.00	-13	34.00
Digital Modulation 454.5 MHz For part 22										
909	39.67	272	1.4	H	-56.1	0.70	0.0	-56.80	-13	43.80
909	40.29	233	1.3	V	-54.0	0.70	0.0	-54.70	-13	41.70
3181.50	46.87	267	1.9	H	-51.8	1.60	9.60	-43.80	-13	30.80
3181.50	48.33	334	1.5	V	-50.6	1.60	9.60	-42.60	-13	29.60
3636.00	50.06	101	1.9	H	-51.0	1.50	9.80	-42.70	-13	29.70
3636.00	52.25	16	2.4	V	-48.3	1.50	9.80	-40.00	-13	27.00

Frequency (MHz)	Receiver Reading (dBμV)	Turn Table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
Analog Modulation 454.5 MHz-25 kHz For part 22										
909	41.96	205	2.4	H	-53.8	0.70	0.0	-54.50	-13	41.50
909	40.87	1	1.7	V	-53.4	0.70	0.0	-54.10	-13	41.10
3636.00	53.64	12	2.1	H	-47.4	1.50	9.80	-39.10	-13	26.10
3636.00	51.87	125	1.8	V	-48.7	1.50	9.80	-40.40	-13	27.40
4090.50	48.34	266	2.3	H	-51.6	1.40	10.00	-43.00	-13	30.00
4090.50	45.77	286	1.6	V	-53.1	1.40	10.00	-44.50	-13	31.50
Analog Modulation 465.0125 MHz-25 kHz For part 80										
930.025	43.42	169	1.7	H	-50.8	0.74	0.0	-51.54	-13	38.54
930.025	42.91	329	1.1	V	-51.4	0.74	0.0	-52.14	-13	39.14
2790.08	48.35	193	1.4	H	-54.5	1.80	9.70	-46.60	-13	33.60
2790.08	46.27	224	1.6	V	-56.2	1.80	9.70	-48.30	-13	35.30
3255.09	45.11	350	1.3	H	-54.5	1.50	9.60	-46.40	-13	33.40
3255.09	43.24	78	1.7	V	-56.4	1.50	9.60	-48.30	-13	35.30
Analog Modulation 450.0125 MHz-25 kHz For part 74										
900.03	41.35	255	2.0	V	-54.4	0.7	0.0	-55.10	-13	42.10
900.03	40.51	41	1.9	H	-53.7	0.7	0.0	-54.40	-13	41.40
2800.09	52.47	203	1.8	H	-51.5	1.80	9.70	-43.60	-13	30.60
2800.09	50.63	185	2.1	V	-53.0	1.80	9.70	-45.10	-13	32.10
3200.10	49.87	224	1.9	H	-49.6	1.60	9.60	-41.60	-13	28.60
3200.10	47.64	238	1.8	V	-52.1	1.60	9.60	-44.10	-13	31.10

Note:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1055 & § 22.355 & §74.464 & § 80.209 & §90.213 - FREQUENCY STABILITY

Applicable Standard

FCC §2.1055, § 22.355, §74.464, § 80.209 and §90.213

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

Test Data

Environmental Conditions

Temperature:	24
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Dylan Li on 2018-01-10.

Test Mode: Transmitting

Note: This device is a Base station.

For 12.5 kHz:

Analog Modulation, Reference Frequency: 453.2125 MHz, Limit: ± 1.5 ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature ()	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	453.21245	-0.1103
40	13.6	453.21247	-0.0662
30	13.6	453.21247	-0.0662
20	13.6	453.21242	-0.1765
10	13.6	453.21241	-0.1986
0	13.6	453.21241	-0.1986
-10	13.6	453.21246	-0.0883
-20	13.6	453.21246	-0.0883
-30	13.6	453.21241	-0.1986
Frequency Stability Versus Input Voltage			
20	11.6	453.21245	-0.1103

Digital Modulation, Reference Frequency: 453.2125 MHz, Limit: ± 1.5 ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature ()	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	453.21245	-0.1103
40	13.6	453.21244	-0.1324
30	13.6	453.21245	-0.1103
20	13.6	453.21249	-0.0221
10	13.6	453.21248	-0.0441
0	13.6	453.21250	0
-10	13.6	453.21246	-0.0883
-20	13.6	453.21242	-0.1765
-30	13.6	453.21249	-0.0221
Frequency Stability Versus Input Voltage			
20	11.6	453.21242	-0.1765

Analog Modulation, Reference Frequency: 454.5 MHz, Limit: ± 2.5 ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature ()	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	454.49995	-0.1100
40	13.6	454.49998	-0.0440
30	13.6	454.49994	-0.1320
20	13.6	454.50000	-0.1760
10	13.6	454.49993	-0.1540
0	13.6	454.49991	-0.1980
-10	13.6	454.49994	-0.1320
-20	13.6	454.49997	-0.0660
-30	13.6	454.49994	-0.1320
Frequency Stability versus Input Voltage			
20	11.6	454.49997	-0.0660

Digital Modulation, Reference Frequency: 454.5 MHz, Limit: ± 2.5 ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature ()	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	454.49995	-0.1100
40	13.6	454.49999	-0.0220
30	13.6	454.49994	-0.1320
20	13.6	454.49998	-0.0440
10	13.6	454.49991	-0.1980
0	13.6	454.49992	-0.1760
-10	13.6	454.49996	-0.0880
-20	13.6	454.49996	-0.0880
-30	13.6	454.49998	-0.0440
Frequency Stability versus Input Voltage			
20	11.6	454.49999	-0.0220

For 25 kHz:

Analog Modulation, Reference Frequency: 453.2125 MHz, Limit: ± 2.5 ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature ()	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	453.21245	-0.1103
40	13.6	453.21245	-0.1103
30	13.6	453.21241	-0.1986
20	13.6	453.21248	-0.0441
10	13.6	453.21248	-0.0441
0	13.6	453.21242	-0.1765
-10	13.6	453.21244	-0.1324
-20	13.6	453.21247	-0.0662
-30	13.6	453.21247	-0.0662
Frequency Stability versus Input Voltage			
20	11.6	453.21249	-0.0221

Analog Modulation, Reference Frequency: 465.0125 MHz, Limit: ± 5.0 ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature ()	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	465.01245	-0.1075
40	13.6	465.01242	-0.1720
30	13.6	465.01243	-0.1505
20	13.6	465.01242	-0.1720
10	13.6	465.01247	-0.0645
0	13.6	465.01242	-0.1720
-10	13.6	465.01242	-0.1720
-20	13.6	465.01244	-0.1290
-30	13.6	465.01243	-0.1505
Frequency Stability versus Input Voltage			
20	11.6	465.01246	-0.0860

Analog Modulation, Reference Frequency: 450.0125 MHz, Limit: ± 2.5 ppm			
Test Environment		Frequency Measure with Time Elapsed	
Temperature ()	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	13.6	450.01243	-0.1556
40	13.6	450.01240	-0.2222
30	13.6	450.01248	-0.0444
20	13.6	450.01242	-0.1778
10	13.6	450.01246	-0.0889
0	13.6	450.01241	-0.2000
-10	13.6	450.01243	-0.1556
-20	13.6	450.01247	-0.0667
-30	13.6	450.01245	-0.1111
Frequency Stability versus Input Voltage			
20	11.6	450.01247	-0.0667

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR


Applicable Standard

Regulations: FCC §90.214

Test method: ANSI/TIA-603-D 2010, section 2.2.19.3

Test Procedure

- Connect the EUT and test equipment as shown on the following block diagram.
- Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- Turn on the transmitter.
- Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P_0 .
- Turn off the transmitter.
- Adjust the RF level of the signal generator to provide RF power equal to P_0 . This signal generator RF level shall be maintained throughout the rest of the measurement.
- Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ± 4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to "Video", and tune the "trigger level" on suitable level. Then set the "trigger offset" to -10ms for turn on and -15ms for turn off.
- Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on} . The trace should be maintained within the allowed divisions during the period t_1 and t_2 .
- Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t_3 .



Test Data

Environmental Conditions

Temperature:	25
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Dylan Li on 2018-01-09.

Channel Separation (kHz)	Transient Period (ms)	Transient Frequency	Result
12.5	10 (t1)	<+/-12.5 kHz	Pass
	25(t2)	<+/-6.25 kHz	
	10 (t3)	<+/-12.5 kHz	


Please refer to the following plots.

Channel: 453.2125 MHz, 12.5 kHz

Turn on



Turn off



***** END OF REPORT *****