



FCC REPORT (Mobile Phone)

Applicant: Zonda Corporation, S.A. de C.V

Address of Applicant: Schiller 329 Street, Chapultepec Morales, Zip code 11560, Mexico City, Mexico

Equipment Under Test (EUT)

Product Name: MOBILE PHONE

Model No.: ZMRK700

Trade mark: ZONDA

FCC ID: YAUZMRK700

Applicable standards: FCC CFR Title 47 Part 2: 2010
FCC CFR Title 47 Part22 Subpart H: 2010
FCC CFR Title 47 Part24 Subpart E: 2010

Date of sample receipt: Oct. 11, 2011

Date of Test: Oct.12-22, 2011

Date of report issued: Oct.24, 2011

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Stephen Guo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	Oct. 24, 2011	Original

Prepared By:

Collin. He

Date:

Oct. 24, 2011

Project Engineer

Check By:

Hans. Hu

Date:

Oct. 24, 2011

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE:	7
5.4 RELATED SUBMITTAL(S) / GRANT (S) ..	7
5.5 TEST METHODOLOGY	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 TEST INSTRUMENTS LIST	8
6 SYSTEM TEST CONFIGURATION.....	9
6.1 EUT CONFIGURATION.....	9
6.2 EUT EXERCISE	9
6.3 CONFIGURATION OF TESTED SYSTEM ..	9
6.4 DESCRIPTION OF TEST MODES	9
6.5 CONDUCTED EMISSIONS.....	10
6.6 CONDUCTED PEAK OUTPUT POWER	15
6.7 OCCUPY BANDWIDTH.....	17
6.8 MODULATION CHARACTERISTIC	22
6.9 OUT OF BAND EMISSION AT ANTENNA TERMINALS	22
6.10 ERP, EIRP MEASUREMENT	31
6.11 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	35
6.12 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	40
6.13 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	42

4 Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Passed* (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Zonda Corporation, S.A. de C.V
Address of Applicant:	Schiller 329 Street, Chapultepec Morales, Zip code 11560, Mexico City, Mexico
Manufacturer:	SHENZHEN RIRIKANG TECHNOLOGY CO.,LTD
Address of Manufacturer:	1705 units, FIYTA BUILDING,RD. 1,SOUTHERN HI-TECH PARK,NANSHAN DISTRICT,SHENZHEN,CHINA
Factory:	SHENZHEN YDE ELECTRONICS CO.,LTD.
Address of Factory:	HuiXin Industrial Park, HePing Community, FuYong Town, Bao'an District, Shenzhen

5.2 General Description of E.U.T.

Product Name:	MOBILE PHONE
Model No.:	ZMRK700
Trade mark:	ZONDA
Operation Frequency range:	GSM/GPRS 850: 824MHz-849MHz PCS1900: 1850MHz-1910MHz
Type of Emission:	248KGXW
IMEI:	352273017386340 352751019523267
Software Version:	V2.0
Hardware Version:	V1.0
Data cable(USB):	Length 1m
Earphone line:	Length 1.5m
AC adapter:	Model:BL-5C Voltage: DC 3.7V Lithium battery Rating Capacity: 1200mAh
Power supply:	Input: AC 100-240V 50/60Hz 120mA Output: DC 5.5V 500mA

Operation Frequency List:

GSM 850		PCS1900	
Channel:	Frequency (MHz)	Channel:	Frequency (MHz)
128	824.20	512	1850.20
129	824.40	513	1850.40
...
189	836.40	660	1879.80
190	836.60	661	1880.00
191	836.80	662	1880.20
...
250	848.60	809	1909.60
251	848.80	810	1909.80

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

GSM850			PCS1900		
	Channel	Frequency(MHz)		Channel	Frequency(MHz)
Lowest channel	128	824.20	Lowest channel	512	1850.20
Middle channel	190	836.60	Middle channel	661	1880.00
Highest channel	251	848.80	Highest channel	810	1909.80

5.3 Test mode:

Communicate mode (GSM850)	Keep the EUT in communicating mode on GSM850 band.
Communicate mode (PCS1900)	Keep the EUT in communicating mode on PCS1900 band.

5.4 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

5.5 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on chapter 13 of ANSI C63.4 (2003) and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- FCC —Registration No.: 600491

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, July 20, 2010.

- Industry Canada (IC)

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-1.

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

5.8 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 30 2011	Mar. 29 2012
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 04 2011	Jul. 03 2012
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 26 2011	Feb. 25 2012
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 30 2011	June 29 2012
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2011	Mar. 29 2012
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	Apr. 01 2011	Mar. 31 2012
9	Coaxial Cable	GTS	N/A	GTS211	Apr. 01 2011	Mar. 31 2012
9	Coaxial cable	GTS	N/A	GTS210	Apr. 01 2011	Mar. 31 2012
11	Coaxial Cable	GTS	N/A	GTS212	Apr. 01 2011	Mar. 31 2012
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 04 2011	Jul. 03 2012
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 04 2011	Jul. 03 2012
14	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Apr. 01 2011	Mar. 31 2012
15	Band filter	Amindeon	82346	GTS219	Apr. 01 2011	Mar. 31 2012
16	Universal radio communication tester	Rohde & Schwarz	CMU200	GTS235	May 11 2011	May 11 2012
17	Signal Generator	Rohde & Schwarz	SML03	GTS236	May 11 2011	May 11 2012
18	Temp. Humidity/ Barometer	Oregon Scientific	BA-888	GTS248	May 11 2011	May 11 2012
19	D.C. Power Supply	Instek	PS-3030	GTS232	NA	NA
20	Splitter	Agilent	11636B	GTS237	May 11 2011	May 11 2012

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS252	Jul. 04 2011	Jul. 03 2012
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	Jul. 04 2011	Jul. 03 2012
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	Jul. 04 2011	Jul. 03 2012
4	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	Jul. 04 2011	Jul. 03 2012
5	Coaxial Cable	GTS	N/A	GTS227	Apr. 01 2011	Mar. 31 2012
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

6 System test configuration


6.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

6.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency which was for the purpose of the measurements.

6.3 Configuration of Tested System



6.4 DESCRIPTION OF TEST MODES


The EUT has been tested under operating condition.
EUT staying in continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing.
The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for both GSM/PCS with power adaptors, earphone and Data cable. The worst-case H mode for GSM 850 band, PCS1900 band.

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.4: 2009														
Test Frequency Range:	150KHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9KHz, VBW=30KHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr> <tr> <th>Quasi-peak</th><th>Average</th></tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement. 														
Test setup:	<p><i>Remark:</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Instruments:	Refer to section 5.8 for details														
Test mode:	Refer to section 5.3 for details														
Test results:	Passed														

Global United Technology Services Co., Ltd.
2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District,
Shenzhen, China 518102

Test mode: GSM850


Live Line:



Condition : FCC PART15 CLASSB QP LISN(2011) LINE
 Job No. : 823RF
 Test Mode : Communication mode
 Test Engineer: Collin
 Remark : GSM850

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.230	36.21	0.64	0.10	36.95	62.44	-25.49	QP
2	0.230	29.38	0.64	0.10	30.12	52.44	-22.32	Average
3	0.360	39.66	0.59	0.10	40.35	58.74	-18.39	QP
4	0.360	30.29	0.59	0.10	30.98	48.74	-17.76	Average
5	0.532	36.12	0.55	0.10	36.77	56.00	-19.23	QP
6	0.532	29.99	0.55	0.10	30.64	46.00	-15.36	Average
7	1.324	32.09	0.45	0.10	32.64	56.00	-23.36	QP
8	1.324	25.69	0.45	0.10	26.24	46.00	-19.76	Average
9	2.249	31.28	0.39	0.10	31.77	56.00	-24.23	QP
10	2.249	23.47	0.39	0.10	23.96	46.00	-22.04	Average
11	5.166	28.15	0.30	0.10	28.55	60.00	-31.45	QP
12	5.166	20.39	0.30	0.10	20.79	50.00	-29.21	Average

Neutral Line:




Condition : FCC PART15 CLASSB QP LISN(2011) NEUTRAL
 Job No. : 823RF
 Test Mode : Communication mode
 Test Engineer: Collin
 Remark : GSM850

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.230	36.75	0.64	0.10	37.49	62.44	-24.95	QP
2	0.230	29.69	0.64	0.10	30.43	52.44	-22.01	Average
3	0.305	36.25	0.61	0.10	36.96	60.10	-23.14	QP
4	0.305	29.36	0.61	0.10	30.07	50.10	-20.03	Average
5	0.604	32.04	0.53	0.10	32.67	56.00	-23.33	QP
6	0.604	24.69	0.53	0.10	25.32	46.00	-20.68	Average
7	1.480	31.51	0.43	0.10	32.04	56.00	-23.96	QP
8	1.480	24.25	0.43	0.10	24.78	46.00	-21.22	Average
9	3.190	25.73	0.35	0.10	26.18	56.00	-29.82	QP
10	3.190	16.89	0.35	0.10	17.34	46.00	-28.66	Average
11	7.486	22.71	0.25	0.17	23.13	60.00	-36.87	QP
12	7.486	15.69	0.25	0.17	16.11	50.00	-33.89	Average

Test mode: PCS1900


Live Line:



Condition : FCC PART15 CLASSB QP LISN(2011) LINE
 Job No. : 823RF
 Test Mode : Communication mode
 Test Engineer: Collin
 Remark : PCS1900

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.230	35.51	0.64	0.10	36.25	62.44	-26.19	QP
2	0.230	28.96	0.64	0.10	29.70	52.44	-22.74	Average
3	0.360	40.63	0.59	0.10	41.32	58.74	-17.42	QP
4	0.360	32.69	0.59	0.10	33.38	48.74	-15.36	Average
5	0.529	36.02	0.55	0.10	36.67	56.00	-19.33	QP
6	0.529	29.96	0.55	0.10	30.61	46.00	-15.39	Average
7	1.610	32.82	0.42	0.10	33.34	56.00	-22.66	QP
8	1.610	24.67	0.42	0.10	25.19	46.00	-20.81	Average
9	2.201	32.60	0.39	0.10	33.09	56.00	-22.91	QP
10	2.201	24.68	0.39	0.10	25.17	46.00	-20.83	Average
11	5.505	27.84	0.29	0.11	28.24	60.00	-31.76	QP
12	5.505	20.13	0.29	0.11	20.53	50.00	-29.47	Average

Neutral Line:




Condition : FCC PART15 CLASSB QP LISN(2011) NEUTRAL
 Job No. : 823RF
 Test Mode : Communication mode
 Test Engineer: Collin
 Remark : PCS1900

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.302	36.74	0.61	0.10	37.45	60.19	-22.74	QP
2	0.302	28.96	0.61	0.10	29.67	50.19	-20.52	Average
3	0.611	35.36	0.53	0.10	35.99	56.00	-20.01	QP
4	0.611	27.57	0.53	0.10	28.20	46.00	-17.80	Average
5	1.610	29.59	0.42	0.10	30.11	56.00	-25.89	QP
6	1.610	20.99	0.42	0.10	21.51	46.00	-24.49	Average
7	3.241	25.41	0.35	0.10	25.86	56.00	-30.14	QP
8	3.241	18.96	0.35	0.10	19.41	46.00	-26.59	Average
9	5.031	25.77	0.30	0.10	26.17	60.00	-33.83	QP
10	5.031	18.94	0.30	0.10	19.34	50.00	-30.66	Average
11	15.635	19.49	0.17	0.20	19.86	60.00	-40.14	QP
12	15.635	11.23	0.17	0.20	11.60	50.00	-38.40	Average

Notes:

1. An initial pre-scan was performed on the live and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

6.6 Conducted Peak Output Power


Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850 7W PCS1900 2W
Test setup:	 <p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a spectrum analysis. Transmitter output was read off the spectrum analysis in dBm. The power output at the transmitter antenna port was determined by adding the value of the attenuator to spectrum analysis reading.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

EUT Mode	Channel	Frequency (MHz)	PK power (dBm)	Limit(dBm)	Result
GSM 850	128	824.20	31.67	38.45	Pass
	190	836.60	31.56		
	251	848.80	31.61		
PCS 1900	512	1850.20	29.23	33.00	Pass
	661	1880.00	28.72		
	810	1909.80	28.16		


Test plot as follows:

Test mode:	GSM850
------------	--------




Date: 12.OCT.2011 12:22:25

Test mode:	PCS1900
------------	---------



6.7 Occupy Bandwidth


Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1049
Test setup:	 <p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
GSM 850	128	824.20	244	316
	190	836.60	244	312
	251	848.80	246	320
PCS 1900	512	1850.20	248	312
	661	1880.00	244	314
	810	1909.80	242	314


Test plot as follows:

Test Item:	99% Occupy bandwidth	Test Mode:	GSM850
------------	----------------------	------------	--------




Date: 12.OCT.2011 12:24:07

Lowest channel



Date: 12.OCT.2011 12:28:08


Middle channel



Date: 12.OCT.2011 12:33:43


Highest channel:

Test Item:	99% Occupy bandwidth	Test Mode:	PCS1900
------------	----------------------	------------	---------




Date: 12.OCT.2011 13:05:49

Lowest channel



Date: 12.OCT.2011 13:10:36


Middle channel



Date: 12.OCT.2011 13:11:29


Highest channel:

Test Item:	-26dB bandwidth	Test Mode:	GSM850
------------	-----------------	------------	--------




Date: 12.OCT.2011 12:23:40

Lowest channel



Date: 12.OCT.2011 12:27:39


Middle channel



Date: 12.OCT.2011 12:33:06


Highest channel:

Test Item:	-26dB bandwidth	Test Mode:	PCS1900
------------	-----------------	------------	---------




Date: 12.OCT.2011 13:05:15

Lowest channel



Date: 12.OCT.2011 13:10:06

Middle channel




Date: 12.OCT.2011 13:12:01

Highest channel:

6.8 MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.


6.9 Out of band emission at antenna terminals

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1051
Limit:	-13dBm
Test setup:	 <p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> 1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:


Spurious emission

Test Mode:	GSM850	Test Channel:	Lowest channel
------------	--------	---------------	----------------



Date: 12.OCT.2011 12:24:42


30MHz~1GHz



Date: 12.OCT.2011 12:25:28


1GHz~9GHz

Test Mode:	GSM850	Test Channel:	Middle channel
------------	--------	---------------	----------------



Date: 12.OCT.2011 12:28:54


30MHz~1GHz



Date: 12.OCT.2011 12:29:10


1GHz~9GHz

Test Mode:	GSM850	Test Channel:	Highest channel
------------	--------	---------------	-----------------



Date: 12.OCT.2011 12:29:47


30MHz~1GHz




Date: 12.OCT.2011 12:29:26

1GHz~9GHz

Test Mode:	PCS1900	Test Channel:	Lowest channel
------------	---------	---------------	----------------




30MHz~1GHz




Date: 12.OCT.2011 13:07:08

1GHz~9GHz




9GHz~19GHz

Test Mode:	PCS1900	Test Channel:	Middle channel
------------	---------	---------------	----------------




30MHz~1GHz




Date: 12.OCT.2011 13:09:08

1GHz~9GHz




9GHz~19GHz

Test Mode:	PCS1900	Test Channel:	Highest channel
------------	---------	---------------	-----------------




30MHz~1GHz



Date: 12.OCT.2011 13:13:00


1GHz~9GHz



9GHz~19GHz


Band edge emission:

Test Mode:	GSM850
------------	--------



Date: 12.OCT.2011 12:26:45


Lowest channel



Date: 12.OCT.2011 12:32:02


Highest channel

Test Mode:	PCS1900
------------	---------



Date: 12.OCT.2011 13:08:10




Lowest channel



Date: 12.OCT.2011 13:13:34

Highest channel

6.10 ERP, EIRP Measurement

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850 7W ERP PCS1900 2W EIRP
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p>  <p>Substituted method:</p> 




Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated. 3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated asfollows: $\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$ 4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows: $\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850	Lowest	H	V	31.50	38.45	Pass
			H	30.10		
		E1	V	29.16		
			H	29.86		
		E2	V	28.65		
			H	29.11		
	Middle	H	V	29.87	38.45	Pass
			H	28.36		
		E1	V	28.03		
			H	28.12		
		E2	V	27.53		
			H	28.01		
	Highest	H	V	29.06	38.45	Pass
			H	28.10		
		E1	V	27.52		
			H	28.01		
		E2	V	27.12		
			H	27.34		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
PCS1900	Lowest	H	V	28.52	33.00	Pass
			H	27.59		
		E1	V	27.16		
			H	27.49		
		E2	V	26.51		
			H	27.06		
	Middle	H	V	27.67	33.00	Pass
			H	26.60		
		E1	V	26.19		
			H	26.44		
		E2	V	26.01		
			H	26.29		
	Highest	H	V	27.58	33.00	Pass
			H	26.23		
		E1	V	26.06		
			H	26.12		
		E2	V	25.67		
			H	25.95		

6.11 Field strength of spurious radiation measurement

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1053
Limit:	-13dBm
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p>  <p>Substituted method:</p> 

Test Procedure:	<ol style="list-style-type: none">1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method.4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Test mode:	GSM850		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
143.26	Vertical	-42.10	-13.00	Pass
2472.60	V	-26.85		
3296.80	V	-42.22		
4121.00	V	-48.77		
4945.20	V	---		
5769.40	V	---		
122.24	Horizontal	-40.46	-13.00	Pass
2472.60	H	-28.17		
3296.80	H	-43.78		
4121.00	H	-50.25		
4945.20	H	---		
5769.40	H	---		
Test mode:	GSM850		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
98.64	Vertical	-42.66	-13.00	Pass
2509.80	V	-26.26		
3346.40	V	-42.32		
4183.00	V	-46.69		
5019.60	V	---		
5856.20	V	---		
136.02	Horizontal	-41.06	-13.00	Pass
2509.80	H	-27.47		
3346.40	H	-43.87		
4183.00	H	-48.05		
5019.60	H	---		
5856.20	H	---		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	GSM850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
113.58	Vertical	-45.29	-13.00	Pass
2546.40	V	-25.14		
3395.20	V	-45.28		
4244.00	V	-44.15		
5092.80	V	---		
5941.60	V	---		
203.69	Horizontal	-44.09	-13.00	Pass
2546.40	H	-26.47		
3395.20	H	-46.72		
4244.00	H	-45.70		
5092.80	H	---		
5941.60	H	---		
Test mode:	PCS1900		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
169.32	Vertical	-43.68	-13.00	Pass
3700.40	V	-38.24		
5550.60	V	-40.75		
7400.80	V	-36.93		
9251.00	V	---		
11101.20	V	---		
143.21	Horizontal	-41.16	-13.00	Pass
3700.40	H	-39.60		
5550.60	H	-42.20		
7400.80	H	-38.56		
9251.00	H	---		
11101.20	H	---		

Remark :


1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	PCS1900		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
103.56	Vertical	-46.02	-13.00	Pass
3760.00	V	-31.37		
5640.00	V	-39.57		
7520.00	V	-36.40		
9400.00	V	---		
11280.00	V	---		
168.02	Horizontal	-44.32	-13.00	Pass
3760.00	H	-32.95		
5640.00	H	-41.19		
7520.00	H	-38.07		
9400.00	H	---		
11280.00	H	---		
Test mode:	PCS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
301.65	Vertical	-46.89	-13.00	Pass
3819.60	V	-28.46		
5729.40	V	-32.01		
7639.20	V	-40.42		
9549.00	V	---		
11458.80	V	---		
264.02	Horizontal	-41.09	-13.00	Pass
3819.60	H	-29.82		
5729.40	H	-33.53		
7639.20	H	-42.06		
9549.00	H	---		
11458.80	H	---		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of other frequencies are very lower than the limit and not show in test report.


6.12 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part2.1055(a)(1)(b)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	 <p>Note : Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> 1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to –20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-20	50	0.0598	2.5	Pass
	-10	52	0.0622		
	0	53	0.0634		
	10	44	0.0526		
	20	40	0.0478		
	30	41	0.0490		
	40	43	0.0514		
	50	47	0.0562		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-20	49	0.0261	2.5	Pass
	-10	51	0.0271		
	0	52	0.0277		
	10	48	0.0255		
	20	45	0.0239		
	30	42	0.0223		
	40	43	0.0229		
	50	46	0.0245		

6.13 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part2.1055(d)(1)(2)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	 <p>Note : Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> 1. Set chamber temperature to 25 °C . Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	45	0.0538	2.5	Pass
	3.70	43	0.0514		
	3.40	40	0.0478		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	42	0.0223	2.5	Pass
	3.70	40	0.0213		
	3.40	46	0.0245		