

Report No: DDT-RE130203

**Issued Date:** 2013/08/16

# FCC CERTIFICATION TEST REPORT

# **FOR**

Applicant	:	Globalscale Technologies Inc
Address	•	5F.No.2 Building, Minxing Industrial Park, Minkang Road, Minzhi Street, Baoan District, Shenzhen, Guangdong, China
<b>Equipment under Test</b>	:	GuruPlug <b>ESTING</b>
Model No	:	003-GP0XXXXXX
Trade Mark	:	
FCC ID	:	YCJ003GP1
Manufacturer	:	Globalscale Technologies Inc
Address	•	5F.No.2 Building, Minxing Industrial Park, Minkang Road, Minzhi Street, Baoan District, Shenzhen, Guangdong, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-22891499 Http://www.dgddt.com



## TABLE OF CONTENTS

	Test report declares	4
1.	Summary of test results	5
2.	General test information	6
2.1.	Description of EUT	6
2.2.	Accessories of EUT	6
2.3.	Assistant equipment used for test	6
2.4.	Block diagram of EUT configuration for test	7
2.5.	Test environment conditions	7
2.6.	Test laboratory	7
2.7.	Measurement uncertainty	8
3.	Maximum Peak Output Power	9
3.1.	Test equipment	9
3.2.	Block diagram of test setup	9
3.3.	Limits	9
3.4.	Test Procedure	9
3.5.	Test Result	9
4.	20dB Bandwidth	10
4.1.	Test equipment	10
4.2.	Block diagram of test setup	10
4.3.	Limits	10
4.4.	Test Procedure	10
4.5.	Test Result	11
4.6.	Original test data	11
5.	Carrier Frequency Separation	15
5.1.	Test equipment	15
5.2.	Block diagram of test setup	15
5.3.	Limits	15
5.4.	Test Procedure	15
5.5.	Test Result	15
5.6.	Original test data	15
6.	Number Of Hopping Channel	15
6.1.	Test equipment	15
6.2.	Block diagram of test setup	15
6.3.	Limits	15
6.4.	Test Procedure	15
6.5.	Test Result	15

6.6.	Original test data	15
7.	Dwell Time	15
7.1.	Test equipment	15
7.2.	Block diagram of test setup	15
7.3.	Limits	15
7.4.	Test Procedure	15
7.5.	Test Result	15
7.6.	Original test data	15
8.	Radiated emission	15
8.1.	Test equipment	15
8.2.	Block diagram of test setup	15
8.3.	Limit	15
8.4.	Test Procedure	15
8.5.	Test result	15
9.	Band Edge Compliance	15
9.1.	Test equipment	15
9.2.	Block diagram of test setup	15
9.3.	Limit	15
9.4.	Test Procedure	15
9.5.	Test result	15
10.	Power Line Conducted Emission	15
10.1.	Test equipment	15
10.2.	Block diagram of test setup	15
10.3.	Power Line Conducted Emission Limits(Class B)	15
10.4.	Test Procedure	15
10.5.	Test Result	15
11.	Antenna Requirements	15
11.1.	Limit	15
11.2.	Result	15
12.	Test setup photograph	15
13.	Photos of the EUT	15

### TEST REPORT DECLARE

Applicant	•	Globalscale Technologies Inc	
Address	•	5F.No.2 Building, Minxing Industrial Park, Minkang Road, Minzhi Street, Baoan District, Shenzhen, Guangdong, China	
<b>Equipment under Test</b>	•	GuruPlug	
Model No	••	003-GP0XXXXXX	
FCC ID	:	YCJ003GP1	
Trade Mark	•		
Manufacturer	•	Globalscale Technologies Inc	
Address	•	5F.No.2 Building, Minxing Industrial Park, Minkang Road, Minzhi Street, Baoan District, Shenzhen, Guangdong, China	

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C: 2012

Test procedure used: ANSI C63.10:2009

#### We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-RE130203				
Date of Test:	2013/08/05~2013/08/13	Date of Report:	2013/8/16		

Prepared By:

Leo Liu/Engineer



Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

# 1. Summary of test results

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2009	PASS
20dB Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2009	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2009	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

### 2. General test information

# 2.1. Description of EUT

	_		
EUT* Name	:	GuruPlug	
Model Number	:	003-GP0XXXXXX	
Difference of Model number	:	"XXXXXX" Represent the different sales regions, Plug and accessories, "X" represent the numbers 1 to 9	
EUT function description	:	Please reference user manual of this device	
Power supply	:	AC100-240V	
Radio Specification	:	Bluetooth V3.0+EDR	
Operation frequency	:	2402MHz -2480MHz	
Modulation	:	GFSK, π/4 QPSK, 8-DPSK	
Data rate	:	Mpbs, 2Mbps, 3Mbps	
Antenna Type	:	Integrated Patch Antenna, 0dBi maximum gain	
Date of Receipt	:	2012/08/03	
Sample Type	:	Series production	

Note1: EUT is the ab. of equipment under test.

### 2.2. Accessories of EUT


Description of Accessories	Manufacturer	Model number or Type	Serial No.	Other
/	/	/	/	/

### 2.3. Assistant equipment used for test

Description of Assistant equipment	Manufacturer	Model number or Type	Other	
HP Pro 3330 Small From Factor (PC)	НР	A6T13PA#AB2	1.5m long, unshielded	FCC DOC
LCD COLOR DISPLAY	НР	GV537A	AC Line: 1.5m long, unshielded VGA line: 1.5m long, unshielded	FCC DOC
Keyboard	НР	KB-0316	Signal line: 1.5m long, unshielded	FCC DOC
Mouse	НР	M-SBF96	Signal line: 1.5m long, unshielded	FCC DOC
Router	TP-LINK	TL-WR842N	/	FCC DOC

Page 6 of 81

### 2.4. Block diagram of EUT configuration for test



EUT was connected to control PC by LAN cable and router, control PC run "putty\_xp.exe" test software and special command provided by manufacturer to control EUT work in Continuous TX mode ,and select test channel, wireless mode and data rate.

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
8-DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
	CH0	2402
GFSK hopping off Tx Mode	CH39	2441
	CH78	2480
	CH0	2402
$\pi/4$ QPSK hopping off Tx Mode	CH39	2441
	CH78	2480
	СНО	2402
8-DPSK hopping off Tx Mode	CH39	2441
	CH78	2480

Note1: Some modes not apply for all the test items.

Note2: For  $\pi/4$  QPSK its same modulation type with 8-DPSK, and based exploratory test, there is no significant difference of that two types test result, so except output power, all other items final test were only performed with 8-DPSK and GFSK. (Based exploratory test, Between Pi/4QPSK and 8-DPSK, 8-DPSK is the worse case)

### 2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25℃
Humidity range:	40-75%
Pressure range:	86-106kPa

#### 2.6. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong

Province, China, 523808 Tel: +86-0769-22891499 <a href="http://www.dgddt.com">http://www.dgddt.com</a>

FCC Registration Number: 270092 Industry Canada site registration number: 10288A-1

### 2.7. Measurement uncertainty

Test Item	Uncertainty
Occupied Channel Bandwidth	±1%
Uncertainty for radio frequency	1×10 <sup>-9</sup>
RF Output power, conducted	±0.6dB
Power Spectral Density, Conducted	±1.2dB
Unwanted Emissions, Conducted	±0.6dB
Temperature	±0.2℃
Humidity	±1%
DC and Low frequency voltage	±0.5%
Time	±1%
Duty Cycle	±1%
Uncertainty for Radiation Emission test	3.14 dB (Polarize: V)
(30MHz-1GHz)	3.16 dB (Polarize: H)
Uncertainty for Radiation Emission test	2.08dB(Polarize: V)
(1GHz to 25GHz)	2.56dB (Polarize: H)
Uncertainty for Conduction emission test(150KHz-30MHz)	2.44dB
Uncertainty for Radiation Emission test (9KHz-150KHz)	3.89dB
Uncertainty for Radiation Emission test (150KHz-30MHz)	3.21dB


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3. Maximum Peak Output Power

### 3.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	R&S	FSU	1166.1660.26	2012/11/26	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2012/11/26	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2012/11/26	1 Year

#### 3.2. Block diagram of test setup



#### 3.3. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

#### 3.4. Test Procedure

- (1) Configure EUT and assistant system according clause 2.4 and 3.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) Measure the maximum output power of EUT by spectrum analyzer with PK detector and RBW=2MHz(above 6dB bandwidth of measured signal), VBW=3MHz

Note: The attenuator loss was inputted into spectrum analyzer as amplitude offset.

#### 3.5. Test Result

EUT: GuruPlug	M/N: 003-GP0	XXXXXX			
Mode	Freq (MHz)	Result (dBm)	Limit (dBm)	Margin (dB)	Conclusion
	2402	3.28	30	26.72	PASS
GFSK	2441	3.19	30	26.81	PASS
	2480	3.10	30	26.9	PASS
	2402	1.23	30	28.77	PASS
π/4 QPSK	2441	0.97	30	29.03	PASS
	2480	0.78	30	29.22	PASS
8-DPSK	2402	1.67	30	28.33	PASS
	2441	1.41	30	28.59	PASS


	2480	1.20	30	28.80	PASS
Test Date: 201	3/08/05		Tes	t Engineer : Lo	eo

### 4. 20dB Bandwidth

#### 4.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	R&S	FSU	1166.1660.26	2012/11/26	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2012/11/26	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2012/11/26	1 Year

### 4.2. Block diagram of test setup



#### 4.3. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

#### 4.4. Test Procedure


- (1) Configure EUT and assistant system according clause 2.4 and 4.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 kHz RBW and 100 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is equal to peak power minus 20dB.


### 4.5. Test Result


EUT: GuruPlug	M/N: 003-GP0	XXXXXX			
Mode	Freq (MHz)	Result (MHz)	Limit (MHz)	Margin (MHz)	Conclusion
	2402	0.89	/	/	PASS
GFSK	2441	0.88	/	/	PASS
	2480	0.85	/	/	PASS
	2402	1.22	/	/	PASS
8-DPSK	2441	1.22	/	/	PASS
	2480	1.22	/	/	PASS
Test Date : 2013/08/05			Т	est Engineer : 1	Leo


### 4.6. Original test data












### 5. Carrier Frequency Separation

### 5.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	R&S	FSU	1166.1660.26	2012/11/26	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2012/11/26	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2012/11/26	1 Year

### 5.2. Block diagram of test setup



#### 5.3. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### 5.4. Test Procedure


- (1) Configure EUT and assistant system according clause 2.4 and 5.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) The carrier frequency was measured by spectrum analyzer with 30 KHz RBW and 100KHz VBW.

#### 5.5. Test Result


EUT: GuruPlug M/N: 003-GP0XXXXXX								
Mode	Channel separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz) 2/3 of 20dB bandwidth	Conclusion				
GFSK	1.0	0.89	0.580	PASS				
8-DPSK	1.0	1.22	0.813	PASS				
Test Date: 2013/08/06 Test Engineer: Leo								

### 5.6. Original test data

### **GFSK**



### 8-DPSK




### 6. Number Of Hopping Channel

### 6.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	R&S	FSU	1166.1660.26	2012/11/26	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2012/11/26	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2012/11/26	1 Year

### 6.2. Block diagram of test setup



### 6.3. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


### 6.4. Test Procedure


- (1) Configure EUT and assistant system according clause 2.4 and 6.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) The number of hopping channel was measured by spectrum analyzer with 300 kHz RBW and 1MHz VBW.

#### 6.5. Test Result

EUT: GuruPlug	GuruPlug M/N: 003-GP0XXXXXX						
Mode	Number of hopping channel Limit Conclusion						
GFSK	79	>15	PASS				
8-DPSK	79	>15	PASS				
Test Date : 2013/08/06 Test Engineer : Leo							

### 6.6. Original test data






### 7. Dwell Time

### 7.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	R&S	FSU	1166.1660.26	2012/11/26	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2012/11/26	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2012/11/26	1 Year

### 7.2. Block diagram of test setup



#### 7.3. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 7.4. Test Procedure

- (1) Configure EUT and assistant system according clause 2.4 and 7.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula Dwell time = Hopping number/measure time \*0.4\*79\*pulse's on time


#### 7.5. Test Result


EUT: GuruPlug	uruPlug M/N: 003-GP0XXXXXX							
Mode	Number of hops/	Occupied of each hop	Dwell time	Limit	Conclusion			
Mode	1s	(ms)	(ms)	Liiiit	Conclusion			
DH1	10	0.390	123.240	<400ms	PASS			
DH3	6	1.647	312.271	<400ms	PASS			
DH5	4	2.903	366.939	<400ms	PASS			
3-DH1	11	0.402	139.735	<400ms	PASS			
3-DH3	5	1.65	260.700	<400ms	PASS			
3-DH5 4		2.898 366.307 <400m		<400ms	PASS			
Test Date : 2013/08/06 Test Engineer : Leo					0			


### 7.6. Original test data




### DH3










### 3-DH5:




### 8. Radiated emission

### 8.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2012/11/26	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2012/11/26	1 Year
3	Loop antenna	TESEQ	HLA6120	20129	2012/11/26	1 Year
4	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2012/11/26	1 Year
5	Double Ridged Horn Antenna	R&S	HF907	100276	2012/11/26	1 Year
6	Horn Antenna	EMCO	3116	00060095	2012/11/26	1 Year
7	Pre-Amplifier	R&S	SCU-01	10049	2012/11/26	1 Year
8	Pre-amplifier	A.H.	PAM0-0118	360	2012/11/26	1 Year
9	Pre-amplifier	A.H.	PAM-1840VH	562	2012/11/26	1 Year
10	RF Cable	R&S	R01	10403	2012/11/26	1 Year
11	RF Cable	R&S	R02	10512	2012/11/26	1 Year

### 8.2. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz




(According to ANSI C63.4:2003)

Report No: DDT-RE130203

In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

#### **8.3.** Limit

8.3.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

Report No: DDT-RE130203

#### 8.3.2 FCC 15.209 Limit.

FREQUENCY	DISTANCE	FIELD STRENGTHS LIMIT				
MHz	Meters	μV/m	dB(μV)/m			
$0.009 \sim 0.490$	300	2400/F(KHz)	67.6-20log(F)			
$0.490 \sim 1.705$	30	24000/F(KHz)	87.6-20log(F)			
1.705 ~ 30.0	30	30	29.54			
30 ~ 88	3	100	40.0			
88 ~ 216	3	150	43.5			
216 ~ 960	3	200	46.0			
960 ~ 1000	3	500	54.0			
Above 1000	3	74.0 dB(μV)/m (Peak)				
710000		54.0 dB(μV)/m (Average)				

Note: (1)The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz.Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$Limit_{3m}(dBuV/m) = Limit_{30m}(dBuV/m) + 40Log(30m/3m)$$

#### 8.3.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

#### 8.4. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic

chamber.

(2) Setup EUT and assistant system according clause 2.4 and 8.2

(3) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Report No: DDT-RE130203

Test frequency range	Test antenna used				
9KHz-30MHz	Active Loop antenna				
30MHz-1GHz	Trilog Broadband Antenna				
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)				
18GHz-40GHz	Horn Antenna(18GHz-40GHz)				

According ANSI C63.10:2009 clause 6.4.4.2 and 6,5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (4) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:
- (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)
  - (b) Change work frequency or channel of device if practicable.
  - (c) Change modulation type of device if practicable.
  - (d) Change power supply range from 85% to 115% of the rated supply voltage
- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below worse case was reported with frequency range from 9KHz to 18GHz.

- (5) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2009 on Radiated Emission test.
- (6) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz,110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also

be measured and need comply with Peak limit.

(7) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Report No: DDT-RE130203

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

(8) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure(according ANSI C63.10:2009 clause 4.2.3.2.3 procedure for average measure).

#### 8.5. Test result

#### PASS. (See below detailed test result)

All the emissions except fundamental emission from 9KHz to 25GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in GFSK, Tx 2441MHz mode.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Note4: For below test data, when the limit tabular marked "/" means this frequency point is the fundamental emission and no need comply with this limit.

Press:100.1kPa

### **Radiated Emission Test Result**

Report No: DDT-RE130203


Test Site : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

EUT : GuruPlug Model Number : 003-GP0XXXXXX

Condition : Temp:24.5'C,Humi:55%,
: P. 100.11 P. Antenna/Distance : 2013 VULB9163/3m/HORIZONTAL

Memo :

Data: 1



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	31.94	51.12	13.15	37.45	0.81	27.63	40.00	-12.37	QP	HORIZONTAL
2	250.19	59.84	11.80	42.66	2.40	31.38	46.00	-14.62	QP	HORIZONTAL
3	350.10	65.89	12.50	42.92	2.89	38.36	46.00	-7.64	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

2. If Peak Result comply with QP limit, QP Result is deemed to comply with QP limit

3. Test setup: RBW: 120kHz, VBW: 300kHz, Sweep time: auto

Report No: DDT-RE130203


Test Site : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**EUT** : GuruPlug **Model Number** : 003-GP0XXXXXX

Condition : Temp:24.5'C,Humi:55%, Press:100.1kPa : Antenna/Distance : 2013 VULB9163/3m/VERTICAL

Memo :

Data: 2



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	42.85	58.50	13.40	37.45	0.95	35.40	40.00	-4.60	QP	VERTICAL
2	149.31	64.22	7.50	41.70	1.81	31.83	43.50	-11.67	QP	VERTICAL
3	250.19	62.83	11.80	42.66	2.40	34.37	46.00	-11.63	QP	VERTICAL
4	350.10	68.44	12.50	42.92	2.89	40.91	46.00	-5.09	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

2. If Peak Result comply with QP limit, QP Result is deemed to comply with QP limit

3. Test setup: RBW: 120kHz, VBW: 300kHz, Sweep time: auto

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 3



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

Report No: DDT-RE130203

Test Site : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6


EUT : GuruPlug Model Number : 003-GP0XXXXXX

 $\begin{tabular}{ll} \textbf{Condition} & : \frac{Temp:24.5\text{'C,Humi:55\%,Press:100.1}}{kPa} \\ \end{tabular}$ 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Memo :

Data: 4



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2402.00	102.86	28.93	43.48	6.47	94.78	/	/	Peak	HORIZONTAL
2	4804.00	64.75	34.01	44.06	9.32	64.02	74.00	-9.98	Peak	HORIZONTAL
3	4804.00	43.61	34.01	44.06	9.32	42.88	54.00	-11.12	Average	HORIZONTAL
4	17881.00	38.94	43.97	41.63	19.04	60.32	74.00	-13.68	Peak	HORIZONTAL
5	17881.00	25.59	43.97	41.63	19.04	46.97	54.00	-7.03	Average	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 5



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

Test Site : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

EUT : GuruPlug Model Number : 003-GP0XXXXXX


 $\begin{tabular}{ll} \textbf{Condition} & : \frac{Temp:24.5\text{'C,Humi:55\%,Press:100.1}}{kPa} \\ \end{tabular}$ 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo :

Data: 6



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2402.00	98.02	28.93	43.48	6.47	89.94	/	/	Peak	VERTICAL
2	4804.00	62.94	34.01	44.06	9.32	62.21	74.00	-11.79	Peak	VERTICAL
3	4804.00	44.37	34.01	44.06	9.32	43.64	54.00	-10.36	Average	VERTICAL
4	17439.00	38.65	43.27	40.83	18.90	59.99	74.00	-14.01	Peak	VERTICAL
5	17439.00	26.29	43.27	40.83	18.90	47.63	54.00	-6.37	Average	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

2. If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH39


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 7



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

Test Site : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

EUT : GuruPlug Model Number : 003-GP0XXXXXX


 $\begin{tabular}{ll} \textbf{Condition} & : \frac{Temp:24.5\text{'C,Humi:55\%,Press:100.1}}{kPa} \\ \end{tabular}$ 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo :

Data: 8



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2441.00	99.75	29.03	43.49	6.53	91.82	/	/	Peak	VERTICAL
2	4842.00	59.58	34.29	44.04	9.41	59.24	74.00	-14.76	Peak	VERTICAL
3	4876.00	45.22	34.29	44.04	9.41	44.88	54.00	-9.12	Average	VERTICAL
4	17303.00	39.09	43.01	41.00	18.87	59.97	74.00	-14.03	Peak	VERTICAL
5	17303.00	26.33	43.01	41.00	18.87	47.21	54.00	-6.79	Average	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH39


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 9



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

2. If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH39


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 10



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2441.00	102.56	29.03	43.49	6.53	94.63	/	/	Peak	HORIZONTAL
2	4882.00	63.44	34.29	44.03	9.41	63.11	74.00	-10.89	Peak	HORIZONTAL
3	4882.00	43.74	34.29	44.03	9.41	43.41	54.00	-10.59	Average	HORIZONTAL
4	17388.00	38.74	43.19	40.91	18.89	59.91	74.00	-14.09	Peak	HORIZONTAL
5	17388.00	25.65	43.19	40.91	18.89	46.82	54.00	-7.18	Average	HORIZONTAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 11



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH78


**Condition** 

: Temp:24.5'C,Humi:55%,Press:100.1 kPa Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 12



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2480.00	102.30	29.18	43.50	6.57	94.55	/	/	Peak	HORIZONTAL
2	4960.00	61.85	34.34	44.01	9.48	61.66	74.00	-12.34	Peak	HORIZONTAL
3	4960.00	43.78	34.34	44.01	9.48	43.59	54.00	-10.41	Average	HORIZONTAL
4	17354.00	38.40	43.12	40.91	18.88	59.49	74.00	-14.51	Peak	HORIZONTAL
5	17354.00	25.43	43.12	40.91	18.88	46.52	54.00	-7.48	Average	HORIZONTAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 13



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

Report No: DDT-RE130203

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug


**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH78

**Condition** 

: Temp:24.5'C,Humi:55%,Press:100.1 kPa Antenna/Distance : HF907 SN100276/3m/VERTICAL

Memo

Data: 14



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2480.00	99.25	29.18	43.50	6.57	91.50	/	/	Peak	VERTICAL
2	4960.00	42.83	34.34	44.01	9.48	42.64	54.00	-11.36	Average	VERTICAL
3	4961.00	59.60	34.34	44.01	9.48	59.41	74.00	-14.59	Peak	VERTICAL
4	17303.00	39.05	43.01	41.00	18.87	59.93	74.00	-14.07	Peak	VERTICAL
5	17303.00	26.11	43.01	41.00	18.87	46.99	54.00	-7.01	Average	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

Test Site : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

EUT : GuruPlug Model Number : 003-GP0XXXXXX

Condition : Temp:24.5'C,Humi:55%,Press:100.1


· kPa

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo :

Data: 19



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 20



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2480.00	98.21	29.18	43.50	6.57	90.46	/	/	Peak	VERTICAL
2	4960.00	58.60	34.34	44.01	9.48	58.41	74.00	-15.59	Peak	VERTICAL
3	4960.00	42.70	34.34	44.01	9.48	42.51	54.00	-11.49	Average	VERTICAL
4	17558.00	38.37	43.40	40.93	18.92	59.76	74.00	-14.24	Peak	VERTICAL
5	17558.00	24.75	43.40	40.93	18.92	46.14	54.00	-7.86	Average	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 21



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 22



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2480.00	101.12	29.18	43.50	6.57	93.37	/	/	Peak	HORIZONTAL
2	4960.00	63.12	34.34	44.01	9.48	62.93	74.00	-11.07	Peak	HORIZONTAL
3	4960.00	43.56	34.34	44.01	9.48	43.37	54.00	-10.63	Average	HORIZONTAL
4	17337.00	38.58	43.09	40.95	18.88	59.60	74.00	-14.40	Peak	HORIZONTAL
5	17337.00	25.70	43.09	40.95	18.88	46.72	54.00	-7.28	Average	HORIZONTAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH39


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 23



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

2. If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH39


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 24



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2441.00	101.05	29.03	43.49	6.53	93.12	/	/	Peak	HORIZONTAL
2	4882.00	62.57	34.29	44.03	9.41	62.24	74.00	-11.76	Peak	HORIZONTAL
3	4882.00	43.66	34.29	44.03	9.41	43.33	54.00	-10.67	Average	HORIZONTAL
4	17286.00	39.08	42.98	41.00	18.87	59.93	74.00	-14.07	Peak	HORIZONTAL
5	17286.00	25.45	42.98	41.00	18.87	46.30	54.00	-7.70	Average	HORIZONTAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH39


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 25



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH39


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 26



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2441.00	98.42	29.03	43.49	6.53	90.49	/	/	Peak	VERTICAL
2	4882.00	58.30	34.29	44.03	9.41	57.97	74.00	-16.03	Peak	VERTICAL
3	4882.00	41.84	34.29	44.03	9.41	41.51	54.00	-12.49	Average	VERTICAL
4	17558.00	38.38	43.40	40.93	18.92	59.77	74.00	-14.23	Peak	VERTICAL
5	17558.00	24.70	43.40	40.93	18.92	46.09	54.00	-7.91	Average	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 27



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
1		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 28



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2402.00	97.84	28.93	43.49	6.47	89.75	/	/	Peak	VERTICAL
2	4804.00	60.31	34.01	44.06	9.32	59.58	74.00	-14.42	Peak	VERTICAL
3	4804.00	43.33	34.01	44.06	9.32	42.60	54.00	-11.40	Average	VERTICAL
4	17371.00	38.70	43.16	40.91	18.89	59.84	74.00	-14.16	Peak	VERTICAL
5	17371.00	24.35	43.16	40.91	18.89	45.49	54.00	-8.51	Average	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 29



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 30



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2402.00	101.11	28.93	43.49	6.47	93.02	/	/	Peak	HORIZONTAL
2	4804.00	63.21	34.01	44.06	9.32	62.48	74.00	-11.52	Peak	HORIZONTAL
3	4804.00	43.77	34.01	44.06	9.32	43.04	54.00	-10.96	Average	HORIZONTAL
4	17371.00	39.00	43.16	40.91	18.89	60.14	74.00	-13.86	Peak	HORIZONTAL
5	17371.00	26.40	43.16	40.91	18.89	47.54	54.00	-6.46	Average	HORIZONTAL


<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

### 9. Band Edge Compliance

### 9.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2012/11/26	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2012/11/26	1 Year
3	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2012/11/26	1 Year
4	Double Ridged Horn Antenna	R&S	HF907	100276	2012/11/26	1 Year
5	Pre-Amplifier	R&S	SCU-01	10049	2012/11/26	1 Year
6	Pre-amplifier	A.H.	PAM0-0118	360	2012/11/26	1 Year
7	RF Cable	R&S	R01	10403	2012/11/26	1 Year
8	RF Cable	R&S	R02	10512	2012/11/26	1 Year

### 9.2. Block diagram of test setup



#### 9.3. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz and 5725MHz to 5850MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

Report No: DDT-RE130203

### 9.4. Test Procedure

Same with clause 8.4 except change investigated frequency range from 2310 MHz to 2415 MHz and 2475 MHz to 2500 MHz.

Both Hopping on and Hopping off mode are been pre tested ,Hopping off mode is the worse case ,and only report worse case plots and result in the test report .

Report No: DDT-RE130203

#### 9.5. Test result

PASS. (See below detailed test result)

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**Model Number EUT** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 1



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2319.58	52.68	28.37	43.47	6.37	43.95	74.00	-30.05	Peak	VERTICAL
2	2390.00	48.55	28.70	43.48	6.47	40.24	74.00	-33.76	Peak	VERTICAL
3	2400.00	74.63	28.93	43.49	6.47	66.54	74.00	-7.46	Peak	VERTICAL
4	2401.86	100.07	28.93	43.49	6.47	91.98	/	/	Peak	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 2



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2355.22	52.89	28.44	43.47	6.42	44.28	74.00	-29.72	Peak	HORIZONTAL
2	2390.00	48.01	28.70	43.48	6.47	39.70	74.00	-34.30	Peak	HORIZONTAL
3	2400.00	78.07	28.93	43.49	6.47	69.98	74.00	-4.02	Peak	HORIZONTAL
4	2402.08	103.34	28.93	43.49	6.47	95.25	/	/	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor

2. If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 15



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2480.10	99.83	29.18	43.50	6.57	92.08	/	/	Peak	VERTICAL
2	2483.50	58.85	29.18	43.50	6.57	51.10	74.00	-22.90	Peak	VERTICAL
3	2496.88	49.74	29.25	43.50	6.59	42.08	74.00	-31.92	Peak	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode GFSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 16



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2479.85	103.17	29.18	43.50	6.57	95.42	/	/	Peak	HORIZONTAL
2	2483.50	62.92	29.18	43.50	6.57	55.17	74.00	-18.83	Peak	HORIZONTAL
3	2483.50	48.12	29.18	43.50	6.57	40.37	54.00	-13.63	Average	HORIZONTAL
4	2496.28	50.01	29.25	43.50	6.59	42.35	74.00	-31.65	Peak	HORIZONTAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 17



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2480.20	101.38	29.18	43.50	6.57	93.63	/	/	Peak	HORIZONTAL
2	2483.50	56.62	29.18	43.50	6.57	48.87	74.00	-25.13	Peak	HORIZONTAL
3	2496.23	49.62	29.25	43.50	6.59	41.96	74.00	-32.04	Peak	HORIZONTAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH78


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 18



Item	Freq	Read Level	Antenna Factor	PRM Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector	Polarization
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2480.18	98.43	29.18	43.50	6.57	90.68	/	/	Peak	VERTICAL
2	2483.50	53.96	29.18	43.50	6.57	46.21	74.00	-27.79	Peak	VERTICAL
3	2492.50	50.04	29.18	43.50	6.57	42.29	74.00	-31.71	Peak	VERTICAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/HORIZONTAL

Report No: DDT-RE130203

Memo

Data: 31



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2334.32	50.01	28.41	43.47	6.39	41.34	74.00	-32.66	Peak	HORIZONTAL
2	2390.00	48.67	28.70	43.48	6.47	40.36	74.00	-33.64	Peak	HORIZONTAL
3	2400.00	77.68	28.93	43.49	6.47	69.59	74.00	-4.41	Peak	HORIZONTAL
4	2401.97	101.18	28.93	43.49	6.47	93.09	/	/	Peak	HORIZONTAL

<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

**Test Site** : DDT 3m Chamber E:\2013 Report data\13QE0070\RE.EM6

**Test Date** : 2013-08-09 **Tested By** : Leo

**EUT Model Number** : 003-GP0XXXXXX : GuruPlug

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode 8-DPSK CH0


: Temp:24.5'C,Humi:55%,Press:100.1 kPa **Condition** 

Antenna/Distance : HF907 SN100276/3m/VERTICAL

Report No: DDT-RE130203

Memo

Data: 32



Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Detector	Polarization
		Level	Factor	Factor	Loss	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	2338.06	49.83	28.41	43.47	6.39	41.16	74.00	-32.84	Peak	VERTICAL
2	2390.00	48.10	28.70	43.48	6.47	39.79	74.00	-34.21	Peak	VERTICAL
3	2400.00	74.24	28.93	43.49	6.47	66.15	74.00	-7.85	Peak	VERTICAL
4	2401.75	97.76	28.93	43.49	6.47	89.67	/	/	Peak	VERTICAL


<sup>2.</sup> If Peak Result comply with AV limit, AV Result is deemed to comply with AV limit

### 10. Power Line Conducted Emission

### 10.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
. 1	Test Receiver	R&S	ESU8	100316	2012/11/26	1 Year
. 2	LISN 1	R&S	ENV216	101109	2012/11/26	1 Year
. 3	LISN 2	R&S	ESH2-Z5	100309	2012/11/26	1 Year
. 4	Pulse Limiter	R&S	ESH3-Z2	101242	2012/11/26	1 Year

### 10.2. Block diagram of test setup



### 10.3. Power Line Conducted Emission Limits(Class B)

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

#### 10.4. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as ANSI C63.4:2003

Report No: DDT-RE130203

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

Report No: DDT-RE130203

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

#### 10.5. Test Result

### PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means peak detection; "----" mans average detection

### **Conducted Emission Test Result**


Report No: DDT-RE130203

Test Site : DDT 1# Shield Room E:\2013 report data\13QE0070\13QE0070.EM6

EUT : GuruPlug Model Number : 003-GP0XXXXXX

 $\begin{tabular}{ll} \textbf{Condition} & : \frac{Temp:24.5'C, Humi:55\%,}{Press:100.1kPa} & \textbf{LISN} & : 2013 \ ENV216/NEUTRAL \\ \end{tabular}$ 

Data: 25



Item	Freq	Read	LISN	Cable	Pulse	Result	Limit	Over	Detector	Phase
		Level	Factor	Loss	Limiter	Level	Line	Limit		
					Factor					
(Mark)	(MHz)	(dBµV)	(dB)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)		
1	0.19	28.94	9.59	0.02	9.85	48.40	53.98	-5.58	Average	NEUTRAL
2	0.19	37.20	9.59	0.02	9.85	56.66	63.98	-7.32	QP	NEUTRAL
3	0.69	22.33	9.62	0.06	9.85	41.86	46.00	-4.14	Average	NEUTRAL
4	0.69	32.84	9.62	0.06	9.85	52.37	56.00	-3.63	QP	NEUTRAL
5	3.92	12.76	9.62	0.10	9.87	32.35	46.00	-13.65	Average	NEUTRAL
6	3.92	22.14	9.62	0.10	9.87	41.73	56.00	-14.27	QP	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss

- 2. If QP Result comply with AV limit, AV Result is deemed to comply with AV limit
- 3. Test setup: RBW: 200Hz(9kHz—150kHz), 9kHz(150kHz—30MHz), Step size:4kHz, Scan time: auto

### **Conducted Emission Test Result**

Report No: DDT-RE130203


Test Site : DDT 1# Shield Room E:\2013 report data\13QE0070\13QE0070.EM6

EUT : GuruPlug Model Number : 003-GP0XXXXXX

**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode

 $\begin{tabular}{ll} \textbf{Condition} & : Temp: 24.5 \cite{C,Humi:} 55\%, \\ Press: 100.1 \cite{RPa} & LISN \\ \end{tabular} & : 2013 \ ENV216 \cite{LINE} \\ \end{tabular}$ 

Data: 27



Item	Freq	Read	LISN	Cable	Pulse	Result	Limit	Over	Detector	Phase
		Level	Factor	Loss	Limiter	Level	Line	Limit		
					Factor					
(Mark)	(MHz)	(dBµV)	(dB)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)		
1	0.19	29.65	9.59	0.02	9.85	49.11	53.98	-4.87	Average	LINE
2	0.19	37.35	9.59	0.02	9.85	56.81	63.98	-7.17	QP	LINE
3	0.72	21.99	9.62	0.07	9.85	41.53	46.00	-4.47	Average	LINE
4	0.72	32.70	9.62	0.07	9.85	52.24	56.00	-3.76	QP	LINE
5	1.66	16.58	9.61	0.06	9.87	36.12	46.00	-9.88	Average	LINE
6	1.66	27.22	9.61	0.06	9.87	46.76	56.00	-9.24	QP	LINE

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss

- 2. If QP Result comply with AV limit, AV Result is deemed to comply with AV limit
- 3. Test setup: RBW: 200Hz(9kHz—150kHz), 9kHz(150kHz—30MHz), Step size:4kHz, Scan time: auto

### 11. Antenna Requirements

### 11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 11.2. Result

The antennas used for this product are built-in undetachable Patch antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.

Report No: DDT-RE130203