

FCC RF Test Report

APPLICANT : Lenovo Mobile Communication Technology Ltd.
EQUIPMENT : Mobile Phone GSM/WCDMA
BRAND NAME : lenovo
MODEL NAME : Lenovo K900
MID : 90000002
FCC ID : YCNK900
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Mar. 26, 2013 and completely tested on Apr. 15, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test	6
1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.6 Testing Site	7
1.7 Applied Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration and system.....	10
2.4 Measurement Results Explanation Example	11
3 TEST RESULT	12
3.1 Conducted Output Power Measurement.....	12
3.2 Peak-to-Average Ratio	14
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	24
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	30
3.5 Band Edge Measurement.....	54
3.6 Conducted Spurious Emission Measurement	69
3.7 Field Strength of Spurious Radiation Measurement	86
3.8 Frequency Stability Measurement.....	103
4 LIST OF MEASURING EQUIPMENTS	108
5 UNCERTAINTY OF EVALUATION	109
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG332604	Rev. 01	Initial issue of report	Apr. 28, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	RSS-132 (5.4) RSS-133 (6.4) RSS-139 (6.4)	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d) §27.50(d)(5)	RSS-132(5.4) RSS-133(6.4) RSS-139 (6.4)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§27.50(d)(4)	RSS-139 (6.4) SRSP-513(5.1.2)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(a) §27.53(h)	RSS-GEN(4.6.1) RSS-133(2.3)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.5)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.5)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.5)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 32.61 dB at 7520.000 MHz
3.8	§2.1055 §22.355 §24.235 §27.54	RSS-132 (5.3) RSS-133 (6.3) RSS-139 (6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

Lenovo Mobile Communication Technology Ltd.

No.999, Qishan North 2nd Road, Information & Optoelectronics Park, Torch Hi-tech Industry Development Zone, Xiamen, P.R.China

1.2 Manufacturer

Lenovo PC HK Limited

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone GSM/WCDMA
Brand Name	lenovo
Model Name	Lenovo K900
MID	90000002
FCC ID	YCNK900
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ WLAN 11bgn / Bluetooth EDR/ Bluetooth v4.0-LE
HW Version	H-3-01
SW Version	S-3-01
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 33.12 dBm GSM1900 : 29.60 dBm WCDMA Band V : 23.72 dBm WCDMA Band IV : 22.20 dBm WCDMA Band II : 22.26 dBm
Antenna Type	Coupling type (LDS)
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.8706	0.04 ppm	248KGXW
Part 22	GSM850 EDGE 8	8PSK	0.2108	0.03 ppm	256KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.1182	0.03 ppm	4M12F9W
Part 24	GSM1900 GSM	GMSK	1.2359	0.02 ppm	246KGXW
Part 24	GSM1900 EDGE 8	8PSK	0.4539	0.02 ppm	250KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.3258	0.02 ppm	4M10F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.4375	0.02 ppm	4M08F9W

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH01-KS	03CH01-KS	149928/4086E-1

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note:


1. The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, RMC 12.2Kbps mode for WCDMA band IV, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM	33.04	33.06	33.12	29.50	29.58	29.60
GPRS 8	33.03	33.05	33.10	29.50	29.58	29.59
GPRS 10	31.04	31.09	31.15	27.35	27.48	27.49
GPRS 11	29.92	29.94	30.03	26.38	26.51	26.54
GPRS 12	28.61	28.63	28.70	24.92	25.00	25.02
EGPRS 8	26.85	26.87	26.89	26.01	26.07	26.09
EGPRS 10	26.84	26.85	26.87	26.01	26.08	26.08
EGPRS 11	26.00	26.00	26.03	25.25	25.24	25.28
EGPRS 12	24.62	24.63	24.68	24.08	24.13	24.16

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Tx Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Rx Channel	4357	4408	4458	9662	9800	9938	1537	1638	1738
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	23.54	23.72	23.62	22.17	22.21	22.26	22.20	22.15	22.17
HSDPA Subtest-1	23.48	23.54	23.46	21.67	21.81	21.75	21.71	21.66	21.65
HSDPA Subtest-2	23.00	23.04	22.94	21.47	21.55	21.54	21.88	22.00	22.06
HSDPA Subtest-3	22.44	22.56	22.45	21.19	21.33	21.31	21.65	21.82	21.80
HSDPA Subtest-4	22.41	22.53	22.41	21.06	21.10	21.07	21.45	21.62	21.59
DC-HSDPA Subtest-1	23.36	23.41	23.30	21.43	21.59	21.63	21.62	21.57	21.55
DC-HSDPA Subtest-2	23.03	23.00	22.92	21.29	21.26	21.30	21.49	21.47	21.36
DC-HSDPA Subtest-3	22.32	22.38	22.26	21.05	21.19	21.30	21.15	21.18	21.16
DC-HSDPA Subtest-4	22.31	22.35	22.24	20.91	21.02	21.06	21.07	21.09	21.10
HSUPA Subtest-1	22.27	22.37	22.32	21.29	21.31	21.28	21.26	21.46	21.39
HSUPA Subtest-2	20.35	20.46	20.50	19.30	19.34	19.39	19.47	19.64	19.61
HSUPA Subtest-3	21.46	21.59	21.52	20.48	20.55	20.59	20.48	20.69	20.65
HSUPA Subtest-4	20.64	20.82	20.77	19.68	19.76	19.79	19.73	19.97	19.91
HSUPA Subtest-5	22.28	22.38	22.31	21.29	21.31	21.40	21.30	21.49	21.40

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-303D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and 10dB attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and 10dB attenuator factor.

Offset = RF cable loss + attenuator factor.

Following table shows an offset computation example with cable loss 4.2 dB.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Compare each band and different modulation combination to show the worst data rate.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	33.04	33.06	33.12	26.85	26.87	26.89	23.54	23.72	23.62
Conducted Power (Watts)	2.01	2.02	2.05	0.48	0.49	0.49	0.23	0.24	0.23

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.50	29.58	29.60	26.01	26.07	26.09	22.17	22.21	22.26
Conducted Power (Watts)	0.89	0.91	0.91	0.40	0.40	0.41	0.16	0.17	0.17

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	22.20	22.15	22.17
Conducted Power (Watts)	0.17	0.16	0.16

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup





3.2.5 Test Result of Peak-to-Average Ratio

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.36	0.38	0.40	2.64	2.49	2.68	2.96	3.08	2.84

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	3.00	2.44	3.04


3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GSM Link
---------------	----------	--------------------	----------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------


Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)




Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
---------------	---------------	--------------------	-------------------


Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)


Date: 11.APR.2013 03:24:20

Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)


Date: 11.APR.2013 03:23:48

Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)




Date: 11.APR.2013 03:23:07




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 25.MAR.2013 15:37:34


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 25.MAR.2013 15:38:00



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 25.MAR.2013 15:38:34

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.80	-48.12	0.00	-1.08	28.24	0.6663
836.40	-18.56	-48.28	0.00	-0.93	28.79	0.7561
848.80	-18.19	-48.35	0.00	-0.76	29.40	0.8706
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.67	-47.97	0.00	-1.08	22.22	0.1668
836.40	-23.77	-48.01	0.00	-0.93	23.31	0.2142
848.80	-23.08	-48.05	0.00	-0.76	24.21	0.2635

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.82	-48.12	0.00	-1.08	22.22	0.1667
836.40	-24.52	-48.28	0.00	-0.93	22.83	0.1920
848.80	-24.35	-48.35	0.00	-0.76	23.24	0.2108
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-30.59	-47.97	0.00	-1.08	16.30	0.0426
836.40	-30.05	-48.01	0.00	-0.93	17.03	0.0505
848.80	-29.38	-48.05	0.00	-0.76	17.91	0.0618

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-26.85	-48.12	0.00	-1.08	20.19	0.1045
836.40	-26.88	-48.28	0.00	-0.93	20.47	0.1113
846.60	-26.87	-48.35	0.00	-0.76	20.72	0.1182
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-32.66	-47.97	0.00	-1.08	14.23	0.0265
836.40	-32.21	-48.01	0.00	-0.93	14.87	0.0307
846.60	-31.76	-48.05	0.00	-0.76	15.53	0.0357

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-23.17	-51.88	0.00	1.96	30.67	1.1668
1880.00	-24.52	-52.99	0.00	2.00	30.47	1.1143
1909.80	-25.97	-54.28	0.00	1.98	30.29	1.0691
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-23.56	-52.13	0.00	1.96	30.53	1.1298
1880.00	-24.37	-53.17	0.00	2.00	30.80	1.2023
1909.80	-25.19	-54.13	0.00	1.98	30.92	1.2359

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-27.30	-51.88	0.00	1.96	26.54	0.4508
1880.00	-28.93	-52.99	0.00	2.00	26.06	0.4036
1909.80	-29.82	-54.28	0.00	1.98	26.44	0.4406
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-27.71	-52.13	0.00	1.96	26.38	0.4345
1880.00	-28.63	-53.17	0.00	2.00	26.54	0.4508
1909.80	-29.54	-54.13	0.00	1.98	26.57	0.4539

WCDMA Band IV (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-34.16	-51.88	0.00	1.96	19.68	0.0929
1732.60	-33.31	-52.99	0.00	2.00	21.68	0.1472
1752.60	-36.45	-54.28	0.00	1.98	19.81	0.0957
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-27.70	-52.13	0.00	1.96	26.39	0.4355
1732.60	-29.01	-53.17	0.00	2.00	26.16	0.4130
1752.60	-29.70	-54.13	0.00	1.98	26.41	0.4375

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.15	-51.88	0.00	1.96	24.69	0.2944
1880.00	-30.24	-52.99	0.00	2.00	24.75	0.2985
1907.60	-31.73	-54.28	0.00	1.98	24.53	0.2838
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.49	-52.13	0.00	1.96	24.60	0.2884
1880.00	-30.20	-53.17	0.00	2.00	24.97	0.3141
1907.60	-30.98	-54.13	0.00	1.98	25.13	0.3258

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth and 26 dB bandwidth of the middle channel for the highest RF powers were measured.

3.4.4 Test Setup



3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (KHz)	248.00	246.00	248.00	248.00	246.00	256.00
26dB BW (KHz)	318.00	314.00	312.00	312.00	310.00	318.00

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (KHz)	242.00	242.00	246.00	250.00	242.00	244.00
26dB BW (KHz)	314.00	316.00	314.00	310.00	306.00	312.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.12	4.08	4.08
26dB BW (MHz)	4.64	4.64	4.64

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.08	4.08	4.08
26dB BW (MHz)	4.66	4.70	4.70


PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880.0	1907.6
99% OBW (MHz)	4.08	4.10	4.08
26dB BW (MHz)	4.66	4.64	4.66

3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GSM Link
---------------	---------	--------------------	----------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 25.MAR.2013 14:31:04

26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 25.MAR.2013 14:12:46

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 25.MAR.2013 14:39:28

26dB Bandwidth Plot on Channel 189 (836.4 MHz)


Date: 25.MAR.2013 14:13:12

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 25.MAR.2013 14:37:27

26dB Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 25.MAR.2013 14:30:37


Band :	GSM 850	Test Mode :	EDGE 8 Link
---------------	---------	--------------------	-------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 25.MAR.2013 14:57:06


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 25.MAR.2013 15:03:27




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 25.MAR.2013 15:11:20


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 25.MAR.2013 14:43:57


99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 25.MAR.2013 14:45:40


26dB Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 25.MAR.2013 14:56:40


Band :	GSM 1900	Test Mode :	GSM Link
---------------	-----------------	--------------------	-----------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 25.MAR.2013 17:13:23

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)


Date: 25.MAR.2013 17:14:05

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 25.MAR.2013 16:48:35

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)


Date: 25.MAR.2013 17:14:31




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 25.MAR.2013 16:37:05

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 25.MAR.2013 17:15:27

Band :	GSM 1900	Test Mode :	EDGE 8 Link
---------------	-----------------	--------------------	--------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 25.MAR.2013 16:18:42

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)


Date: 25.MAR.2013 16:17:24




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 25.MAR.2013 16:19:07


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 25.MAR.2013 16:12:58


99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 25.MAR.2013 16:28:35


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 25.MAR.2013 16:29:51

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
---------------	--------------	--------------------	-------------------


99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)


Date: 25.MAR.2013 15:17:39

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 25.MAR.2013 15:16:21

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 25.MAR.2013 15:18:04


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 25.MAR.2013 15:16:47




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 25.MAR.2013 15:18:30

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 25.MAR.2013 15:17:12




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 11.APR.2013 03:35:55


26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 11.APR.2013 03:34:36




99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 11.APR.2013 03:36:21


26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 11.APR.2013 03:35:02




99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 11.APR.2013 03:36:47

26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)




Date: 11.APR.2013 03:35:28




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 25.MAR.2013 15:52:52


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 25.MAR.2013 15:31:23




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 25.MAR.2013 15:33:07


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 25.MAR.2013 15:31:49




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 25.MAR.2013 15:45:00

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 25.MAR.2013 15:32:15

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-15.95dBm	Measurement Value :	-16.20dBm


Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 25.MAR.2013 14:16:20

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-16.02dBm	Measurement Value :	-16.27dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 25.MAR.2013 14:16:46

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-23.98dBm	Measurement Value :	-24.23dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)


Date: 25.MAR.2013 14:59:22

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-25.39dBm	Measurement Value :	-25.64dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 25.MAR.2013 14:59:48

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-25.14dBm	Measurement Value :	-25.37dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 25.MAR.2013 16:38:31

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-24.58dBm	Measurement Value :	-24.81dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 25.MAR.2013 16:38:57

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.17dB	Maximum 26dB Bandwidth :	0.312MHz
Band Edge :	-26.36dBm	Measurement Value :	-26.53dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 25.MAR.2013 16:03:19

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.17dB	Maximum 26dB Bandwidth :	0.312MHz
Band Edge :	-27.96dBm	Measurement Value :	-28.13dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 25.MAR.2013 16:03:45

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.33dB	Maximum 26dB Bandwidth :	4.64MHz
Band Edge :	-30.10dBm	Measurement Value :	-26.77dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)


Date: 25.MAR.2013 15:19:57

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.33dB	Maximum 26dB Bandwidth :	4.64MHz
Band Edge :	-30.46dBm	Measurement Value :	-27.13dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)


Date: 25.MAR.2013 15:20:23

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.70MHz
Band Edge :	-26.73dBm	Measurement Value :	-23.45dBm

Lower Band Edge Plot on Channel 1312 (1712.4 MHz)


Date: 11.APR.2013 03:38:14

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.70MHz
Band Edge :	-23.83dBm	Measurement Value :	-20.55dBm

Higher Band Edge Plot on Channel 1513 (1752.6 MHz)


Date: 11.APR.2013 03:38:41

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.32dB	Maximum 26dB Bandwidth :	4.66MHz
Band Edge :	-27.35dBm	Measurement Value :	-24.03dBm


Lower Band Edge Plot on Channel 9262 (1852.4 MHz)


Date: 25.MAR.2013 15:35:00

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.32dB	Maximum 26dB Bandwidth :	4.66MHz
Band Edge :	-26.85dBm	Measurement Value :	-23.53dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 25.MAR.2013 15:35:26

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 25.MAR.2013 14:22:46

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.MAR.2013 14:25:37

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 25.MAR.2013 14:26:11

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 25.MAR.2013 14:26:43

Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 25.MAR.2013 14:51:01

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.MAR.2013 14:52:03

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 25.MAR.2013 14:52:35

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 25.MAR.2013 14:53:11

Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 25.MAR.2013 16:42:08

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.MAR.2013 16:42:55

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 25.MAR.2013 16:43:33

Conducted Spurious Emission Plot between 7GHz ~ 13.6G




Date: 25.MAR.2013 16:44:03


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz


Date: 25.MAR.2013 16:44:39


Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 25.MAR.2013 16:07:21


Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 25.MAR.2013 16:08:08

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 25.MAR.2013 16:08:44

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 25.MAR.2013 16:09:12

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 25.MAR.2013 16:09:46




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 25.MAR.2013 15:29:06


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 25.MAR.2013 15:26:31




Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 25.MAR.2013 15:27:01

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 25.MAR.2013 15:27:42

Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link	Frequency :	1732.6 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 11.APR.2013 03:26:01

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 11.APR.2013 03:26:34

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 11.APR.2013 03:28:05

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz




Date: 11.APR.2013 03:28:35


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz


Date: 11.APR.2013 03:29:07


Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 25.MAR.2013 15:39:26


Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 25.MAR.2013 15:40:19

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 25.MAR.2013 15:40:59

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 25.MAR.2013 15:41:36

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 25.MAR.2013 15:42:07

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13\text{dBm}.$$
12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.7.6 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR HORIZONTAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-56.90	-13	-43.90	-57.33	-57.55	0.57	3.37	H	Pass
2510	-51.49	-13	-38.49	-57.20	-53.72	0.78	5.16	H	Pass
3344	-55.61	-13	-42.61	-62.25	-59.25	0.87	6.66	H	Pass

Band :	GSM850	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR VERTICAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-54.04	-13	-41.04	-57.52	-54.69	0.57	3.37	V	Pass
2510	-51.13	-13	-38.13	-59.32	-53.36	0.78	5.16	V	Pass
3344	-53.43	-13	-40.43	-61.88	-57.07	0.87	6.66	V	Pass



Band :	GSM850	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR HORIZONTAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-63.46	-13	-50.46	-62.62	-64.11	0.57	3.37	H	Pass
2512	-53.11	-13	-40.11	-58.82	-55.34	0.78	5.16	H	Pass
3344	-56.10	-13	-43.10	-62.74	-59.74	0.87	6.66	H	Pass




Band :	GSM850	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR VERTICAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-60.91	-13	-47.91	-61.53	-61.56	0.57	3.37	V	Pass
2509	-55.89	-13	-42.89	-64.08	-58.12	0.78	5.16	V	Pass
3344	-54.61	-13	-41.61	-63.06	-58.25	0.87	6.66	V	Pass

Band :	GSM1900	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR HORIZONTAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-52.83	-13	-39.83	-60.70	-59.21	0.78	7.16	H	Pass
5640	-57.71	-13	-44.71	-66.39	-66.25	1.04	9.58	H	Pass
7520	-48.65	-13	-35.65	-63.75	-58.76	1.35	11.46	H	Pass



Band :	GSM1900	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR VERTICAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.24	-13	-43.24	-64.06	-62.62	0.78	7.16	V	Pass
5640	-55.82	-13	-42.82	-64.68	-64.36	1.04	9.58	V	Pass
7520	-46.77	-13	-33.77	-63.98	-56.88	1.35	11.46	V	Pass



Band :	GSM1900	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR HORIZONTAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.03	-13	-43.03	-62.93	-62.41	0.78	7.16	H	Pass
5640	-56.35	-13	-43.35	-65.03	-64.89	1.04	9.58	H	Pass
7520	-48.81	-13	-35.81	-63.91	-58.92	1.35	11.46	H	Pass




Band :	GSM1900	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR VERTICAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-55.59	-13	-42.59	-63.41	-61.97	0.78	7.16	V	Pass
5640	-57.09	-13	-44.09	-65.95	-65.63	1.04	9.58	V	Pass
7520	-46.06	-13	-33.06	-63.27	-56.17	1.35	11.46	V	Pass

Band :	WCDMA Band V	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR HORIZONTAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-62.25	-13	-49.25	-61.41	-62.90	0.57	3.37	H	Pass
2509	-58.99	-13	-45.99	-64.70	-61.22	0.78	5.16	H	Pass
3344	-56.82	-13	-43.82	-63.46	-60.46	0.87	6.66	H	Pass




Band :	WCDMA Band V	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR VERTICAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-60.28	-13	-47.28	-60.90	-60.93	0.57	3.37	V	Pass
2509	-56.33	-13	-43.33	-64.52	-58.56	0.78	5.16	V	Pass
3340	-52.56	-13	-39.56	-61.01	-56.20	0.87	6.66	V	Pass


Band :	WCDMA Band IV	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR HORIZONTAL
 Project : (FG)332604
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3464	-56.32	-13	-43.32	-62.61	-61.72	2.2	7.60	H	Pass
5194	-49.09	-13	-36.09	-59.26	-55.87	3.12	9.90	H	Pass
6924	-54.49	-13	-41.49	-63.55	-62.38	2.98	10.87	H	Pass

Band :	WCDMA Band IV	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR VERTICAL
 Project : IFG1332604

Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3464	-57.29	-13	-44.29	-61.56	-62.69	2.2	7.6	V	Pass
5194	-54.22	-13	-41.22	-63.38	-61.00	3.12	9.9	V	Pass
6924	-55.80	-13	-42.80	-64.56	-63.69	2.98	10.87	V	Pass




Band :	WCDMA Band II	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR HORIZONTAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-54.28	-13	-41.28	-61.18	-60.66	0.78	7.16	H	Pass
5640	-56.96	-13	-43.96	-65.64	-65.50	1.04	9.58	H	Pass
7520	-48.96	-13	-35.96	-64.06	-59.07	1.35	11.46	H	Pass

Band :	WCDMA Band II	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR VERTICAL
 : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
 Project : (FG)332604
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.18	-13	-37.18	-61.07	-56.56	0.78	7.16	V	Pass
5640	-54.95	-13	-41.95	-63.81	-63.49	1.04	9.58	V	Pass
7520	-45.61	-13	-32.61	-62.82	-55.72	1.35	11.46	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	38	0.04	21	0.02	PASS
-20	32	0.04	16	0.02	
-10	26	0.03	12	0.01	
0	23	0.03	-21	-0.02	
10	17	0.02	-16	-0.02	
20	14	0.02	-17	-0.02	
30	21	0.02	-14	-0.02	
40	18	0.02	-13	-0.02	
50	17	0.02	-22	-0.03	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	38	0.02	32	0.02	PASS
-20	32	0.02	24	0.01	
-10	27	0.01	21	0.01	
0	21	0.01	19	0.01	
10	18	0.01	16	0.01	
20	16	0.01	18	0.01	
30	20	0.01	12	0.01	
40	16	0.01	17	0.01	
50	14	0.01	13	0.01	

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	22	0.03	PASS
-20	16	0.02	
-10	21	0.02	
0	13	0.02	
10	-12	-0.01	
20	-8	-0.01	
30	-12	-0.01	
40	-16	-0.02	
50	-24	-0.03	

Band :	WCDMA Band IV	Channel :	1413
Limit (ppm) :	2.5	Frequency :	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	33	0.02	PASS
-20	22	0.01	
-10	19	0.01	
0	15	0.01	
10	-18	-0.01	
20	-15	-0.01	
30	-18	-0.01	
40	-22	-0.01	
50	-17	-0.01	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	35	0.02	PASS
-20	24	0.01	
-10	16	0.01	
0	13	0.01	
10	-21	-0.01	
20	-14	-0.01	
30	-21	-0.01	
40	-24	-0.01	
50	-18	-0.01	

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	27	0.03	2.5	PASS
		BEP	31	0.04		
		4.35	16	0.02		
	EDGE 8	3.8	-15	-0.02		
		BEP	17	0.02		
		4.35	-12	-0.01		
GSM 1900 CH661	GSM	3.8	21	0.01		
		BEP	35	0.02		
		4.35	18	0.01		
	EDGE 8	3.8	17	0.01		
		BEP	24	0.01		
		4.35	12	0.01		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	11	0.01		
		BEP	-7	-0.01		
		4.35	-12	-0.01		
WCDMA Band IV CH1413	RMC 12.2Kbps	3.8	12	0.01		
		BEP	-8	0.00		
		4.35	13	0.01		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	11	0.01		
		BEP	-11	-0.01		
		4.35	16	0.01		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.6 V.

4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2012	Mar. 25, 2013 ~Apr. 12, 2013	Dec. 28, 2013	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV30	100845	9kHz~30GHz	Nov. 06, 2012	Mar. 25, 2013 ~Apr. 12, 2013	Nov. 05, 2013	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 29, 2012	Mar. 25, 2013 ~Apr. 12, 2013	Dec. 28, 2013	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 22, 2012	Mar. 25, 2013 ~Apr. 12, 2013	Aug. 21, 2013	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 29, 2012	Mar. 25, 2013 ~Apr. 12, 2013	Dec. 28, 2013	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Apr.15, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	Jun. 01, 2012	Apr.15, 2013	May 31, 2013	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Apr.15, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Apr.15, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	Jun. 01, 2012	Apr.15, 2013	May 31, 2013	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Apr.15, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Apr.15, 2013	Nov. 22, 2013	Radiation (03CH01-KS)
HFH2-Z2 Loop Antenna	R&S	HFH2-Z2	100321	9KHZ-30MHZ	N/A	Apr.15, 2013	N/A	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 19, 2012	Apr.15, 2013	Sep. 18, 2013	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
--	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------



Appendix A. Photographs of EUT

Please refer to Sporton report number EP332604 as below.