

# **FCC RF EXPOSURE REPORT**

**FCC ID: YDB-SNOMD765**

**Project No. : 1506143**  
**Equipment : VoIP Phone**  
**Model : D765, snom D765, snom 765, 765**  
**Applicant : Snom technology AG**  
**Address : Wittestr. 30 G, Berlin, Germany 13509.**


**According: : FCC Guidelines for Human Exposure IEEE C95.1**

**BTL Inc.**

**B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan**

**TEL : (0769) 8318-3000 FAX : (0769) 8319-6000**

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1		AT8010-E2R9HAA	Chip	N/A	2.50

## GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
6.98	5	10

According to FCC KDB447498 V05, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq 50$  mm

The maximum measured output peak power of this EUT is 5 mW, less than 10 mW at 10mm distance.

**Conclusion: No SAR evaluation required since transmitter power is below FCC threshold**