System Check_Body_835MHz_121226

DUT: D835V2-SN:499

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL_850_121226 Medium parameters used: f = 835 MHz; $\sigma = 0.995$ mho/m; $\varepsilon_r = 54.886$; $\rho =$

Date: 2012/12/26

 1000 kg/m^3

Ambient Temperature: 22.3 °C; Liquid Temperature: 21.3 °C

DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Configuration/Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 3.07 mW/g

Configuration/Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 57.250 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.858 mW/g

SAR(1 g) = 2.63 mW/g; SAR(10 g) = 1.73 mW/g

Maximum value of SAR (measured) = 3.04 mW/g



0 dB = 3.04 mW/g = 9.66 dB mW/g

System Check_Body_1900MHz_121226

DUT: D1900V2-SN:5d041

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121226 Medium parameters used: f = 1900 MHz; $\sigma = 1.516$ mho/m; $\varepsilon_r = 53.631$; ρ

Date: 2012/12/26

 $= 1000 \text{ kg/m}^3$

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(4.67, 4.67, 4.67); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

Configuration/Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 11.9 mW/g

Configuration/Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 88.221 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 15.616 mW/g

SAR(1 g) = 9.57 mW/g; SAR(10 g) = 5.34 mW/g

Maximum value of SAR (measured) = 11.8 mW/g



0 dB = 11.8 mW/g = 21.44 dB mW/g