



PDF 檔案使用 "pdfFactory Pro" 試用版本建立 www.ahasoft.com.tw/FinePrint

BOM

P/N	PART	METAL	NUTEK P/N	Q'ty
1	TOP/BOTTOM CASE	PC/ABS GE C1200 BLACK	IABK0001	1
2	KEY CHAIN	IRON/nickel plated	MA150000	1
3	RUBBER KEYPAD	Dow Corning Toray SE 470/PU COATING	NKBK08A0	1
4	PCB			1
5	BATTERY	LITHIUM BATTERY	BTCR2032	1
6	BAT. positive CILP	STAINLESS SUS301	мсвкоооо	1
7	SCREW	STEEL/Zinc plated black	MTF02008	1

*Tolerance please refer specification of tolerance limits "c"

1. TEXTURE OF TOP/BOT CASE IS SAME AS NAL SAMPLE

2. Radious will be 0.2 if not specified.

HUTCT TOLERANCE SPEC.							
CRADE	A ±	B ±	C ±	Ì			
UNDER 5	0.08	0.16	0.50	1			
6~30	0.10	0.20	0.40	1			
30~120	0.20	0.40	0.80	1			
120~300	0.40	0.80	2.00	1			

SCALE: 1:1	UNIT: M/M	DRN BY Eric	DA 4/2-	те ′10	NUTEK CORPORATION			
MATERIAL		CHK BY			TITLE Water Proof TX for M&M Scorpio 408		Л	
FINISH		APPD BY			3coi più 408			
		VICTOR			SIZE	DEPT	DRAWING NO	RĐV
CODE		SHEET	OF		А3		9910030	2