

Produkte
Products

| | | | |
|--|--|--|--|
| Prüfbericht - Nr.: 14049237 001 | | Seite 1 von 15 | |
| <i>Test Report No.:</i> | | <i>Page 1 of 15</i> | |
| Auftraggeber: <i>Client:</i> | Stadlbauer Marketing + Vertrieb GmbH Rennbahn Allee 1, 5412 Puch Salzburg, Austria | | |
| Gegenstand der Prüfung: <i>Test Item:</i> | Short Range Device - Radio Control Toy Transmitter (2.4GHz) | | |
| Bezeichnung: <i>Identification:</i> | 370900050 | Serien-Nr.: <i>Serial No.:</i> | Engineering sample |
| Wareneingangs-Nr.: <i>Receipt No.:</i> | A000542309-001 | Eingangsdatum: <i>Date of Receipt:</i> | 05.04.2017 |
| Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of test item at delivery:</i> | | Test sample is not damaged and suitable for testing. | |
| Prüfört: <i>Testing Location:</i> | TÜV Rheinland Hong Kong Ltd. 3/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong | | |
| Prüfgrundlage: <i>Test Specification:</i> | FCC Part 15 Subpart C RSS-210 Issue 9 ANSI C63.10-2013 | | |
| Prüfergebnis: <i>Test Results:</i> | Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed . | | |
| Prüflaboratorium: <i>Testing Laboratory:</i> | TÜV Rheinland Hong Kong Ltd. 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong | | |
| geprüft/ tested by: | | kontrolliert/ reviewed by: | |
| 19.06.2017 | Kevin Wong | 19.06.2017 | Mika Chan |
| <i>Date</i> | <i>Name/Position</i> | <i>Date</i> | <i>Name/Position</i> |
| | <i>Signature</i> | | <i>Signature</i> |
| Sonstiges: Other Aspects | | FCC ID: YFA370900050 IC: 12260A-370900050 | |
| Abkürzungen: | P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet | Abbreviations: | P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested |
| Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i> | | | |

Table of Content

| | Page |
|--|---------------|
| Cover Page | 1 |
| Table of Content | 2 |
| Product information..... | 4 |
| Manufacturers declarations | 4 |
| Product function and intended use | 4 |
| Submitted documents..... | 4 |
| Independent Operation Modes | 4 |
| Related Submittal(s) Grants | 4 |
| Remark | 4 |
| Test Set-up and Operation Mode..... | 5 |
| Principle of Configuration Selection | 5 |
| Test Operation and Test Software | 5 |
| Special Accessories and Auxiliary Equipment..... | 5 |
| Countermeasures to achieve EMC Compliance..... | 5 |
| Test Methodology | 6 |
| Radiated Emission | 6 |
| Field Strength Calculation..... | 6 |
| Test Setup Diagram | 7 |
| List of Test and Measurement Instruments..... | 8 |
| Measurement Uncertainty | 9 |
| Results FCC Part 15 – Subpart C / RSS-210 Issue 9..... | 10 |
| FCC 15.203 – Antenna Requirement 1..... | Pass 10 |
| FCC 15.204 – Antenna Requirement 2..... | Pass 10 |
| RSS-Gen 6.3 – External Control..... | Pass 10 |
| RSS-Gen 8.3 – Antenna Requirement | Pass 10 |
| FCC 15.207/RSS-Gen 8.8 – Conducted Emission on AC Mains..... | N/A 11 |
| Subclause 15.215 (c) – 20 dB Bandwidth..... | Pass 11 |
| RSS-Gen 6.6 – Occupied Bandwidth..... | Pass 11 |
| Subclause 15.249 (a)/RSS-210 B.10 (a)–Field Strength of Fundamental and Harmonics..... | Pass 12 |
| Subclause 15.249 (d), 15.205/RSS-210 B.10 (b) – Out Of Band Radiated Emission | Pass 14 |

| | |
|--|---------|
| Appendix 1 – Test protocols | 5 pages |
| Appendix 2 – Test setup | 2 pages |
| Appendix 3 – EUT External Photos | 3 pages |
| Appendix 4 – EUT Internal Photos | 5 pages |
| Appendix 5 – RF exposure information | 2 pages |

Product information

Manufacturers declarations

| | Transmitter |
|---|--------------------------|
| Operating frequency range | 2403 - 2477MHz |
| Type of modulation | GFSK |
| Number of channels | 25 |
| Type of antenna | Wire Antenna |
| Power level | fix |
| Connection to public utility power line | No |
| Nominal voltage | V _{nor} : 3.0 V |

Product function and intended use

The equipment under test (EUT) is a radio control toy transceiver operating at 2.4GHz. It is powered by battery only.

FCC ID: YFA370900050 / IC: 12260A-370900050

| Models | Product description |
|-----------|---|
| 370900050 | Short Range Device - Radio Control Toy Transmitter (2.4GHz) |

Submitted documents

Circuit Diagram
 Block Diagram
 Bill of material
 Technical Description
 User manual
 Rating Label

Independent Operation Modes

The basic operation modes are:

- Transmitting mode.
- Normal operation mode

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- A test mode sample which can transmit continuously in the lowest, middle and highest frequency channels at its maximum power was provided by the applicant..

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- None

Countermeasures to achieve EMC Compliance

- None

Test Methodology

Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.
R = Reading of Spectrum Analyzer in dBuV.
AF = Antenna Factor in dB.
CF = Cable Attenuation Factor in dB.
FA = Filter Attenuation Factor in dB.
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.


Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



List of Test and Measurement Instruments

Hong Kong Productivity Council (FCC/ IC Registration number: 90656/ 4780A-1)

Radiated Emission

| Equipment | Manufacturer | Type | Cal. Date | Due Date |
|---|--------------------|---------------|-----------|-----------|
| Semi-anechoic Chamber | Frankonia | Nil | 25-Apr-17 | 25-Apr-18 |
| Test Receiver | R & S | ESU40 | 26-Jul-16 | 26-Jul-17 |
| Active Loop Antenna | EMCO | 6502 | 27-Oct-16 | 27-Oct-17 |
| Bi-conical Antenna | R & S | HK116 | 1-Sep-15 | 1-Sep-17 |
| Log Periodic Antenna | R & S | HL223 | 1-Sep-15 | 1-Sep-17 |
| Standard Gain Horn | ETS-Lindgren | 3160-07 | 3-Mar-16 | 3-Mar-18 |
| Standard Gain Horn | ETS-Lindgren | 3160-08 | 3-Mar-16 | 3-Mar-18 |
| Standard Gain Horn | ETS-Lindgren | 3160-10 | 3-Mar-16 | 3-Mar-18 |
| Double-Ridged Waveguide Horn | EMCO | 3116 | 17-Jun-16 | 17-Jun-18 |
| Double-Ridged Waveguide Horn | EMCO | 3117 | 22-Jun-16 | 22-Jun-18 |
| Coaxial cable | Harbour | LL335 | 10-Jun-16 | 10-Jun-18 |
| High Frequency Cable | Pasternack | PE3VNA4001-3M | 27-Jan-17 | 27-Jan-18 |
| Microwave amplifier 0.5-26.5GHz, 25dB gain | HP | 83017A | 18-Jul-16 | 18-Jul-18 |
| Preamplifier 18GHz to 40GHz with cable (EMC656) | A.H. Systems, Inc. | PAM-1840VH | 27-Jan-17 | 27-Jan-18 |
| High Pass Filter (cutoff freq. =1000MHz) | Trilithic | 23042 | 28-Oct-15 | 28-Oct-17 |

TÜV Rheinland Hong Kong Ltd

Radio Test

| Equipment | Manufacturer | Type | Cal. Date | Due Date |
|-------------------|--------------|-------|-----------|-------------|
| Spectrum Analyzer | R & S | FSP30 | 15-Oct-16 | 15-Oct-2017 |

Measurement Uncertainty

The estimated combined standard uncertainty for power-line conducted emissions measurements is $\pm 2.42\text{dB}$.

The estimated combined standard uncertainty for radiated emissions measurements is $\pm 4.81\text{dB}$ (9kHz to 30MHz) and $\pm 4.62\text{dB}$ (30MHz to 200MHz) and $\pm 5.67\text{dB}$ (200MHz to 1000MHz) and is $\pm 5.07\text{dB}$ (1GHz to 8.2GHz) and $\pm 4.58\text{dB}$ (8.2GHz to 12.4GHz) and $\pm 4.78\text{dB}$ (12.4GHz to 18GHz)

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for the level of confidence is approximately 95%.

Results FCC Part 15 – Subpart C / RSS-210 Issue 9

| | | |
|---|--|-------------|
| FCC 15.203 – Antenna Requirement 1 | | Pass |
| FCC Requirement: No antenna other than that furnished by the responsible party shall be used with the device | | |
| Results: | a) Antenna type: Fixed Integral antenna b) Manufacturer and model no: N/A c) Peak Gain: 0dBi | |
| Verdict: | Pass | |

| | | |
|--|--|-------------|
| FCC 15.204 – Antenna Requirement 2 | | Pass |
| FCC Requirement: An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator. | | |
| Results: | Only one integral antenna can be used. | |
| Verdict: | N/A | |

| | | |
|---|--|-------------|
| RSS-Gen 6.3 – External Control | | Pass |
| IC Requirement: The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the limits prescribed in the applicable RSS. | | |
| Results: | The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard. | |
| Verdict: | Pass | |

| | | |
|---|--|-------------|
| RSS-Gen 8.3 – Antenna Requirement | | Pass |
| IC Requirement: When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. | | |
| Results: | a) Antenna type: Fixed Integral wire antenna b) Manufacturer: N/A c) model no: N/A d) Gain with reference to an isotropic radiator: 0 dBi | |
| Verdict: | Pass | |

| | |
|---|------------|
| FCC 15.207/ RSS-Gen 8.8 – Conducted Emission on AC Mains | N/A |
| There is no AC power input or output ports on the EUT. | |

| Subclause 15.215 (c) – 20 dB Bandwidth | | Pass | | |
|--|------------------|--|-------------------|-------------|
| Test Specification : ANSI C63.10 – 2013 Mode of operation : Tx mode Port of testing : Enclosure Supply voltage : 3.0VDC, 2 x 1.5V AA size new battery Temperature : 23°C Humidity : 50% | | | | |
| Requirement: | | The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated. | | |
| Results: | | Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. For test protocols refer to Appendix 1. | | |
| Frequency (MHz) | 20 dB left (MHz) | Limit (MHz) | 20 dB right (MHz) | Limit (MHz) |
| 2403 | 2402.650 | > 2400 | 2404.090 | < 2483.5 |
| 2442 | 2441.720 | > 2400 | 2442.960 | < 2483.5 |
| 2477 | 2476.770 | > 2400 | 2477.900 | < 2483.5 |

| | | | |
|---|------------|--|---------------------|
| RSS-Gen 6.6 – Occupied Bandwidth | | Pass | |
| FCC/ IC Requirement : N/A | | | |
| Test Specification : RSS-Gen Mode of operation : Tx mode Port of testing : Temporary antenna port Detector : Peak Supply voltage : 3.0VDC, 2 x 1.5V AA size new battery Temperature : 23°C Humidity : 50% | | | |
| Results: | | Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. For test protocols refer to Appendix 1. | |
| Frequency (MHz) | Left (MHz) | Right (MHz) | 99% bandwidth (MHz) |
| 2403 | 2476.770 | 2403.840 | 1.060 |
| 2442 | 2441.940 | 2442.780 | 0.840 |
| 2477 | 2477.090 | 2477.570 | 0.480 |

| | | |
|--|-------------------------|-----------------------------------|
| Subclause 15.249 (a) / RSS-210 B.10 (a) – Field Strength of Fundamental and Harmonics Pass | | |
| Test Specification : ANSI C63.10 – 2013 Mode of operation : Tx mode Port of testing : Enclosure Frequency range : 9kHz – 25GHz Supply voltage : 3.0VDC, 2 x 1.5V AA size new battery Temperature : 23°C Humidity : 50% | | |
| Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit. | | |
| Results: PASS. | | |
| Fundamental Frequency 2403MHz Vertical Polarization | | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m |
| 2403.108 | 76.22 | 114.0 / PK |
| 2403.269 | 44.56 | 94.0 / AV |
| Fundamental Frequency 2403MHz Horizontal Polarization | | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m |
| 2403.160 | 78.02 | 114.0 / PK |
| 2403.240 | 45.07 | 94.0 / AV |
| Harmonics 2403MHz Vertical Polarization | | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m |
| 4806.282 | 59.11 | 74.0 / PK |
| 4806.426 | 42.24 | 54.0 / AV |
| Harmonics 2403MHz Horizontal Polarization | | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m |
| 4806.417 | 58.97 | 74.0 / PK |
| 4806.513 | 42.91 | 54.0 / AV |
| Fundamental Frequency 2442MHz Vertical Polarization | | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m |
| 2442.304 | 80.70 | 114.0 / PK |
| 2442.144 | 45.66 | 94.0 / AV |

| Fundamental Frequency 2442MHz | | Horizontal Polarization | |
|-------------------------------|-----------------|---------------------------|--|
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 2442.080 | 77.12 | 114.0 / PK | |
| 2442.321 | 44.75 | 94.0 / AV | |
| Harmonics 2442MHz | | Vertical Polarization | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 4884.213 | 56.52 | 74.0 / PK | |
| 4884.406 | 40.95 | 54.0 / AV | |
| Harmonics 2442MHz | | Horizontal Polarization | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 4884.471 | 55.77 | 74.0 / PK | |
| 4884.529 | 41.14 | 54.0 / AV | |
| Fundamental Frequency 2477MHz | | Vertical Polarization | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 2477.692 | 80.09 | 114.0 / PK | |
| 2477.244 | 46.11 | 94.0 / AV | |
| Fundamental Frequency 2477MHz | | Horizontal Polarization | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 2477.324 | 75.09 | 114.0 / PK | |
| 2477.356 | 43.51 | 94.0 / AV | |
| Harmonics 2477MHz | | Vertical Polarization | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 4954.897 | 58.78 | 74.0 / PK | |
| 4954.577 | 42.18 | 54.0 / AV | |
| Harmonics 2477MHz | | Horizontal Polarization | |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 4954.744 | 56.81 | 74.0 / PK | |
| 4954.487 | 41.77 | 54.0 / AV | |

| | | | |
|---|-------------------------|-----------------------------------|-------------------------|
| Subclause 15.249 (d), 15.205 / RSS-210 B.10 (b) – Out Of Band Radiated Emission | | | Pass |
| Test Specification : ANSI C63.10 – 2013 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak Frequency range : 9kHz – 25GHz Supply voltage : 3.0VDC, 2 x 1.5V AA size new battery Temperature : 23°C Humidity : 50% | | | |
| Requirement: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation. | | | |
| Results: All three transmit frequency modes comply with the field strength limit of section 15.209. There is no spurious found below 30MHz. | | | |
| Tx frequency 2403MHz | | | Vertical Polarization |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 2390.000 | 44.74 | 74.0 / PK | |
| 2390.000 | 32.94 | 54.0 / AV | |
| 2748.795 | 56.86 | 74.0 / PK | |
| 2748.924 | 45.64 | 54.0 / AV | |
| Tx frequency 2403MHz | | | Horizontal Polarization |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 2390.000 | 46.53 | 74.0 / PK | |
| 2390.000 | 32.83 | 54.0 / AV | |
| 2748.910 | 54.40 | 74.0 / PK | |
| 2748.910 | 43.45 | 54.0 / AV | |
| Tx frequency 2442MHz | | | Vertical Polarization |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 2793.548 | 58.04 | 74.0 / PK | |
| 2793.372 | 47.51 | 54.0 / AV | |
| Tx frequency 2442MHz | | | Horizontal Polarization |
| Freq MHz | Level dBuV/m | Limit/ Detector dBuV/m | |
| 2793.382 | 56.52 | 74.0 / PK | |
| 2793.478 | 45.34 | 54.0 / AV | |

| | | | | | |
|----------------------|--|-----------------|-------------------------|---------------------------|--|
| Tx frequency 2477MHz | | | Vertical Polarization | | |
| Freq MHz | | Level dBuV/m | | Limit/ Detector dBuV/m | |
| 2483.500 | | 53.23 | | 74.0 / PK | |
| 2483.500 | | 32.73 | | 54.0 / AV | |
| 2833.461 | | 58.09 | | 74.0 / PK | |
| 2833.429 | | 46.92 | | 54.0 / AV | |
| Tx frequency 2477MHz | | | Horizontal Polarization | | |
| Freq MHz | | Level dBuV/m | | Limit/ Detector dBuV/m | |
| 2483.500 | | 46.98 | | 74.0 / PK | |
| 2483.500 | | 32.69 | | 54.0 / AV | |
| 2833.526 | | 55.75 | | 74.0 / PK | |
| 2833.494 | | 44.44 | | 54.0 / AV | |