Report No.: NTC1509066F FCC ID: YGB-WDV8000



FCC PART 15 SUBPART C MEASURMENT AND TEST REPORT

For

SHUOYING DIGITAL SCIENCE&TECHNOLOGY(CHINA)Co.,Ltd

No.187, 5th Binhai Road, Wenzhou, Zhejiang, China

E.U.T.: Wifi Camera

Model Name: WDV8000

Brand Name: N/A

FCC ID: YGB-WDV8000

Report Number: NTC1509066F

Test Date(s): September 12, 2015 to September 28, 2015

Report Date(s): September 28, 2015

Prepared by

Dongguan Nore Testing Center Co., Ltd.

Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong, China

Tel: +86-769-22022444

Fax: +86-769-22022799

Prepared By

Approved & Authorized Signer

Rose Hu / Engineer

Sunm Lv / Q.A. Director

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Dongguan Nore Testing Center Co., Ltd. The test results referenced from this report are relevant only to the s ample tested.

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F FCC ID: YGB-WDV8000



Table of Contents

1.	GENERAL INFORMATION	4
	1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	4
	1.2 RELATED SUBMITTAL(S) / GRANT (S)	
	1.3 TEST METHODOLOGY	
	1.4 EQUIPMENT MODIFICATIONS	
	1.5 SUPPORT DEVICE	
	1.6 TEST FACILITY AND LOCATION	
	1.7 SUMMARY OF TEST RESULTS	
2.	SYSTEM TEST CONFIGURATION	9
	2.1 EUT CONFIGURATION	g
	2.2 SPECIAL ACCESSORIES	9
	2.3 DESCRIPTION OF TEST MODES	
	2.4 EUT EXERCISE	9
3.	CONDUCTED EMISSIONS TEST	. 10
	3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	10
	3.2 TEST CONDITION	
	3.3 MEASUREMENT RESULTS	10
4.	MAX. CONDUCTED OUTPUT POWER	. 13
	4.1 MEASUREMENT PROCEDURE	13
	4.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
	4.3 MEASUREMENT RESULTS	
5.	6DB&20DB BANDWIDTH	
	5.1 MEASUREMENT PROCEDURE	
	5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
	5.3 MEASUREMENT RESULTS	
6	POWER SPECTRAL DENSITY	
٠.		
	6.1 MEASUREMENT PROCEDURE	
	6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
_	6.3 MEASUREMENT RESULTS	
1.	BAND EDGE AND CONDUCTED SPURIOUS EMISSIONS	
	7.1 REQUIREMENT AND MEASUREMENT PROCEDURE	
	7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
	7 3 MEASUPEMENT RESULTS	36



8. RADIATED SPURIOUS EMISSIONS AND RESTRICTED BANDS	46
8.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	46
8.2 MEASUREMENT PROCEDURE	47
8.3 LIMIT	48
8.4 MEASUREMENT RESULTS	48
9. ANTENNA APPLICATION	54
9.1 Antenna requirement	54
9.2 MEASUREMENT RESULTS	54
10 TEST FOLIPMENT LIST	55

Report No.: NTC1509066F FCC ID: YGB-WDV8000



1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a Wifi Camera, it's powered by DC 5V come from USB port or DC 3.8V li-ion battery. For more details features, please refer to User's Manual.

Manufacturer : SHUOYING DIGITAL

SCIENCE&TECHNOLOGY(CHINA)Co.,Ltd

Address : No.187, 5th Binhai Road, Wenzhou, Zhejiang, China

Factory : SHUOYING DIGITAL

SCIENCE&TECHNOLOGY(CHINA)Co.,Ltd

Address : No.187, 5th Binhai Road, Wenzhou, Zhejiang, China

Power Supply : DC 5V Come from USB Port

DC 3.7V li-ion battery

Test voltage : AC 120V 60Hz (Adapter input)

Model name : WDV8000

Model difference : N/A

Hardware version : WDV8000SA-MAIN-V1.4

Software version : 001 Serial number : N/A

Report No.: NTC1509066F FCC ID: YGB-WDV8000



Technical parameters For WIFI Function

Frequency Range : 2412-2462MHz for 802.11b/g/n(HT20)

Modulation : CCK, DQPSK, DBPSK for 802.11b

OFDM for 802.11g/n

Number of Channel : 11

Channel space : 5MHz

Date Rate : 802.11b:1~11Mbps, 802.11g:6~54Mbps

802.11n: 6.5~72Mbps

Antenna Type : Integral antenna

Antenna Gain : 2 dBi (declared by manufacturer)



WIFI Channel List

802.11 b/g/n(HT20)					
Channel	Frequency MHz				
1	2412				
2	2417				
3	2422				
4	2427				
5	2432				
6	2437				
7	2442				
8	2447				
9	2452				
10	2457				
11	2462				

Note: According to section 15.31(m), regards to the operating frequency range over 10MHz, the Lowest, middle, and the Highest frequency of channel were selected to perform the test. The selected frequency see below:

802.11b/g/n(HT20)					
Channel	Frequency MHz				
1	2412				
6	2437				
11	2462				

Report No.: NTC1509066F FCC ID: YGB-WDV8000



1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **YGB-WDV8000** filing to comply with Section 15.247 of the FCC Part 15(2014), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10-2013 and KDB558074 (v03r02). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters. All other measurements were made in accordance with the procedures in 47 CFR part 2.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

Adapter : Model: BSYC050200UW

Input: AC100-240V 50/60Hz 0.5A Output: DC 5.0V 2000mA

1.6 Test Facility and Location

Listed by FCC, August 02, 2011 The Certificate Registration Number is 665078. Listed by Industry Canada, July 01, 2011 The Certificate Registration Number is 46405-9743.

Dongguan NTC Co., Ltd.

(Full Name: Dongguan Nore Testing Center Co., Ltd.)

Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong, China (Full Name: Building D, Gaosheng Science & Technology Park, Zhouxi Longxi Road, Nancheng District, Dongguan, Guangdong, China.

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F FCC ID: YGB-WDV8000



1.7 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207 (a)	AC Power Conducted Emission	Compliance
§15.247(b)(3)	Max. Conducted Output Power	Compliance
§15.247(a)(2)	6dB Bandwidth	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band Edge and Conducted Spurious Emissions	Compliance
§15.247(d),§15.209, §15.205	Radiated Spurious Emissions and Restricted Bands	Compliance
§15.203	Antenna Requirement	Compliance

Report No.: NTC1509066F FCC ID: YGB-WDV8000



2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes

The EUT has been tested under continuous operating condition. Test program used to control the EUT staying in continuous transmitting mode. The Lowest, middle and highest channel were chosen for testing, and modulation type CCK, DQPSK, DBPSK, OFDM and all data rate were tested. But only the worst case data is shown in this report.

2.4 EUT Exercise


The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

Report No.: NTC1509066F FCC ID: YGB-WDV8000



3. Conducted Emissions Test

3.1 Test SET-UP (Block Diagram of Configuration)



3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

Detector: RBW 9KHz, VBW 30KHz

Operation Mode: Charging+WIFI Mode

3.3 Measurement Results

Please refer to following plots.

Report No.: NTC1509066F FCC ID: YGB-WDV8000




Site: Conduction



Dongguan NTC Co., Ltd. Tel: +86-769-22022444 Fax: +86-769-22022799

Norw Testing Center Web: Http://www.ntc-c.com

Test Time: 2015-9-18 20:04:28



Report No.: WDV8000

Test Standard: FCC PART 15_Class B_QP

Test item: Conducted Emission Phase:

Applicant: SHUOYING 26(C) / 60 % Temp.()/Hum.(%): Product: Wifi Camera AC 120V 60Hz Power Rating: Model No.: WDV8000 Test Engineer: Jerry

Test Mode: Charging+WIFI Mode

Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1539	10.80	30.50	41.30	65.78	-24.48	QP	Р	
2	0.1539	10.80	11.60	22.40	55.78	-33.38	AVG	Р	
3	0.5380	10.80	24.70	35.50	56.00	-20.50	QP	Р	
4	0.5380	10.80	11.80	22.60	46.00	-23.40	AVG	Р	
5	0.7740	10.80	18.00	28.80	56.00	-27.20	QP	Р	
6	0.7740	10.80	3.60	14.40	46.00	-31.60	AVG	Р	
7	1.0540	10.80	18.80	29.60	56.00	-26.40	QP	Р	
8	1.0540	10.80	2.40	13.20	46.00	-32.80	AVG	Р	
9	1.2740	10.80	18.30	29.10	56.00	-26.90	QP	Р	
10	1.2740	10.80	1.80	12.60	46.00	-33.40	AVG	Р	
11	2.3420	10.80	14.50	25.30	56.00	-30.70	QP	Р	
12	2.3420	10.80	-1.20	9.60	46.00	-36.40	AVG	Р	

Report No.: NTC1509066F FCC ID: YGB-WDV8000




Site: Conduction



Dongguan NTC Co., Ltd. Tel: +86-769-22022444 Fax: +86-769-22022799

ng Center Web: Http://www.ntc-c.com



Report No.: WDV8000

FCC PART 15_Class B_QP Test Standard:

Test item: **Conducted Emission**

Applicant: SHUOYING Temp.()/Hum.(%): 26(C) / 60 % Product: Wifi Camera Power Rating: AC 120V 60Hz Model No.: WDV8000 Test Engineer: Jerry

Phase:

Test Mode: Charging+WIFI Mode

Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1580	10.80	29.70	40.50	65.56	-25.06	QP	Р	
2	0.1580	10.80	12.60	23.40	55.56	-32.16	AVG	Р	
3	0.5340	10.80	27.40	38.20	56.00	-17.80	QP	Р	
4	0.5340	10.80	19.70	30.50	46.00	-15.50	AVG	Р	
5	0.9100	10.80	18.30	29.10	56.00	-26.90	QP	Р	
6	0.9100	10.80	7.80	18.60	46.00	-27.40	AVG	Р	
7	1.5700	10.80	15.60	26.40	56.00	-29.60	QP	Р	
8	1.5700	10.80	4.80	15.60	46.00	-30.40	AVG	Р	
9	2.0300	10.80	15.90	26.70	56.00	-29.30	QP	Р	
10	2.0300	10.80	4.50	15.30	46.00	-30.70	AVG	Ք	
11	3.3860	10.80	14.90	25.70	56.00	-30.30	QP	Р	
12	3.3860	10.80	3.40	14.20	46.00	-31.80	AVG	Р	

Report No.: NTC1509066F FCC ID: YGB-WDV8000



4. Max. Conducted Output Power

4.1 Measurement Procedure

Maximum Conducted Output power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC KDB558074 (v03r02):

Maximum conducted (Average) output power:

- 1. Set the RBW = 1-5% of the OBW, not to exceed 1MHz.
- 2. Set the VBW \geq 3 x RBW
- 3. Set the span \geq 1.5 x OBW
- 4. Detector = RMS
- 5. Sweep time = auto couple.
- 6. Number of points in sweep ≥2x span/RBW. (This gives bin-to-bin spacing≤2, so that narrowband signals are not lost between frequency bins.)
- 7. Trace mode = Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- 8. If transmit duty cycle <98%, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously(i.e., with no off intervals) or at duty cycle ≥98%, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".
- 9. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

4.2 Test SET-UP (Block Diagram of Configuration)



4.3 Measurement Results

Pass

Please refer to following table and plots.

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F FCC ID: YGB-WDV8000




Temperature :	24 °C	Humidity:	50%	
Test By:	Sance	Test Date :	September 18, 2015	
Test Result:	PASS			
Frequency MHz	Data Rate Mbps	AV Output Power dBm		Limit dBm
IEEE	802.11b Mode (CC	K, Antenna Gain	=2dBi)	
Low Channel: 2412	1	6.2	4	30
Middle Channel: 2437	1	7.1	30	
High Channel: 2462	1	6.9	30	
IEEE	802.11g Mode (OF	OM, Antenna Gair	n=2dBi)	
Low Channel: 2412	6	6.7	30	
Middle Channel: 2437	6	7.62		30
High Channel: 2462	6	8.58		30
IEEE 802.11n(HT20) Mode (OFDM, Antenna Gain=2dBi)				
Low Channel: 2412	6.5	6.97		30
Middle Channel: 2437	6.5	7.64		30
High Channel: 2462	6.5	8.4	30	


Report No.: NTC1509066F FCC ID: YGB-WDV8000




Maximum Average Conducted Output Power 802.11b Low Channel



802.11b Middle Channel







Bandwidth








802.11g Middle Channel



19.7435897 MHz

80.11g High Channel


7.62 dBm




Report No.: NTC1509066F FCC ID: YGB-WDV8000



802.11n(HT20) Low Channel



802.11n(HT20) Middle Channel



802.11n(HT20) High Channel



Report No.: NTC1509066F FCC ID: YGB-WDV8000



5. 6dB&20dB Bandwidth

5.1 Measurement Procedure

DTS 6dB Channel Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC KDB558074(v03r02):

- 1. For 6dB bandwidth, Set the RBW = 100KHz. For 20dB bandwidth, Set the RBW=1-5% of the OBW, not to exceed 1MHz.
- 2. Set the VBW \geq 3 x RBW
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Results

Pass

Please refer to following table and plots.


Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F FCC ID: YGB-WDV8000



Temperature :	24 °C	Humidity:	50 %			
Test By:	Sance	Test Date :	18, 2015			
Test Result:	PASS		<u> </u>			
Frequency MHz	Data Rate Mbps	6dB 20dB Bandwidth Bandwidth MHz MHz		Limit		
	IEEE 802.11b I	Mode (CCK)				
Low Channel: 2412	1	10.19	17.31	>500KHz		
Middle Channel: 2437	1	10.19	17.24	>500KHz		
High Channel: 2462	1	10.19	16.99	>500KHz		
	IEEE 802.11g M	lode (OFDM)				
Low Channel: 2412	6	16.63	19.74	>500KHz		
Middle Channel: 2437	6	16.73	19.74	>500KHz		
High Channel: 2462	6	16.73	19.74	>500KHz		
	IEEE 802.11n(HT20) Mode (OFDM)					
Low Channel: 2412	6.5	17.98	20.38	>500KHz		
Middle Channel: 2437	6.5	17.93	20.32	>500KHz		
High Channel: 2462	6.5	17.93	20.32	>500KHz		




6dB Bandwidth 802.11b Low Channel



Date: 18.SEP.2015 15:47:52


802.11b Middle Channel



Date: 18.SEP.2015 15:53:54








Date: 18.SEP.2015 15:56:54

802.11g Low Channel




Date: 18.SEP.2015 16:00:17

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F

FCC ID: YGB-WDV8000




802.11g Middle Channel



Date: 18.SEP.2015 16:02:01


802.11g High Channel




Date: 18.SEP.2015 16:03:38

Report No.: NTC150906 FCC ID: YGB-WDV8000








Date: 18.SEP.2015 16:05:13


802.11n(HT20) Middle Channel




Date: 18.SEP.2015 16:08:11

Report No.: NTC1509066F FCC ID: YGB-WDV8000








Date: 18.SEP.2015 16:09:17

20dB Bandwidth 802.11b Low Channel




Date: 18.SEP.2015 16:57:30

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F

FCC ID: YGB-WDV8000




802.11b Middle Channel



Date: 18.SEP.2015 16:58:56

802.11b High Channel



Date: 18.SEP.2015 16:59:53

Report No.: NTC1509066F FCC ID: YGB-WDV8000








Date: 18.SEP.2015 17:01:29


802.11g Middle Channel



Date: 18.SEP.2015 17:02:44




802.11g High Channel



Date: 18.SEP.2015 17:03:55

802.11n(HT20) Low Channel




Date: 18.SEP.2015 17:05:22

Report No.: NTC1509066F FCC ID: YGB-WDV8000




802.11n(HT20) Middle Channel



Date: 18.SEP.2015 17:08:10

802.11n(HT20) High Channel



Date: 18.SEP.2015 17:09:26

Report No.: NTC1509066F FCC ID: YGB-WDV8000



6. Power Spectral Density

6.1 Measurement Procedure

DTS 6dB Channel Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC KDB558074 (v03r02):

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: 3 kHz≤RBW≤100KHz
- 4. Set the VBW \geq 3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Results

Pass

Please refer to following table and plots.

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F FCC ID: YGB-WDV8000




	1		T					
Temperature :	24 °C	Humidity:	50 %					
Test By:	Sance	Test Date :	September 18, 2015					
Test Result:	PASS							
Frequency MHz	Data Rate Mbps	PSD dBm	Limit dBm					
	IEEE 802.11b	Mode (CCK)						
Low Channel: 2412	1	-17.56	8					
Middle Channel: 2437	1	-16.69	8					
High Channel: 2462	1	-15.86	8					
IEEE 802.11g Mode (OFDM)								
Low Channel: 2412	6	-17.40	8					
Middle Channel: 2437	6	-16.48	8					
High Channel: 2462	6	-15.68	8					
	IEEE 802.11n(HT20) Mode (OFDM)							
Low Channel: 2412	6.5	-17.38	8					
Middle Channel: 2437	6.5	-16.47	8					
High Channel: 2462	6.5	-15.69	8					

Report No.: NTC150906 FCC ID: YGB-WDV8000



802.11b Low Channel



Date: 18.SEP.2015 16:14:19

802.11b Middle Channel



Date: 18.SEP.2015 16:15:26




802.11b High Channel



Date: 18.SEP.2015 16:16:05

802.11g Low Channel




Date: 18.SEP.2015 16:17:29

Report No.: NTC1509066F FCC ID: YGB-WDV8000




802.11g Middle Channel



Date: 18.SEP.2015 16:20:44

802.11g High Channel




Date: 18.SEP.2015 16:20:00

Report No.: NTC1509066F FCC ID: YGB-WDV8000




802.11n(HT20) Low Channel



Date: 18.SEP.2015 16:23:26


802.11n(HT20) Middle Channel



Date: 18.SEP.2015 16:24:53



802.11n(HT20) High Channel



Date: 18.SEP.2015 16:43:46

Report No.: NTC1509066F FCC ID: YGB-WDV8000




7. Band Edge and Conducted Spurious Emissions

7.1 Requirement and Measurement Procedure

Out of Band Conducted Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz, and the video bandwidth set to 300KHz.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Results

The test plots showed that all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20dB below the highest level of the desired power in the passband. Please refer to below tables and plots.

Report No.: NTC1509066F FCC ID: YGB-WDV8000



Spurious Emission in restricted band:

Operation Mode: TX Test Date: September 18, 2015

Frequency Range: Above 1GHz Temperature: 24 $^{\circ}$ C Test Result: PASS Humidity: 50 $^{\circ}$ Measured Distance: 3m Test By: Sance

Freq.	Ant.Pol.	Rea	ding	Factor	Emissio	n Level	Limit 3m		Margin	
•		Level(dBuV)		(dBı	(dBuV)		V/m)	(dB)	
(MHz)	(H/V)	PK	AV	(dB/m)	PK	AV	PK	AV	PK	AV
				Test Mo	de: 802.1	1b				
2388.063	Н	27.65	11.97	8.08	35.73	20.05	74.00	54.00	-38.27	-33.95
2388.063	V	26.25	12.92	8.08	34.33	21.00	74.00	54.00	-39.67	-33.00
2399.990	Н	41.16	27.22	8.09	49.25	35.31	74.00	54.00	-24.75	-18.69
2399.990	V	41.11	26.91	8.09	49.20	35.00	74.00	54.00	-24.80	-19.00
2483.501	Н	36.53	25.49	8.36	44.89	33.85	74.00	54.00	-29.11	-20.15
2483.501	V	35.72	23.41	8.36	44.08	31.77	74.00	54.00	-29.92	-22.23
				Test Mo	de: 802.1	1g				
2388.063	Н	26.34	13.35	8.08	34.42	21.43	74.00	54.00	-39.58	-32.57
2388.063	V	26.67	14.01	8.08	34.75	22.09	74.00	54.00	-39.25	-31.91
2399.990	Н	39.36	25.92	8.09	47.45	34.01	74.00	54.00	-26.55	-19.99
2483.501	V	38.86	25.82	8.09	46.95	33.91	74.00	54.00	-27.05	-20.09
2483.501	Н	39.67	26.93	8.36	48.03	35.29	74.00	54.00	-25.97	-18.71
2483.501	V	38.39	30.45	8.36	46.75	38.81	74.00	54.00	-27.25	-15.19
			Tes	st Mode:	802.11n(HT20)				
2388.063	Н	27.13	14.36	8.08	35.21	22.44	74.00	54.00	-38.79	-31.56
2388.063	V	28.12	17.00	8.08	36.20	25.08	74.00	54.00	-37.80	-28.92
2399.990	Н	48.91	28.91	8.09	57.00	37.00	74.00	54.00	-17.00	-17.00
2483.501	V	44.89	26.61	8.09	52.98	34.70	74.00	54.00	-21.02	-19.30
2483.501	Н	44.20	32.82	8.36	52.56	41.18	74.00	54.00	-21.44	-12.82
2483.501	V	42.64	28.25	8.36	51.00	36.61	74.00	54.00	-23.00	-17.39


Note: (1) All Readings are Peak Value and AV.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss

(3) Measurement uncertainty: ±3.7dB




Band Edge 802.11b Low Channel



Date: 18.SEP.2015 16:46:15

802.11b High Channel




Date: 18.SEP.2015 16:47:42

Report No.: NTC150906 FCC ID: YGB-WDV8000




802.11g Low Channel



Date: 18.SEP.2015 16:49:15


802.11g High Channel



Date: 18.SEP.2015 16:50:20




802.11n(HT20) Low Channel



Date: 18.SEP.2015 16:52:02


802.11n(HT20) High Channel



Date: 18.SEP.2015 16:52:46




Conducted Spurious Emissions 802.11b Low Channel



Date: 18.SEP.2015 12:14:02


Middle Channel



Date: 18.SEP.2015 12:13:21








Date: 18.SEP.2015 12:12:31

Note: Sweep points=30001pts

802.11g Low Channel




Date: 18.SEP.2015 12:14:37

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F

FCC ID: YGB-WDV8000



Middle Channel



Date: 18.SEP.2015 12:15:03

Date: 18.SEP.2015 12:15:34


Note: Sweep points=30001pts

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F

FCC ID: YGB-WDV8000




802.11n(HT20) Low Channel



Date: 18.SEP.2015 12:16:06

Middle Channel




Date: 18.SEP.2015 12:16:33

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F

FCC ID: YGB-WDV8000







Date: 18.SEP.2015 12:17:17

Note: Sweep points=30001pts


Report No.: NTC1509066F FCC ID: YGB-WDV8000




8. Radiated Spurious Emissions and Restricted Bands

8.1 Test SET-UP (Block Diagram of Configuration)

8.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz






Report No.: NTC1509066F FCC ID: YGB-WDV8000



8.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



8.2 Measurement Procedure

- a. Blow 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room. Above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi- anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- e. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

For 30MHz to 1GHz:

Sept the spectrum analyzer as: RBW=120kHz, VBW=300kHz, Detector=Quasi-Peak

For Above 1GHz:

Set the spectrum analyzer as: RBW=1MHz, VBW=3MHz, Detector=Peak. Set the spectrum analyzer as: RBW=1MHz, VBW=10Hz, Detector=Peak.

Report No.: NTC1509066F FCC ID: YGB-WDV8000



During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band Level Resolution Bandwidth Video Bandwidth (MHz) QP 300 kHz 30 to 1000 120 kHz Peak 1 MHz 3 MHz Above 1000 1 MHz 10 Hz Average

8.3 Limit

Frequency range MHz	Distance Meters	5 ,
IVITIZ		μV/m
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

Remark : (1) Emission level (dB) μ V = 20 log Emission level μ V/m

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
- (5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

8.4 Measurement Results

Please refer to following plots.

Report No.: NTC1509066F FCC ID: YGB-WDV8000




Site: Radiation



Dongguan NTC Co., Ltd. Tel:+86-769-22022444 Fax:+86-769-22022799

ng Center Web: Http://www.ntc-c.com



Report No.: WDV8000

Test Standard: FCC Part 15_Class B_3M

Test item: Radiation Emission

Applicant: SHUOYING

Product: WiFi Camera Model No.: WDV8000

Test Mode: Charging+WIFI Mode Remark: 802.11b Higest channel

Test Distance:

Ant. Polarization: Horizontal

Temp.(C)/Hum.(%): 21(C) / 55 %

Power Rating: AC 120V 60Hz

Test Engineer: Gavin

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	174.5300	-14.53	51.93	37.40	43.50	-6.10	QP			Р	
2	274.4400	-11.09	49.69	38.60	46.00	-7.40	QP			Р	
3	324.8799	-9.78	46.68	36.90	46.00	-9.10	QP			Р	
4	475.0700	-7.34	47.44	40.10	46.00	-5.90	QP			Р	
5	522.7600	-6.72	46.92	40.20	46.00	-5.80	QP			Р	
6	574.1699	-5.75	41.55	35.80	46.00	-10.20	QP			Р	

Report No.: NTC1509066F FCC ID: YGB-WDV8000




Site: Radiation



Dongguan NTC Co., Ltd. Tel:+86-769-22022444 Fax:+86-769-22022799

ore Web: Http://www.ntc-c.com

Test Time: 2015-9-22 14:31:12



Report No.: WDV8000

FCC Part 15_Class B_3M Test Standard:

Test item: Radiation Emission

SHUOYING Applicant: Product: WiFi Camera

Model No.: WDV8000

Test Mode: Charging+WIFI Mode Remark: 802.11b Higest channel

Test Distance:

Ant. Polarization: Vertical

Temp.(C)/Hum.(%): 21(C) / 55 %

AC 120V 60Hz Power Rating:

Test Engineer: Gavin

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	174.5300	-17.53	53.23	35.70	43.50	-7.80	QP			Р	
2	224.0000	-15.76	45.86	30.10	46.00	-15.90	QP			Р	
3	274.4399	-13.09	40.79	27.70	46.00	-18.30	QP			Р	
4	475.2300	-9.34	41.24	31.90	46.00	-14.10	QP			Р	
5	523.7300	-8.71	40.51	31.80	46.00	-14.20	QP			Р	
6	625.5800	-6.81	37.61	30.80	46.00	-15.20	QP			Р	

Report No.: NTC1509066F FCC ID: YGB-WDV8000



Test Mode: 802.11b Test Date: September 18, 2015

Frequency Range: Above 1GHz Temperature : 24℃
Test Result: PASS Humidity : 50 %
Measured Distance: 3m Test By: Sance

Freq. Ant.Pol.		Rea	•	Factor	Emissio		Limit 3m		Margin	
(MHz)	(H/V)	Level(dBuV)	(dB/m)	(dBuV)		(dBuV/m)		(dB)	
(1711 12)	(11/ /)	PK	AV	(uD/III)	PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
4824	V	39.31	24.42	14.72	54.03	39.14	74.00	54.00	-19.97	-14.86
7236	V	39.35	24.89	20.74	60.09	45.63	74.00	54.00	-13.91	-8.37
4824	Н	39.04	24.68	14.72	53.76	39.40	74.00	54.00	-20.24	-14.6
7236	Н	39.19	25.03	20.74	59.93	45.77	74.00	54.00	-14.07	-8.23
			Ope	ration Mo	ode: TX N	lode (Mi	d)			
4874	V	41.19	31.29	14.93	56.12	46.22	74.00	54.00	-17.88	-7.78
7311	V	38.57	27.38	20.88	59.45	48.26	74.00	54.00	-14.55	-5.74
4874	Н	38.79	24.46	14.93	53.72	39.39	74.00	54.00	-20.28	-14.61
7311	Н	40.23	25.31	20.88	61.11	46.19	74.00	54.00	-12.89	-7.81
			Oper	ation Mo	de: TX M	ode (Hiç	gh)			
4924	V	38.07	23.08	15.15	53.22	38.23	74.00	54.00	-20.78	-15.77
7386	V	37.92	23.22	21.04	58.96	44.26	74.00	54.00	-15.04	-9.74
4924	Н	36.29	22.08	15.15	51.44	37.23	74.00	54.00	-22.56	-16.77
7386	Н	37.68	23.24	21.04	58.72	44.28	74.00	54.00	-15.28	-9.72
					-					

Note: (1) All Readings are Peak Value and AV.

- (2) Emission Level= Reading Level + Factor
- (3) Factor= Antenna Gain + Cable Loss Amplifier Gain
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
- (5) Measurement uncertainty: ±3.7dB.
- (6) Horn antenna used for the emission over 1000MHz.

Report No.: NTC1509066F FCC ID: YGB-WDV8000



Test Mode: 802.11g Test Date: September 18, 2015

Frequency Range: Above 1GHz Temperature : 24° C Test Result: PASS Humidity : 50° Measured Distance: 3m Test By: Sance

Freq. Ant.Pol (MHz) (H/V)		Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
(IVII IZ)	(1 1/ V)	PK	AV	(ub/III)	PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
4824	V	39.44	23.53	14.72	54.16	38.25	74.00	54.00	-19.84	-15.75
7236	V	39.12	24.86	20.74	59.86	45.60	74.00	54.00	-14.14	-8.40
4824	Н	39.70	25.80	14.72	54.42	40.52	74.00	54.00	-19.58	-13.48
7236	Н	39.37	24.89	20.74	60.11	45.63	74.00	54.00	-13.89	-8.37
			Ope	ration Mo	ode: TX N	lode (Mi	d)			
4874	V	41.58	26.74	14.93	56.51	41.67	74.00	54.00	-17.49	-12.33
7311	V	39.51	25.12	20.88	60.39	46.00	74.00	54.00	-13.61	-8.00
4874	Н	39.48	25.16	14.93	54.41	40.09	74.00	54.00	-19.59	-13.91
7311	Н	39.59	25.13	20.88	60.47	46.01	74.00	54.00	-13.53	-7.99
			Oper	ation Mo	de: TX M	ode (Hig	gh)			
4924	V	38.91	25.01	15.15	54.06	40.16	74.00	54.00	-19.94	-13.84
7386	V	38.55	25.18	21.04	59.59	46.22	74.00	54.00	-14.41	-7.78
4924	Н	41.25	27.74	15.15	56.40	42.89	74.00	54.00	-17.60	-11.11
7386	Н	39.29	25.10	21.04	60.33	46.14	74.00	54.00	-13.67	-7.86
		-	· · · · · · · · · · · · · · · · · · ·							

Note: (1) All Readings are Peak Value and AV.

- (2) Emission Level= Reading Level + Factor
- (3) Factor= Antenna Gain + Cable Loss Amtplifier Gain
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
- (5) Measurement uncertainty: ±3.7dB.
- (6) Horn antenna used for the emission over 1000MHz.

Report No.: NTC1509066F FCC ID: YGB-WDV8000



Test Mode: 802.11n(HT20) Test Date: September 18, 2015

Frequency Range: Above 1GHz Temperature : 24℃
Test Result: PASS Humidity : 50 %
Measured Distance: 3m Test By: Sance

Freq. Ant.Pol (MHz) (H/V)		Reading Level(dBuV)		Factor (dB/m)	Emissio (dBı		Limit 3m (dBuV/m)		Margin (dB)	
(IVII IZ)	(11/7)	PK	AV	(ub/III)	PK	AV	PK	AV	PK	AV
			Oper	ation Mo	de: TX M	lode (Lo	w)			
4824	V	40.90	26.42	14.72	55.62	41.14	74.00	54.00	-18.38	-12.86
7236	V	38.99	24.89	20.74	59.73	45.63	74.00	54.00	-14.27	-8.37
4824	Н	39.23	24.89	14.72	53.95	39.61	74.00	54.00	-20.05	-14.39
7236	Н	37.34	24.92	20.74	58.08	45.66	74.00	54.00	-15.92	-8.34
			Ope	ration Mo	ode: TX N	lode (Mi	d)			
4874	V	38.84	24.77	14.93	53.77	39.70	74.00	54.00	-20.23	-14.30
7311	V	39.02	25.12	20.88	59.90	46.00	74.00	54.00	-14.10	-8.00
4874	Н	41.92	24.58	14.93	56.85	39.51	74.00	54.00	-17.15	-14.49
7311	Н	39.08	25.13	20.88	59.96	46.01	74.00	54.00	-14.04	-7.99
			Oper	ation Mo	de: TX M	ode (Hig	gh)			
4924	V	42.26	24.45	15.15	57.41	39.60	74.00	54.00	-16.59	-14.4
7386	V	39.22	25.22	21.04	60.26	46.26	74.00	54.00	-13.74	-7.74
4924	Н	38.83	24.73	15.15	53.98	39.88	74.00	54.00	-20.02	-14.12
7386	Н	38.99	25.28	21.04	60.03	46.32	74.00	54.00	-13.97	-7.68

Note: (1) All Readings are Peak Value and AV.

- (2) Emission Level= Reading Level + Factor
- (3) Factor= Antenna Gain + Cable Loss Amplifier Gain
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
- (5) Measurement uncertainty: ±3.7dB.
- (6) Horn antenna used for the emission over 1000MHz.

Report No.: NTC1509066F FCC ID: YGB-WDV8000



9. Antenna Application

9.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

9.2 Measurement Results

The antenna is integral antenna and no consideration of replacement, and the best case gain of the antenna is 2dBi. So, the antenna is consider meet the requirement.

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1509066F FCC ID: YGB-WDV8000



10. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Nov. 24, 2014	Nov. 23, 2015
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Nov. 27, 2014	Nov. 26, 2015
Positioning Controller	UC	UC 3000	N/A	0~360°, 1-4m	N/A	N/A
Color Monitor	SUNSPO	SP-140A	N/A	N/A	N/A	N/A
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	32A	N/A	N/A
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	200A	N/A	N/A
DC Power Filter	SAEMC	PF301A-200	110245	200A	N/A	N/A
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Nov. 08, 2014	Nov. 07, 2015
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Nov. 08, 2014	Nov. 07, 2015
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Nov. 08, 2014	Nov. 07, 2015
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	15GHz~26.5GHz	Oct.24, 2014	Oct.23, 2015
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Nov. 06, 2014	Nov. 05, 2015
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Oct.11, 2014	Oct.10, 2015
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Sep. 01, 2015	Aug. 31,2016
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Nov. 04, 2014	Nov. 03, 2015
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Nov. 08, 2014	Nov. 07, 2015