

## TEST REPORT



Applicant	Armour Home Electronics Limited
Address	Stortford Hall Industrial Park, Dunmov Road, Bishops Stortford, Hertfordshire, CM23 5GZ, United Kingdom

Manufacturer or Supplier	Armour Home Electronics Limited
Address	Stortford Hall Industrial Park, Dunmov Road, Bishops Stortford, Hertfordshire, CM23 5GZ, United Kingdom
Product	Q Acoustics M2 Soundbar
Brand Name	Q Acoustics
Model	M2 Soundbar
Additional Model & Model Difference	N/A
Date of tests	Jun. 03, 2016 ~ Jun. 27, 2016, Nov. 16, 2016 ~ Nov. 25, 2016

the tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C, Section 15.247**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	 Date: Dec. 14, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>5</b>
<b>1 SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
<b>2 MEASUREMENT UNCERTAINTY .....</b>	<b>6</b>
<b>3 GENERAL INFORMATION.....</b>	<b>7</b>
3.1 GENERAL DESCRIPTION OF EUT.....	7
3.2 DESCRIPTION OF TEST MODES.....	7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST .....	9
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	11
3.4 DESCRIPTION OF SUPPORT UNITS.....	11
<b>4 TEST TYPES AND RESULTS .....</b>	<b>12</b>
4.1. CONDUCTED EMISSION MEASUREMENT .....	12
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	12
4.1.2 TEST INSTRUMENTS.....	12
4.1.3 TEST PROCEDURES .....	13
4.1.4 DEVIATION FROM TEST STANDARD .....	13
4.1.5 TEST SETUP .....	14
4.1.6 EUT OPERATING CONDITIONS .....	14
4.1.7 TEST RESULTS.....	15
4.2. RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	17
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	17
4.2.2 TEST INSTRUMENTS.....	18
4.2.3 TEST PROCEDURES.....	19
4.2.4 DEVIATION FROM TEST STANDARD.....	19
4.2.5 TEST SETUP .....	20
4.2.6 EUT OPERATING CONDITIONS .....	21
4.2.7 TEST RESULTS.....	22
4.3. NUMBER OF HOPPING FREQUENCY USED.....	22
4.3.1. LIMIT OF HOPPING FREQUENCY USED .....	30
4.3.2. TEST SETUP .....	30
4.3.3. TEST INSTRUMENTS.....	30
4.3.4. TEST PROCEDURES .....	31
4.3.5. DEVIATION FROM TEST STANDARD .....	31
4.3.6. TEST RESULTS.....	31



**Test Report No.: RF161116N002**

4.4. DWELL TIME ON EACH CHANNEL .....	34
4.4.1 LIMIT OF DWELL TIME USED .....	34
4.4.2 TEST SETUP .....	34
4.4.3 TEST INSTRUMENTS .....	34
4.4.4 TEST PROCEDURES.....	34
4.4.5 DEVIATION FROM TEST STANDARD.....	35
4.4.6 TEST RESULTS.....	35
4.5. CHANNEL BANDWIDTH.....	38
4.5.1 LIMITS OF CHANNEL BANDWIDTH.....	38
4.5.2 TEST SETUP .....	38
4.5.3 TEST INSTRUMENTS .....	38
4.5.4 TEST PROCEDURE .....	38
4.5.5 DEVIATION FROM TEST STANDARD.....	38
4.5.6 EUT OPERATING CONDITION .....	38
4.5.7 TEST RESULTS.....	39
4.6. HOPPING CHANNEL SEPARATION .....	43
4.6.1. LIMIT OF HOPPING CHANNEL SEPARATION .....	43
4.6.2. TEST SETUP .....	43
4.6.3. TEST INSTRUMENTS.....	43
4.6.4. TEST PROCEDURES .....	43
4.6.5. DEVIATION FROM TEST STANDARD .....	43
4.6.6. TEST RESULTS.....	44
4.7. MAXIMUM OUTPUT POWER.....	48
4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT.....	48
4.7.2 TEST SETUP .....	48
4.7.3 TEST INSTRUMENTS .....	48
4.7.4 TEST PROCEDURES.....	48
4.7.5 DEVIATION FROM TEST STANDARD.....	48
4.7.6 EUT OPERATING CONDITION.....	48
4.7.7 TEST RESULTS.....	49
4.8. OUT OF BAND EMISSION MEASUREMENT .....	50
4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....	50
4.8.2 TEST INSTRUMENTS .....	50
4.8.3 TEST PROCEDURE .....	50
4.8.4 DEVIATION FROM TEST STANDARD.....	50
4.8.5 EUT OPERATING CONDITION .....	50
4.8.6 TEST RESULTS.....	50



Test Report No.: RF161116N002

5. PHOTOGRAPHS OF THE TEST CONFIGURATION .....	53
6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	54



Test Report No.: RF161116N002

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF160603N045	Original release	Jun. 28, 2016
RF161116N002	Based on the original report RF160603N045 changed the appearance, product name, model no. and press key PCB, update the EUT photo, but it needed to be retested radiated emission(below 1GHz) after engineer evaluated.	Dec. 14, 2016

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)&15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

## 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	3.83dB
	1GHz ~ 18GHz	4.93dB
	18GHz ~ 40GHz	4.80dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Q Acoustics M2 Soundbar
<b>MODEL NO.</b>	M2 Soundbar
<b>FCC ID</b>	YGM-M2
<b>POWER SUPPLY</b>	AC 120V 60Hz
<b>MODULATION TECHNOLOGY</b>	FHSS
<b>MODULATION TYPE</b>	GFSK, 8DPSK, $\pi/4$ DQPSK
<b>OPERATING FREQUENCY</b>	2402MHz~2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>MAX. OUTPUT POWER</b>	2.523mW (Max. Measured)
<b>ANTENNA TYPE</b>	Integral PCB Antenna, 2.12dBi Gain
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	AC Line: Unshielded, Detachable, 1.30m

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 161116N002) for detailed product photo.



### 3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



### 3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

### 3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	Powered By AC 120V 60Hz

Where **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission

**RE≥1G**: Radiated Emission above 1GHz  
**APCM**: Antenna Port Conducted Measurement

#### **RADIATED EMISSION TEST (BELOW 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

#### **RADIATED EMISSION TEST (ABOVE 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

**POWER LINE CONDUCTED EMISSION TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	39	FHSS	GFSK	DH5

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 55%RH	AC 230V 50Hz	Hardy Leng
RE≥1G	25deg. C, 55%RH	AC 230V 50Hz	Hardy Leng
PLC	20deg. C, 56%RH	AC 120V 60Hz	Breeze Jiang
APCM	20deg. C, 55%RH	AC 120V 60Hz	Breeze Jiang



### **3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. Section 15.247**  
**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

### **3.4 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together without other necessary accessories or support units.



## 4 TEST TYPES AND RESULTS

### 4.1. CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101588	Jan. 22,16	Jan. 21,17
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,16	Mar. 03,17
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,16	Apr. 04,17
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 08,16	Jan. 07,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
  2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



#### 4.1.5 TEST SETUP



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.




## 4.1.7 TEST RESULTS

## CONDUCTED WORST-CASE DATA: GFSK CH39

PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.72	35.84	17.13	45.56	26.85	66.00	56.00	-20.44	-29.15
2	0.16567	9.72	39.01	18.55	48.73	28.27	65.17	55.17	-16.44	-26.90
3	0.18825	9.72	36.84	16.99	46.56	26.71	64.11	54.11	-17.55	-27.40
4	0.22864	9.71	31.81	14.54	41.52	24.25	62.50	52.50	-20.97	-28.24
5	0.38400	9.71	25.90	25.83	35.61	35.54	58.19	48.19	-22.58	-12.65
6	10.65975	9.99	25.03	17.72	35.02	27.71	60.00	50.00	-24.98	-22.29


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16800	9.72	38.15	19.84	47.87	29.56	65.06	55.06	-17.19	-25.50
2	0.18825	9.72	35.99	17.13	45.71	26.85	64.11	54.11	-18.40	-27.26
3	0.38400	9.71	26.68	26.62	36.39	36.33	58.19	48.19	-21.80	-11.86
4	1.15125	9.84	18.12	15.94	27.96	25.78	56.00	46.00	-28.04	-20.22
5	10.41225	9.97	23.48	17.36	33.45	27.33	60.00	50.00	-26.55	-22.67
6	12.71625	10.01	25.49	19.13	35.50	29.14	60.00	50.00	-24.50	-20.86

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.







## **4.2. RADIATED EMISSION AND BANDEDGE MEASUREMENT**

### **4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT**

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

<b>FREQUENCIES (MHz)</b>	<b>FIELD STRENGTH (microvolts/meter)</b>	<b>MEASUREMENT DISTANCE (meters)</b>
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 18,16	May 17,17
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 16	Aug. 07, 17
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,16	Mar. 03, 17
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Apr. 25,16	Apr. 24,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,16	Nov. 03,17
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 08,16	Aug. 07,17

**NOTE:**

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and 24 months the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 494399.

#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. Bluetooth duty factor correction is not correct as it is based on 79 channels, worst casde would be with AFH enabled and device using the minimum of 20 channels.Channel hop rate = 800 hops/second (AFH Mode), Adjusted channel hop rate for DH5 mode = 133.33 hops/second, Time per channel hop = 1 / 133.33 hops/second = 7.5 ms, Time to cycle through all channels = 7.5 x 20 channels = 150 ms, Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s), Worst case dwell time = 7.5 ms, Duty cycle connection factor =  $20\log_{10}(7.5\text{ms} / 100\text{ms}) = -22.5 \text{ dB}$ . Average value = peak reading +  $20\log(\text{duty cycle})$ .
- 4.All modes of operation were investigated and the worst-case emissions are reported.
- 5.The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.


#### 4.2.5 TEST SETUP

##### Below 1GHz test setup



**Note:** For the actual test configuration, please refer to the attached file (Test Setup Photo).

##### Above 1GHz test setup



**Note:** For the actual test configuration, please refer to the attached file (Test Setup Photo).



**Test Report No.: RF160603N045**

#### 4.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



**BUREAU  
VERITAS**

Test Report No.: RF160603N045

## 4.2.7 TEST RESULTS

### BELOW 1GHz WORST-CASE DATA:


#### GFSK DH5

<b>CHANNEL</b>	Channel 39	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	107.32	28.84	43.50	-14.66	100	0	46.68	-17.84
2	155.12	29.46	43.50	-14.04	100	0	46.16	-16.70
3	167.77	28.13	43.50	-15.37	100	0	46.11	-17.98
4	242.28	29.16	46.00	-16.84	100	0	45.13	-15.97
5	377.23	30.79	46.00	-15.21	100	0	41.56	-10.77
6	513.59	34.12	46.00	-11.88	100	0	40.43	-6.31

#### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China


Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

<b>CHANNEL</b>	Channel 39	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	31.41	31.49	40.00	-8.51	200	0	42.96	-11.47
2	107.32	30.63	43.50	-12.87	200	0	48.47	-17.84
3	513.59	36.28	46.00	-9.72	200	0	42.59	-6.31
4	593.72	33.75	46.00	-12.25	200	0	38.16	-4.41
5	648.55	35.93	46.00	-10.07	200	0	39.15	-3.22
6	879.10	33.17	46.00	-12.83	200	0	32.79	0.38

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





**BUREAU  
VERITAS**

Test Report No.: RF160603N045

# ABOVE 1GHz DATA

## BT\_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	41.1 PK	74.0	-32.9	1.12 H	16	38.55	2.53
2	2390.00	18.6 AV	54.0	-35.4	1.12 H	16	16.05	2.53
3	*2402.00	91.1 PK			1.12 H	16	88.50	2.56
4	*2402.00	68.6 AV			1.12 H	16	66.00	2.56
5	4804.00	43.2 PK	74.0	-30.8	1.53 H	207	35.49	7.74
6	4804.00	20.7 AV	54.0	-33.3	1.53 H	207	12.99	7.74
7	#7206.00	51.9 PK	71.1	-19.2	1.45 H	162	38.52	13.37
8	#7206.00	29.4 AV	48.6	-19.2	1.45 H	162	16.02	13.37
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	41.3 PK	74.0	-32.7	1.26 V	83	38.75	2.53
2	2390.00	18.8 AV	54.0	-35.2	1.26 V	83	16.25	2.53
3	*2402.00	96.2 PK			1.26 V	83	93.65	2.56
4	*2402.00	73.7 AV			1.26 V	83	71.15	2.56
5	4804.00	44.7 PK	74.0	-29.3	1.76 V	203	36.94	7.74
6	4804.00	22.2 AV	54.0	-31.8	1.76 V	203	14.44	7.74
7	#7206.00	53.8 PK	76.2	-22.4	1.56 V	301	40.39	13.37
8	#7206.00	31.3 AV	53.7	-22.4	1.56 V	301	17.89	13.37

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	91.2 PK			1.32 H	264	88.57	2.66
2	*2441.00	68.7 AV			1.32 H	264	66.07	2.66
3	4882.00	46.7 PK	74.0	-27.3	1.49 H	263	38.86	7.87
4	4882.00	24.2 AV	54.0	-29.8	1.49 H	263	16.36	7.87
5	7323.00	51.8 PK	74.0	-22.2	1.58 H	230	38.17	13.64
6	7323.00	29.3 AV	54.0	-24.7	1.58 H	230	15.67	13.64
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	92.8 PK			1.24 V	208	90.10	2.66
2	*2441.00	70.3 AV			1.24 V	208	67.60	2.66
3	4882.00	48.3 PK	74.0	-25.7	1.36 V	298	40.38	7.87
4	4882.00	25.8 AV	54.0	-28.2	1.36 V	298	17.88	7.87
5	7323.00	52.4 PK	74.0	-21.6	1.96 V	253	38.77	13.64
6	7323.00	29.9 AV	54.0	-24.1	1.96 V	253	16.27	13.64

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



**BUREAU  
VERITAS**

**Test Report No.: RF160603N045**

<b>CHANNEL</b>	TX Channel 78	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	91.9 PK			1.25 H	215	89.13	2.76
2	*2480.00	69.4 AV			1.25 H	215	66.63	2.76
3	2483.50	44.7 PK	74.0	-29.3	1.25 H	215	41.90	2.77
4	2483.50	22.2 AV	54.0	-31.8	1.25 H	215	19.40	2.77
5	4960.00	46.8 PK	74.0	-27.2	1.35 H	11	38.81	7.98
6	4960.00	24.3 AV	54.0	-29.7	1.35 H	11	16.28	7.98
7	7440.00	47.9 PK	74.0	-26.1	1.62 H	108	33.95	13.91
8	7440.00	25.4 AV	54.0	-28.6	1.62 H	108	11.45	13.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	95.6 PK			1.15 V	62	92.83	2.76
2	*2480.00	73.1 AV			1.15 V	62	70.33	2.76
3	2483.50	46.3 PK	74.0	-27.7	1.15 V	62	43.49	2.77
4	2483.50	23.8 AV	54.0	-30.2	1.15 V	62	20.99	2.77
5	4960.00	48.6 PK	74.0	-25.4	1.56 V	231	40.63	7.98
6	4960.00	26.1 AV	54.0	-27.9	1.56 V	231	18.13	7.98
7	7440.00	50.4 PK	74.0	-23.6	1.85 V	259	36.51	13.91
8	7440.00	27.9 AV	54.0	-26.1	1.85 V	259	14.01	13.91

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.

Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



**BUREAU  
VERITAS**

**Test Report No.: RF160603N045**

**BT\_8DPSK**

<b>CHANNEL</b>	TX Channel 0	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	41.6 PK	74.0	-32.4	1.32 H	185	39.04	2.53
2	2390.00	19.1 AV	54.0	-34.9	1.32 H	185	16.54	2.53
3	*2402.00	89.9 PK			1.32 H	185	87.36	2.56
4	*2402.00	67.4 AV			1.32 H	185	64.86	2.56
5	4804.00	45.5 PK	74.0	-28.5	1.69 H	356	37.79	7.74
6	4804.00	23.0 AV	54.0	-31.0	1.69 H	356	15.29	7.74
7	#7206.00	51.9 PK	69.9	-18.0	1.28 H	84	38.51	13.37
8	#7206.00	29.4 AV	47.4	-18.0	1.28 H	84	16.01	13.37
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	40.9 PK	74.0	-33.1	1.15 V	84	38.35	2.53
2	2390.00	18.4 AV	54.0	-35.6	1.15 V	84	15.85	2.53
3	*2402.00	92.3 PK			1.15 V	84	89.71	2.56
4	*2402.00	69.8 AV			1.15 V	84	67.21	2.56
5	4804.00	48.0 PK	74.0	-26.0	1.59 V	261	40.29	7.74
6	4804.00	25.5 AV	54.0	-28.5	1.59 V	261	17.79	7.74
7	#7206.00	50.2 PK	72.3	-22.1	1.02 V	251	36.85	13.37
8	#7206.00	27.7 AV	49.8	-22.1	1.02 V	251	14.35	13.37

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	90.4 PK			1.85 H	203	87.72	2.66
2	*2441.00	67.9 AV			1.85 H	203	65.22	2.66
3	4882.00	48.8 PK	74.0	-25.2	1.35 H	261	40.90	7.87
4	4882.00	26.3 AV	54.0	-27.7	1.35 H	261	18.40	7.87
5	7323.00	49.3 PK	74.0	-24.7	1.49 H	238	35.64	13.64
6	7323.00	26.8 AV	54.0	-27.2	1.49 H	238	13.14	13.64
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	95.9 PK			1.38 V	205	93.22	2.66
2	*2441.00	73.4 AV			1.38 V	205	70.72	2.66
3	4882.00	48.0 PK	74.0	-26.0	1.96 V	201	40.12	7.87
4	4882.00	25.5 AV	54.0	-28.5	1.96 V	201	17.62	7.87
5	7323.00	50.5 PK	74.0	-23.5	1.42 V	201	36.88	13.64
6	7323.00	28.0 AV	54.0	-26.0	1.42 V	201	14.38	13.64

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



**BUREAU  
VERITAS**

**Test Report No.: RF160603N045**

<b>CHANNEL</b>	TX Channel 78	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
<b>NO.</b>	<b>FREQ. (MHz)</b>	<b>EMISSION LEVEL (dBuV/m)</b>	<b>LIMIT (dBuV/m)</b>	<b>MARGIN (dB)</b>	<b>ANTENNA HEIGHT (m)</b>	<b>TABLE ANGLE (Degree)</b>	<b>RAW VALUE (dBuV)</b>	<b>CORRECTION FACTOR (dB/m)</b>
1	*2480.00	98.5 PK			1.26 H	263	95.75	2.76
2	*2480.00	76.0 AV			1.26 H	263	73.25	2.76
3	2483.50	43.1 PK	74.0	-30.9	1.26 H	263	40.33	2.77
4	2483.50	20.6 AV	54.0	-33.4	1.26 H	263	17.83	2.77
5	4960.00	49.8 PK	74.0	-24.2	1.68 H	259	41.77	7.98
6	4960.00	27.3 AV	54.0	-26.7	1.68 H	259	19.27	7.98
7	7440.00	50.3 PK	74.0	-23.7	1.41 H	230	36.39	13.91
8	7440.00	27.8 AV	54.0	-26.2	1.41 H	230	13.89	13.91
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
<b>NO.</b>	<b>FREQ. (MHz)</b>	<b>EMISSION LEVEL (dBuV/m)</b>	<b>LIMIT (dBuV/m)</b>	<b>MARGIN (dB)</b>	<b>ANTENNA HEIGHT (m)</b>	<b>TABLE ANGLE (Degree)</b>	<b>RAW VALUE (dBuV)</b>	<b>CORRECTION FACTOR (dB/m)</b>
1	*2480.00	94.2 PK			1.29 V	310	91.41	2.76
2	*2480.00	71.7 AV			1.29 V	310	68.91	2.76
3	2483.50	47.7 PK	74.0	-26.3	1.29 V	310	44.89	2.77
4	2483.50	25.2 AV	54.0	-28.8	1.29 V	310	22.39	2.77
5	4960.00	48.7 PK	74.0	-25.3	1.82 V	234	40.68	7.98
6	4960.00	26.2 AV	54.0	-27.8	1.82 V	234	18.18	7.98
7	7440.00	51.4 PK	74.0	-22.6	1.42 V	258	37.50	13.91
8	7440.00	28.9 AV	54.0	-25.1	1.42 V	258	15.00	13.91

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* " : Fundamental frequency.


**Bureau Veritas Shenzhen Co., Ltd.**  
**Dongguan Branch**

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

**4.7 NUMBER OF HOPPING FREQUENCY USED****4.2.1. LIMIT OF HOPPING FREQUENCY USED**

At least 15 channels frequencies, and should be equally spaced.

**4.2.2. TEST SETUP****4.2.3. TEST INSTRUMENTS**

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 13, 16	Oct.12, 17
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,16	Sep. 04,17
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 04,16	Nov. 03,17
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Signal Generator	Agilent	N5183A	MY50140980	Nov. 04,16	Nov. 03,17
Agile Signal Generator	Agilent	8645A	Agilent	Aug.08, 16	Aug.07, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Apr. 22, 16	Apr. 21, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug.07, 17

**NOTE:**

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



#### 4.2.4. TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.



#### 4.2.5. DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.6. TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

**GFSK**









BUREAU  
VERITAS

Test Report No.: RF160603N045

## 8DPSK



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China


Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

### 4.3. DWELL TIME ON EACH CHANNEL

#### 4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 4.4.2 TEST SETUP



#### 4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

#### 4.4.4 TEST PROCEDURES

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.



Test Report No.: RF160603N045

#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 TEST RESULTS

##### GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	50	316.00	0.474	149.78	400	PASS
DH3	79	31.6	5	25	158.00	1.750	276.50	400	PASS
DH5	79	31.6	5	17	107.44	2.992	321.46	400	PASS

##### 8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	50	316.00	0.456	144.10	400	PASS
DH3	79	31.6	5	26	164.32	1.770	290.85	400	PASS
DH5	79	31.6	5	16	101.12	3.040	307.40	400	PASS

**NOTE:** Test plots of the transmitting time slot are shown on next 2 page.



BUREAU  
VERITAS

Test Report No.: RF160603N045

## GFSK





BUREAU  
VERITAS

Test Report No.: RF160603N045

## 8DPSK






## **4.4. CHANNEL BANDWIDTH**

### **4.5.1 LIMITS OF CHANNEL BANDWIDTH**

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### **4.5.2 TEST SETUP**



### **4.5.3 TEST INSTRUMENTS**

Refer to section 4.3.3 to get information of above instrument.

### **4.5.4 TEST PROCEDURE**

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

### **4.5.5 DEVIATION FROM TEST STANDARD**

No deviation.

### **4.5.6 EUT OPERATING CONDITION**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 4.5.7 TEST RESULTS

### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.938
39	2441	0.941
78	2480	0.942

### CH 0







BUREAU  
VERITAS

Test Report No.: RF160603N045

CH 39



CH 78








BUREAU  
VERITAS

Test Report No.: RF160603N045

## 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.27
39	2441	1.27
78	2480	1.27

## CH 0







BUREAU  
VERITAS

Test Report No.: RF160603N045

## CH 39



## CH 78






## 4.5. HOPPING CHANNEL SEPARATION

### 4.5.1. LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

### 4.5.2. TEST SETUP



### 4.5.3. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.5.4. TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

### 4.5.5. DEVIATION FROM TEST STANDARD

No deviation.



BUREAU  
VERITAS

Test Report No.: RF160603N045


#### 4.5.6. TEST RESULTS

##### GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.938	0.625	PASS
39	2441	1.01	0.941	0.627	PASS
78	2480	1.01	0.942	0.628	PASS

**NOTE:** The minimum limit is two-third 20dB bandwidth.

##### CH 0







BUREAU  
VERITAS

Test Report No.: RF160603N045

## CH 39



## CH 78






8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.27	0.847	PASS
39	2441	1.01	1.27	0.847	PASS
78	2480	1.00	1.27	0.847	PASS

**NOTE:** The minimum limit is two-third 20dB bandwidth.

CH 0







BUREAU  
VERITAS

Test Report No.: RF160603N045

## CH 39



## CH 78






## **4.6. MAXIMUM OUTPUT POWER**

### **4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT**

The Maximum Output Power Measurement is 125mW.

### **4.7.2 TEST SETUP**



### **4.7.3 TEST INSTRUMENTS**

Refer to section 4.3.3 to get information of above instrument.

### **4.7.4 TEST PROCEDURES**

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

### **4.7.5 DEVIATION FROM TEST STANDARD**

No deviation.

### **4.7.6 EUT OPERATING CONDITION**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.





## 4.7.7 TEST RESULTS

**MAXIMUM PEAK OUTPUT POWER****GFSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	<b>4.02</b>	<b>2.523</b>	125	PASS
39	2441	3.82	2.410	125	PASS
78	2480	3.39	2.183	125	PASS

**8DPSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	2.72	1.871	125	PASS
39	2441	2.28	1.690	125	PASS
78	2480	1.54	1.426	125	PASS

**AVERAGE OUTPUT POWER(FOR REFERENCE)****GFSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	<b>2.55</b>	<b>1.799</b>
39	2441	2.34	1.714
78	2480	1.91	1.552

**8DPSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.53	1.130
39	2441	-0.01	0.998
78	2480	-0.86	0.820



## **4.7. OUT OF BAND EMISSION MEASUREMENT**

### **4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT**

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

### **4.8.2 TEST INSTRUMENTS**

Refer to section 4.3.3 to get information of above instrument.

### **4.8.3 TEST PROCEDURE**

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

### **4.8.4 DEVIATION FROM TEST STANDARD**

No deviation.

### **4.8.5 EUT OPERATING CONDITION**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### **4.8.6 TEST RESULTS**

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




BUREAU  
VERITAS


Test Report No.: RF160603N045

GFSK

### Low Channel



### High Channel






BUREAU  
VERITAS

Test Report No.: RF160603N045

## 8DPSK





Test Report No.: RF160603N045

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF160603N045

## 6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---