

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>			<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--		<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>			<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--		<b>1</b>	<b>30</b>

**Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$**

Where  $P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

		Channel	Channel Frequency (MHz)	Output Peak power (dBm)	Output Peak power (mW)	Antenna Gain (dBi)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
5745 ~ 5825 GHz	802.11a	Low	5745.00	22.83	191.94	0	0.038185	1
		Mid	5780.00	22.89	194.54	0	0.038703	1
		High	5825.00	22.95	197.25	0	0.039242	1
	802.11n (20 MHz)	Low	5745.00	22.92	195.85	0	0.038963	1
		Mid	5780.00	23.00	199.44	0	0.039677	1
		High	5825.00	22.97	198.08	0	0.039407	1
	802.11n (40 MHz)	Low	5755.00	22.96	197.79	0	0.039349	1
		High	5795.00	22.92	195.78	0	0.038949	1
5150 ~ 5250 GHz	802.11a	Low	5180.00	15.42	34.80	0	0.006923	1
		Mid	5200.00	15.39	34.60	0	0.006883	1
		High	5240.00	15.40	34.68	0	0.006899	1
	802.11n (20 MHz)	Low	5180.00	15.06	32.03	0	0.006372	1
		Mid	5200.00	15.02	31.77	0	0.006320	1
		High	5240.00	15.05	31.96	0	0.006358	1
	802.11n (40 MHz)	Low	5190.00	15.32	34.04	0	0.006772	1
		High	5230.00	15.29	33.77	0	0.006718	1

*The MPE is calculated as 0.039677 mW / cm<sup>2</sup> < limit 1 mW / cm<sup>2</sup>. So, RF exposure limit warning or SAR test are not required.*