

# FCC RF Test Report

APPLICANT : CT Asia  
EQUIPMENT : Smartphone  
BRAND NAME : BLU  
MODEL NAME : Speed 4.7 LTE  
FCC ID : YHLBLUSPEED47  
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)  
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)


The product was received on Jan. 17, 2015 and testing was completed on Feb. 26, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Supervisor



---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,  
Nanshan District, Shenzhen, Guangdong, P. R. China**



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification subjective to this standard.....	6
1.5 Modification of EUT .....	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	7
1.7 Testing Location .....	7
1.8 Applicable Standards .....	8
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>9</b>
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System .....	11
2.3 Support Unit used in test configuration .....	11
2.4 Measurement Results Explanation Example .....	12
<b>3 TEST RESULT .....</b>	<b>13</b>
3.1 Conducted Output Power Measurement.....	13
3.2 Peak-to-Average Ratio .....	15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	25
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	31
3.5 Band Edge Measurement.....	55
3.6 Conducted Spurious Emission Measurement.....	63
3.7 Field Strength of Spurious Radiation Measurement .....	71
3.8 Frequency Stability Measurement.....	80
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>86</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>87</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG511702A	Rev. 01	Initial issue of report	Mar. 24, 2015

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 23.30 dB at 2510.000 MHz
3.8	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22 Within Authorized Band	PASS	-
	§2.1055 §24.235 §27.54				



# 1 General Description

## 1.1 Applicant

**CT Asia**

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

## 1.2 Manufacturer

**Tinno Mobile Technology Corp.**

4/F, H-3 Building, OCT Eastern industrial Park, No.1 XiangShan East Road, Nan Shan District, Shenzhen, P.R.China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Smartphone
<b>Brand Name</b>	BLU
<b>Model Name</b>	Speed 4.7 LTE
<b>FCC ID</b>	YHLBLUSPEED47
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(Downlink Only)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0+ EDR/ Bluetooth v4.0 LE
<b>HW Version</b>	V1.0
<b>SW Version</b>	S8515_BLU_V01
<b>EUT Stage</b>	Pre-Production

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 32.68 dBm GSM1900 : 29.84 dBm WCDMA Band V : 23.19 dBm WCDMA Band IV : 23.05 dBm WCDMA Band II : 23.40 dBm
<b>Antenna Type</b>	PIFA Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Downlink Only)

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.85	0.0048 ppm	244KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.21	0.0132 ppm	255KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.10	0.0311 ppm	4M14F9W
Part 24	GSM1900 GSM	GMSK	1.17	0.0027 ppm	243KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.46	0.0037 ppm	249KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.23	0.0037 ppm	4M15F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.18	0.0046 ppm	4M16F9W

## 1.7 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	1F & 2F,Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH01-SZ	OTA02-SZ

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH01-SZ	831040



## **1.8 Applicable Standards**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

### **Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
<b>GSM 850</b>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE class 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE class 8 Link</li> </ul>
<b>GSM 1900</b>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE class 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE class 8 Link</li> </ul>
<b>WCDMA Band V</b>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
<b>WCDMA Band II</b>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
<b>WCDMA Band IV</b>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>

**Note:** The maximum power levels are chosen to test as the worst case configuration as follows:

GSM mode for GMSK modulation,

EDGE multi-slot class 8 mode for 8PSK modulation,

RMC 12.2Kbps mode for WCDMA band V and WCDMA band IV,


RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

**Conducted Power Measurement Results:**

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.54	32.65	32.68	29.84	29.82	29.76
GPRS class 8	32.46	32.58	32.61	29.76	29.74	29.72
GPRS class 10	29.40	29.52	29.70	26.91	26.81	26.65
GPRS class 11	27.47	27.56	27.74	25.04	24.90	24.75
GPRS class 12	26.23	26.35	26.50	23.82	23.67	23.49
EGPRS class 8	26.81	26.56	26.37	24.93	25.41	25.38
EGPRS class 10	23.83	23.58	23.36	22.08	22.31	22.19
EGPRS class 11	21.78	21.53	21.32	20.21	20.45	20.24
EGPRS class 12	20.45	20.20	19.97	18.87	19.06	18.89

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.09	23.16	23.18	23.29	23.32	23.39	22.88	22.96	23.04
RMC 12.2K	23.10	23.17	23.19	23.30	23.34	23.40	22.90	22.97	23.05
HSDPA Subtest-1	22.91	22.99	23.06	22.90	22.90	22.88	22.48	22.70	22.81
HSDPA Subtest-2	22.91	22.97	23.03	22.83	22.85	22.80	22.45	22.67	22.74
HSDPA Subtest-3	22.44	22.51	22.55	22.40	22.41	22.37	22.01	22.19	22.29
HSDPA Subtest-4	22.43	22.51	22.57	22.37	22.40	22.36	22.02	22.18	22.28
HSUPA Subtest-1	20.35	20.46	20.51	20.26	20.30	20.26	20.10	20.06	20.12
HSUPA Subtest-2	20.85	20.92	20.96	20.64	20.65	20.64	20.38	20.48	20.56
HSUPA Subtest-3	21.78	21.87	21.86	21.62	21.63	21.53	21.24	21.46	21.53
HSUPA Subtest-4	20.70	20.35	20.45	20.20	20.19	20.61	20.13	19.98	20.03
HSUPA Subtest-5	22.90	23.00	23.10	22.90	22.90	22.90	21.90	22.80	22.80

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW	3303D	N/A	N/A	Unshielded, 1.8 m



## 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### 3.1.4 Test Setup



### 3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.54	32.65	32.68	26.81	26.56	26.37	23.10	23.17	23.19

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.84	29.82	29.76	24.93	25.41	25.38	23.30	23.34	23.40

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	22.90	22.97	23.05

**Note:** maximum burst average power for GSM, and maximum average power for WCDMA.

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GSM/EGPRS operating modes:
  - a. Set EUT in maximum power output.
  - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
  - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
  - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
  - a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
  - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak-to-Average Ratio



PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.25	0.25	0.25	3.06	2.86	2.81	2.76	2.72	2.72

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	2.88	2.88	2.84




### 3.2.6 Test Result (Plots) of Peak-to-Average Ratio

<b>Band :</b>	GSM 1900	<b>Test Mode :</b>	GSM Link (GMSK)
---------------	----------	--------------------	-----------------

**Peak-to-Average Ratio on Channel 512 (1850.2 MHz)**

**Peak-to-Average Ratio on Channel 661 (1880.0 MHz)**





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 10.FEB.2015 09:24:03




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

## Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)



Date: 10.FEB.2015 10:14:45


## Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)



Date: 10.FEB.2015 10:15:17



Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)




Date: 10.FEB.2015 10:15:36




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 9.FEB.2015 17:37:07


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 9.FEB.2015 17:37:35



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 9.FEB.2015 17:37:54



### **3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement**

#### **3.3.1 Description of the ERP/EIRP Measurement**

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band).

#### **3.3.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

#### **3.3.3 Test Procedures**

1. The testing follows FCC KDB 971168 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
3. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;  
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
5. The table was rotated 360 degrees to determine the position of the highest radiated power.
6. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
7. Taking the record of maximum ERP/EIRP.
8. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
9. The conducted power at the terminal of the dipole antenna is measured.
10. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
11.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

$P_s$  (dBm) : Input power to substitution antenna.

$G_s$  (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

$AF$  (dB/m) : Receive antenna factor

$R_t$  : The highest received signal in spectrum analyzer for EUT.

$R_s$  : The highest received signal in spectrum analyzer for substitution antenna.

### 3.3.4 Test Setup



### 3.3.5 Test Result of ERP

<b>GSM850 (GSM) Radiated Power ERP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-17.74	-48.12	0.00	-1.08	29.30	0.85
836.40	-18.46	-48.28	0.00	-0.93	28.89	0.77
848.80	-19.54	-48.35	0.00	-0.76	28.05	0.64
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-27.93	-47.97	0.00	-1.08	18.96	0.08
836.40	-28.05	-48.01	0.00	-0.93	19.03	0.08
848.80	-27.81	-48.05	0.00	-0.76	19.48	0.09

<b>GSM850 (EDGE class 8) Radiated Power ERP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.84	-48.12	0.00	-1.08	23.20	0.21
836.40	-24.30	-48.28	0.00	-0.93	23.05	0.20
848.80	-25.39	-48.35	0.00	-0.76	22.20	0.17
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-33.96	-47.97	0.00	-1.08	12.93	0.02
836.40	-33.87	-48.01	0.00	-0.93	13.21	0.02
848.80	-33.73	-48.05	0.00	-0.76	13.56	0.02



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-27.10	-48.12	0.00	-1.08	19.94	0.10
836.40	-27.76	-48.28	0.00	-0.93	19.59	0.09
846.60	-28.48	-48.35	0.00	-0.76	19.11	0.08
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-36.83	-47.97	0.00	-1.08	10.06	0.01
836.40	-37.26	-48.01	0.00	-0.93	9.82	0.01
846.60	-37.07	-48.05	0.00	-0.76	10.22	0.01

**3.3.6 Test Result of EIRP**

<b>GSM1900 (GSM) Radiated Power EIRP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-24.65	-51.88	0.00	1.96	29.19	0.83
1880.00	-25.05	-52.99	0.00	2.00	29.94	0.99
1909.80	-25.57	-54.28	0.00	1.98	30.69	1.17
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.23	-52.13	0.00	1.96	28.86	0.77
1880.00	-25.27	-53.17	0.00	2.00	29.90	0.98
1909.80	-25.68	-54.13	0.00	1.98	30.43	1.10

<b>GSM1900 (EDGE class 8) Radiated Power EIRP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.37	-51.88	0.00	1.96	23.47	0.22
1880.00	-29.76	-52.99	0.00	2.00	25.23	0.33
1909.80	-29.59	-54.28	0.00	1.98	26.67	0.46
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.70	-52.13	0.00	1.96	23.39	0.22
1880.00	-30.16	-53.17	0.00	2.00	25.01	0.32
1909.80	-29.78	-54.13	0.00	1.98	26.33	0.43



WCDMA Band IV (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-31.38	-51.88	0.00	1.96	22.46	0.18
1732.60	-32.86	-52.99	0.00	2.00	22.13	0.16
1752.60	-34.08	-54.28	0.00	1.98	22.18	0.17
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-34.38	-52.13	0.00	1.96	19.71	0.09
1732.60	-35.48	-53.17	0.00	2.00	19.69	0.09
1752.60	-36.12	-54.13	0.00	1.98	19.99	0.10

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.31	-51.88	0.00	1.96	22.53	0.18
1880.00	-31.83	-52.99	0.00	2.00	23.16	0.21
1907.60	-32.62	-54.28	0.00	1.98	23.64	0.23
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.78	-52.13	0.00	1.96	22.31	0.17
1880.00	-32.34	-53.17	0.00	2.00	22.83	0.19
1907.60	-32.93	-54.13	0.00	1.98	23.18	0.21

### 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3\*RBW, peak detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3\*RBW, peak detector, trace maximum hold.

#### 3.4.4 Test Setup



**3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth**

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	242.00	244.00	241.00	251.00	252.00	255.00
26dB BW (kHz)	301.00	287.00	304.00	301.00	318.00	302.00

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	241.00	238.00	243.00	249.00	248.00	248.00
26dB BW (kHz)	300.00	300.00	300.00	309.00	310.00	306.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.14	4.13	4.13
26dB BW (MHz)	4.70	4.70	4.71

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.16	4.15	4.13
26dB BW (MHz)	4.74	4.71	4.71






PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.14	4.15	4.14
26dB BW (MHz)	4.71	4.72	4.71



## 3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GSM Link (GMSK)
--------	---------	-------------	-----------------

## 99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 9.FEB.2015 16:50:54


## 26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 9.FEB.2015 16:43:50




### 99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 9.FEB.2015 16:51:29


### 26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 9.FEB.2015 16:45:47




### 99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 9.FEB.2015 16:52:59

### 26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 9.FEB.2015 16:46:56




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 9.FEB.2015 17:04:35


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 9.FEB.2015 17:01:35




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 9.FEB.2015 17:06:01


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 9.FEB.2015 17:02:52




### 99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 9.FEB.2015 17:06:37

### 26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 9.FEB.2015 17:03:48




Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

## 99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date : 9.FEB.2015 15:48:43

## 26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date : 9.FEB.2015 15:41:28






99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 9.FEB.2015 15:49:18


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 9.FEB.2015 15:42:06




### 99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 9.FEB.2015 15:49:53

### 26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 9.FEB.2015 15:42:54




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

### 99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 9.FEB.2015 16:16:58


### 26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 9.FEB.2015 16:14:23




### 99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 9.FEB.2015 16:17:39


### 26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 9.FEB.2015 16:15:04




### 99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 9.FEB.2015 16:18:15

### 26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 9.FEB.2015 16:16:03




Band : WCDMA Band V Test Mode : RMC 12.2Kbps Link (QPSK)

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 10.FEB.2015 10:21:39


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 10.FEB.2015 10:16:50




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 10.FEB.2015 10:22:39


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 10.FEB.2015 10:17:48




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 10.FEB.2015 10:23:32

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 10.FEB.2015 10:18:27






Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 10.FEB.2015 10:08:54


26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 10.FEB.2015 10:06:26




### 99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 10.FEB.2015 10:09:32


### 26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 10.FEB.2015 10:07:10




### 99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 10.FEB.2015 10:10:11

### 26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)




Date: 10.FEB.2015 10:07:51




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 9.FEB.2015 17:27:07


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 10.FEB.2015 10:03:02




### 99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 9.FEB.2015 17:28:00


### 26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 10.FEB.2015 10:03:36




### 99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 9.FEB.2015 17:28:39

### 26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 10.FEB.2015 10:04:17

### 3.5 Band Edge Measurement

#### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

#### 3.5.4 Test Setup






## 3.5.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Test Mode :	GSM Link (GMSK)
--------	--------	-------------	-----------------

## Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 9.FEB.2015 16:40:19

## Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 9.FEB.2015 16:42:58






Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

## Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 9.FEB.2015 16:35:15

## Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 9.FEB.2015 16:30:33




Band :	GSM1900	Test Mode :	GSM Link (GMSK)
--------	---------	-------------	-----------------

## Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 9.FEB.2015 15:58:11

## Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 9.FEB.2015 15:56:00




Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

## Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 9.FEB.2015 16:03:21

## Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 9.FEB.2015 16:06:07




Band : WCDMA Band V Test Mode : RMC 12.2Kbps Link (QPSK)

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Date: 9.FEB.2015 17:48:06

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 9.FEB.2015 17:52:24




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

## Lower Band Edge Plot on Channel 1312 (1712.4 MHz)



Date: 9.FEB.2015 17:55:47

## Higher Band Edge Plot on Channel 1513 (1752.6 MHz)




Date: 9.FEB.2015 17:59:17




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 9.FEB.2015 17:44:44

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 9.FEB.2015 17:41:09

## 3.6 Conducted Spurious Emission Measurement

### 3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

### 3.6.4 Test Setup






## 3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 9.FEB.2015 16:58:31





Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

## Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 9.FEB.2015 17:07:45



Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 9.FEB.2015 15:51:06



Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 9.FEB.2015 16:19:28



Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 10.FEB.2015 10:24:51



Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1732.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 18GHz




Date: 10.FEB.2015 10:13:08



Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date: 9.FEB.2015 17:30:20

## 3.7 Field Strength of Spurious Radiation Measurement

### 3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12.  $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

### 3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





**3.7.5 Test Result of Field Strength of Spurious Radiated**

Band :	GSM850	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Kear Huang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
1672	-38.72	-13	-25.72	-55.38	-45.40	0.57	9.40	H	Pass
2510	-36.30	-13	-23.30	-60.31	-44.00	0.75	10.60	H	Pass
3346	-48.18	-13	-35.18	-72.55	-57.76	0.87	12.60	H	Pass

Band :	GSM850					Temperature :	23~25°C		
Test Mode :	GSM Link (GMSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
1672	-44.60	-13	-31.60	-61.25	-51.28	0.57	9.40	V	Pass
2510	-41.54	-13	-28.54	-66.93	-49.24	0.75	10.60	V	Pass
3346	-43.64	-13	-30.64	-72.47	-53.22	0.87	12.60	V	Pass



Band :	GSM850					Temperature :	23~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
1672	-42.71	-13	-29.71	-59.00	-49.39	0.57	9.40	H	Pass
2510	-44.00	-13	-31.00	-66.46	-51.70	0.75	10.60	H	Pass
3346	-48.05	-13	-35.05	-72.42	-57.63	0.87	12.60	H	Pass

Band :	GSM850					Temperature :	23~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
1672	-48.21	-13	-35.21	-64.43	-54.89	0.57	9.40	V	Pass
2510	-47.30	-13	-34.30	-70.66	-55.00	0.75	10.60	V	Pass
3346	-43.59	-13	-30.59	-72.43	-53.17	0.87	12.60	V	Pass



Band :	GSM1900	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Kear Huang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
( MHz )	( dBm )	( dBm )	( dB )	(dBm)	( dBm )	( dB )	(dBi)	(H/V)	
3760	-44.76	-13	-31.76	-73.40	-56.49	0.87	12.60	H	Pass
5640	-42.07	-13	-29.07	-72.39	-54.10	1.07	13.10	H	Pass
7520	-44.93	-13	-31.93	-76.59	-54.36	1.87	11.30	H	Pass

Band :	GSM1900	Temperature :	23~25°C						
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%						
Test Engineer :	Kear Huang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
3760	-45.82	-13	-32.82	-74.27	-57.55	0.87	12.6	V	Pass
5640	-42.13	-13	-29.13	-73.26	-54.16	1.07	13.1	V	Pass
7520	-43.64	-13	-30.64	-75.53	-53.07	1.87	11.3	V	Pass



Band :	GSM1900	Temperature :	23~25℃						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	48~52%						
Test Engineer :	Kear Huang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
3760	-45.23	-13	-32.23	-73.87	-56.96	0.87	12.60	H	Pass
5640	-42.79	-13	-29.79	-73.64	-54.82	1.07	13.10	H	Pass
7520	-44.66	-13	-31.66	-76.32	-54.09	1.87	11.30	H	Pass

Band :	GSM1900					Temperature :	23~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
( MHz )	( dBm )	( dBm )	( dB )	(dBm)	( dBm )	( dB )	(dBi)	(H/V)	
3760	-44.98	-13	-31.98	-73.43	-56.71	0.87	12.6	V	Pass
5640	-42.29	-13	-29.29	-73.42	-54.32	1.07	13.1	V	Pass
7520	-43.71	-13	-30.71	-75.6	-53.14	1.87	11.3	V	Pass



Band :	WCDMA Band V					Temperature :	23~25°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
( MHz )	( dBm )	( dBm )	( dB )	( dBm )	( dBm )	( dB )	( dBi )	(H/V)	
1672	-49.41	-13	-36.41	-64.43	-56.09	0.57	9.40	H	Pass
2510	-47.78	-13	-34.78	-69.22	-55.48	0.75	10.60	H	Pass
3346	-48.31	-13	-35.31	-72.68	-57.89	0.87	12.60	H	Pass

Band :	WCDMA Band V					Temperature :	23~25°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading ( dBm )	Power ( dBm )	loss ( dB )	Gain ( dBi )	(H/V)	
1672	-50.94	-13	-37.94	-66.65	-57.62	0.57	9.40	V	Pass
2510	-47.40	-13	-34.40	-70.73	-55.10	0.75	10.60	V	Pass
3346	-40.70	-13	-27.70	-70.70	-50.28	0.87	12.60	V	Pass



Band :	WCDMA Band IV	Temperature :	23~25℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Kear Huang	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
3465	-44.42	-13	-31.42	-71.05	-56.21	0.81	12.60	H	Pass
5197.5	-44.03	-13	-31.03	-73.55	-55.78	0.95	12.70	H	Pass
6930	-45.02	-13	-32.02	-75.42	-55.59	1.13	11.70	H	Pass

Band :	WCDMA Band IV	Temperature :	23~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%						
Test Engineer :	Kear Huang	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit	Reading	Power	loss	Gain		
			( dB )	(dBm)	( dBm )	( dB )	(dBi)	(H/V)	
3465	-49.18	-13	-36.18	-71.46	-60.97	0.81	12.6	V	Pass
5197.5	-49.47	-13	-36.47	-74	-61.22	0.95	12.7	V	Pass
6930	-44.09	-13	-31.09	-75.9	-54.66	1.13	11.7	V	Pass



Band :	WCDMA Band II					Temperature :	23~25°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
3760	-45.49	-13	-32.49	-74.13	-57.22	0.87	12.60	H	Pass
5640	-43.71	-13	-30.71	-74.03	-55.74	1.07	13.10	H	Pass
7520	-44.11	-13	-31.11	-75.77	-53.54	1.87	11.30	H	Pass

Band :	WCDMA Band II					Temperature :	23~25°C		
Test Mode :	RMC 12.2Kbps Link (QPSK)					Relative Humidity :	48~52%		
Test Engineer :	Kear Huang					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
( MHz )	( dBm )	( dBm )	Limit ( dB )	Reading (dBm)	Power ( dBm )	loss ( dB )	Gain (dBi)	(H/V)	
3760	-45.88	-13	-32.88	-74.33	-57.61	0.87	12.6	V	Pass
5640	-42.22	-13	-29.22	-73.35	-54.25	1.07	13.1	V	Pass
7520	-44.28	-13	-31.28	-76.17	-53.71	1.87	11.3	V	Pass

### 3.8 Frequency Stability Measurement

#### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.8.3 Test Procedures for Temperature Variation


1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.



### 3.8.5 Test Setup



### 3.8.6 Test Result of Temperature Variation

<b>Band :</b>	GSM 850	<b>Channel :</b>	189
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.4 MHz

Temperature (°C)	GSM		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
50	-15	0.0048	-19	0.0084	PASS
40	-14	0.0036	-21	0.0108	
30	-12	0.0012	-15	0.0036	
20(Ref.)	-11	0.0000	-12	0.0000	
10	-9	0.0024	-14	0.0024	
0	-12	0.0012	-17	0.0060	
-10	-13	0.0024	-22	0.0120	
-20	-13	0.0024	-18	0.0072	
-30	-14	0.0036	-23	0.0132	

<b>Band :</b>	GSM 1900	<b>Channel :</b>	661
<b>Limit (ppm) :</b>	within authorized band	<b>Frequency :</b>	1880.0 MHz

Temperature (°C)	GSM		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
50	22	0.0021	24	0.0037	PASS
40	21	0.0016	21	0.0021	
30	20	0.0011	19	0.0011	
20(Ref.)	18	0.0000	17	0.0000	
10	17	0.0005	18	0.0005	
0	19	0.0005	19	0.0011	
-10	20	0.0011	21	0.0021	
-20	21	0.0016	20	0.0016	
-30	23	0.0027	22	0.0027	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

<b>Band :</b>	WCDMA Band V	<b>Channel :</b>	4182
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
50	-14	0.0048	PASS
40	-11	0.0012	
30	-12	0.0024	
20(Ref.)	-10	0.0000	
10	-11	0.0012	
0	12	0.0263	
-10	13	0.0275	
-20	15	0.0299	
-30	16	0.0311	

<b>Band :</b>	WCDMA Band IV	<b>Channel :</b>	1413
<b>Limit (ppm) :</b>	within authorized band	<b>Frequency :</b>	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
50	-18	0.0029	PASS
40	-19	0.0035	
30	-15	0.0012	
20(Ref.)	-13	0.0000	
10	-16	0.0017	
0	-14	0.0006	
-10	-17	0.0023	
-20	-21	0.0046	
-30	-20	0.0040	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



<b>Band :</b>	WCDMA Band II	<b>Channel :</b>	9400
<b>Limit (ppm) :</b>	within authorized band	<b>Frequency :</b>	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
50	-24	0.0032	PASS
40	-25	0.0037	
30	-21	0.0016	
20(Ref.)	-18	0.0000	
10	-17	0.0005	
0	-19	0.0005	
-10	-21	0.0016	
-20	-20	0.0011	
-30	-23	0.0027	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

### 3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	4.2	-12	0.0012	2.5	PASS
		3.7	-11	0.0000		
		BEP	-12	0.0012		
	EDGE class 8	4.2	-14	0.0024		
		3.7	-12	0.0000		
		BEP	-13	0.0012		
GSM 1900 CH661	GSM	4.2	19	0.0005	(Note 3.)	
		3.7	18	0.0000		
		BEP	20	0.0011		
	EDGE class 8	4.2	19	0.0011		
		3.7	17	0.0000		
		BEP	19	0.0011		
WCDMA Band V CH4182	RMC 12.2Kbps	4.2	-11	0.0012	2.5	
		3.7	-10	0.0000		
		BEP	-12	0.0024		
WCDMA Band IV CH1413	RMC 12.2Kbps	4.2	-15	0.0012	(Note 3.)	
		3.7	-13	0.0000		
		BEP	-14	0.0006		
WCDMA Band II CH9400	RMC 12.2Kbps	4.2	-19	0.0005	(Note 3.)	
		3.7	-18	0.0000		
		BEP	-19	0.0005		

**Note:**

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Feb. 09, 2015~ Feb. 10, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	May 08, 2014	Feb. 09, 2015~ Feb. 10, 2015	May 07, 2015	Conducted (TH01-SZ)
Thermal Chamber	Hongzhangroup	LP-150U	HD20120425	-40℃~150℃	Jan. 28, 2015	Feb. 09, 2015~ Feb. 10, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
EMI TEST Receiver	R&S	ESC17	100768	9kHz~3GHz	May 04, 2014	Feb. 06, 2015	May 03, 2015	Radiation (03CH01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2014	Feb. 06, 2015	May 25, 2015	Radiation (03CH01-SZ)
Bilog Antenna	TESEQ	CBL 6112D	37877	30MHz~2GHz	Oct. 15, 2014	Feb. 06, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 15, 2014	Feb. 06, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
Double Ridged Horn Antenna	COM-POWER	AH-840	101073	18GHz~40GHz	Jun. 09, 2014	Feb. 06, 2015	Jun. 08, 2015	Radiation (03CH01-SZ)
Amplifier	com-power	PA-103A	161069	1~1000MHz	May 04, 2014	Feb. 06, 2015	May 03, 2015	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 08, 2014	Feb. 06, 2015	May 07, 2015	Radiation (03CH01-SZ)
AC Source	Chroma	61601ACSO URCE	61601000247 0	100Vac~240Vac	NCR	Feb. 06, 2015	NCR	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0~360 degree	NCR	Feb. 06, 2015	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m~4 m	NCR	Feb. 06, 2015	NCR	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Jul. 17, 2014	Feb. 26, 2015	Jul. 16, 2015	ERP/EIRP (OTA02-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000MHz	N/A	Feb. 26, 2015	N/A	ERP/EIRP (OTA02-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	N/A	Feb. 26, 2015	N/A	ERP/EIRP (OTA02-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	N/A	Feb. 26, 2015	N/A	ERP/EIRP (OTA02-SZ)



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.9dB
--	-------