




# RF TEST REPORT



Report No.: 16071342-FCC-R1

Supersede Report No.: N/A

Applicant	BLU Products, Inc.	
Product Name	Smartphone	
Model No.	LIFE ONE X2 MINI	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; FCC Part 27:2015; ANSI/TIA-603-D: 2010	
Test Date	November 26 to December 12, 2016	
Issue Date	December 13, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16071342-FCC-R1
Page	3 of 98

---

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	10
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	11
6.1 RF EXPOSURE (SAR).....	11
6.2 RF OUTPUT POWER .....	12
6.3 PEAK-AVERAGE RATIO.....	25
6.4 OCCUPIED BANDWIDTH.....	30
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	45
6.6 SPURIOUS RADIATED EMISSIONS .....	61
6.7 BAND EDGE.....	68
6.8 FREQUENCY STABILITY .....	82
ANNEX A. TEST INSTRUMENT.....	87
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	89
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	94
ANNEX C.II. EUT OPERATING CONKITIONS .....	96
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....	97
ANNEX E. DECLARATION OF SIMILARITY .....	98

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071342-FCC-R1	NONE	Original	December 13, 2016

## 2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

## 4. Equipment under Test (EUT) Information

Description of EUT:	Smartphone
Main Model:	LIFE ONE X2 MINI
Serial Model:	N/A
Date EUT received:	November 25, 2016
Test Date(s):	November 26 to December 12, 2016
Equipment Category :	PCE
Antenna Gain:	GSM850: -0.5dBi PCS1900: 0.5dBi UMTS-FDD Band V: -0.5dBi UMTS-FDD Band IV: 0.5dBi UMTS-FDD Band II: 0.5dBi LTE Band II: 0.5dBi LTE Band IV: 0.5dBi LTE Band VII: 0.8dBi LTE Band XII: -0.5dBi LTE Band XVII: -0.5dBi WIFI: 1.6dBi Bluetooth/BLE: 1.6dBi GPS: 0.5dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK, 8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK GPS: BPSK

RF Operating Frequency (ies):

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz  
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz  
 UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz  
 UMTS-FDD Band IV TX: 1712.4 ~ 1752.6 MHz;  
     RX : 2112.4 ~ 2152.6 MHz  
 UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;  
     RX: 1932.4 ~ 1987.6 MHz  
 LTE Band II TX: 1850.7 ~ 1909.3 MHz; RX : 1930.7 ~ 1989.3 MHz  
 LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7 ~ 2154.3 MHz  
 LTE Band VII TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz  
 LTE Band XII TX: 699.7 ~ 715.3 MHz; RX : 729.7 ~ 745.3 MHz  
 LTE Band XVII TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz  
 WIFI: 802.11b/g/n(20M): 2412-2462 MHz  
 WIFI: 802.11n(40M): 2422-2452 MHz  
 Bluetooth& BLE: 2402-2480 MHz  
 GPS: 1575.42 MHz

Maximum Conducted  
 AV Power to Antenna:

GSM Voice: GSM850: 32.45 dBm  
     PCS1900: 30.13 dBm  
 GPRS: GSM850: 32.40 dBm  
     PCS1900: 29.92 dBm  
 EGPRS(MCS1): GSM850: 32.36 dBm  
     PCS1900: 29.86 dBm  
 EGPRS(MCS5): GSM850: 24.83 dBm  
     PCS1900: 23.52 dBm  
 RMC: UMTS-FDD Band V: 22.88 dBm  
     UMTS-FDD Band II: 21.79 dBm  
     UMTS-FDD Band IV: 21.34 dBm  
 HSDPA: UMTS-FDD Band V: 21.88 dBm  
     UMTS-FDD Band II: 20.48 dBm  
     UMTS-FDD Band IV: 20.41 dBm  
 HSUPA: UMTS-FDD Band V: 21.76 dBm  
     UMTS-FDD Band II: 20.45 dBm  
     UMTS-FDD Band IV: 20.43 dBm

Test Report	16071342-FCC-R1
Page	8 of 98

	GSM Voce:GSM850: 29.72 dBm / ERP
	PCS1900:30.62 dBm / EIRP
	GPRS:GSM850: 29.85 dBm / ERP
	PCS1900: 30.34 dBm / EIRP
	EGPRS(MCS5):GSM850: 22.29 dBm / ERP
	PCS1900: 23.95 dBm / EIRP
ERP/EIRP:	RMC:UMTS-FDD Band V: 20.15dBm / ERP
	UMTS-FDD Band II: 22.27 dBm / EIRP
	UMTS-FDD Band IV: 21.73 dBm / EIRP
	HSUPA:UMTS-FDD Band V: 19.05 dBm / ERP
	UMTS-FDD Band II: 20.87 dBm / EIRP
	UMTS-FDD Band IV: 20.81 dBm / EIRP
	HSDPA:UMTS-FDD Band V: 19.16 dBm / ERP
	UMTS-FDD Band II: 20.94 dBm / EIRP
	UMTS-FDD Band IV: 20.76 dBm / EIRP
	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band IV: 202CH
	UMTS-FDD Band II: 277CH
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH
	GPS:1CH
Port:	USB Port, Earphone Port
	Adapter:
	Model: US-BM-1500
	Input: AC 100-240V,50/60Hz, 0.25A
	Output: DC5V,1550mA
Input Power:	Battery:
	Model: C705904300P
	Spec: 3.84V,3000mAh,11.52Wh
	Charging Limited Voltage: 4.4V



Test Report	16071342-FCC-R1
Page	9 of 98

---

Trade Name : BLU

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: YHLBLULOX2MN

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

## 6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

### 6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;  
Please refer to RF Exposure Evaluation Report: 16071342-FCC-H.

## 6.2 RF Output Power

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>
§27.50 (c)	c)	EIRP: 30dBm	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station                      EUT</p>
------------	---

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> <li>- The transmitter output port was connected to base station.</li> <li>- Set EUT at maximum power through base station.</li> <li>- Select lowest, middle, and highest channels for each band and different test mode.</li> </ul> <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> <li>- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>- The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>- The frequency range up to tenth harmonic of the fundamental</li> </ul>
----------------	---

Test Report	16071342-FCC-R1
Page	13 of 98

	<p>frequency was investigated.</p> <ul style="list-style-type: none"> <li>- Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.</li> <li>- Spurious emissions in dB = <math>10 \log (\text{TX power in Watts}/0.001)</math> – the absolute level</li> <li>- Spurious attenuation limit in dB = <math>43 + 10 \text{ Log}_{10} (\text{power out in Watts})</math>.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A  
 Test Plot ☐ Yes (See below) ☒ N/A

## Conducted Power

### GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	<b>32.45</b>	32.41	32.40	32±1	29.98	<b>30.13</b>	30.11	30±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	<b>32.40</b>	32.35	32.36	32±1	29.81	<b>29.92</b>	29.85	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	30.10	30.12	30.15	30±1	28.47	28.63	28.71	28±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	25.74	25.74	25.84	25±1	24.76	24.61	24.69	24±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	<b>32.36</b>	32.34	32.35	32±1	29.80	<b>29.86</b>	29.52	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	30.21	30.13	30.18	30±1	28.44	28.48	28.81	28±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	25.74	25.73	25.84	25±1	24.42	24.33	24.51	24±1
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	<b>24.83</b>	24.72	24.63	24±1	23.43	<b>23.52</b>	23.49	23±1
EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	23.53	23.59	23.64	23±1	23.31	23.38	23.33	23±1
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	21.30	21.37	21.46	21.3±1	21.6	21.88	21.84	21.3±1

Test Report	16071342-FCC-R1
Page	15 of 98

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

## UMTS Mode:

### UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	<b>22.88</b>	22±1
	4175	835	22.71	22±1
	4233	846.6	22.84	22±1
HSDPA Subtest1	4132	826.4	<b>21.88</b>	21.3±1
	4175	835	21.76	21.3±1
	4233	846.6	21.65	21.3±1
HSDPA Subtest2	4132	826.4	21.69	21.3±1
	4175	835	21.62	21.3±1
	4233	846.6	21.77	21.3±1
HSDPA Subtest3	4132	826.4	21.76	21.3±1
	4175	835	21.78	21.3±1
	4233	846.6	21.82	21.3±1
HSDPA Subtest4	4132	826.4	21.83	21.3±1
	4175	835	21.80	21.3±1
	4233	846.6	21.79	21.3±1
HSUPA Subtest1	4132	826.4	21.71	21.3±1
	4175	835	21.70	21.3±1
	4233	846.6	<b>21.76</b>	21.3±1
HSUPA Subtest2	4132	826.4	21.65	21.3±1
	4175	835	21.66	21.3±1
	4233	846.6	21.69	21.3±1
HSUPA Subtest3	4132	826.4	21.63	21.3±1
	4175	835	21.62	21.3±1
	4233	846.6	21.66	21.3±1
HSUPA Subtest4	4132	826.4	21.64	21.3±1
	4175	835	21.69	21.3±1
	4233	846.6	21.67	21.3±1
HSUPA Subtest5	4132	826.4	21.59	21.3±1
	4175	835	21.58	21.3±1
	4233	846.6	21.53	21.3±1



## UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	<b>21.79</b>	21.3±1
	9400	1880	21.41	21.3±1
	9538	1907.6	21.75	21.3±1
HSDPA Subtest1	9262	1852.4	20.36	21.3±1
	9400	1880	20.39	21.3±1
	9538	1907.6	20.37	21.3±1
HSDPA Subtest2	9262	1852.4	20.40	21.3±1
	9400	1880	20.40	21.3±1
	9538	1907.6	20.44	21.3±1
HSDPA Subtest3	9262	1852.4	20.46	21.3±1
	9400	1880	20.41	21.3±1
	9538	1907.6	20.43	21.3±1
HSDPA Subtest4	9262	1852.4	20.47	21.3±1
	9400	1880	<b>20.48</b>	21.3±1
	9538	1907.6	20.44	21.3±1
HSUPA Subtest1	9262	1852.4	20.33	21.3±1
	9400	1880	20.31	21.3±1
	9538	1907.6	20.33	21.3±1
HSUPA Subtest2	9262	1852.4	20.31	21.3±1
	9400	1880	20.33	21.3±1
	9538	1907.6	20.36	21.3±1
HSUPA Subtest3	9262	1852.4	20.39	21.3±1
	9400	1880	20.38	21.3±1
	9538	1907.6	20.41	21.3±1
HSUPA Subtest4	9262	1852.4	<b>20.45</b>	21.3±1
	9400	1880	20.36	21.3±1
	9538	1907.6	20.38	21.3±1
HSUPA Subtest5	9262	1852.4	20.37	21.3±1
	9400	1880	20.31	21.3±1
	9538	1907.6	20.33	21.3±1

## UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	1313	1712.6	<b>21.34</b>	21.3±1
	1413	1732.6	21.10	21.3±1
	1512	1752.4	21.20	21.3±1
HSDPA Subtest1	1313	1712.6	20.33	21.3±1
	1413	1732.6	20.36	21.3±1
	1512	1752.4	20.31	21.3±1
HSDPA Subtest2	1313	1712.6	20.39	21.3±1
	1413	1732.6	<b>20.41</b>	21.3±1
	1512	1752.4	20.33	21.3±1
HSDPA Subtest3	1313	1712.6	20.36	21.3±1
	1413	1732.6	20.33	21.3±1
	1512	1752.4	20.34	21.3±1
HSDPA Subtest4	1313	1712.6	20.33	21.3±1
	1413	1732.6	20.39	21.3±1
	1512	1752.4	20.35	21.3±1
HSUPA Subtest1	1313	1712.6	20.36	21.3±1
	1413	1732.6	20.34	21.3±1
	1512	1752.4	20.37	21.3±1
HSUPA Subtest2	1313	1712.6	20.38	21.3±1
	1413	1732.6	20.38	21.3±1
	1512	1752.4	20.33	21.3±1
HSUPA Subtest3	1313	1712.6	20.31	21.3±1
	1413	1732.6	20.36	21.3±1
	1512	1752.4	20.41	21.3±1
HSUPA Subtest4	1313	1712.6	20.42	21.3±1
	1413	1732.6	<b>20.43</b>	21.3±1
	1512	1752.4	20.31	21.3±1
HSUPA Subtest5	1313	1712.6	20.33	21.3±1
	1413	1732.6	20.32	21.3±1
	1512	1752.4	20.36	21.3±1

## ERP & EIRP

### GSM Voice

#### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	23.45	V	6.8	0.53	29.72	38.45
824.2	21.67	H	6.8	0.53	27.94	38.45
836.6	23.41	V	6.8	0.53	29.68	38.45
836.6	21.63	H	6.8	0.53	27.90	38.45
848.8	23.4	V	6.9	0.53	<b>29.77</b>	38.45
848.8	21.62	H	6.9	0.53	27.99	38.45

#### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.41	V	7.88	0.85	30.44	33
1850.2	21.63	H	7.88	0.85	28.66	33
1880	23.58	V	7.88	0.85	30.61	33
1880	21.75	H	7.88	0.85	28.78	33
1909.8	23.61	V	7.86	0.85	<b>30.62</b>	33
1909.8	21.78	H	7.86	0.85	28.79	33

## GPRS:

### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	23.49	V	6.8	0.53	29.76	38.45
824.2	21.71	H	6.8	0.53	27.98	38.45
836.6	23.42	V	6.8	0.53	29.69	38.45
836.6	21.64	H	6.8	0.53	27.91	38.45
848.8	23.48	V	6.9	0.53	<b>29.85</b>	38.45
848.8	21.72	H	6.9	0.53	28.09	38.45

### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.26	V	7.88	0.85	30.29	33
1850.2	21.47	H	7.88	0.85	28.50	33
1880	23.31	V	7.88	0.85	<b>30.34</b>	33
1880	21.52	H	7.88	0.85	28.55	33
1909.8	23.33	V	7.86	0.85	30.34	33
1909.8	21.55	H	7.86	0.85	28.56	33

## EGPRS (MCS5):

### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	15.74	V	6.8	0.53	22.01	38.45
824.2	13.92	H	6.8	0.53	20.19	38.45
836.6	15.83	V	6.8	0.53	22.10	38.45
836.6	14.01	H	6.8	0.53	20.28	38.45
848.8	15.92	V	6.9	0.53	<b>22.29</b>	38.45
848.8	14.1	H	6.9	0.53	20.47	38.45

### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	16.84	V	7.88	0.85	23.87	33
1850.2	15.03	H	7.88	0.85	22.06	33
1880	16.92	V	7.88	0.85	<b>23.95</b>	33
1880	15.11	H	7.88	0.85	22.14	33
1909.8	16.93	V	7.86	0.85	23.94	33
1909.8	15.12	H	7.86	0.85	22.13	33

## RMC

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.75	V	6.8	0.53	20.02	38.45
826.4	12.84	H	6.8	0.53	19.11	38.45
835	13.68	V	6.8	0.53	19.95	38.45
835	12.76	H	6.8	0.53	19.03	38.45
846.6	13.78	V	6.9	0.53	<b>20.15</b>	38.45
846.6	12.86	H	6.9	0.53	19.23	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	15.24	V	7.88	0.85	<b>22.27</b>	33
1852.4	14.39	H	7.88	0.85	21.42	33
1880	14.86	V	7.88	0.85	21.89	33
1880	13.98	H	7.88	0.85	21.01	33
1907.6	15.26	V	7.86	0.85	22.27	33
1907.6	14.41	H	7.86	0.85	21.42	33

### EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	14.79	V	7.76	0.82	<b>21.73</b>	30
1712.4	13.84	H	7.76	0.82	20.78	30
1740	14.68	V	7.76	0.82	21.62	30
1740	13.75	H	7.76	0.82	20.69	30
1752.6	14.74	V	7.74	0.82	21.66	30
1752.6	13.81	H	7.74	0.82	20.73	30

## HSDPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.74	V	6.8	0.53	19.01	38.45
826.4	11.83	H	6.8	0.53	18.10	38.45
835	12.67	V	6.8	0.53	18.94	38.45
835	11.75	H	6.8	0.53	18.02	38.45
846.6	12.79	V	6.9	0.53	<b>19.16</b>	38.45
846.6	11.87	H	6.9	0.53	18.24	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.87	V	7.88	0.85	20.90	33
1852.4	12.99	H	7.88	0.85	20.02	33
1880	13.91	V	7.88	0.85	<b>20.94</b>	33
1880	13.03	H	7.88	0.85	20.06	33
1907.6	13.85	V	7.86	0.85	20.86	33
1907.6	12.97	H	7.86	0.85	19.98	33

### EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	13.82	V	7.76	0.82	<b>20.76</b>	30
1712.4	12.95	H	7.76	0.82	19.89	30
1740	13.79	V	7.76	0.82	20.73	30
1740	12.91	H	7.76	0.82	19.85	30
1752.6	13.84	V	7.74	0.82	20.76	30
1752.6	12.97	H	7.74	0.82	19.89	30

## HSUPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.63	V	6.8	0.53	18.90	38.45
826.4	11.72	H	6.8	0.53	17.99	38.45
835	12.58	V	6.8	0.53	18.85	38.45
835	11.66	H	6.8	0.53	17.93	38.45
846.6	12.68	V	6.9	0.53	<b>19.05</b>	38.45
846.6	11.76	H	6.9	0.53	18.13	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.75	V	7.88	0.85	20.78	33
1852.4	12.86	H	7.88	0.85	19.89	33
1880	13.84	V	7.88	0.85	<b>20.87</b>	33
1880	12.97	H	7.88	0.85	20.00	33
1907.6	13.83	V	7.86	0.85	20.84	33
1907.6	12.96	H	7.86	0.85	19.97	33

### EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	13.85	V	7.76	0.82	20.79	30
1712.4	12.98	H	7.76	0.82	19.92	30
1740	13.87	V	7.76	0.82	<b>20.81</b>	30
1740	13.02	H	7.76	0.82	19.96	30
1752.6	13.78	V	7.74	0.82	20.70	30
1752.6	12.9	H	7.74	0.82	19.82	30




### 6.3 Peak-Average Ratio

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	<input checked="" type="checkbox"/>

Test Setup	 <p>The diagram illustrates the test setup. On the left is a green box labeled 'Base Station'. A cable connects its output to the input of a green box labeled 'Spectrum Analyzer'. Another cable connects the output of the Spectrum Analyzer to the input of a blue box labeled 'EUT' (Equipment Under Test).</p>
------------	--

Test Procedure	<p><b>According with KDB 971168 v02r02</b></p> <p><b>5.7.2 Alternate procedure for PAPR</b></p> <p><b>5.1.2 Peak power measurements with a peak power meter</b></p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p><b>5.2.3 Average power measurement with average power meter</b></p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle <math>\geq 98\%</math>) and at all times the EUT is transmitting at its maximum output</p>
----------------	--

Test Report	16071342-FCC-R1
Page	26 of 98

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle &lt; 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than <math>\pm 2</math> percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to <math>10\log(1/\text{duty cycle})</math></p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A  
 Test Plot ☐ Yes (See below) ☒ N/A

#### GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.97	29.98	1.99
1880	32.16	30.13	2.03
1909.8	32.15	30.11	2.04

#### GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.85	29.81	2.04
1880	31.95	29.92	2.03
1909.8	31.86	29.85	2.01

#### EGPRS (MSC5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	25.54	23.43	2.11
1880	25.53	23.49	2.04
1909.8	25.59	23.52	2.07

#### RMC : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	25.16	21.79	3.37
1880	25.22	21.41	3.81
1907.6	25.33	21.75	3.58

#### UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	24.66	21.34	3.32
1740	24.59	21.1	3.49
1752.6	24.51	21.2	3.31

#### HSUPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.39	20.33	3.06
1880	23.35	20.31	3.04
1907.6	23.36	20.33	3.03

#### UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	22.46	20.36	2.10
1740	23.19	20.34	2.85
1752.6	22.39	20.37	2.02

#### HSDPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.39	20.36	3.03
1880	20.43	20.39	0.04
1907.6	23.41	20.37	3.04

#### UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	22.35	20.33	2.02
1740	23.23	20.36	2.87
1752.6	23.39	20.31	3.08

## 6.4 Occupied Bandwidth

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup	<p>Base Station      Spectrum Analyzer      EUT</p>		
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data    ☒ Yes      ☐ N/A

Test Plot    ☒ Yes (See below)      ☐ N/A

## GSM Voice:

### Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	247.5878	318.720
190	836.6	248.8446	317.055
251	848.8	244.5993	316.704

### PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	244.3853	315.905
661	1880.0	243.0819	321.228
810	1909.8	245.0886	322.912

## GPRS:

### Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	247.9935	311.647
190	836.6	245.2941	307.727
251	848.8	244.6523	313.986

### PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.0737	318.527
661	1880.0	241.8542	319.326
810	1909.8	246.7276	321.207

## EGPRS (MCS 5):

### Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	244.9588	320.883
190	836.6	244.8559	317.770
251	848.8	244.6590	324.229

### PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	243.5482	318.998
661	1880.0	241.2289	316.173
810	1909.8	246.7132	321.403



**RMC:**

**UMTS-FDD Band V (Part 22H)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1260	4.725
4175	835.0	4.1328	4.747
4233	846.6	4.1247	4.746

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1424	4.724
9400	1880.0	4.1198	4.755
9538	1907.6	4.1368	4.717

**UMTS-FDD Band IV (Part 27)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1326	4.738
1413	1733	4.1197	4.722
1512	1752	4.1372	4.740

## HSUPA:

### UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1169	4.736
4175	835.0	4.1325	4.760
4233	846.6	4.1201	4.734

### UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1199	4.716
9400	1880.0	4.1307	4.739
9538	1907.6	4.1399	4.720

### UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1292	4.748
1413	1733	4.1313	4.746
1512	1752	4.1354	4.745

## HSDPA:

### UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1312	4.726
4175	835.0	4.1404	4.724
4233	846.6	4.1249	4.718

### UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1314	4.705
9400	1880.0	4.1327	4.730
9538	1907.6	4.1292	4.720

### UMTS-FDD Band IV (Part 27)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1330	4.741
1413	1733	4.1312	4.741
1512	1752	4.1375	4.739

## Test Plots


### GMS Voice:




## GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz





PCS 1900 BW - High CH 1910MHz


## EGPRS:




RMC:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.6 MHz




Band II BW - Low CH 1853MHz




Band II BW - Mid CH 1880MHz


Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz





Band IV BW - High CH 1752MHz





## HSUPA:



## Band V BW - Low CH 826.6 MHz




## Band V BW - High CH 846.4 MHz




## Band II BW - Mid CH 1880 MHz


## Band II BW - High CH 1907 MHz



Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz



Band IV BW - High CH 1752MHz

Agilent 17:30:53 Dec 1, 2016 R T

Ref 35 dBm  
#Peak  
Log  
10  
dB/  
Offset  
4  
dB

Atten 45 dB

Center 826.6 MHz  
Res BW 100 kHz

#VBW 300 kHz

Span 10 MHz  
Sweep 4 ms (401 pts)

Occupied Bandwidth  
4.1312 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 7.766 kHz  
x dB Bandwidth 4.726 MHz

Agilent 17:32:18 Dec 1, 2016 R T

Ref 35 dBm  
#Peak  
Log  
10  
dB/  
Offset  
4  
dB

Atten 45 dB

Center 835 MHz  
Res BW 100 kHz

#VBW 300 kHz

Span 10 MHz  
Sweep 4 ms (401 pts)

Occupied Bandwidth  
4.1404 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -7.457 kHz  
Occupied Bandwidth 4.724 MHz

Agilent 17:33:47 Dec 1, 2016 R T

Ref 35 dBm  
#Peak  
Log  
10  
dB/  
Offset  
4  
dB

Atten 45 dB

Center 846.6 MHz  
Res BW 100 kHz

#VBW 300 kHz

Span 10 MHz  
Sweep 4 ms (401 pts)

Occupied Bandwidth  
4.1249 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -203.872 kHz  
Occupied Bandwidth 4.718 MHz

Agilent 17:38:40 Dec 1, 2016 R T

Ref 35 dBm  
#Peak  
Log  
10  
dB/  
Offset  
4.5  
dB

Atten 45 dB

Center 1.853 GHz  
Res BW 100 kHz

#VBW 300 kHz

Span 10 MHz  
Sweep 4 ms (401 pts)

Occupied Bandwidth  
4.1314 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -394.936 kHz  
Occupied Bandwidth 4.705 MHz

Agilent 17:41:48 Dec 1, 2016 R T

Ref 35 dBm  
#Peak  
Log  
10  
dB/  
Offset  
4.5  
dB

Atten 45 dB

Center 1.88 GHz  
Res BW 100 kHz

#VBW 300 kHz

Span 10 MHz  
Sweep 4 ms (401 pts)

Occupied Bandwidth  
4.1327 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -4.181 kHz  
x dB Bandwidth 4.730 MHz

Agilent 17:45:23 Dec 1, 2016 R T

Ref 35 dBm  
#Peak  
Log  
10  
dB/  
Offset  
4.5  
dB

Atten 45 dB

Center 1.907 GHz  
Res BW 100 kHz

#VBW 300 kHz

Span 10 MHz  
Sweep 4 ms (401 pts)

Occupied Bandwidth  
4.1292 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -114.461 kHz  
x dB Bandwidth 4.720 MHz

Agilent 17:45:23 Dec 1, 2016 R T

Ref 35 dBm  
#Peak  
Log  
10  
dB/  
Offset  
4.5  
dB

Atten 45 dB

Center 1.907 GHz  
Res BW 100 kHz


#VBW 300 kHz

Span 10 MHz  
Sweep 4 ms (401 pts)


Occupied Bandwidth  
4.1292 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB


Transmit Freq Error -114.461 kHz  
x dB Bandwidth 4.720 MHz



Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz



Band IV BW - High CH 1752MHz

## 6.5 Spurious Emissions at Antenna Terminals

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

### Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup	<p>Base Station      Spectrum Analyzer      EUT</p>		
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured.</li> <li>- Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data    ☒ Yes      ☐ N/A  
 Test Plot    ☒ Yes (See below)      ☐ N/A


## Test Plots

### GSM Voice:


### Cellular Band (Part 22H) result




## PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1



PCS 1900 - High Channel-2


## GPRS:

### Cellular Band (Part 22H) result






## PCS Band (Part24E) result




## EGPRS (MCS 5):

### Cellular Band (Part 22H) result




## PCS Band (Part24E) result




## RMC


### UMTS-FDD Band V (Part 22H)




## UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

## UMTS-FDD Band IV (Part 27)




HSUPA:

UMTS-FDD Band V (Part 22H)




## UMTS-FDD Band II (Part 24E)






## UMTS-FDD Band IV (Part 27)




## HSDPA:


### UMTS-FDD Band V (Part 22H)



## UMTS-FDD Band II (Part 24E)



## UMTS-FDD Band IV (Part 27)




## 6.6 Spurious Radiated Emissions

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> <li>The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.</li> </ol> <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---

Test Report	16071342-FCC-R1
Page	62 of 98

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

## Cellular Band (Part 22H) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.67	V	7.95	0.78	-36.5	-13	-23.50
1648.4	-44.13	H	7.95	0.78	-36.96	-13	-23.96
329.7	-52.87	V	6.4	0.26	-46.73	-13	-33.73
604.5	-52.94	H	6.8	0.37	-46.51	-13	-33.51

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.69	V	7.95	0.78	-36.52	-13	-23.52
1673.2	-44.02	H	7.95	0.78	-36.85	-13	-23.85
329.8	-52.67	V	6.4	0.26	-46.53	-13	-33.53
605.3	-52.94	H	6.8	0.37	-46.51	-13	-33.51

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.84	V	7.95	0.78	-36.67	-13	-23.67
1697.6	-44.13	H	7.95	0.78	-36.96	-13	-23.96
327.4	-52.78	V	6.4	0.26	-46.64	-13	-33.64
606.9	-52.68	H	6.8	0.37	-46.25	-13	-33.25

#### Note:

1, The testing has been conformed to  $10 \times 848.8 \text{ MHz} = 8,488 \text{ GHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## PCS Band (Part24E) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.76	V	10.25	2.73	-41.24	-13	-28.24
3700.4	-49.23	H	10.25	2.73	-41.71	-13	-28.71
326.5	-53.34	V	6.4	0.26	-47.2	-13	-34.2
601.8	-53.86	H	6.8	0.37	-47.43	-13	-34.43

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.71	V	10.25	2.73	-41.19	-13	-28.19
3760	-49.43	H	10.25	2.73	-41.91	-13	-28.91
328.1	-53.27	V	6.4	0.26	-47.13	-13	-34.13
605.3	-53.76	H	6.8	0.37	-47.33	-13	-34.33

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.67	V	10.36	2.73	-41.04	-13	-28.04
3819.6	-49.52	H	10.36	2.73	-41.89	-13	-28.89
325.7	-53.47	V	6.4	0.26	-47.33	-13	-34.33
603.5	-52.03	H	6.8	0.37	-45.6	-13	-32.6

#### Note:

1, The testing has been conformed to  $10 \times 1909.8 \text{ MHz} = 19,098 \text{ GHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.



## UMTS-FDD Band V (Part 22H)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.83	V	7.95	0.78	-39.66	-13	-26.66
1652.8	-45.81	H	7.95	0.78	-38.64	-13	-25.64
326.4	-52.67	V	6.4	0.26	-46.53	-13	-33.53
604.7	-53.29	H	6.8	0.37	-46.86	-13	-33.86

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-46.59	V	7.95	0.78	-39.42	-13	-26.42
1670	-45.73	H	7.95	0.78	-38.56	-13	-25.56
329.1	-52.46	V	6.4	0.26	-46.32	-13	-33.32
606.7	-52.87	H	6.8	0.37	-46.44	-13	-33.44

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-46.87	V	7.95	0.78	-39.7	-13	-26.7
1693.2	-45.69	H	7.95	0.78	-38.52	-13	-25.52
330.5	-52.73	V	6.4	0.26	-46.59	-13	-33.59
604.3	-53.01	H	6.8	0.37	-46.58	-13	-33.58

#### Note:

1, The testing has been conformed to  $10 \times 846.6 \text{ MHz} = 8,466 \text{ GHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## UMTS-FDD Band II (Part 24E)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-49.56	V	10.25	2.73	-42.04	-13	-29.04
3704.8	-49.97	H	10.25	2.73	-42.45	-13	-29.45
331.2	-53.57	V	6.4	0.26	-47.43	-13	-34.43
606.7	-53.68	H	6.8	0.37	-47.25	-13	-34.25

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.35	V	10.25	2.73	-41.83	-13	-28.83
3760	-49.75	H	10.25	2.73	-42.23	-13	-29.23
328.6	-53.68	V	6.4	0.26	-47.54	-13	-34.54
603.1	-53.49	H	6.8	0.37	-47.06	-13	-34.06

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-49.57	V	10.36	2.73	-41.94	-13	-28.94
3815.2	-48.86	H	10.36	2.73	-41.23	-13	-28.23
328.4	-53.46	V	6.4	0.26	-47.32	-13	-34.32
607.9	-53.94	H	6.8	0.37	-47.51	-13	-34.51

#### Note:

1, The testing has been conformed to  $10 \times 1907.6 \text{ MHz} = 19,076 \text{ GHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

## UMTS-FDD Band IV (Part 27)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-46.23	V	10.07	2.52	-38.68	-13	-25.68
3424.8	-48.55	H	10.07	2.52	-41	-13	-28
326.8	-57.32	V	6.4	0.26	-51.18	-13	-38.18
735.9	-52.67	H	7.1	0.42	-45.99	-13	-32.99

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-46.38	V	10.09	2.52	-38.81	-13	-25.81
3480	-46.29	H	10.09	2.52	-38.72	-13	-25.72
324.1	-57.24	V	6.4	0.26	-51.1	-13	-38.1
735.8	-53.43	H	7.1	0.42	-46.75	-13	-33.75

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-46.29	V	10.09	2.52	-38.72	-13	-25.72
3505.2	-45.73	H	10.09	2.52	-38.16	-13	-25.16
323.8	-57.81	V	6.4	0.26	-51.67	-13	-38.67
736.4	-52.35	H	7.1	0.42	-45.67	-13	-32.67

#### Note:

1, The testing has been conformed to  $10 \times 1752.6 \text{ MHz} = 17.526 \text{ GHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases.

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## 6.7 Band Edge

Temperature	25°C
Relative Humidity	54%
Atmospheric Pressure	1002mbar
Test date :	December 02, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup	 <p>The diagram illustrates the test setup. A Base Station (green box) and a Spectrum Analyzer (green box) are connected to a power divider (black box). The power divider is then connected to the EUT (blue box). The Base Station and Spectrum Analyzer are both connected to the power divider, which then splits the signal to the EUT.</p>		
Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9950	-17.93	-13
849.0200	-17.22	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9950	-15.77	-13
1910.0025	-14.73	-13

**GPRS:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-15.62	-13
849.0050	-18.35	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.53	-13
1910.0025	-14.49	-13

### EGPRS (MCS5):

#### Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-17.34	-13
849.0200	-17.76	-13

#### PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.92	-13
1910.0200	-15.23	-13

### RCM:

#### UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-22.22	-13
849.025	-23.92	-13

#### UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-22.40	-13
1910.025	-22.00	-13

#### UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-23.00	-13
1755.025	-24.24	-13

## HSUPA:

### UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-22.12	-13
849.025	-22.75	-13

### UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-24.18	-13
1910.025	-22.31	-13

### UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-21.96	-13
1755.025	-24.35	-13

## HSDPA:

### UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-21.90	-13
849.025	-24.36	-13

### UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-23.07	-13
1910.025	-22.89	-13


**UMTS-FDD Band IV (Part 27)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-21.12	-13
1755.025	-24.44	-13




## GSM Voice:

### Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.19/3)=4.0+0.3=4.3dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.17/3)=4.0+0.2=4.2dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.16/3)=4.5+0.2=4.7dB




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.23/3)=4.5+0.3=4.8dB


## GPRS:

### Test Plots





## EGPRS (MCS5):

### Test Plots




**RMC:**





UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log  
(47.38/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.40/30)=4.5+2.0=6.5 dB

## HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.36/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.34/30)=4.0+2.0=6.0 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
(47.16/30)=4.5+2.0=6.5 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log  
(47.20/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log  
(47.48/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log  
(47.45/30)=4.5+2.0=6.5 dB

## HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.26/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(47.18/30)=4.0+2.0=6.0 dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log  
(47.05/30)=4.5+2.0=6.5 dB



UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log  
(47.20/30)=4.5+2.0=6.5 dB





UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
(47.41/30)=4.5+2.0=6.5 dB




UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.5) + 10log  
(47.39/30)=4.5+2.0=6.5 dB

## 6.8 Frequency Stability

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1001mbar
Test date :	December 01, 2016
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	<input checked="" type="checkbox"/>
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup	 <p>The diagram illustrates the test setup. On the left, a green rectangular box represents the 'Base Station'. A horizontal line connects a small circle on the right side of the Base Station to another small circle on the left side of a blue rectangular box inside a dashed-line rectangle. This dashed rectangle is labeled 'Thermal Chamber' at the bottom.</p>																																		

Test Report	16071342-FCC-R1
Page	83 of 98

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ( $\pm 2.5\text{ppm}$ ) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0227	2.5
0		20	0.0239	2.5
10		14	0.0167	2.5
20		16	0.0191	2.5
30		17	0.0203	2.5
40		12	0.0143	2.5
50		11	0.0131	2.5
55		19	0.0227	2.5
25	4.2	20	0.0239	2.5
	3.5	17	0.0203	2.5

**PCS Band (Part 24E) result**

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0080	2.5
0		19	0.0101	2.5
10		14	0.0074	2.5
20		17	0.0090	2.5
30		16	0.0085	2.5
40		15	0.0080	2.5
50		18	0.0096	2.5
55		14	0.0074	2.5
25	4.2	13	0.0069	2.5
	3.5	17	0.0090	2.5

RMC:

**UMTS-FDD Band V (Part 22H)**

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0228	2.5
0		15	0.0180	2.5
10		17	0.0204	2.5
20		16	0.0192	2.5
30		20	0.0240	2.5
40		16	0.0192	2.5
50		19	0.0228	2.5
55		17	0.0204	2.5
25	4.2	13	0.0156	2.5
	3.5	17	0.0204	2.5

**UMTS-FDD Band II (Part 24E)**

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0080	2.5
0		17	0.0090	2.5
10		16	0.0085	2.5
20		18	0.0096	2.5
30		19	0.0101	2.5
40		14	0.0074	2.5
50		16	0.0085	2.5
55		17	0.0090	2.5
25	4.2	13	0.0069	2.5
	3.5	17	0.0090	2.5

### UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1733$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0192	2.5
0		19	0.0228	2.5
10		15	0.0180	2.5
20		16	0.0192	2.5
30		17	0.0204	2.5
40		15	0.0180	2.5
50		13	0.0156	2.5
55		20	0.0240	2.5
25	4.2	19	0.0228	2.5
	3.5	20	0.0240	2.5

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>RF Conducted Test</b>					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/15/2016	09/14/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/08/2016	10/07/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/09/2016	03/08/2017	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>


Test Report	16071342-FCC-R1
Page	88 of 98


Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------




## Annex B. EUT And Test Setup Photographs

### Annex B.i. Photograph: EUT External Photo







EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View




**Annex B.ii. Photograph: EUT Internal Photo**



Cover Off - Top View




Battery - Front View



Battery - Rear View



Mainboard with Shielding - Front View



Mainboard without Shielding - Front View



Mainboard with Shielding - Rear View






Mainboard without Shielding - Rear View




LCD - Front View



LCD - Rear View



GSM/PCS/UMTS-FDD Antenna View




LTE - Antenna View




WIFI/BT/BLE/GPS - Antenna View

**Annex B.iii. Photograph: Test Setup Photo**



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above  
1GHz

## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK

#### Block Configuration Diagram for Radiated Emissions



## **Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION**

The following is a description of supporting equipment and details of cables used with the EUT.

### **Supporting Equipment:**

Manufacturer	Equipment Description	Model	Serial No
BLU Products, Inc.	Adapter	US-BM-1500	D05362

### **Supporting Cable:**

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	D05362

Test Report	16071342-FCC-R1
Page	96 of 98

## Annex C.ii. EUT OPERATING CONKITIONS

N/A



Test Report	16071342-FCC-R1
Page	97 of 98

## Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	16071342-FCC-R1
Page	98 of 98

## Annex E. DECLARATION OF SIMILARITY

N/A